

Examples of Monitored Data

The OS collects different types of data at different layers.

- ▶ System call traces: describe the activities or behaviors of processes running in the system.
- ▶ Log file: information on user activity, including user' login record, history of commands, etc.
- ▶ File integrity checksums: periodically scan critical files for changes and compare cryptographic checksums for these files, with a record of known good values.
- ▶ Registry access: monitor access to the registry. This is specific to Windows operating systems.
- ▶ Kernel and driver-level monitoring: this source provides insight into OS kernel-level anomalies.
- ▶ Resource usage: CPU, memory or I/O utilization and activities can indicate the execution of some malicious behaviors.
- ▶ Network activities: include established connections and received packets

Intrusion Detection

Intrusion Detection System (IDS)

- ▶ A system used to detect unauthorized intrusions into computer systems.
- ▶ IDS can be implemented at different layers, including network-based IDS, host-based IDS.
- ▶ We mainly focus on host-based IDS, which monitors the characteristics of a single host for suspicious activities.

An IDS comprises three logical components:

- ▶ Sensors: responsible for collecting data.
- ▶ Analyzers: responsible for determining if an intrusion has occurred, and the possible evidence. It may provide guidance about what actions to take as a result of the intrusion.
- ▶ User interface: enables a user to view output from the system or control the behavior of the system.

Detection Methodologies

Signature-based detection

- ▶ Flag any activity that matches the structure of a known attack
- ▶ It is *blacklisting*: keep a list of patterns that are not allowed, and alert if we see something on the list.
- ▶ Advantage: simple and easy to build; good at detecting known attacks.
- ▶ Disadvantage: cannot catch new attacks without a known signature.

Anomaly-based detection

- ▶ Develop a model of what normal activities look like. Alert on any activities that deviates from normal activities.
- ▶ It is *whitelisting*: keep a list of allowed patterns, and alert if we see something that is not on the list.
- ▶ Advantage: can detect attacks we have not seen before.
- ▶ Disadvantage: false positive rate can be high (many non-attacks look unusual).

Outline

- ▶ **Security Protection Stages in OS**
 - ▶ Authentication
 - ▶ Authorization with Access Control
 - ▶ Logging, Monitoring & Auditing
- ▶ **Privilege Management in OS**

Privileged Rings Inside OS

Operating modes

- ▶ Kernel mode has the highest privilege, running the critical functions and services; user mode has the least privilege.
- ▶ Entities in the higher rings cannot call the functions and access the objects in the lower rings directly.
- ▶ Context switch is required to achieve the above procedure, system call, interrupt, etc.
- ▶ Status flag allows system to work in different modes.

