

Lab # : 4; Lab Name : Hive 2 - a few features; Subject Name : Information Storage and Retrieval; Week #: 4; Lab Duration : 20 to 30 mins

## Intro

In this lab, we will go over a few more Hive features and commands, which are useful for managing data in Hive. We will go over the following features:

- Partitioning a Table
- Bucketing a Table
- Check Storage format of a Hive table
- Hive on MR vs Tez
- Hive Views
- User Defined Functions

Here are a few points to get to know Hive:

- Hive can organize data in tables in partitions based on chosen column/s in a table. Partitioning a table creates multiple HDFS folders for the respective partitioned data.
- Buckets in a hive table are individual files physically.
- Bucketing can be done along with Partitioning on Hive tables and even without partitioning.
- Hive lets checking metadata of a Hive table
- Hive on Tez is a new feature in Hive, which runs faster than Hive alone on MR.
- Hive views could be created to filter data. Even UDF could be applied to views.
- For creating analytical operators, you can create custom User Defined Functions in java, python and other languages.

NOTE: All the codes in labs are samples only. You can always use variations of the code as applies. The intention of these labs, are to get you familiar with these concepts at physical level. However, these are vast areas to learn within a few minutes.

**Let's go!**

**Step-1.PARTITIONED Table**

Partitions are horizontal slices of data, which allow large sets of data to be segmented into more manageable blocks. Partitioning creates folder at HDFS level.

```
CREATE TABLE Web_Session_Log_Partitioned – u could choose another name as well  
(  
  DATETIME varchar(500), USERID varchar(500), SESSIONID varchar(500),  
  PRODUCTID varchar(500), REFERERURL varchar(500))  
COMMENT 'This is the Twitter streaming data'  
PARTITIONED BY(DATETIME STRING)  
ROW FORMAT DELIMITED  
FIELDS TERMINATED BY '\t' (or as per the dataset)  
STORED AS TEXTFILE;
```

Now, let's load data into the same table.

-- from the table you created in your previous lab; in case you don't have, you need to recreate.

```
FROM Web_Session_Log – the name you used in your previous lab  
  
INSERT OVERWRITE TABLE Web_Session_Log_Partitioned PARTITION  
(DATETIME="2014-01-02 00:00:06 GMT") SELECT *;
```

Now, please check the folder and files for the table in HDFS. You might have to drill down to locate the folder.

## Step-2. Bucketing a table

Bucketing is a technique that allows you to cluster or segment large sets of data to optimize query performance.

```
CREATE TABLE Web_Session_Log_Bucket – or choose a name of your choice
(DATETIME varchar(500),
USERID varchar(500),
SESSIONID varchar(500),
PRODUCTID varchar(500),
REFERERURL varchar(500))
COMMENT 'This is the Web Session Log data' PARTITIONED BY( PRODUCTID
STRING)
CLUSTERED BY(USERID) INTO 2 BUCKETS ROW FORMAT DELIMITED
FIELDS TERMINATED BY '\t'
STORED AS TEXTFILE;
```

```
set hive.enforce.bucketing = true;
```

```
FROM Web_Session_Log -- the table you created in your previous lab
INSERT OVERWRITE TABLE Web_Session_Log_Bucketing PARTITION
(PRODUCTID="/product/MT65XF2YA")
SELECT *;
```

Now, please check the folder and files for the table in HDFS. Do you see any difference? Please refer to Hive documentation, to further read on bucketing and partitioning as these are very much used in any hive implementation.

## Step-3. Let's check an existing table about it's table properties.

```
describe Web_Session_Log;
```

Here is the sample output:

```
.....
datetime varchar(500)
userid varchar(500)
```

sessionid varchar(500)  
productid varchar(500)  
refererurl varchar(500)  
Time taken: 0.111 seconds, Fetched: 5 row(s)

Here is another way to do the same for more details:  
describe **formatted** Web\_Session\_Log;

col\_name data\_type comment  
datetime varchar(500)  
userid varchar(500)  
sessionid varchar(500)  
productid varchar(500)  
refererurl varchar(500)  
Detailed Table Information  
Database: default  
Owner: ubuntu  
CreateTime: Thu May 28 06:11:32 UTC 2015  
LastAccessTime: UNKNOWN  
Protect Mode: None  
Retention: 0  
Location: hdfs://ip-10-85-31-243.eu-west-  
1.compute.internal:8020/user/hive/warehouse/web\_session\_log  
Table Type: MANAGED\_TABLE  
Table Parameters:  
COLUMN\_STATS\_ACCURATE true  
numFiles 1  
numRows 0  
rawDataSize 0  
totalSize 4513792  
transient\_lastDdlTime 1432793495  
Storage Information  
SerDe Library: org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe  
InputFormat: org.apache.hadoop.mapred.TextInputFormat  
OutputFormat: org.apache.hadoop.hive.ql.io.HiveIgnoreKeyTextOutputFormat  
Compressed: No  
Num Buckets: -1  
Bucket Columns: []  
Sort Columns: []  
Storage Desc Params:  
field.delim \t

```
serialization.format \t
```

```
Time taken: 0.1 seconds, Fetched: 36 row(s)
```

Please notice above Input and Output formats. These are all customizable as well.

#### **Step-4. Let's join two tables.**

In Hive, you can do various kinds of joins like, inner join, left outer join, right outer join, etc.

Here is an example query. You could create two tables of your choice and join them.

```
SELECT
Web_Session_Log.DATETIME,Web_Session_Log.USERID,User_Data.FIRSTNAME,U
ser_Data.LASTNAME,User_Data.LOCATION,Web_Session_Log.PRODUCTID,Web_
Session_Log.REFERERURL from Web_Session_Log JOIN User_Data ON
(User_Data.USERID=Web_Session_Log.USERID);
```

#### **Step-5. Hive on Tez.**

Tez is a new application framework built on Hadoop Yarn that can execute complex directed acyclic graphs of general data processing tasks. In many ways it can be thought of as a more flexible and powerful successor of the map-reduce framework.

```
Here is a way to set Tez Environment Variable on hive
set hive.execution.engine=tez;
you can change back to MR
set hive.execution.engine=mr;
```

Please read further on this topic using your hive site. Hive on Tez is very much used in HDP version of Hadoop from Hortonworks.

#### **Step-6. UDF**

Let's write a simple udf function in python as follows.

Streaming.py code:

```
import sys
from datetime import datetime
for line in sys.stdin.readlines():
    boolVal = "false"
```

```
line = line.strip()
DATETIME = datetime.strptime(line, "%m/%d/%Y")
print DATETIME
```

Now, let's register the Python function in hive; You can run this command in hive prompt as follows:

```
add file streaming.py;
```

Now, you can use the UDF as follows:

```
create table dev_schema.rpt_asset_extract as
select TRANSFORM(DATETIME) USING 'streaming.py' AS DATETIME from YOURTABLE;
```

**Questions/For your further reading/research:**

Please use your reference materials like Apache site, Cloudera site for further research.

Q1: How would partitioning a table help?

Q2: Why buckets are created or used?

Q3: Using Hive on Tez feature, would it help?

Q4: What is a DAG?

Q5: Why do u need to register an UDF before using?