Cache Lab: Understanding Cache Memories

1 Logistics

You will work on this lab alone or in pairs, and it is expected that you are working on one of the CS open lab machines on the console or via schizo.cs.byu.edu.

Any clarifications and revisions to the assignment will be posted on the course Web page.

2 Overview

This lab will help you understand the impact that cache memories can have on the performance of your C programs.

The lab consists of two parts. In the first part you will write part of a small C program (about 30-60 lines) that simulates the behavior of a cache memory. In the second part, you will optimize a small matrix transpose function, with the goal of minimizing the number of cache misses.

3 Starting the assignment

Start by copying http://cs224.byu.edu/cachelab-handout.tar to a protected Linux directory on one of the CS open lab machines in which you plan to do your work. Then give the command

```
linux> tar xvf cachelab-handout.tar
```

This will create a directory called cachelab-handout that contains a number of files. You will be modifying two files: csim.c and trans.c. To compile these files, type:

```
linux> make clean
linux> make
```

4 Description

The lab has two parts. In Part A you will implement a cache simulator. In Part B you will write a matrix transpose function that is optimized for cache performance.

4.1 Reference Trace Files

The traces subdirectory of the handout directory contains a collection of *reference trace files* that we will use to evaluate the correctness of the cache simulator you write in Part A. The trace files are generated by a Linux program called valgrind. For example, typing

```
linux> valgrind --log-fd=1 --tool=lackey -v --trace-mem=yes ls -1
```

on the command line runs the executable program "ls -1", captures a trace of each of its memory accesses in the order they occur, and prints them on stdout.

Valgrind memory traces have the following form:

```
I 0400d7d4,8
M 0421c7f0,4
L 04f6b868,8
S 7ff0005c8,8
```

Each line denotes one or two memory accesses. The format of each line is

```
[space]operation address, size
```

The *operation* field denotes the type of memory access: "I" denotes an instruction load, "L" a data load, "S" a data store, and "M" a data modify (i.e., a data load followed by a data store). There is never a space before each "I". There is always a space before each "M", "L", and "S". The *address* field specifies a 64-bit hexadecimal memory address. The *size* field specifies the number of bytes accessed by the operation.

4.2 Part A: Writing a Cache Simulator

In Part A you will finish a partial implementation of a cache simulator in csim.c that takes a valgrind memory trace as input, simulates the hit/miss behavior of a cache memory on this trace, and outputs the total number of hits, misses, and evictions. You have to write the most important function: void accessData (mem_addr_t addr)

We have provided you with the binary executable of a *reference cache simulator*, called <code>csim-ref</code>, that simulates the behavior of a cache with arbitrary size and associativity on a <code>valgrind</code> trace file. It uses the LRU (least-recently used) replacement policy when choosing which cache line to evict.

The reference simulator takes the following command-line arguments:

```
Usage: ./csim-ref [-hv] -s <s> -E <E> -b <b> -t <tracefile>
```

- -h: Optional help flag that prints usage info
- -v: Optional verbose flag that displays trace info
- -s <s>: Number of set index bits ($S=2^s$ is the number of sets)

- -E <E>: Associativity (number of lines per set)
- -b

: Number of block bits ($B = 2^b$ is the block size)
- -t <tracefile>: Name of the valgrind trace to replay

The command-line arguments are based on the notation (s, E, and b) from page 597 of the CS:APP2e textbook. For example:

```
linux> ./csim-ref -s 4 -E 1 -b 4 -t traces/yi.trace
hits:4 misses:5 evictions:3
```

The same example in verbose mode:

```
linux> ./csim-ref -v -s 4 -E 1 -b 4 -t traces/yi.trace
L 10,1 miss
M 20,1 miss hit
L 22,1 hit
S 18,1 hit
L 110,1 miss eviction
L 210,1 miss eviction
M 12,1 miss eviction hit
hits:4 misses:5 evictions:3
```

Your job for Part A is to implement the void accessData (mem_addr_t addr) in the csim.c file so that it produces the identical output as the reference simulator. Notice that this function completely empty. You'll need to read and understand the given code, and then write void accessData (mem_addr_t addr) from scratch.

Programming Rules for Part A

- Include your name and loginID in the header comment for csim.c.
- Your csim.c file must compile without warnings in order to receive credit.
- For this this lab, you should assume that memory accesses are aligned properly, such that a single memory access never crosses block boundaries. By making this assumption, you can ignore the request sizes in the valgrind traces.

4.3 Part B: Optimizing Matrix Transpose

In Part B you will write a transpose function in trans.c that causes as few cache misses as possible.

Let A denote a matrix, and A_{ij} denote the component on the ith row and jth column. The *transpose* of A, denoted A^T , is a matrix such that $A_{ij} = A_{ii}^T$.

To help you get started, we have given you an example transpose function in trans.c that computes the transpose of $N \times M$ matrix A and stores the results in $M \times N$ matrix B:

```
char trans_desc[] = "Simple row-wise scan transpose";
void trans(int M, int N, int A[N][M], int B[M][N])
```

The example transpose function is correct, but it is inefficient because the access pattern results in relatively many cache misses.

Your job in Part B is to write a similar function, called transpose_submit, that minimizes the number of cache misses across different sized matrices:

```
char transpose_submit_desc[] = "Transpose submission";
void transpose_submit(int M, int N, int A[N][M], int B[M][N]);
```

Do *not* change the description string ("Transpose submission") for your transpose_submit function. The autograder searches for this string to determine which transpose function to evaluate for credit.

Programming Rules for Part B

- Include your name and loginID in the header comment for trans.c.
- Your code in trans.c must compile without warnings to receive credit.
- You are allowed to define at most 12 local variables of type int per transpose function. 1
- You are not allowed to side-step the previous rule by using any variables of type long or by using any bit tricks to store more than one value to a single variable.
- Your transpose function may not use recursion.
- If you choose to use helper functions, you may not have more than 12 local variables on the stack at a time between your helper functions and your top level transpose function. For example, if your transpose declares 8 variables, and then you call a function which uses 4 variables, which calls another function which uses 2, you will have 14 variables on the stack, and you will be in violation of the rule.
- Your transpose function may not modify array A. You may, however, do whatever you want with the contents of array B.
- You are NOT allowed to define any arrays in your code or to use any variant of malloc.

5 Evaluation

This section describes how your work will be evaluated. The full score for this lab is 60 points:

• Part A: 27 Points

¹The reason for this restriction is that our testing code is not able to count references to the stack. We want you to limit your references to the stack and focus on the access patterns of the source and destination arrays.

• Part B: 20 Points

• Style: 7 Points

5.1 Evaluation for Part A

For Part A, we will run your cache simulator using different cache parameters and traces. There are eight test cases, each worth 3 points, except for the last case, which is worth 6 points:

```
linux> ./csim -s 1 -E 1 -b 1 -t traces/yi2.trace
linux> ./csim -s 4 -E 2 -b 4 -t traces/yi.trace
linux> ./csim -s 2 -E 1 -b 4 -t traces/dave.trace
linux> ./csim -s 2 -E 1 -b 3 -t traces/trans.trace
linux> ./csim -s 2 -E 2 -b 3 -t traces/trans.trace
linux> ./csim -s 2 -E 4 -b 3 -t traces/trans.trace
linux> ./csim -s 5 -E 1 -b 5 -t traces/trans.trace
linux> ./csim -s 5 -E 1 -b 5 -t traces/long.trace
```

You can use the reference simulator csim-ref to obtain the correct answer for each of these test cases. During debugging, use the -v option for a detailed record of each hit and miss.

For each test case, outputting the correct number of cache hits, misses and evictions will give you full credit for that test case. Each of your reported number of hits, misses and evictions is worth 1/3 of the credit for that test case. That is, if a particular test case is worth 3 points, and your simulator outputs the correct number of hits and misses, but reports the wrong number of evictions, then you will earn 2 points.

5.2 Evaluation for Part B

For Part B, we will evaluate the correctness and performance of your transpose_submit function on three different-sized output matrices:

```
• 32 \times 32 \ (M = 32, N = 32)
```

•
$$64 \times 64$$
 ($M = 64, N = 64$)

•
$$61 \times 67 \ (M = 61, N = 67)$$

5.2.1 Performance (26 pts)

For each matrix size, the performance of your transpose_submit function is evaluated by using valgrind to extract the address trace for your function, and then using the reference simulator to replay this trace on a cache with parameters (s = 5, E = 1, b = 5).

Your performance score for each matrix size scales linearly with the number of misses, m, up to some threshold:

- 32×32 : 16 points if m < 300, 0 points if m > 600
- 64×64 : 4 points if m < 1,300, 0 points if m > 2,000
- 61×67 : 4 points if m < 2,000, 0 points if m > 3,000

The 61×67 matrix is **extra credit**. Your code must be correct to receive any performance points for a particular size. Your code only needs to be correct for these three cases and you can optimize it specifically for these three cases. In particular, it is perfectly OK for your function to explicitly check for the input sizes and implement separate code optimized for each case.

5.3 Evaluation for Style

There are 7 points for coding style. These will be assigned manually by the course staff. Style guidelines can be found on the course website.

The course staff will inspect your code in Part B for illegal arrays and excessive local variables.

6 Working on the Lab

6.1 Working on Part A

We have provided you with an autograding program, called test-csim, that tests the correctness of your cache simulator on the reference traces. Be sure to compile your simulator before running the test:

linux> make								
linux> ./test-csim								
			Your si	mulator	Reference simulator			
Points	(s,E,b)	Hits	Misses	Evicts	Hits	Misses	Evicts	
3	(1, 1, 1)	9	8	6	9	8	6	traces/yi2.trace
3	(4, 2, 4)	4	5	2	4	5	2	traces/yi.trace
3	(2, 1, 4)	2	3	1	2	3	1	traces/dave.trace
3	(2, 1, 3)	167	71	67	167	71	67	traces/trans.trace
3	(2, 2, 3)	201	37	29	201	37	29	traces/trans.trace
3	(2, 4, 3)	212	26	10	212	26	10	traces/trans.trace
3	(5, 1, 5)	231	7	0	231	7	0	traces/trans.trace
6	(5, 1, 5)	265189	21775	21743	265189	21775	21743	traces/long.trace
27								

For each test, it shows the number of points you earned, the cache parameters, the input trace file, and a comparison of the results from your simulator and the reference simulator.

Here are some hints and suggestions for working on Part A:

• Do your initial debugging on the small traces, such as traces/dave.trace.

- The reference simulator takes an optional -v argument that enables verbose output, displaying the hits, misses, and evictions that occur as a result of each memory access. You are not required to implement this feature in your csim.c code, but we strongly recommend that you do so using the verbosity global variable. It will help you debug by allowing you to directly compare the behavior of your simulator with the reference simulator on the reference trace files.
- Each data load (L) or store (S) operation can cause at most one cache miss. The data modify operation (M) is treated as a load followed by a store to the same address. Thus, an M operation can result in two cache hits, or a miss and a hit plus a possible eviction.

6.2 Working on Part B

We have provided you with an autograding program, called test-trans.c, that tests the correctness and performance of each of the transpose functions that you have registered with the autograder.

You can register up to 100 versions of the transpose function in your trans.c file. Each transpose version has the following form:

```
/* Header comment */
char trans_simple_desc[] = "A simple transpose";
void trans_simple(int M, int N, int A[N][M], int B[M][N])
{
    /* your transpose code here */
}
```

Register a particular transpose function with the autograder by making a call of the form:

```
registerTransFunction(trans_simple, trans_simple_desc);
```

in the registerFunctions routine in trans.c. At runtime, the autograder will evaluate each registered transpose function and print the results. Of course, one of the registered functions must be the transpose_submit function that you are submitting for credit:

```
registerTransFunction(transpose_submit, transpose_submit_desc);
```

See the default trans.c function for an example of how this works.

The autograder takes the matrix size as input. It uses valgrind to generate a trace of each registered transpose function. It then evaluates each trace by running the reference simulator on a cache with parameters (s = 5, E = 1, b = 5).

For example, to test your registered transpose functions on a 32×32 matrix, rebuild test-trans, and then run it with the appropriate values for M and N:

```
linux> make
linux> ./test-trans -M 32 -N 32
Step 1: Evaluating registered transpose funcs for correctness:
```

```
func 0 (Transpose submission): correctness: 1
func 1 (Simple row-wise scan transpose): correctness: 1
func 2 (column-wise scan transpose): correctness: 1
func 3 (using a zig-zag access pattern): correctness: 1

Step 2: Generating memory traces for registered transpose funcs.

Step 3: Evaluating performance of registered transpose funcs (s=5, E=1, b=5)
func 0 (Transpose submission): hits:1766, misses:287, evictions:255
func 1 (Simple row-wise scan transpose): hits:870, misses:1183, evictions:1151
func 2 (column-wise scan transpose): hits:870, misses:1183, evictions:1151
func 3 (using a zig-zag access pattern): hits:1076, misses:977, evictions:945
Summary for official submission (func 0): correctness=1 misses=287
```

In this example, we have registered four different transpose functions in trans.c. The test-trans program tests each of the registered functions, displays the results for each, and extracts the results for the official submission.

Here are some hints and suggestions for working on Part B.

• The test-trans program saves the trace for function i in file trace. fi. These trace files are invaluable debugging tools that can help you understand exactly where the hits and misses for each transpose function are coming from. To debug a particular function, simply run its trace through the reference simulator with the verbose option:

```
linux> ./csim-ref -v -s 5 -E 1 -b 5 -t trace.f0
S 68312c,1 miss
L 683140,8 miss
L 683124,4 hit
L 683120,4 hit
L 603124,4 miss eviction
S 6431a0,4 miss
...
```

- Since your transpose function is being evaluated on a direct-mapped cache, conflict misses are a potential problem. Think about the potential for conflict misses in your code, especially along the diagonal. Try to think of access patterns that will decrease the number of these conflict misses.
- Blocking is a useful technique for reducing cache misses. See

```
http://csapp.cs.cmu.edu/public/waside/waside-blocking.pdf
```

for more information.

²Because valgrind introduces many stack accesses that have nothing to do with your code, we have filtered out all stack accesses from the trace. This is why we have banned local arrays and placed limits on the number of local variables.

6.3 Putting it all Together

We have provided you with a *driver program*, called ./driver.py, that performs a complete evaluation of your simulator and transpose code. This is the same program your instructor uses to evaluate your handins. The driver uses test-csim to evaluate your simulator, and it uses test-trans to evaluate your submitted transpose function on the three matrix sizes. Then it prints a summary of your results and the points you have earned.

To run the driver, type:

linux> ./driver.py

7 Handing in Your Work

Each time you type make in the cachelab-handout directory, the Makefile creates a tarball, called userid-handin-version.tar, that contains your current csim.c and trans.c files. The user ID does not need to be set as in the Architecture lab, it gets that automatically from the USER environment variable on the open lab systems; however, the VERSION value does need to be set each time you submit. Only the latest (e.g., highest value) version in graded.

To submit your files, check the VERSION value in the Makefile and then run the handin target with the following command at the prompt:

linux> make handin

As with the Architecture lab, you can use the stat command to verify the tar-archive was moved into the directory indicated in the Makefile. Additionally, please upload the archive to Learning Suite.

IMPORTANT: The handin target only works on the department open lab machines.