
CSC373H1 Summer 2014 Assignment 4

Names: John Armstrong, Henry Ku

SNs\CDF username: 993114492\g2jarmst, 998551348\g2kuhenr

Question #	Score
1	
2	
3	
4	
Total	

Acknowledgements:

"We declare that we have not used any outside help in completing this assignment."

Name: John Armstrong, Henry Ku

Date: July 28, 2014

Q1. The Mute Prison

Claim: The mute prison problem is NP-complete.

Proof:

1. Show the mute prison problem is NP.
2. Show the mute prison problem is NP-hard.

1. Suppose we are given a certificate S and have access to value k and matrix T . We can verify that the certificate is satisfiable in the following way. Suppose each element in S represents an inmate. Verification would involve iterating on each inmate in the following way:

```

for inmate in  $S$  do
     $j = 1$ ;
    while  $j \leq m$  do
        if  $T[inmate, j]$  then
            for ( $otherinmate \neq inmate$ ) in  $S$  do
                if  $T[otherinmate, j]$  then
                     $S$  is not a subset of inmates who do don't speak the same language;
                end
            end
        end
         $j++$ ;
    end
end

```

Clearly, the verification that S is a subset where no two inmates speak the same language can run in polynomial time $O(mn^2)$. Once this verification is complete all that is left to do is to verify that $|S| \geq k$, which is $O(1)$. Therefore the mute prison problem is NP. ■

2. To show that the mute prison problem is NP-hard we must perform a reduction using an NP-complete problem. We will use a reduction on NP-complete 3-SAT in CNF, in order to show $3\text{-SAT} \leq_p \text{Mute Prison Problem}$.

Properties of Reduction

Suppose that ϕ is an instance of 3-SAT and C_1, C_2, \dots, C_m are the clauses of ϕ . By construction of 3-SAT in CNF we have $C_i = (z_{i1} \vee z_{i2} \vee z_{i3})$. In the reduction each C_i 's boolean value will represent a boolean value for each language, L_i , spoken by some inmate(s), precisely, $L_i = C_i = (z_{i1} \vee z_{i2} \vee z_{i3})$. Each boolean value for L_i has a specific mean:

$$L_i = \begin{cases} 1 & \text{if } L_i \text{ is spoken by at most 1 inmate} \\ 0 & \text{if } L_i \text{ is spoken by at least 1 inmate} \end{cases}$$

Producing L_1, L_2, \dots, L_m will take polynomial time since we iterate through each C_i and perform a boolean operation on each z_i in C_i which takes $O(m)$.

Finally, the mute prison problem requires a matrix T to produce the subset of inmates S . Let T be an $m \times m$ matrix, so that no inmates are left without a language. The rows in T will represent inmates and the columns will represent languages such that column i represents L_i . The algorithm that performs the reduction will

iterate through each L_i . If $L_i = 1$ then set $T[i, i] = 1$, else if $L_i = 0$ then $T[1, i] = T[2, i] = \dots = T[m, i] = 1$. Assigning all inmates to speak L_i , when $L_i = 0$, will guarantee that $|S| = 0$. Alternatively, $\forall i$, if $L_i = 1$ then $|S| = m$. So that if ϕ satisfies 3-SAT, then T will satisfy the mute prison problem if we set $k = m$. Again this process is polynomial as it iterates through m L_i 's and assigns at most m inmates the language L_i , so it will run $O(m^2)$.

ϕ of 3-SAT is satisfiable \rightarrow L and k of mute prison problem is satisfiable

Suppose ϕ of 3-SAT is satisfiable, then each clause C_1, C_2, \dots, C_m is satisfied. A set of L_1, \dots, L_m is produced such that $\forall L_i, L_i = 1$. Then we form matrix T of size $m \times m$, such that T resembles the identity matrix as each $T[i, i] = 1$. Also, $k = m$, so that when S is assembled all m inmates speak a different language, then $|S| \geq k$ is satisfied.

L and k of mute prison problem is satisfiable $\rightarrow \phi$ of 3-SAT is satisfiable

Suppose that T and k of the mute prison problem are satisfiable. Also, suppose $|S|$ is at least $m=k$. Choose only the first m inmates from S , and extract only their rows from T to form a new matrix T' . It will follow that in T' there will be only m columns where there is at most one entry with the value 1. We will attribute these m columns with variables L_1, \dots, L_m , such that, $1 \leq i \leq m, L_i = 1$. We then form m clauses of a 3-SAT CNF, call them C_i, \dots, C_m . Each C_i relates to L_i , so that the boolean value of $C_i = (z_{i1} \vee z_{i2} \vee z_{i3}) = 1$. Thus set any one of the z_{i1}, z_{i2} , or z_{i3} to 1. It follows that all $C_i = 1$, thus $\phi = (C_1 \wedge C_2 \wedge \dots \wedge C_m)$ is satisfiable.

So, ϕ of 3-SAT is satisfiable \Leftrightarrow L and k of mute prison problem is satisfiable. Also, because the reduction was shown to be polynomial it is proven that the mute prison problem is NP-hard. ■

By the proofs 1. and 2. it follows that the mute prison problem is NP-complete. ■

Q2. The Nonsense Prerequisites

Claim: The nonsense prerequisites problem is NP-complete.

Proof:

1. Show the nonsense prerequisites problem is NP.
2. Show the nonsense prerequisites problem is NP-hard.

1. Suppose we know $G(V, E)$ and k and we are given E' as a certificate. We verify the certificate with the following algorithm:

```

 $E'' = E - E'$ ;
Produce function  $w$ , such that  $\forall (u, v) \in E'', w(u, v) = -1$ ;
Produce new  $G'(V, E'', w)$ ;
for  $v$  in  $V$  do
    Perform Bellman-Ford( $G', w, v$ );
    for each edge  $(u, v) \in G'.E''$  do
        if  $v.d > u.d + w(u, v)$  then
            | There is a cycle and the certificate is not satisfiable.
        end
    end
end

```

If there is a cycle in $G'(V, E'')$ then setting each edge in G' to a weight -1 will produce a negative edge cycle which, after relaxations, we can identify easily. Given that $G(V, E'')$ may or may not be connected, to locate a cycle in the graph we must perform the relaxation with Bellman-Ford $|V|$ times. Bellman-Ford runs at $O(VE)$, it is executed $|V|$ times in the verifier, thus we have $O(V^2E)$ for our algorithm. Since $|V| = n$, and $|E| = O(n^2)$, the verifier runs $O(n^4)$. So the verifier is polynomial and then the nonsense prerequisites problem is NP. ■

2.

Q3. T-rex Christmas

Q4. Vertex Cover