



THE EASY WAY

MAINTAIN YOUR LAWN MOWER

REQUIREMENTS

- **Tools**

- Dustpan and Brush
- Lawn Mower
- Safety Gloves
- Socket Set
- Wire Brush

- **Materials**

- Oil
- Petrol
- Rags
- Spark Plug
- WD40

I. SAFETY



- Put on safety gloves
- Put throttle in off position
- Disconnect the spark plug





2. CLEAN



Use dustpan brush to remove dirt, grime and grass that has built up on the outside.

3. APPLY LUBRICANT



Apply WD40 to the following:

- Wheels
- Throttle Cable
- Height Adjuster

Use rag to wipe away any excess WD40





4. THE SPARK PLUG



- Use the socket set to remove the spark plug.
- Clean it with the wire brush

Note: if replacing the spark plug, screw it in with your fingers as far as you can to ensure it does not cross-thread. Then tighten it with the socket.

5. THE AIR FILTER



- Remove the cover for the air filter
- Clean with light bristle brush
- **Note:** if the air filter is dirty, replace with new air filter





6. THE CATCHER



- Remove the catcher from the mower
- Use a hose to thoroughly clean and wash out the catcher.

7. UNDERSIDE



- Lean the mower back to check underneath
- Use brush to remove dirt/grass
- Inspect blades for damage
- **Note:** Avoid laying the mower upside down. If the blades are damaged, please notify us on (07) 4046 8050





8. THE OIL



- Remove the cap for the oil compartment
- Check oil level on the dipstick
- Top up the oil if low
- **Note:** if the oil is dark and dirty, it will need to be drained and replaced.

9. READY TO GO!



- **Pro Tip** - Only add petrol to the mower before you use it so that it will not go stale.

