

Autonomous surf life saving device

Jarod Lam

2018-2019 VRES project at Queensland University of Technology

Abstract—Make boat that saves people

I. INTRODUCTION

II. SYSTEM OVERVIEW

III. COMMUNICATIONS

Communications between the SRB and the base station are done using XBee radios. By attaching a pair of XBee modules to the base station computer and the on-board Arduino, a virtual serial connection is effectively created between the two devices.

A. NMEA 0183 protocol

NMEA 0183 is a communications specification designed to create a standardised serial interface for GPS devices. Every NMEA ‘sentence’ begins with a \$ and ends with *CS\r\n, where CS is a two-digit hexadecimal checksum of the sentence.

A common NMEA sentence type is GPRMC, the GPS recommended minimum. GPRMC sentences are specified as follows: [1]

```
$GPRMC,<Time>,<Status>,<Lat>,<LatDir>,<Lon>,<LonDir>,<Speed>,<Angle>,<Date>,<MagVar>,<MagDir>*CS
```

Where:

<Time>	UTC timestamp in HHmmss format
<Status>	Status A=active, V=void
<Lat>	Latitude in ddmm.mmm format
<LatDir>	N or S hemisphere
<Lon>	Longitude in dddmm.mmm format
<LonDir>	E or W hemisphere
<Speed>	Ground speed in knots
<Angle>	Track angle in degrees from north
<Date>	Date in DDMMYY format
<MagVar>	Magnetic variation magnitude
<MagDir>	Magnetic variation direction
*CS	Two-digit hexadecimal checksum

A NMEA sentence parser was written for the SRB to interpret messages from the on-board GPS and extract location information.

B. Proprietary NMEA sentences

Some advantages of using NMEA sentences are that they are standardised, human-readable, robust, and relatively simple to implement. Specified below is a set of custom NMEA sentence types was created for communication between the SRB and the base station.

1) *SRBSM - Status Message*: The SRBSM sentence is sent periodically by the SRB to update the base station with status information.

```
$SRBSM,<ID>,<Lat>,<Lon>,<Speed>,<Heading>,<BattV>*CS
```

Where:

<ID>	ID of target SRB
<Lat>	Latitude in decimal degrees
<Lon>	Longitude in decimal degrees
<Speed>	Speed in metres per second
<Heading>	Compass heading in degrees from north
<BattV>	Current battery voltage
*CS	Two-digit hexadecimal checksum

REFERENCES

- [1] D. DePriest, “Nmea data,” accessed November 2018. [Online]. Available: <https://www.gpsinformation.org/dale/nmea.htm>