

PrimeFaces

Jaroslav Dytrych

Faculty of Information Technology Brno University of Technology
Božetěchova 1/2. 612 66 Brno - Královo Pole
dytrych@fit.vutbr.cz



24 October 2023

PrimeFaces



- JSF doesn't provide rich set of components
 - It is left for 3rd party libraries
- PrimeFaces
 - rich set of components
 - uses JQuery library for custom components
 - AJAX support (based on JSF 2.0)
 - push support via Atmosphere framework (WebSocket/Comet)
 - In 7.0 Push has been removed. Please use the JSF 2.3 socket or OmniFaces now.
 - one-jar library, no configuration nor dependencies
 - lots of built-in themes, visual theme designer tool
 - Old versions ThemeRoller <https://jqueryui.com/themeroller/>
 - Theme Designer <https://www.primefaces.org/designer-jsf/>
 - extensive documentation
 - XHTML facelets on client combined with Java on the server side

- PrimeFaces
 - Theming concept
 - Inputs and selects
 - Client side validations
 - Panels
 - Data iteration components
 - Menus
 - Dialog framework
 - Working with files and images
 - Drag & Drop
 - Charts
 - Push
 - RequestContext (`PrimeFaces.current()`)



- Themes
 - 10 Built-In Themes
 - 18 Premium Themes
 - 38 Community Themes
- Configuration (web.xml)

```
<context-param>  
    <param-name>primefaces.THEME</param-name>  
    <param-value>aristo</param-value>  
</context-param>
```

- May be dynamic

```
<context-param>  
    <param-name>primefaces.THEME</param-name>  
    <param-value>#{loggedInUser.preferences.theme}</param-value>  
</context-param>
```

- Custom theme must be present in one .jar file.
- mandatory structure

.jar

- META-INF
 - resources
 - primefaces-yourtheme
 - theme.css
 - images

- Image addressing
 - `url("images/my_image.png")` must be changed to
 - `url("#{resource['primefaces-yourtheme:images/my_image']}")`

Selector	Description
.ui-widget	All PrimeFaces components
.ui-widget-header	Header section of a component
.ui-widget-content	Content section of a component
.ui-state-default	Default class of a clickable
.ui-state-hover	Class applied when cursor is over widget
.ui-state-active	When clickable is activated
.ui-state-disabled	Disabled elements
.ui-state-highlight	Highlighted elements
.ui-icon	An element to represent an icon



- Input mask
 - minimizes the chances for the user to input incorrect data

```
<p:inputMask value="#{maskController.phone}"
              mask="(999) 999-999-999"/>
```
 - a kind of regular expressions
 - 9 is used as a pattern for 0 – 9
- Input language
 - kind of regular expressions for validating input
 - asterisk for multiple occurrence
 - question mark for optional occurrence

```
<p:inputMask value="#{inputMaskController.productKey}"
              mask="a*-999-a999" />
```




- Autocomplete

- method complete takes a string and returns a List<String>

```
<p:autoComplete id="simple" value="#{autoCompleteController.txt1}"
    completeMethod="#{autoCompleteController.complete}" />
```

- Autocomplete event

```
<p:autoComplete value="#{autoCompleteController.txt1}"
    completeMethod="#{autoCompleteController.complete}">
    <p:ajax event="itemSelect"
        listener="#{autoCompleteController.handleSelect}"
        update="messages" />
</p:autoComplete>
```

```
public void handleSelect(SelectEvent event) {
    Object selectedObject = event.getObject();
    MessageUtil.addInfoMessage("selected.object", selectedObject);
}
```

- Every input component can fire appropriate AJAX events when they occur.



- `InputTextArea`
 - events/attributes: `onkeyup`, `onfocus`, `onblur`, ...
- `TextEditor`
 - rich text editing features (<https://quilljs.com/>)
- `SelectManyCheckBox`
 - used to choose multiple items from a collection
- `Calendars`
 - multiple display modes
- `Spinner`
 - boundaries
- `Slider`
 - it is possible to set min/max value, step, range, ...
 - vertical or horizontal
- ...



- Partial processing allows updating JSF components with AJAX.
- Partial processing speeds up large form processing.
- Partial rendering defines elements to be updated.

```
<h:form id="myform">
    <p:commandButton value="Update" update="myform:display" />
    <h:outputText id="display" value="#{bean.value}" />
</h:form>
```

- Partial validations
 - may prevent unwanted validations

```
<h:form>
    <h:selectOneMenu id="cities" value="#{bean.city}">
        <f:selectItems value="#{bean.cityChoices}" />
        <p:ajax actionListener="#{bean.populateSuburbs}"
            event="change" update="suburbs" process="@this" />
    </h:selectOneMenu>
    ...
</h:form>
```

- Search expression framework

Keyword	Type	Description
@this	Standard	Current component
@all	Standard	Whole view
@form	Standard	Closest ancestor form
@none	Standard	No component
@namingcontainer	PrimeFaces	Closest ancestor naming container
@parent	PrimeFaces	Parent of the current component
@composite	PrimeFaces	Closest composite component ancestor
@child(n)	PrimeFaces	Nth child
@previous	PrimeFaces	Previous sibling
@next	PrimeFaces	Next sibling
@widgetVar(name)	PrimeFaces	Component with given widget variable

- Validations must be compatible with server side implementation.
- Conversion and validation happens at client side.
- Partial process&update support for AJAX.
- i18n support along with component specific messages.
- Client side renderers for message components.
- Easy to write custom client converters and validators.
- Global or component based enable/disable.
- Advanced bean validation integration.
- Little footprint using HTML5.



- Client side validations are disabled by default, has to be enabled in configuration (web.xml)

```
<context-param>  
  <param-name>primefaces.CLIENT_SIDE_VALIDATION</param-name>  
  <param-value>true</param-value>  
</context-param>
```

- Non-AJAX
 - In non-AJAX case, all visible and editable input components in the form are validated and message components must be placed inside the form.
- AJAX
 - partial processing and updates
- Custom validation
 - implementing client validation interface
 - method validate()

- Bean validation
 - constraints via annotations

```
<h:form>
    <p:growl />
    <h:panelGrid>
        <h:outputLabel for="name" value="Name:" />
        <p:inputText id="name" value="#{bean.name}" label="Name"/>
        <p:message for="name" />
        <h:outputLabel for="age" value="Age: (@Min(10) @Max(20))" />
        <p:inputText id="age" value="#{bean.age}" label="Age"/>
        <p:message for="age" />
    </h:panelGrid>
    <p:commandButton value="Save" validateClient="false" ajax="false" />
</h:form>
```

```
public class Bean {
    @Size(min=2,max=5)
    private String name;
    @Min(10) @Max(20)
    private Integer age;
}
```

- growl is used for messages (in the top right corner)

- Messages components are used to display FacesMessages.
 - Severity: Info, Warn, Error or Fatal.
 - Messages can indicate errors in the forms.

```
<p:messages id="messages" showDetail="true" closable="true" >
  <p:autoUpdate/>
</p:messages>
...
<p:outputLabel for="txt" value="Text:" />
<p:inputText id="txt" required="true" />
<p:message for="txt" display="text" />
```

```
FacesContext.getCurrentInstance().addMessage(null,
    new FacesMessage(FacesMessage.SEVERITY_FATAL, "Fatal!",
        "System Error"));
```




- Panels serves as containers for storing of other widgets.
- Panel is a generic component.
 - toggling
 - closing
 - built-in pop-up menu
 - AJAX listeners
- Panel grid
 - support for colspan and rowspan.
- Dynamic content loading
 - Tabs can be lazily loaded based on a value of underlying JavaBean.
- Dynamic tabbing
 - `AccordionPanel`



- Overflow content
 - ScrollPanel
- Buttons grouping
 - toolbars, separators
- Draggable widgets
 - DashBoard panel
 - grid with row and columns constraints
- Element layout (Primefaces < 10.0)
 - at element level, styled with CSS
 - Layout component was removed in PrimeFaces 10.0 in favor of pure CSS. PF Extensions still has a similar Layout component.
- Full Page layout (Primefaces < 10.0)
 - North, West, Center, East, South
 - In PrimeFaces 10.0 can be replaced by PF Extensions
- Panels can fire appropriate events
 - close, toggle, resize

```
<p:ajax event="close" listener="#{panelView.onClose}"
        update="msgs" />
```

- Data iteration components are usually data tables or trees.
- Selection

- selection mode (single or multiple)

```
<p:dataTable id="multipleSelectionCheckbox" var="car"
             value="#{dataTableController.cars}"
             rowKey="#{car.name}"
             selection="#{dataTableController.selectedCars}">
  <p:column selectionMode="multiple"/>
  ...
</p:dataTable>
```

- property listeners

- Selected object is referenced as a variable and can be passed to underlying Java method.

```
<f:setPropertyActionListener value="#{car}"
                             target="#{dataTableController.selectedCar}" />
```



- Sorting and filtering in DataTable

- Sorting

```
<p:dataTable id="sorting" var="car"
              value="#{dataTableController.cars}">
  <p:column headerText="Year" sortBy="#{car.year}">
    <h:outputText value="#{car.year}" />
  </p:column>
</p:dataTable>
```

- Filtering

- displays filter text fields
 - user filters the data
 - all fields can be searched

```
<p:dataTable id="filtering" var="car"
              value="#{dataTableController.cars}">
  <p:column headerText="Year" filterBy="#{car.year}">
    <h:outputText value="#{car.year}" />
  </p:column>
  <p:column headerText="Name" filterBy="#{car.name}">
    <h:outputText value="#{car.name}" />
  </p:column>
</p:dataTable>
```



- In cell editing
 - AJAX events

```
<p:ajax event="rowEdit"
        listener="#{dataTableController.onEdit}"
        update=":form:growl" />
<p:ajax event="rowEditCancel"
        listener="#{dataTableController.onCancel}"
        update=":form:growl" />
```

- Lazy models – handling lots of records
 - supports pagination
 - `org.primefaces.LazyDataModel`
 - Programmer must implement `load`, `getRowData` and `getRowKey` methods.

```
<p:dataTable id="lazyModel" var="car"
             value="#{lazyDataTableController.lazyModel}"
             paginatorTemplate="{RowsPerPageDropdown} {FirstPageLink}
                               {PreviousPageLink} {CurrentPageReport} {NextPageLink}
                               {LastPageLink}"
             paginator="true" rows="10" lazy="true">
```

- Trees and TreeTables
 - Events
 - collapse, expand, select, unselect
- Context menu support

```
<p:contextMenu for="withContextMenu" nodeType="node">
    <p:menuitem value="View" update="dialogPanel"
        icon="pi pi-search"
        oncomplete="nodeDialog.show()"/>
</p:contextMenu>
<p:contextMenu for="withContextMenu" nodeType="leaf">
    <p:menuitem value="View"
        update="dialogPanel" icon="pi pi-search"
        oncomplete="nodeDialog.show()"/>
    <p:menuitem value="Delete"
        update="withContextMenu" icon="pi pi-times"
        actionListener="#{treeDataController.deleteNode}"/>
</p:contextMenu>
```

- Menu positioning
 - static
 - displayed in page by default
 - dynamic
 - overlay, not displayed by default
 - defines trigger button, position relative to that button

- Programmatic menu

- Menu can be defined also in Java

```
<p:menu model="#{programmaticMenuController.model}"/>
```

- Model object returns constructed menu.

- Context menu

```
<p:contextMenu for="fileSystem">
    <p:menuitem value="View" update="growl"
        actionListener="#{contextMenuController.viewNode}"
        icon="pi pi-search"/>
    <p:menuitem value="Delete" update="fileSystem"
        actionListener="#{contextMenuController.deleteNode}"
        icon="pi pi-times"/>
</p:contextMenu>
```



- Other menus
 - Menubar
 - displays root items horizontally and nested items as tiered
 - for static menus
 - MegaMenu
 - multi-column menu
 - displays submenus of root items together
 - TieredMenu
 - submenus in nested overlays
 - PanelMenu
 - hybrid of accordion-tree
 - SlideMenu
 - displays nested submenus with a slide animation
 - SelectCheckBoxMenu
 - menu with checkboxes which are on or off



- Simple dialogs
 - `<p:dialog ...`
 - Yes|No questions, notifications, asking for input
- Dialog framework
 - opens an external XHTML page in a dialog that is generated
- Dialogs requires configuration in `faces-config.xml`

```
<application>
  <action-listener>
    org.primefaces.application.DialogActionListener
  </action-listener>
  <navigation-handler>
    org.primefaces.application.DialogNavigationHandler
  </navigation-handler>
  <view-handler>
    org.primefaces.application.DialogViewHandler
  </view-handler>
</application>
```



- FileUpload component
 - equivalent to HTML `<input type="file">`
 - HTML 5 powered UI, such as Drag & Drop
- Approaches
 - Native
 - works since JSF 2.2 – Servlet Part API
 - Commons
 - requires configuration
 - may specify size threshold, upload directory (init-param), ...

```
<filter>
  <filter-name>PrimeFaces FileUpload Filter</filter-name>
  <filter-class>
    org.primefaces.webapp.filter.FileUploadFilter
  </filter-class>
</filter>
<filter-mapping>
  <filter-name>PrimeFaces FileUpload Filter</filter-name>
  <servlet-name>Faces Servlet</servlet-name>
</filter-mapping>
```



- Two file upload modes

- Simple

```
<h:form enctype="multipart/form-data">
  <p:fileUpload value="#{fileController.file}" mode="simple" />
  <p:commandButton value="Submit" ajax="false"/>
</h:form>
```

A simple file upload UI consisting of a text input field and a "Browse..." button.

- Advanced

- specifies upload handler

```
<p:fileUpload mode="advanced"
  listener="#{fileController.handleFileUpload}" />
```

- may limit maximum number of files to be uploaded, file type etc.

```
public void handleFileUpload(FileUploadEvent event) {
    UploadedFile file = event.getFile();
    MessageUtil.addInfoMessage("upload.successful",
        file.getFileName() + " is uploaded.");
}
```

An advanced file upload UI with three buttons: "+ Choose", "↗ Upload", and "⊗ Cancel". Below the buttons is a text input field.

- File download
 - bean must return streamed content

```
<p:commandButton value="Download" ajax="false">  
    <p:fileDownload value="#{fileController.file}" />  
</p:commandButton>
```

- Status of upload/download is monitored by JavaScript.
- Galleria widget for multiple images

```
<p:galleria value="#{galleriaController.cars}" var="car">  
    <p:graphicImage  
        value="/resources/images/autocomplete/#{car.name}.png"/>  
</p:galleria>
```



- PrettyFaces is an OpenSource URL-rewriting library with enhanced support for JavaServer Faces.
- Enables creation of bookmarkable, pretty URLs (Search Engine Optimization friendly).
- Maven dependency (or .zip distribution).
- Workflow:

- Add PrettyFaces to your pom.xml

- Create pretty-config.xml

```
<url-mapping id="login">
    <pattern value="/login" />
    <view-id value="/user/login.jsp" />
</url-mapping>

<!-- Map "/user/#{username}"
    to the URL "/user/view.xhtml?username=value" -->
<url-mapping id="view-user">
    <pattern value="/user/#{username}" />
    <view-id value="/user/view.xhtml" />
</url-mapping>
```

- Run your application.



- PrettyFaces breaks PrimeFaces file upload.
- Prerequisites
 - `commons-fileupload` and `commons-io` are present in the webapp's runtime classpath (`/WEB-INF/lib`)
 - The `FileUploadFilter` is mapped on the exact `<servlet-name>` of the `FacesServlet` as is been defined in your `web.xml`.
 - The enctype of the `<h:form>` needs to be set to `multipart/form-data`.
 - In simple file upload with `mode="simple"`, AJAX must be disabled on any PrimeFaces command buttons/links by `ajax="false"`.

- Solution (web.xml):

```
<filter>
  <filter-name>PrimeFaces FileUpload Filter</filter-name>
  <filter-class>
    org.primefaces.webapp.filter.FileUploadFilter
  </filter-class>
</filter>
<filter-mapping>
  <filter-name>PrimeFaces FileUpload Filter</filter-name>
  <servlet-name>Faces Servlet</servlet-name>
  <dispatcher>FORWARD</dispatcher>
</filter-mapping>
<servlet>
  <servlet-name>Faces Servlet</servlet-name>
  <servlet-class>javax.faces.webapp.FacesServlet</servlet-class>
  <load-on-startup>1</load-on-startup>
</servlet>
<servlet-mapping>
  <servlet-name>Faces Servlet</servlet-name>
  <url-pattern>/faces/*</url-pattern>
</servlet-mapping>
```



- Making panel draggable

```
<p:panel id="pnl" header="Draggable panel with default settings">  
    <h:outputText value="Drag me around"/>  
</p:panel>  
<p:draggable for="pnl"/>
```

- Draggable restrictions

- Horizontal `<p:draggable for="hpnl" axis="x"/>`
- Vertical `<p:draggable for="vpnl" axis="y"/>`
- Grid `<p:draggable for="gpnl" grid="40,50"/>`
- Boundary `<p:draggable for="pic" containment="parent"/>`

- Drag & Drop may be used in AJAX requests,
- can be integrated with data iteration components.



- Defining draggable targets

- Client-side callback onDrop

```
<h:panelGroup id="drop" layout="block" styleClass="ui-widget-content"
              style="height:150px;width:300px;">
    <p class="ui-widget-header" style="margin:0;padding:5px;">
        Drop here
    </p>
    <p:droppable onDrop="handleDrop" tolerance="fit"/>
</h:panelGroup>
```

- Dropping restrictions

- defining tolerance and acceptance
 - Tolerance specifies which mode to use for testing if a draggable component is over a droppable.
 - Four types of tolerance – fit, intersect, pointer, touch
 - Acceptance defines scope attributes, droppable must have same scope as draggable if Drag & Drop is to be applied.
 - Scope is some sort of string id

```
<p:droppable onDrop="handleDrop" scope="dnd"/>
<p:draggable scope="dnd"/>
```




- PrimeFaces provides simple API for displaying various types of Charts
- Client-side chart refers to Chart model value defined on the server.
- Types
 - Area
 - Bar
 - Line
 - Bubble
 - Donut
 - Pie
 - ...
- Appropriate model value has to be returned from JavaBean

```
<p:chart type="line" model="#{bean.model}" />
```

- Facelet defines legends, axis values etc.
- Java implementation of a model

```
LineChartModel model = new LineChartModel();  
LineChartSeries sales = new LineChartSeries();  
sales.setLabel("Sales");  
sales.set("2004", 1000);  
sales.set("2005", 1170);  
sales.set("2006", 660);  
sales.set("2007", 1030);  
LineChartSeries expenses =  
    new LineChartSeries();  
expenses.setLabel("Expenses");  
expenses.set("2004", 400);  
expenses.set("2005", 460);  
expenses.set("2006", 1120);  
expenses.set("2007", 540);  
model.addSeries(sales);  
model.addSeries(expenses);
```





- RemoteCommand provides a simple way how to execute backing bean methods with JavaScript.

```
<h:form>
  <p:remoteCommand name="rc" update="msgs"
    actionListener="#{remoteCommandView.execute}" />
  <p:growl id="msgs" showDetail="true" />
  <p:commandButton type="button" onclick="rc()" value="Execute"
    icon="ui-icon-refresh" />
</h:form>
```

- can be used also for partial processing of the form

```
<h:form id="form">
  <p:remoteCommand name="updateList" update="users" process="@this" />
  ...
function handleMessage(message) {
  ...
  updateList();
}
```



- Atmosphere framework is used for sending asynchronous messages from the server to the client.
- Requires special configuration (web.xml)

```
<servlet>
    <servlet-name>Push Servlet</servlet-name>
    <servlet-class>org.primefaces.push.PushServlet</servlet-class>
    <async-supported>true</async-supported>
</servlet>
<servlet-mapping>
    <servlet-name>Push Servlet</servlet-name>
    <url-pattern>/primepush/*</url-pattern>
</servlet-mapping>
```

- Uses annotations for defining push endpoints and message callbacks.

- `@PushEndpoint`
 - A class annotated with this annotation defines push channel, through which the server can contact the client.
- `@OnMessage`
 - When data are ready to be delivered, method annotated with this annotation will be called.
- Connection lifecycle annotations
 - `@OnOpen`
 - `@OnClose`
- `@PathParam`
 - parameters in path in URI

```
@PushEndpoint("/somepath/{room}/{user}")
@Singleton
public class ChatResource {
    @PathParam("room")
    private String room;
    @PathParam("user")
    private String username;
    ...
}
```

- API

- RemoteEndPoint

- represents client-side browser

- EventBus

- class for interacting with Push endpoints
 - uses Pub-Sub and Point-to-Point messaging domains

```
EventBus eventBus =  
    EventBusFactory.getDefault().eventBus();  
eventBus.publish("/counter", "Some data");
```

- Encoders and decoders

- has to be used when broadcasting a value

```
@PushEndpoint("/counter")  
public class CounterResource {  
    @OnMessage(encoders = {JSONEncoder.class})  
    public String onMessage(String count) {  
        return count;  
    }  
}
```

- Client side

- has to declare socket, through which it can accept the data.

```
<h:form id="form">
    <h:outputText id="out" value="#{globalCounter.count}" />
    <p:commandButton value="Click"
        actionListener="#{globalCounter.increment}" />
</h:form>

<p:socket channel="/counter">
    <p:ajax event="message" update="form:out" />
</p:socket>
```

- socket defines a channel
 - often convenient to use JavaScript

```
<p:socket onMessage="handleMessage" channel="/notify" />
<script type="text/javascript">
    function handleMessage(facesmessage) {
        facesmessage.severity = 'info';
        PF('growl').show([facesmessage]);
    }
</script>
```


- Update component(s) programmatically.
 - dynamic rendering

- Execute JavaScript from beans.

```
if (!FacesContext.getCurrentInstance().isPostback()) {  
    RequestContext.getCurrentInstance()  
        .execute("alert('This onload script is added from backing bean.')");  
}
```

- Add AJAX callback parameters.
- Scroll to a specific component after AJAX update.



- Allows to update component(s) programmatically.
 - dynamic rendering
 - `PrimeFaces.current().ajax().update()`

- Execute JavaScript from beans.

```
if (!PrimeFacesContext.getCurrentInstance().isPostback()) {  
    PrimeFaces.current()  
        .executeScript("alert('This onload script is added from backing bean.')");  
}
```

- Add AJAX callback parameters.
- Scroll to a specific component after AJAX update.

- <http://www.primefaces.org/showcase/>
- <http://primefaces.org/>
- <http://www.ocpsoft.org/prettyfaces/>
- <http://blog.hatemalimam.com/using-prettyfaces-with-primefaces-upload/>
- <https://jqueryui.com/themeroller/>

- <https://github.com/primefaces/primefaces/tree/master/primefaces-showcase/src/main/java/org/primefaces/showcase/service>
- https://primefaces.github.io/primefaces/10_0_0/#/.. /migrationguide/migrationguide
- <https://www.primefaces.org/showcase-ext/views/home.jsf>
- <https://github.com/primefaces-extensions/primefaces-extensions>
- <https://stackoverflow.com/questions/15146052/what-does-the-arrow-operator-do-in-java>
- <https://dzone.com/articles/java-8-lambda-functions-usage-examples>
- <https://showcase.omnifaces.org/push/socket>
- <https://stackoverflow.com/questions/30128395/identifying-and-solving-javax-el-propertyNotFoundException-target-unreachable>

Thank you for your attention!