

Conversa — How everything works

A reference for the architecture and each subsystem. For a click-by-click test script, see TESTING-GUIDE.md.

1. Stack & big picture

Layer	Choice
Framework	Next.js 16 (App Router, React 19, Server Components ...)
Language	TypeScript (strict)
Styling	Tailwind CSS v4 (CSS-first tokens in globals.css)
UI	Hand-built shadcn-style primitives in src/components...
Data / Auth	Supabase (Postgres, Auth, Realtime, Storage)
Server state	React Server Components + Server Actions
Client state	TanStack Query where needed; local component state e...
Forms/validation	React Hook Form + Zod (and Zod in server actions)
Charts	Recharts
Flow builder	dnd-kit

Conversa is **multi-tenant**: every row belongs to an [organisation](#), and Postgres **Row-Level Security (RLS)** enforces that users only ever read/write data for organisations they are an active member of. The UI additionally gates features by role (capabilities), but RLS is the real security boundary.

2. Directory map

```
src/
  app/
    (marketing)/      Public site (home). Own layout with nav + footer.
    (auth)/           login, register, forgot-password, reset-password
    onboarding/       Create-organisation wizard (step 1 functional)
    auth/callback/route.ts Exchanges email/reset codes for a session
    app/              Authenticated product; layout loads app context
      inbox/          Shared inbox (4-column) + realtime
      contacts/ reports/ ai-agents/ knowledge/ chatbots/[id]/
      broadcasts/ integrations/ settings/ notifications/
  components/
    ui/               Button, Input, Card, Badge, Avatar, Menu, Skeleton...
    app/              PrimarySidebar, Topbar, PageHeader, EmptyState, nav
    inbox/            Composer, ConversationActions, meta, realtime
    chatbots/         FlowBuilder, NodeCard, SettingsPanel, Simulator
    reports/          Recharts wrappers
    marketing/ brand/
```

lib/	
supabase/	client (browser), server, admin, middleware, types
auth/	context (session/org), roles (capabilities), actions
data/	conversation queries + server actions
chatbots/	types, geometry, validate, simulate, actions
onboarding/	validations/
supabase/migrations/	0001-0009 ordered SQL (schema, RLS, realtime)
scripts/	apply-migrations, seed, gen-types, emit-test-message
docs/	this folder

3. Request lifecycle & auth

- **Middleware** (`src/middleware.ts` → `lib/supabase/middleware.ts`) runs on every request, refreshes the Supabase session cookie, and redirects unauthenticated users away from `/app/*` and `/onboarding`. (It no-ops before Supabase env vars are set so the app is still inspectable.)
- **Server Components** read data with a `**request-scoped Supabase server client**` (`lib/supabase/server.ts`) that carries the user's cookies, so all queries run **as the signed-in user under RLS**.
- ``getAppContext()`` (`lib/auth/context.ts`, React-cached per request) resolves the user, their `user_profiles` row, all active memberships, and the **active organisation** (from the `conversa_org` cookie, else the default membership). It redirects to `/login` when signed out and `/onboarding` when the user has no organisation.
- **Mutations** are **Server Actions** ("use server"). They re-resolve the context, perform the write under RLS, write an `audit_logs` row where relevant, and call `revalidatePath` so the affected Server Components re-render.

Auth flows

`lib/auth/actions.ts` wraps Supabase Auth: `signInAction`, `signUpAction`, `signOutAction`, `forgotPasswordAction`, `resetPasswordAction`. Email confirmation and password-reset links land on `/auth/callback`, which exchanges the code for a session and redirects onward.

4. Multi-tenancy & RLS (the security model)

- Every tenant table has an `organisation_id`.
- Membership lives in `organisation_members` (`user_id`, `organisation_id`, `role`).
- Helper functions (SECURITY DEFINER, in `0002`):
 - `is_org_member(org)` — is the caller an active member?

- `has_org_role(org, roles[]) / can_manage_org(org)` — role checks.
- `0008_rls_policies.sql`:
 - A loop enables RLS and adds a generic `org_isolation` policy (`using/ with check is_org_member(organisation_id)`) to **every** table that has an `organisation_id`.
 - Junction/child tables without that column (e.g. `contact_tags`, `conversation_participants`, `ticket_status_history`) are gated by an `EXISTS` join to their parent.
 - `organisations`, `user_profiles`, `roles`, and reference tables (`permissions`, `subscription_plans`) get bespoke policies.
 - **Service role** (used only by `scripts/seed.ts` and — in future — inbound webhooks / the public widget endpoint) bypasses RLS by design and is never exposed to the browser.

Roles → capabilities (UI gating)

`lib/auth/roles.ts` maps the 7 roles (Platform Admin, Owner, Org Admin, Support Manager, Support Agent, Marketing, Reporting) to capability keys (`inbox.view`, `automations.manage`, `broadcasts.manage`, ...). `PrimarySidebar` shows only the modules a role can access; server actions still re-check on the server.

5. Shared inbox

- **Data** (`lib/data/conversations.ts`): `listConversations(org, user, view)` applies the selected view (mine / unassigned / waiting / resolved / AI-handled / spam / all) as query filters; `getViewCounts` returns badge counts; `getConversation` loads a thread with messages, notes and contact.
- **Page** (`app/app/inbox/page.tsx`) is a Server Component reading `?view=` and `?c=` from the URL, rendering the four columns: views · conversation list · workspace (timeline + composer) · details.
- **Actions** (`lib/data/conversation-actions.ts`): `sendReplyAction`, `addNoteAction`, `setStatusAction`, `setPriorityAction`, `assignToMeAction` — each writes under RLS and revalidates.
- **Composer** (client) supports Reply, Internal note, **AI draft (demo)**, and “Send & resolve”.

Realtime

-

`0009_realtime.sql` adds `messages`, `conversations`, `internal_notes` to the `supabase_realtime` publication with `REPLICA IDENTITY FULL`.

- `components/inbox/realtime.tsx` subscribes (browser client) to `postgres_changes` for those tables filtered by `organisation_id`, sets the Realtime JWT so **RLS applies to the stream**, and debounces a `router.refresh()` on any change — so the server-rendered inbox re-queries and the list order, previews, counts and open thread all update live. A green
 - **Live** indicator shows connection state.
 - Test it with `npx tsx scripts/emit-test-message.ts "..."` while the inbox is open (see the testing guide).
-

6. AI (demo mode)

- `AI_PROVIDER=demo` by default. Demo responses are ****deterministic and clearly labelled ("AI · demo mode") and are never**** presented as coming from a live model. In the inbox, "AI draft" inserts a labelled draft you must review before sending; AI-handled conversations render an "AI agent · demo" bubble and an `ai_runs` row is recorded.
 - The schema (`ai_agents`, `ai_agent_versions`, `ai_agent_sources`, `ai_runs`, `ai_feedback`) plus knowledge tables model a grounded-agent design: answer only from approved sources, record every run with a confidence score, and escalate.
 - To enable a live provider later: set `AI_PROVIDER=anthropic` and `ANTHROPIC_API_KEY`, then implement the provider adapter behind the same interface. Demo mode remains the fallback when no key is present.
-

7. Visual chatbot builder

- **Model** (`lib/chatbots/types.ts`): `FlowDefinition = { nodes, edges }`. 18 node types with a catalogue (`NODE_DEFS`) describing icon, colour, category, output handles and default data.
- **Editor** (`components/chatbots/flow-builder.tsx`): a canvas with pan (drag background), zoom, minimap and dotted grid. Nodes are dragged with **dnd-kit** (delta ÷ scale committed to `position`). Edges are created by ****click a source handle → click a target node****, drawn as SVG bezier curves with arrowheads; click an edge to delete it. Branch handles exist for Condition (True/False), Multiple Choice (per option) and Business Hours (Open/Closed).
- **Validation** (`lib/chatbots/validate.ts`): missing/duplicate Start, dangling edges, dead-ends and unreachable nodes.

- **Simulator** (`lib/chatbots/simulate.ts` + `components/chatbots/simulator.tsx`):

a pure, deterministic interpreter that runs the flow as a chat — great for testing branches without publishing.

- **Persistence** (`lib/chatbots/actions.ts`): draft `definition` is saved on the `chatbot_flows` row; **Publish** validates, writes a `chatbot_versions` row and bumps `current_version`; **Duplicate** clones the flow. Definitions are versioned JSON with relational ownership/status/audit.

7b. Automation rules

- **Model**: ``automation_rules` (trigger_type, trigger_config, conditions[], actions[], status, position)` with an `automation_runs`` history table.
- **Catalogue** (`lib/automations/catalogue.ts`): 10 triggers, 7 condition fields × 4 operators, and 12 action types.
- **List** (`/app/automations`): rules ordered by `position`, **drag-to-reorder** (dnd-kit sortable, persisted), enable/disable switch, delete.
- **Editor** (`/app/automations/[id]`): a **When** → **If** → **Then** form — pick a trigger (+inline config), add AND-ed conditions (field/operator/value), and add actions (each with its own parameter). Saved via a server action.
- **Test** (`lib/automations/evaluate.ts` + `testRuleAction`): evaluates the rule's conditions against your most recent conversation, records an `automation_runs` row (success/skipped), and shows which actions *would* run.
- The live event-driven engine (firing rules automatically on events, with the `automation_runs.depth` loop-protection column) is a labelled build-out; ordering, storage, evaluation and history are in place.

7c. Broadcast composer

- **Audience** (`lib/broadcasts/audience.ts`): `resolveAudience` resolves the eligible recipients for a channel + segment (tags / company / search), **enforcing consent** (`consent_status = opted_in`) and the ***suppression list***, and requiring a usable channel identifier. It returns the eligible contacts plus excluded counts (no consent / suppressed / no address).
- **Personalisation** (`lib/broadcasts/personalize.ts`): `{{first_name}}`, `{{last_name}}`, `{{company}}` are detected and substituted per recipient; the composer shows a live preview.
- **Composer** (`/app/broadcasts/[id]`): message (channel, optional approved template, body + variable chips + preview) · audience (tag filters, consent toggle, **Preview audience** with live counts) · schedule (send now / schedule,

frequency cap) · a right rail for **send test**, **approval gate**, and **dispatch**.

- **Dispatch** (`dispatchBroadcastAction`): requires approval, materialises the eligible audience into `broadcast_recipients` (idempotent upsert per broadcast+contact), then schedules or **simulates delivery** (demo — no live provider is contacted) and records per-recipient statuses.
- **Delivery tracking**: metrics (queued/sent/delivered/read/replied/failed/opted-out) are aggregated from `broadcast_recipients` and shown as a stacked bar + legend.

7d. CSV contact import

- **Parser** (`lib/contacts/csv.ts`): a dependency-free RFC-4180-ish parser (quotes, escaped quotes, embedded commas/newlines, BOM), plus header auto-mapping via synonyms and an email validator.
- **Wizard** (`/app/contacts/import`, client): **Upload** (drag/drop or picker, ≤5 MB, `.csv` only) → **Map & review** (auto-guessed column mapping, a live preview, and validation counts: ready / invalid email / no identifier / in-file duplicates) → **Consent** capture (unknown vs opted-in + source) → **Import**.
- **Import** (`importContactsAction`): validates each row (needs email or phone), **de-duplicates against existing contacts by email/phone** (updates matches, merging only provided fields; inserts the rest), upserts and links **tags**, and writes **consent_records** when opted-in. Returns a created/updated/skipped/tags summary. Capped at 5000 rows; a production build would stream larger files.

8. Data model (overview)

~60 tables across `0001–0007`, grouped:

- **Tenancy**: organisations, organisation_members, user_profiles, roles, permissions, teams, team_members, agent_availability
- **Channels/contacts**: inboxes, channels, channel_connections, contacts, contact_channels, contact_custom_fields, contact_field_values, tags, contact_tags
- **Conversations**: conversations, conversation_participants, conversation_tags, messages, message_attachments, message_status_events, internal_notes, mentions, tickets (+tags/assignments/status_history), saved_replies, saved_views
- **AI/knowledge**: ai_agents (+versions/sources), ai_runs, ai_feedback, knowledge_collections/articles (+versions)/documents/chunks/gaps
- **Automation/bots**: chatbot_flows (+versions/runs), automation_rules (+runs)

- **Outbound/platform:** broadcasts (+recipients), message_templates, consent_records, suppression_entries, sla_policies, business_hours, notifications, webhook_endpoints, webhook_events, integration_logs, audit_logs, subscription_plans, organisation_subscriptions, usage_records

Conventions: UUID PKs, `created_at/updated_at` (auto-touched by a trigger), FKs with sensible `on delete`, useful indexes (incl. trigram search on contacts and knowledge), soft-delete via `deleted_at` where appropriate, and a `webhook_events.idempotency_key` unique constraint for idempotent inbound events.

9. Channels (adapter pattern)

Channels are modelled generically (`channel_type` enum: whatsapp, email, web_chat, messenger, instagram, sms). Each `channel` has a `channel_connection` holding **non-secret** config and a `secret_ref` (never the secret itself).

Unconnected channels run a **demo adapter** (clearly labelled).

Live WhatsApp inbound webhook (implemented)

`/api/webhooks/whatsapp` (Node runtime) implements the **official Meta WhatsApp Business Cloud API** shape — no unofficial automation:

- **GET** — the verification handshake: echoes `hub.challenge` when `hub.verify_token` matches `WHATSAPP_VERIFY_TOKEN`.
 - **POST** — verifies the `X-Hub-Signature-256` HMAC against the raw body using `WHATSAPP_APP_SECRET` (timing-safe) and returns 401 on mismatch, then ingests:
 - **Idempotent** — each provider message id is stored in `webhook_events` (unique key); replays are no-ops (and `messages.external_id` is unique too).
 - **Routing** — `metadata.phone_number_id` → `channel_connections.config` resolves the org/channel/inbox.
 - **Mapping** — finds or creates the contact (by WhatsApp id) and an open conversation, inserts the inbound message, and updates the conversation. Because `messages` is in the realtime publication, the inbox updates live.
 - **Statuses** — `sent/delivered/read/failed` update the message and append a `message_status_events` row.
 - Test locally without a real number: `npm run wa:sim` (and ``npm run wa:sim status`` maps the demo WhatsApp channel to a test `phone_number_id`, signs a sample payload, and POSTs it. Email (Resend) and Meta Messenger/Instagram plug in behind the same adapter shape.
-

10. Environment & scripts

See `.env.example` for all variables. Key ones:

`NEXT_PUBLIC_SUPABASE_URL`, `NEXT_PUBLIC_SUPABASE_ANON_KEY` (public),
`SUPABASE_SERVICE_ROLE_KEY`, `SUPABASE_DB_URL` (server-only secrets),
`AI_PROVIDER` (demo by default).

Command	Purpose
<code>npm run dev</code>	Dev server
<code>npm run build</code>	Production build
<code>npm run typecheck</code>	<code>tsc --noEmit</code>
<code>npm run lint</code>	ESLint
<code>npm run db:push</code>	Apply <code>supabase/migrations/*.sql</code> (idempotent)
<code>npm run db:seed</code>	Seed the demo org (clears + recreates it)
<code>npm run db:types</code>	Generate typed DB definitions from the live schema

> **Windows note:** on this machine `npm` intermittently drops from the shell
> PATH. If `npm run dev` fails with “npm not found”, launch Next directly:
> `node node_modules/next/dist/bin/next dev`.

10b. Testing

- **Vitest** (`tests/unit`, `tests/integration`):
 - **Unit** (no DB): role capabilities, the CSV parser + auto-mapping + email validation, chatbot validation + simulation, automation condition evaluation, broadcast audience resolution (consent/suppression/tags via a stub client) + personalisation, and the Zod auth schemas.
 - **Integration** (live Supabase, auto-skipped without env): ****RLS tenant isolation**** — an ephemeral outsider in another org cannot read or write grovefield's conversations/contacts/messages, while a member can; and **ticket transitions** — the status-history trigger fires on change (and not on a no-op), plus a member message write+read under RLS.
 - **Playwright** (`tests/e2e`): critical **auth** flows (protected-route redirect, sign-in, sign-out) and **inbox** (open a conversation + send a reply, view filtering). Config reuses a running dev server.
 - Commands: `npm run test:unit`, `npm run test:integration`, `npm test` (both), `npm run test:e2e`. E2E needs `npx playwright install chromium` once.

11. What's live vs. still a build-out

Fully working: design system · auth (register/login/verify/reset) · onboarding org creation · org switching & role-gated nav · shared inbox (reply/note/AI-draft/assign/priority/resolve/reopen) · **inbox realtime** · contacts table · reports (real metrics + charts) · **chatbot builder** (canvas/validate/test/save/publish/version) · **automation-rule builder** (triggers/conditions/actions, reorder, test, run history) · **broadcast composer** (consent-enforced audience, personalisation, approval, scheduling, delivery tracking) · **CSV contact import** (mapping, validation, dedupe, tags, consent) · data-backed lists for AI agents, knowledge, integrations, settings.

The **WhatsApp inbound webhook is live** (signature-verified, idempotent, maps to conversations); outbound WhatsApp send and the other channel adapters follow the same pattern.

Honest build-outs (labelled in the UI): the live event-driven automation engine (rules are built, ordered, evaluated and tested now) · outbound message delivery to providers (broadcasts record recipients and simulate delivery in demo mode) · email/Messenger/Instagram adapters · CSV export · knowledge document upload & re-indexing · full settings subpages · presence/typing indicators.

Having security building blocks (RLS, audit logs, consent/suppression tables) does **not** by itself make the software compliant or certified.