

# Conversa — Deploying to Vercel

The repo is ready to deploy as-is. It uses the same Supabase project that's already migrated and seeded, so there's **no database step** — you only set env vars.

## 1. Import the repo

- Go to <<https://vercel.com/new>> and **Import** [jarrodthompson/conversa](#).
- Framework preset: **Next.js** (auto-detected). Leave build/output settings default.
  - `.npmrc` (`legacy-peer-deps=true`) is committed so Vercel's `npm install`

resolves dev-dependency peers exactly like local.

## 2. Environment variables

Add these under **Project** → **Settings** → **Environment Variables** (Production + Preview).

### Required (runtime)

| Name                          | Value                                                                                         |
|-------------------------------|-----------------------------------------------------------------------------------------------|
| NEXT_PUBLIC_SUPABASE_URL      | <a href="https://skxholkfrcwemyjybdx.supabase.co">https://skxholkfrcwemyjybdx.supabase.co</a> |
| NEXT_PUBLIC_SUPABASE_ANON_KEY | your Supabase anon/publishable key                                                            |
| SUPABASE_SERVICE_ROLE_KEY     | your Supabase service-role key (secret)                                                       |
| NEXT_PUBLIC_APP_URL           | your Vercel URL, e.g. <a href="https://conversa.vercel.app">https://conversa.vercel.app</a>   |
| NEXT_PUBLIC_APP_NAME          | Conversa                                                                                      |
| AI_PROVIDER                   | demo                                                                                          |
| CRON_SECRET                   | a long random string (enables the cron sweep — see §...                                       |

- > Set `NEXT_PUBLIC_APP_URL` to the real domain after the first deploy, then redeploy —
- > it's used for auth email (verify/reset) redirect links.

### Optional (channels — leave unset to stay in demo mode)

`WHATSAPP_PHONE_NUMBER_ID`, `WHATSAPP_ACCESS_TOKEN`, `WHATSAPP_VERIFY_TOKEN`,  
`WHATSAPP_APP_SECRET`, `RESEND_API_KEY`, `EMAIL_FROM`, `RESEND_WEBHOOK_SECRET`,  
`META_APP_SECRET`, `META_PAGE_ACCESS_TOKEN`.

- > `SUPABASE_DB_URL` is **not** needed at runtime — it's only for local
- > `npm run db:push / db:seed`. Don't add it to Vercel.

## 3. Supabase auth redirect URLs

In the Supabase dashboard → **Authentication** → **URL Configuration**:

- **Site URL**: <https://<your-vercel-domain>>

- **Redirect URLs:** add <https://<your-vercel-domain>/auth/callback>

Without this, email confirmation and password-reset links won't complete in production.

## 4. Cron — time-based automation sweep

`vercel.json` schedules the sweep every 15 minutes:

```
{ "crons": [{ "path": "/api/cron/sweep", "schedule": "*/15 * * * *" } ] }
```

- When a `CRON_SECRET` env var exists, **\*\*Vercel automatically sends `Authorization: Bearer <CRON_SECRET>` with each cron invocation, which the endpoint verifies — so no extra wiring is needed.**

- **Plan note:** Vercel **Hobby** runs crons at most **once per day**; change the schedule to e.g. `0 * * * *` (hourly) or `0 9 * * *` (daily) if the 15-minute cadence is rejected. **Pro** supports the 15-minute schedule.

- You can trigger it manually any time:

```
curl -H "Authorization: Bearer <CRON_SECRET>" https://<domain>/api/cron/sweep
```

## 5. Channel webhooks (only when going live)

Point providers at your deployed URLs and set the matching env vars:

- WhatsApp: <https://<domain>/api/webhooks/whatsapp> (verify token = `WHATSAPP_VERIFY_TOKEN`)
- Email (Resend): <https://<domain>/api/webhooks/email> (signing secret = `RESEND_WEBHOOK_SECRET`)

## 6. Deploy

Click **Deploy**. Every push to `main` redeploys automatically. After the first deploy, set `NEXT_PUBLIC_APP_URL` to the real domain and redeploy once.