



2.07 Fueling

1. Purpose

The purpose of the Standard Operating Procedure (SOP) is to identify the Hazards and define the steps in fueling opportunities .

2. Scope

This procedure is intended for the use for all Silverpoint employees .

3. Hazard Assessment & Identification

- Pinch Points
- Cattle and Gates
- Weather
- Fuel Spills and Splashes
- Open Pits
- Communication
- Flammable Material
- Time of day

4. EHS Requirements

- F/R Coveralls
- Steel Toed Boots .
- Safety Glasses .
- Gloves .
- Hard hat

5. References

- Silverpoint Corporate Codes of Practice
- Alberta OH&S
- Silverpoint Task List
- Silverpoint THA 2.07



6. Procedure

This procedure will show you the different fueling opportunities when working in shallow gas and long-term oil/gas wells, fueling procedure, reporting and communication between operators.

6.1. Fueling Locations

- 6.1.1. Shallow gas projects: Fuel trailer at cement pit or remote sump locations.
- 6.1.2. Long term wells: fuel stations.
- 6.1.3. On certain projects the oil company will supply fuel; Fuel will either be set up at a central fuel location or will be available from the rig.

6.2. Opportunities

- 6.2.1. When working on a shallow gas project the best time to go fuel up is after you have cleaned the tanks after surface cement.
- 6.2.2. On long term wells you will need to coordinate with the drilling supervisor to arrange to leave location to get fuel.
- 6.2.3. There may be an opportunity to fuel up with the fuel truck, right on location, The rig usually gets fuel every 3 to 4 days, coordinate with the rig manager to order clear fuel for your truck.
- 6.2.4. When you are working on long term wells, you have to remember that you could be busy for long periods of time so make sure that you have fuel. Companies have been known to charge back any cost involved for lost drilling time because a vacuum truck has ran out of fuel.
- 6.2.5. When possible, fuel up during daylight hours, if this is not possible be sure to have a flashlight available to monitor fuel level.

6.3. Operating Trailer mounted Fuel Pumps.

- 6.3.1. Park truck so you can reach both tanks with the fuel hose.
- 6.3.2. Shut off engine.
- 6.3.3. Remove fuel pump lock.
- 6.3.4. Zero fuel meter by pushing the reset button.
- 6.3.5. Check that the fuel nozzle is closed, and fuel pump is turned off.
- 6.3.6. Fuel trailer are equipped with a 12-volt male plug on an extension cord that will attach to a female plug hard wired to the truck's battery box.
- 6.3.7. Plug the two electrical connectors together.



- 6.3.8. Lay out fuel hose, remove fuel cap and place the fuel nozzle in the fuel tank. Turn fuel pump switch on.
- 6.3.9. Squeeze fuel nozzle to start fueling truck.

Operator must monitor fueling at all times. Do not leave fuel nozzle unattended for any reason. If you must leave the fueling process, close the fuel nozzle, turn off the fuel pump and place nozzle back in the fuel trailer.

Do not block open the fuel nozzle for any reason, the hold open features have been removed from Silverpoint fuel pumps to ensure operators are present during the fueling process.

- 6.3.10. Fill tank to no more than 90% capacity, this will leave room for fuel expansion.
- 6.3.11. Replace fuel tank cap and repeat procedure for other fuel tanks.
- 6.3.12. When fueling is complete turn off pump, place nozzle back in holder, replace fuel pump lock and record amount of fuel used on log book

6.4. Fueling at a Fuel Station

- 6.4.1. Park truck and shut off engine
- 6.4.2. Check that the fuel nozzle is closed, and fuel pump is turned off.
- 6.4.3. Remove fuel cap and place nozzle in tank.
- 6.4.4. Follow instruction for fuel station card lock system to activate pump
- 6.4.5. Squeeze fuel nozzle to start fueling truck.

Operator must monitor fueling at all times. Do not leave fuel nozzle unattended for any reason. If you must leave the fueling process, close the fuel nozzle, turn off the fuel pump and place nozzle back in the proper holder.

Do not block open the Fuel Nozzle

- 6.4.6. Fill tank to no more than 90% capacity, this will leave room for fuel expansion.
- 6.4.7. Replace fuel tank cap and repeat procedure for other fuel tanks.



6.4.8. When fueling is complete turn off pump , place nozzle back in holder and record amount of fuel used on logbook .

6.4.9. **Use a Spotter** if you need to back up to leave the fueling station .

6.5. Recording

6.5.1. As part of your daily logbook , you are required to record the amount of fuel, where (including province) and at what time .

6.5.2. Always keep track of how much fuel is left in the tank; if it is low, you must report it to your supervisor so we can make arrangements to get fuel out to the tank before it runs out.

6.6. Communications

6.6.1. Communication is very important when working with another operator . It should be decided when they will fill up, the day shift usually has more time to go fuel up. Regardless of what is decided be sure to check your fuel level at the start of each shift .

6.6.2. Be sure to inform the drilling supervisor when you are leaving location to fuel up, let them know approximately how long you will be gone .

6.6.3. Do not postpone fueling because you think you are too busy, or someone tells you there is not enough time to fuel up. Keeping fuel in the truck should be at the top of your priority list, consider half a tank is an empty tank .

6.7. **DO NOT use the company fuel card to fuel up your personal vehicle or fuel up personal vehicle from one of the remote tanks , this is considered theft and will result in criminal charges as well as possible dismissal from Silverpoint .**

Remember : if you are in doubt about what to do, call your Supervisor