



5.04 General Shack Information

1. Purpose

The purpose of the Standard Operating Procedure is to identify the hazards and define the steps in winterizing shacks

2. Scope

This procedure is intended for use by Silverpoint employees .

3. Hazard Identification

- Physical Stress .
- Personal Injury .
- Equipment Damage .
- Equipment Failure /Stress .
- Eye Injury .
- Contaminate Water Supply .
- Slips, Trips and Falls .

4. EHS Requirements

- Fire Retardant Coveralls .
- Steel Toed Boots .
- Safety Glasses .
- Rubber Gloves .
- Hard Hat .
- Hearing Protection .
- Follow Procedures .
- Isolate Using Valves .



- PMI's.

5. References

- Silverpoint Corporate Codes of Practice
- Alberta OH&S
- Silverpoint Task List
- Silverpoint THA 1.17

There is no smoking permitted in any Silverpoint Shacks or Equipment

6. Procedure

This procedure may need to be modified slightly for different shacks as the water systems are not all the same. Procedures will be posted in each shack. Please consult the maintenance department if you have any questions regarding this procedure. Shack will be winterized regardless of weather conditions any time they are shut down between October 01 and April 30.

If weather condition warrant winterizing outside of this time frame, it is the operator's responsibility to complete the trailer winterization .

- 6.1. Turn off power or propane to hot water tank or hot water on demand .
- 6.2. Turn off water pump .
- 6.3. Drain main water tank and isolate .
- 6.4. Drain hot water tank and isolate so as to not fill tank with RV antifreeze .
- 6.5. Shacks have a primer funnel that you pour the RV antifreeze into, and others may have a small hose you can put in the RV antifreeze jug. Fill the pump, turn on power to the pump and continue filling until it reaches the shut off pressure , flush one set of taps at a time, starting with the furthest from the pump .

Example: in the kitchen you will slowly open the cold tap until RV antifreeze comes out then slowly open the hot tap until RV antifreeze comes out. You will need to go back and check your RV antifreeze level, so you don't lose prime on the pump.



- 6.6. Fill water pump with RV antifreeze and turn the pump on. Flush toilet to empty toilet tank. Be sure to close water valve on toilet as soon as it is flushed with RV antifreeze, or you will fill the toilet tank with RV antifreeze.
- 6.7. RV antifreeze will have to be pumped through shower head (on single control tap you need to turn the control to hot and cold to fill both water lines with RV antifreeze). Drain showerhead if there is a drain for it.
- 6.8. Repeat on all taps in the shack until you have RV antifreeze through out the water system. Kitchen sink, Shower, Bathroom sink, Toilet and Washing Machine if equipped.
- 6.9. If the shack has a washing machine you will need to select the fill setting and start the washer so the RV antifreeze flows into the wash tub, this must be done on the hot water setting and the cold-water setting (do not use the warm setting as one line may flow more than the other and you will still have water in one line). Once you have flushed both lines into the washing machine you need to select the pump out or discharge cycle (SPIN) on the washer to pump the water out of the washer tub. When the washer is empty, pour 2 liters of RV antifreeze into the tub and repeat the pump out procedure, this will fill the washing machine discharge pump with RV antifreeze to prevent it from freezing.
- 6.10. Pour 1 liter of RV antifreeze into each sink and the shower drain to flush the "P" traps, also pour some into the toilet bowl and tank.

Most shacks will use between 8 to 12 liters of RV antifreeze to completely winterize the system.

- 6.11. Turn off power to the water pump; open all taps and the drain on the water pump.
- 6.12. Drain all lines after flushing the system.
- 6.13. Shack will be winterized any time they are shut down between Oct. 01 – April. 30
- 6.14. Setup: try to park on level ground, block wheels, level trailer with jack, try to find a high spot if possible.
- 6.15. Trailer paperwork tube: know where it is on the shack your hauling,
- 6.16. Check before leaving shop: suspension & tire inspection, greasing, Lost bearing caps, Trailer brakes, master cylinder fluid level, tug test,
- 6.17. Towing: shacks add a lot of weight to the unit so drive slower, OD sign must be on the front of the truck while towing and must be folded up or removed when not towing, corner flags must be on all four corners of the shack and in good condition, When hauling over dimensional load you are required to stop and perform a walk around check every 2 hours, be sure to record it in your log book as a 15 minutes walk around VI
- 6.18. Hitch: look for cracks, bring it home with truck if shut down. Make sure that the hitch is on the truck properly, that the hitch is closed the correct way that the safety chains are hooked up the right way. If you are unsure how to check for wear, ask. Safety chains must be crossed so that they cradle the trailer if it should come unhooked. Check both hook latches to make sure they are working properly.



- 6.19. Safety board : Emergency Notification List, Guiding Principles for Worker Safety, safety meetings , Safety Policy
- 6.20. Water system : do not travel with full tank, drain when finished with water . If the shack is equipped with an electric water heater , ensure that the breaker is off until the tank is filled with water , or you will burn out the element .
- 6.21. Generators : be sure to check it over before starting , maintenance
- 6.22. Heating system : Understand how to start furnace , always read the instructions , to be serviced by a qualified person if repairs are needed
- 6.23. A/C: will be tested yearly at the shop . clean out fridge before leaving shack , clean stove , and oven out , empty garbage ,
- 6.24. Breaker box: turn off water pump and hot water tank
- 6.25. Propane tanks : must be shut off while traveling or parked indoors , check propane level regularly and before you head to a distant location Lay down TV, toilet tank lid, anything that might fall, Electric hot water tanks must be turned off before draining or else heating element will burn out.
- 6.26. Shack Insurance : Personal items in the shacks are not covered under Silverpoint insurance . In fact, Silverpoint is unable to obtain insurance to cover other people's content in our shacks and trucks . This means that in the event that any of our trucks or shacks is destroyed anything you may have in them will be lost . You may be able to claim your belongings through your home insurance but to be on the safe side you might want to consider getting content insurance . Content insurance will cover your belongings in case of destruction of Silverpoint equipment . The same thing goes for electronic equipment such as Xboxes . If the rig has a power spike and it damages your Xbox , then you are not covered . Silverpoint recommends that you purchase a good surge protector for your shacks if you plan on running any expensive electronics . It is also recommended that you do not keep anything of immense personal value in your shacks or trucks . If you are unsure of your level of personal coverage , check with your personal insurance provider to see if you are covered .
 - 6.26.1 . Before you leave the shop , know where the insurance and registration are kept . Usually , it is kept in the trailer tube mounted somewhere on the shack . Be sure you know where it is .
- 6.27. Cleaning : you are required to keep your shack clean , as the driver /operator who will be switching you out will not stay in a dirty shack . Also , it is in your shack PMI to keep a clean shack .
- 6.28. Ensure any damage to the shack is marked in the wellsite trailer PMI i.e., suspension and tire inspection , lost bearing caps , missing lug nuts , master cylinder fluid level , any damage , or missing parts .
- 6.29. Ensure that everything that might fall or move during the move is secure or tied down to prevent damage .
- 6.30. Should you be shut down for a period of time , ensure that you empty out the fridge of all perishables to prevent spoilage .

Remember : if you are in doubt about what to do, call your supervisor



5.04 General Shack Information