V10 · fixed CSD implementation versus original RTL · full paired table

Every constant/context pair · wrapping unsigned32 arithmetic · Δ = CSD − original · LUT4 primary, carry descriptive

K	Original context	Orig. LUT4	CSD LUT4	Δ LUT4	Carry orig. → CSD	Δ carry
11	Kx	119	92	**-27**	29 → 30	+1
11	Kx + y	176	148	**-28**	30 → 29	-1
11	K(x − y)	182	155	**-27**	60 → 61	+1
11	K((x & 63) − y)	181	154	**-27**	60 → 61	+1
44	Kx	111	86	**-25**	27 → 28	+1
44	Kx + y	141	141	**+0**	56 → 28	-28
44	K(x − y)	170	145	**-25**	56 → 57	+1
44	K((x & 63) − y)	169	144	**-25**	56 → 57	+1
85	Kx	206	137	**-69**	28 → 27	-1
85	Kx + y	228	200	**-28**	29 → 28	-1
85	K(x − y)	247	200	**-47**	59 → 58	-1
85	K((x & 63) − y)	246	199	**-47**	59 → 58	-1
340	Kx	190	127	**-63**	26 → 25	-1
340	Kx + y	220	186	**-34**	55 → 26	-29
340	K(x − y)	229	186	**-43**	55 → 54	-1
340	K((x & 63) − y)	228	185	**-43**	55 → 54	-1

K	Original context	Orig. LUT4	CSD LUT4	Δ LUT4	Carry orig. → CSD	Δ carry
341	Kx	219	180	**-39**	26 → 26	+0
341	Kx + y	284	240	**-44**	30 → 28	-2
341	K(x − y)	281	243	**-38**	57 → 57	+0
341	K((x & 63) − y)	281	242	**-39**	57 → 57	+0
511	Kx	299	62	**-237**	27 → 30	+3
511	Kx + y	366	94	**-272**	30 → 30	+0
511	K(x − y)	389	117	**-272**	58 → 61	+3
511	K((x & 63) − y)	389	117	**-272**	58 → 61	+3
1364	Kx	206	166	**-40**	24 → 24	+0
1364	Kx + y	232	222	**-10**	53 → 26	-27
1364	K(x − y)	260	225	**-35**	53 → 53	+0
1364	K((x & 63) − y)	260	224	**-36**	53 → 53	+0
2044	Kx	278	58	**-220**	25 → 28	+3
2044	Kx + y	306	90	**-216**	54 → 29	-25
2044	K(x − y)	362	109	**-253**	54 → 57	+3
2044	K((x & 63) − y)	362	109	**-253**	54 → 57	+3

Fixed eight-constant × four-context grid. No pair filtering or outcome-based rewrite selection. No population CI, device timing or CPU speedup claim.
Universal actual-RTL pair equality is separate from 2,148 sampled mapped-netlist checks per arm. Full original/CSD formulas remain in figure-data.json.