

Here is the comprehensive, field-by-field mapping across all the provided attachments. This table is designed to support a streamlined data pipeline, allowing you to drop operational noise at the routing layer (e.g., via Cribl) before it consumes ingest quota in observability platforms like Azure Data Explorer or Splunk Core.

The mapping aligns with the **OCSF Email Activity (4009)** class.

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
a	MTA Metric	Attachment index sequence number used internally by Proofpoint/Sendmail to iterate through file arrays.	Drop: Purely an operational counter. Retain actual attachment names/hashes, not the index number.	N/A
adkim	Auth	DMARC DKIM alignment mode, indicating whether the sender requires strict (s) or relaxed (r) alignment.	Keep: Highly relevant for troubleshooting spoofing investigations and understanding why DMARC evaluations failed.	unmapped.dmarc_adkim
arc_override	Auth	Authenticated Received Chain (ARC) override flag, indicating if local policy bypassed standard ARC results.	Keep: Critical for understanding authentication chains on forwarded emails (e.g., mailing lists).	unmapped.arc_override
arc_result	Auth	The overall outcome of the Authenticated Received Chain evaluation (e.g., pass, fail).	Keep: Essential for tracking the integrity of email authentication across multiple hops.	auth_info.arc_statuses
arc_result_detail	Auth	Granular string output explaining the exact reason for the ARC result outcome.	Keep: Provides necessary context for analysts investigating complex forwarding spoof attempts.	unmapped.arc_result_detail
arc_trusted_flag	Auth	Boolean flag indicating whether the receiving MTA trusts the	Keep: Validates if the upstream forwarder is a sanctioned	unmapped.arc_trusted_flag

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		upstream ARC sealer.	partner.	
archive_count	MTA Metric	Internal marker tracking the number of archives processed within the message.	Drop: Redundant operational noise if file extraction is handled elsewhere.	N/A
archive_depth	MTA Metric	Tracks the nesting level of archives (e.g., a zip inside a rar).	Drop: Unless specifically building alerts for zip-bomb evasion techniques, this is excess noise.	N/A
aspf	Auth	DMARC SPF alignment mode, indicating strict (s) or relaxed (r) domain matching.	Keep: Needed to determine if a message failed DMARC due to a subdomain mismatch vs. an unauthorized IP.	unmapped.dmarc_aspf
B	Routing	Highly obfuscated internal logic state marker (often indicating a Block/Bounce module action).	Drop: Relies entirely on proprietary vendor logic; rely on standard disposition fields instead.	N/A
bits	Encryption	Identifies the key length (e.g., 256) established during the STARTTLS handshake.	Keep: Required for hunting weak encryption ciphers or downgrade attacks in transit.	connection_info.tls_key_length
bodytype	Context	The MIME classification of the email payload (e.g., multipart/mixed, text/html).	Keep: Useful for identifying anomalous message structures or filtering out plain-text administrative alerts.	file.mime_type or unmapped.bodytype
C	Routing	Obfuscated	Drop:	N/A

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		internal module logic state marker (often indicating a Continue/Clean action).	Unnecessary telemetry that bloats the index.	
cert_issuer	Encryption	The Certificate Authority that issued the TLS certificate for the transmitting server.	Keep: Excellent observable for identifying rogue infrastructure utilizing self-signed or unauthorized CAs.	connection_info.tls.certificate.issuer
cert_subject	Encryption	The subject/identity bound to the transmitting server's TLS certificate.	Keep: Can be correlated against the helo string to detect mismatched infrastructure.	connection_info.tls.certificate.subject
cipher	Encryption	The exact TLS cipher suite negotiated between the MTAs.	Keep: Critical for compliance reporting and identifying vulnerable transit connections.	connection_info.tls.cipher
cipher_bits	Encryption	Redundant or alternate field for bits, showing encryption strength.	Keep: Only if bits is unpopulated; otherwise drop to save space.	connection_info.tls.key_length
class	MTA Metric	Internal Sendmail priority classification based on message size and headers.	Drop: Holds zero value for threat hunting or security analytics.	N/A
corrupted	Integrity	Flag triggered when the email contains structural anomalies or malformed MIME boundaries.	Keep: High-fidelity indicator of potential evasion techniques or parser exploitation attempts.	status_id or unmapped.corrupted
daemon	MTA Metric	Name of the specific Sendmail backend process	Drop: Purely IT operations/infrastructure telemetry.	N/A

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		that handled the transaction.		
data_notroutes	Routing	Internal array of failed local delivery paths for the message body.	Drop: Infrastructure routing noise.	N/A
data_routes	Routing	Internal array of successful local delivery paths.	Drop: Infrastructure routing noise.	N/A
delay	MTA Metric	Secondary timing metric tracking how long a message sat in the Sendmail queue.	Drop: IT operations telemetry, not security data.	N/A
dmARC_detail	Auth	Deep diagnostic output explaining the exact reason a DMARC policy passed or failed.	Keep: Eliminates the need to pivot back to the Proofpoint UI during an active phishing investigation.	auth_info.dmarc.status_detail
dmARC_record	Auth	The raw or partially parsed DMARC TXT record retrieved from the sender's DNS.	Keep: Valuable for verifying if the sender recently changed their posture to p=none.	auth_info.dmarc.record
dmARCoverride_type	Auth	Specifies if a local allowlist or safe-sender policy bypassed a DMARC failure.	Keep: Critical for identifying security gaps caused by overly permissive local routing rules.	unmapped.dmarc_override
dmARCverified	Auth	The final binary boolean state indicating if the message passed DMARC.	Keep: Primary field for constructing KQL queries looking for spoofed domains.	auth_info.dmarc.status
dnsid	Routing	Temporary DNS query identifier used during MTA routing checks.	Drop: Highly ephemeral and too noisy for standard retention.	N/A
dyndmarc_override_id	Auth	Internal database reference ID	Drop: Meaningless	N/A

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		pointing to a specific UI-configured DMARC override rule.	outside of the Proofpoint administrative console.	
elapsed	MTA Metric	Timer showing total wall-clock time for the email transaction.	Drop: IT performance metric.	N/A
extended	MTA Metric	Internal marker for Proofpoint extended processing modules.	Drop: Vendor processing noise.	N/A
fo	DMARC	DMARC failure reporting options flag extracted from the DNS record.	Drop: Defines when reports are sent, which doesn't aid in individual message hunting.	N/A
folder	MTA Metric	Internal memory or disk pointer used during quarantine/processing.	Drop: Purely operational.	N/A
form	Process	Internal identifier for the form/type of message being processed.	Drop: Unnecessary string bloat.	N/A
helo	Network	The self-identified hostname provided by the sending server during the initial SMTP handshake.	Keep: A top-tier observable for infrastructure hunting; frequently mismatches the actual sender IP in malicious campaigns.	connection_info.unmapped.helo
hops	MTA Metric	The count of Received: headers, indicating how many MTAs touched the message.	Drop: While anomalous hops can indicate routing loops, it is generally too noisy for security	N/A

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
			analytics.	
id	Routing	Internal null or queue ID used by the local MTA, distinct from the global Message-ID.	Drop: Do not index; ensure you capture the actual Message-ID header instead.	N/A
L	Routing	Obfuscated internal logic state marker (often indicating a Log action).	Drop: Proprietary vendor state marker.	N/A
lang	Context	Extracted language code of the email body (e.g., en, es).	Drop: Can be useful for generic filtering, but usually redundant if your platform does its own text analytics.	N/A
lint	Integrity	Warning flags related to improper MIME formatting or RFC violations in the email structure.	Keep: Threat actors intentionally break RFC standards to bypass basic security scanners.	unmapped.lint
mailer	MTA Metric	Specific internal process/module designation handling the message routing.	Drop: Infrastructure noise.	N/A
maxquerydepth	MTA Metric	The configuration limit defining how deep the MTA will recursively query DNS.	Drop: Static system configuration value.	N/A
msgs	MTA Metric	Internal batch or sequence marker.	Drop: Vendor logic noise.	N/A
notroutes	Routing	Array of unresolvable internal or external delivery paths.	Drop: IT operations data.	N/A
orderId	Commercial	Custom billing/metric tag	Drop: Holds absolutely no	N/A

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		likely injected by a log forwarding agent or cloud environment.	security context or email transit value.	
orig_dmarc_result	Auth	The DMARC status of the message <i>before</i> any local Proofpoint overrides were applied.	Keep: Essential for auditing the effectiveness (or risk) of local allowlist policies.	auth_info.original_auth (Extension)
original_auth_result	Auth	The broader authentication status (SPF/DKIM) prior to local modification.	Keep: Core metadata for understanding true inbound posture.	auth_info.original_auth (Extension)
p	DMARC	The sender's published primary DMARC domain policy (none, quarantine, reject).	Keep: The most critical field for determining if a spoofed email <i>should</i> have been blocked.	auth_info.dmarc.policy
pct	DMARC	The percentage of the sender's mail flow to which the DMARC policy applies.	Drop: Adds minimal value to individual event investigations.	N/A
perlwait	MTA Metric	Timing metric tracking latency for internal Perl-based filtering scripts.	Drop: Pure performance telemetry.	N/A
pri	MTA Metric	Sendmail calculated routing priority based on message size.	Drop: Operational data.	N/A
profile	Routing	Internal processing profile designated for the message (e.g., mail).	Drop: Vendor processing noise.	N/A
protected	Context	Likely an internal flag indicating a message was processed by a	Keep: Conditionally useful to ensure all mail flow is	unmapped.protected

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		specific TAP/Protection module.	passing through the advanced sandbox.	
pss	Host Metric	Proportional Set Size; standard Linux memory metric for the underlying MTA process.	Drop: Infrastructure health data, not security data.	N/A
purpose	MTA Metric	Internal variable for routing categorization.	Drop: Vendor logic noise.	N/A
quantity	Commercial	Custom volumetric tag injected by external pipelines.	Drop: Irrelevant to email security.	N/A
querydepth	MTA Metric	The number of recursive DNS lookups executed to resolve the sender.	Drop: IT operations data.	N/A
r	MTA Metric	Recipient index sequence counter used in multi-recipient messages.	Drop: Redundant; index the actual recipient addresses instead.	N/A
rcpt_notroutes	Routing	Internal array tracking delivery failures on a per-recipient basis.	Drop: IT operations data.	N/A
rcpt_routes	Routing	Internal array tracking successful internal hops per recipient.	Drop: IT operations data.	N/A
record	MTA Metric	Internal memory or database pointer.	Drop: Vendor logic noise.	N/A
redirect	Routing	Flag or URL indicating if a link was rewritten by URL Defense, or if the message was rerouted.	Keep: Highly valuable if it contains the rewritten URL or indicates an irregular internal detour.	unmapped.redirect
result_detail	Auth	High-level string	Keep: Broad	auth_info.status_d

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		explaining the overarching authentication checks.	context for the primary status_id.	etail
rf	DMARC	DMARC Reporting Format tag extracted from DNS.	Drop: Static configuration string.	N/A
ri	DMARC	DMARC Reporting Interval (timing for aggregate reports) extracted from DNS.	Drop: Static configuration string.	N/A
routes	Routing	Complete array of internal processing hops.	Drop: Unnecessary index bloat.	N/A
rss	Host Metric	Resident Set Size; standard Linux memory metric.	Drop: Infrastructure health data.	N/A
rua	DMARC	The mailto: URI for DMARC aggregate reports.	Drop: Unnecessary string data for SIEM/Data Lake indexing.	N/A
ruf	DMARC	The mailto: URI for DMARC forensic/failure reports.	Drop: Unnecessary string data.	N/A
SAMSON_PROD	Environment	Custom tenant identifier or infrastructure cluster tag added by your data pipeline.	Drop: Holds no email security context.	N/A
signature	Auth/AV	Can represent the DKIM selector string or a triggered anti-virus signature name.	Keep: Used heavily in attribution and identifying specific malware families or DKIM rotation strategies.	auth_info.dkim.signature
smtputf8	Context	Flag indicating the MTA accepted	Drop: Rarely actionable for	N/A

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		international character sets in headers.	threat hunting.	
sp	DMARC	The sender's published DMARC policy for subdomains.	Keep: Important for evaluating spoofing campaigns that leverage legitimate but unused subdomains.	unmapped.dmarc_sp
starttls	Encryption	Boolean/flag indicating the connection successfully upgraded to TLS.	Keep: Tracks baseline encryption standards for inbound transit.	connection_info.tls.version
suborg	Context	The internal tenant or organization ID processing the message.	Keep: Necessary for multi-tenant environments to separate reporting logic.	unmapped.suborg
sz	Host Metric	Total memory size metric for the Linux processing daemon.	Drop: Infrastructure health data.	N/A
threshold	Filtering	The internal numerical limit required to classify an email as spam or phishing.	Keep: Conditionally useful to tune false-positive/false-negative ratios.	unmapped.threshold
tls	Encryption	General flag indicating TLS was utilized.	Keep: Maps to core OCSF transit encryption requirements.	connection_info.tls.version
tls_verify	Encryption	The outcome of validating the sender's TLS certificate chain.	Keep: Identifies broken or malicious certificate chains in transit.	connection_info.tls.certificate.status
tls_version	Encryption	The specific TLS protocol version negotiated (e.g., TLSv1.2).	Keep: Identifies legacy or vulnerable transit paths.	connection_info.tls.version
value	MTA Metric	Generic internal	Drop: Vendor logic	N/A

Proofpoint Field	Category	Detailed Description & Security Relevance	Keep/Drop Justification	OCSF Master Schema Mapping
		processing variable.	noise.	
verified	Auth	Final binary state of the SPF/DKIM validation process.	Keep: Primary authentication outcome mapping.	auth_info.status
verify	Auth	Specific verification check trigger flag.	Keep: Primary authentication outcome mapping.	auth_info.status
version	Context	The local software version of the Proofpoint module handling the message.	Drop: Static noise across all logs.	N/A
virtual	Routing	Internal Virtual Host designation.	Drop: IT operations data.	N/A
warn	Filtering	Warning details generated by the scanning engine, often preceding a block or quarantine.	Keep: Provides analysts with the "why" behind a specific automated action.	unmapped.warn
xdelay	MTA Metric	Extended processing delay metric from the Sendmail daemon.	Drop: IT operations telemetry.	N/A