

This is a comprehensive list of fields, mixing critical email authentication protocols with standard Sendmail operational noise.

When building a lightweight, high-fidelity security data pipeline—especially when routing logs through pipeline tools like Cribl into observability platforms like Splunk Core or Datadog rather than a traditional SIEM—ruthlessly dropping MTA operational metrics is essential to control ingest costs and keep dashboards performant.

Here is the OCSF Master Schema mapping and filter justification for the fields in your images.

● High/Medium Importance (Keep for Security Analytics)

These fields relate to Authentication (ARC/DMARC), Encryption (TLS), and Message Integrity. They map well to the OCSF **Email Activity (4009)** class and should be prioritized.

Field Name	Description & Security Justification	OCSF Mapping
arc_override, arc_result, arc_result_detail, arc_trusted_flag	Authenticated Received Chain (ARC) preserves authentication results across forwards. Keep: Critical for investigating spoofing in forwarded email flows.	auth_info.arc.status (for result), map details to unmapped.arc_*
cert_issuer, cert_subject	The Certificate Authority and subject of the TLS connection. Keep: Useful for identifying anomalous or self-signed infrastructure.	connection_info.tls.certificate.issuer, connection_info.tls.certificate.subject.
cipher, cipher_bits, starttls, tls, tls_verify, tls_version	Details the encryption strength of the SMTP transit. Keep: Identifies downgrade attacks or insecure transit.	connection_info.tls.cipher, connection_info.tls.version, connection_info.tls.key_length.
corrupted	Flag indicating malformed structural elements in the email. Keep: Often indicates evasion techniques or parser exploits.	status_id (if it leads to an action) or unmapped.corrupted.
dmarc_detail, dmarc_record, dmarcoverride_type, dmarcverified	Deep details on DMARC evaluation and local policy overrides. Keep: Primary indicators of domain spoofing.	auth_info.dmarc.status, auth_info.dmarc.record, unmapped.dmarc_override.
orig_dmarc_result, original_auth_result	The authentication status <i>before</i> any local MTA modifications or forwarding. Keep: Vital for timeline analysis on spoofed emails.	auth_info.original_auth... (Custom OCSF extension) or unmapped.
helo	The string the sending server used to identify itself during the SMTP handshake. Keep: A highly valuable observable for identifying rogue infrastructure.	connection_info.unmapped.helo or as a standard Observable.

Field Name	Description & Security Justification	OCSF Mapping
result_detail, verified, verify	Outcome flags for SPF/DKIM/DMARC checks. Keep: Core security metadata.	auth_info.dmarc.status, auth_info.spf.status, etc.
signature	Depending on context, this is either the DKIM signature selector or an AV signature hit. Keep: Used for both attribution and threat detection.	auth_info.dkim.signature or finding_info.uid.

● Contextual Importance (Keep Conditionally)

These fields provide context but might be too noisy depending on your storage budget.

Field Name	Description & Security Justification	OCSF Mapping
bodytype	Typically the MIME type (e.g., text/html, multipart/mixed). Keep conditionally: Useful if hunting for anomalous attachment types, but often redundant if you already parse attachment extensions.	file.mime_type or unmapped.bodytype.
dnsid	The DNS query ID used during routing/auth checks. Keep conditionally: Useful for deep network forensics, but usually too noisy for general log retention.	unmapped.dnsid.
protected	Likely a Proofpoint internal flag for a specific protection module (e.g., TAP). Keep conditionally.	unmapped.protected.
threshold	An internal spam/phishing scoring limit. Keep conditionally: Only useful if you are correlating specific score boundaries with false positives.	unmapped.threshold.

● Low Importance (Drop / Filter Out)

These fields are purely operational for the underlying Sendmail MTA or Proofpoint's internal queue management. Dropping these saves significant pipeline bandwidth.

Field Name	Description & Filter Justification
archive_depth	Internal tracker for nested archives (zips within zips). Drop unless you specifically build alerts on zip bombs.
class, daemon, mailer	Sendmail delivery priority, backend daemon

Field Name	Description & Filter Justification
	name, and internal mailer process. Zero security value. Drop.
data_notroutes, data_routes, notroutes, rcpt_notroutes, rcpt_routes, routes	Internal arrays detailing how the MTA resolved the local vs. external delivery path. Purely operational. Drop.
delay, elapsed, perlwait	MTA timing metrics indicating how long processing scripts took or how long the mail sat in queue. Drop.
dyndmarc_override_id	Internal database ID for a UI-configured override. Too specific to be useful outside the vendor portal. Drop.
folder, purpose, record, value, virtual	Generic internal processing variables and memory pointers for Proofpoint's filtering engine. Drop.
maxquerydepth, querydepth	Limits on how deep the MTA will recursively query DNS before timing out. Drop.
smtputf8	Flag indicating if international characters are allowed in the email headers. Not a security metric. Drop.
version	The software version of the Proofpoint module handling the message. Static noise. Drop.