

Lertify SMS API Documentation

Last Updated: 31. 8. 2026

The Lertify SMS API enables an authenticated account to send SMS messages to one or more recipients through a simple HTTP interface.

Base URL

```
https://api.lertify.app/v1/sms/messages
```

Authentication

Every request must include a valid API key in the HTTP header.

Header	Type	Required	Description
apikey	string (UUID)	Yes	API key used to authenticate the request.

```
apikey: 12345678-1234-1234-1234-123456789abc
```

If the API key is missing or is not a valid UUID, the API returns 400 Bad Request. If the API key does not exist or is no longer valid, the API returns 401 Unauthorized.

Send SMS

Endpoint

```
POST https://api.lertify.app/v1/sms/messages
```

Request

```
Content-Type: application/json
```

Request parameters

Field	Type	Required	Description
sender	string	Yes	Sender name or phone number configured for the user account.
destinations	array[string]	Yes	List of recipient phone numbers.
message.content	string	Yes	SMS message content. Maximum of 640 characters after message processing.
message.isUnicode	boolean	No (default false)	Specifies whether the message should be treated as Unicode.
deliveryReportUrl	string	No	URL that receives delivery report webhooks.

Field	Type	Required	Description
scheduledTime	long	No	Unix timestamp in seconds specifying when the message should be sent.
priceReport	boolean	No (default false)	When true, delivery reports include the message price when available.

Message length limit

The maximum allowed message length is:

640 characters

The limit is validated after message preprocessing. If message.isUnicode is false, unsupported non-GSM characters are replaced with GSM equivalents whenever possible before the message length is calculated. If message.isUnicode is true, the message content is preserved and processed as Unicode.

If the message is empty, contains only whitespace, or exceeds 640 characters, the API returns 400 Bad Request.

The number of SMS segments is not equal to the number of characters. It depends on the message encoding and the actual message content.

SMS segments

The API automatically calculates the number of SMS segments based on the message content and encoding.

Encoding	Description
GSM-7	Used when the message content is compatible with the GSM character set.
Unicode	Used for Unicode messages or when Unicode is explicitly requested.

The segmentCount field in the response represents the number of SMS segments per individual message (recipient).

Example: a message has segmentCount = 2 and the request contains 3 recipients. The total billable amount is 6 SMS segments.

Scheduled sending

The scheduledTime field must contain a Unix timestamp expressed in seconds.

Value	Behavior
Field is omitted	The message is sent immediately.
Timestamp is in the future	The message is scheduled for the specified time.
Timestamp is equal to or earlier than the current time	The message is sent immediately.
Negative value	The API returns 400 Bad Request.

The scheduled time is interpreted as an absolute Unix timestamp and is also returned in UTC format in the API response.

Example scheduled time

```
{
  "scheduledTime": 1789297200
}
```

Corresponding UTC time:
2026-09-13T09:00:00Z

For messages sent immediately, the scheduledTime and scheduledAt fields are not included in the response.

Example request

```
{
  "sender": "Lertify01",
  "destinations": [
    "+38640123456",
    "+38640987654"
  ],
  "message": {
    "content": "Test SMS message",
    "isUnicode": false
  },
  "deliveryReportUrl": "https://example.com/delivery-report",
  "scheduledTime": 1789297200,
  "priceReport": true
}
```

Successful response

When a request is successfully accepted, the API returns 202 Accepted.

Response structure

Field	Type	Description
messages	array	List of created messages.
messages[].messageId	UUID	Unique message identifier.
messages[].destination	string	Recipient phone number.
status	string	accepted or scheduled.
scheduledTime	long	Present only for scheduled messages.
scheduledAt	datetime	Present only for scheduled messages. Time is returned in UTC.
segmentCount	integer	Number of SMS segments for each individual message.

Example response - immediate sending

```
{
  "messages": [
    {
      "messageId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "destination": "+38640123456"
    },
    {
      "messageId": "4bb95b02-a2d7-46d8-bd66-73b65df4fe33",
      "destination": "+38640987654"
    }
  ],
  "status": "accepted",
  "segmentCount": 1
}
```

Example response - scheduled sending

```
{
  "messages": [
    {
      "messageId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "destination": "+38640123456"
    }
  ],
  "status": "scheduled",
  "scheduledTime": 1789297200,
  "scheduledAt": "2026-09-13T09:00:00Z",
  "segmentCount": 1
}
```

Error Responses

HTTP status	Description
400 Bad Request	Invalid request, message content, sender, destination phone number, scheduled time, or insufficient account balance.
401 Unauthorized	Invalid API key.
500 Internal Server Error	An unexpected server error occurred.

Example error response

```
{
  "error": "Error: 401 - API key is not valid."
}
```

If one or more recipient phone numbers are invalid, the response also includes a list of the invalid destination numbers.

Phone Numbers

Phone numbers must be provided in international E.164 format, for example:

```
+38640123456
```

Messages can only be sent to countries for which Lertify has an active SMS price list. If the destinations array contains at least one invalid or unsupported phone number, the entire request is rejected.

Delivery Report Webhook

If deliveryReportUrl is provided in the request, the system sends HTTP POST requests to the specified URL whenever the delivery status of an SMS message changes.

If deliveryReportUrl is not provided, the system first uses the delivery report URL configured for the sender. If no delivery report URL is configured for the sender, no delivery report webhook is sent.

Delivery reports are sent individually for each recipient.

Webhook endpoint requirements

- Accept HTTP POST requests.
- Return an HTTP 2xx status code.
- Be publicly accessible from the Lertify platform.

Each delivery report request includes the following HTTP header:

```
X-Message-Id: 3fa85f64-5717-4562-b3fc-2c963f66afa6
```

If the endpoint does not return a successful 2xx response, the retry mechanism is automatically triggered.

Delivery report payload

Field	Type	Always Present	Description
messageId	UUID	Yes	Unique message identifier.
status	string	Yes	Current public message status.
segments	integer	Yes	Number of SMS segments for the message.
price	decimal	No	Message price. Included only when priceReport was requested and pricing information is available.

Example without price

```
{
  "messageId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "status": "DELIVERED",
  "segments": 1
}
```

Example with price

```
{
  "messageId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "status": "DELIVERED",
  "segments": 2,
  "price": 0.084
}
```

The price field is included only when priceReport was set to true in the original send request and pricing information is available in the billing system. If the billing service is unavailable or the price cannot be retrieved, the delivery report is still sent and the price field is omitted.

Delivery report statuses

Status	Description
SCHEDULED	The message has been scheduled for future delivery.
SENT	The message has been successfully submitted to the SMS provider or mobile operator.
DELIVERED	The message has been successfully delivered to the recipient's device.
FAILED	The message could not be sent or delivered.
REJECTED	The message was rejected before being submitted to the operator.
UNKNOWN	The final delivery status could not be determined.
CANCELLED	The scheduled message was cancelled before delivery.

The accepted status returned by the Send SMS API only indicates that the request has been accepted for processing. It is not a delivery report status.

A delivery report may contain multiple status updates for the same message during its lifecycle.

Typical message lifecycle:

```
accepted -> SENT -> DELIVERED
```

For scheduled messages:

```
scheduled -> SCHEDULED -> SENT -> DELIVERED
```

Message Pricing

The Send SMS endpoint does not return the message price. To receive pricing information, enable price reporting in the request:

```
{
  "priceReport": true
}
```

When pricing information becomes available, it is included in the delivery report for each individual message:

```
{
  "messageId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "status": "DELIVERED",
  "segments": 2,
  "price": 0.084
}
```

Pricing is returned per recipient (messageId). The currency is determined by your account configuration or applicable price list. The current webhook payload does not include a separate currency field.

Inbound Webhook

If an inboundUrl is configured for the sender, the system sends an HTTP POST request to that URL whenever an inbound SMS message is received. The inbound webhook forwards messages sent by end users to the phone number or sender assigned within the Lertify platform.

Inbound webhook requirements

- Accept HTTP POST requests.
- Return an HTTP 2xx status code.
- Be publicly accessible from the Lertify platform.

If the endpoint does not return a successful response, the retry mechanism is automatically triggered.

Inbound webhook payload

Field	Type	Description
Sender	string	Phone number of the user who sent the SMS message.
Recipient	string	Sender ID or phone number to which the message was sent.
Message	string	Content of the received SMS message.
Time	string	Time the message was received, formatted as yyyy-MM-dd HH:mm:ss.

Example payload

```
{
  "Sender": "+38640123456",
  "Recipient": "+38631234567",
  "Message": "TEST",
  "Time": "2026-05-15 14:32:10"
}
```

Retry Policy

If a webhook endpoint does not return an HTTP 2xx response, the system retries delivery using the following formula:

$$\text{delay} = (\text{attempt}^2) + 1 \text{ minutes}$$

Maximum number of retry attempts: 10

Attempt	Delay	Total Elapsed Time
1	2 min	2 min
2	5 min	7 min
3	10 min	17 min
4	17 min	34 min
5	26 min	60 min
6	37 min	97 min
7	50 min	147 min
8	65 min	212 min
9	82 min	294 min
10	101 min	395 min

Error response

The API returns an HTTP error status together with an error message containing an application-specific numeric error code.

Example:

```
{
  "error": "Error: 3 - Invalid recipient (to) number"
}
```

Possible application error codes:

Code	Name	Description
1	MsgTooLongOrEmpty	Message is too long or empty
2	InvalidSender	Invalid sender (from) number
3	InvalidToNumber	Invalid recipient (to) number
4	NumberNotRegistered	Number not registered
5	ScheduledTimeInvalid	ScheduledTime must be a valid Unix timestamp
6	BalanceTooLow	Balance too low to send message
7	Rejected	Rejected
8	ServerError	Internal server error

For invalid destination numbers, the error message also contains the invalid numbers:

```
{
  "error": "Error: 3 - Invalid recipient (to) number | Invalid destination numbers: +38640123, 041123456"
}
```

Code Examples

cURL

```
curl --request POST \  
  --url https://api.lertify.app/v1/sms/messages \  
  --header "Content-Type: application/json" \  
  --header "apikey: YOUR_API_KEY" \  
  --data '{  
    "sender": "Lertify01",  
    "destinations": [  
      "+38640123456"  
    ],  
    "message": {  
      "content": "Test SMS message",  
      "isUnicode": false  
    },  
    "deliveryReportUrl": "https://example.com/delivery-report",  
    "priceReport": true  
  }'
```

Python

```
import requests  
  
url = "https://api.lertify.app/v1/sms/messages"  
headers = {  
    "Content-Type": "application/json",  
    "apikey": "YOUR_API_KEY"  
}  
data = {  
    "sender": "Lertify01",  
    "destinations": [  
        "+38640123456",  
        "+38640987654"  
    ],  
    "message": {  
        "content": "Test SMS message",  
        "isUnicode": False  
    },  
    "deliveryReportUrl": "https://example.com/delivery-report",  
    "priceReport": True  
}  
  
response = requests.post(url, json=data, headers=headers)  
print("Status code:", response.status_code)  
print("Response:", response.json())
```

PHP

```
<?php
$url = "https://api.lertify.app/v1/sms/messages";
$apiKey = "YOUR_API_KEY";
$data = [
    "sender" => "Lertify01",
    "destinations" => [
        "+38640123456"
    ],
    "message" => [
        "content" => "Test SMS message",
        "isUnicode" => false
    ],
    "deliveryReportUrl" => "https://example.com/delivery-report",
    "priceReport" => true
];

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_HTTPHEADER, [
    "Content-Type: application/json",
    "apikey: " . $apiKey
]);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));
$response = curl_exec($ch);
$statuscode = curl_getinfo($ch, CURLINFO_HTTP_CODE);

if (curl_errno($ch)) {
    echo "Error: " . curl_error($ch);
} else {
    echo "Status code: " . $statusCode . PHP_EOL;
    echo "Response: " . $response;
}
curl_close($ch);
```