💀 THE ULTIMATE 90-DAY HACKING ROADMAP 💀

From Absolute Zero to Executing Deep Tactical Exploits—like popping remote root shells, bypassing enterprise firewalls, and automating SQL injections.

AUTHOR'S NOTE: Listen to me before we start. I am from Spain. My English is not perfect. I don't write like a robot or a university professor. I write with my own messy grammar because I want to keep it real. If you want a boring academic textbook, leave now. If you want to learn how to actually hack, stay. Let's go. And This content is for educational purposes only and should be practiced only in legal environments such as labs and authorized platforms.

You can check out the full video from here about this topic it is 45-minute video: - https://youtu.be/2Ni7I6wt35Y

🚫 3 FATAL BEGINNER MISTAKES

Before I give you the roadmap, I need to stop you from failing. 90% of guys who start this journey quit in the first month because they make these 3 mistakes:

1. !

The "Tool Zombie" Mistake: You open Kali Linux and immediately click on random tools. You launch `sqlmap` but you don't even know what SQL is. *Fix: Learn how the technology is built before you try to break it.*

2. !

Tutorial Purgatory: You watch 50 hours of hacking videos on YouTube but you never open a terminal yourself. Watching someone ride a bike doesn't mean you know how to ride a bike. *Fix: For every 1 hour of video, do 3 hours of hands-on lab work.*

3. !

The "Everything at Once" Burnout: You try to learn Python, Linux, Networking, Web Hacking, and Cryptography all in the same weekend. Your brain melts and you quit. *Fix: Follow a strict timeline. One thing at a time. That is why this 90-day roadmap exists.*

🗁 PHASE 1: THE FOUNDATION (Days 1 - 30)

You cannot break a system if you don't know how it was built. Put the hacking tools away. We need to build your brain first.

🛠 WEEK 1: Breaking the Illusion & The CIA Triad

Most people think a hacker is a guy in a hoodie typing super fast to steal a password. Hollywood garbage. In the real world, hackers are categorized by motives:

- **White Hats:** The good guys. Penetration testers. Hired to break in legally.
- **Black Hats:** The criminals. Ransomware gangs shutting down hospitals for millions.
- **Grey Hats:** The wildcards. They break the rules, hack without permission, but don't steal the data.

Every single hack in history targets the **CIA Triad**:

- C

Confidentiality: Nobody else should see your data. (Example: A hacker intercepts your network and reads your private emails. They didn't steal money, but privacy is broken).

- I

Integrity: Data must be accurate. (Example: A hacker logs into a hospital database and changes a patient's blood type. Deadly).

- A

Availability: The system is there when you need it. (Example: A DDoS attack takes a bank offline. Your money is safe, but you can't access it).

🛠️ WEEK 2: Networking (The Roads)

If you skip this, you will never be a hacker. Period. You need to know how the internet moves data.

- **The OSI Model:** Understand the 7 layers of the internet. Hackers use this as a blueprint. If they can't hack the application (Layer 7), they attack the physical wire (Layer 1).
- **IPs and Ports:** An IP address is like an apartment building. A Port is the apartment number. Your computer has 65,535 ports. Web traffic uses port 80 or 443. Secure logins use port 22. Hackers scan all these doors to see what is unlocked.

🛠️ WEEK 3: Linux (Your New Home)

Windows is for gaming. Hackers use Linux because we want raw, unfiltered control over the machine.

- **Install Kali Linux** on a Virtual Machine.
- **Throw away your mouse.** Learn the terminal. `ls` (list files), `cd` (change directory), `grep` (search for text).
- **Goal:** The ultimate hack is "Privilege Escalation"—starting as a restricted user and hacking your way to become `root` (the god of the system).

🛠️ WEEK 4: Web Architecture

Every company has a website. To a hacker, a website is a front door with a million locks.

- **HTTP Requests & Responses:** The internet is a conversation. Your browser asks for a page, the server replies. What happens if we intercept that request and inject poison into it?
- **Cookies:** HTTP has no memory. Websites give you a "Cookie" (a VIP wristband) to keep you logged in. If a hacker steals your wristband, they become you. They don't even need your password.

🔪 PHASE 2: OFFENSE & DEFENSE (Days 31 - 60)

Now we cross the line. You know how the internet works. Time to kick the doors off the hinges.

✵ WEEK 5: The OWASP Top 10

This is the hacker's bible. The top 10 most critical vulnerabilities on the internet.

- **SQL Injection (SQLi):** Instead of typing a username, you type raw database code like `' OR 1=1 --`. The server gets confused and vomits the entire database of passwords onto your screen.
- **Cross-Site Scripting (XSS):** You inject malicious JavaScript into a public forum comment. Every innocent user who views your comment silently emails you their session cookies in the background. Weaponized trust.

✵ WEEK 6: The Cyber Kill Chain

Real hacking is a patient, step-by-step process.

1. **Reconnaissance:** Stalking. Finding leaked passwords and employee emails using OSINT (Open Source Intelligence).
2. **Scanning:** Pinging the target's servers to see what ports are open.
3. **Exploitation:** The breach. You send the malicious payload and break the lock.
4. **Post-Exploitation:** You upload a "Reverse Shell" which forces the target server to connect back to your laptop, giving you a remote command line.

✵ WEEK 7: Cryptography & Cracking

You must understand the math that protects the internet.

- **Encryption:** A two-way street. You lock a message with a key, the receiver unlocks it.
- **Hashing:** A one-way meat grinder. You put a password in, it outputs random text (a hash). You cannot reverse a hash back to a password.
- **Cracking:** How do hackers get passwords? They take a dictionary of 10 million words, run them all through the meat grinder, and see which output matches your hash.

✵ WEEK 8: Blue Team (Building the Castle)

To be an elite attacker, you must think like a defender.

- **Active Directory (AD):** The brain of corporate networks. If you hack AD, you own the whole company.
- **Firewalls & EDR:** Learn how security systems block attacks. A modern EDR doesn't just look for viruses; it looks for *behavior*. If you try to open a reverse shell, the EDR will kill the process immediately. You must learn how to hide.

🚀 PHASE 3: THE ENDGAME & THE ARSENAL (Days 61 - 90)

Stop reading. Start doing. Here is where you get your hands dirty.

🧰 WEEK 9 & 10: Master The Arsenal (10 Core Tools)

Script kiddies just click buttons. You need to master these 10 tools deeply:

1. **Wireshark:** The magnifying glass. It captures raw network packets flying through the air. You can literally pluck unencrypted passwords right out of the traffic.
2. **Burp Suite:** The interceptor. It sits between your browser and the server. You can pause web requests, manipulate data, change the price of an item to $1, and forward it.
3. **Nmap:** The radar. It scans IP addresses and tells you exactly what ports are open and what software versions are running.
4. **Metasploit:** The sniper rifle. A massive database of pre-written exploits. You point it, set your payload, and fire.
5. **SQLmap:** The database ripper. You feed it a vulnerable URL, and it automates the SQL injection to download the target's entire database.
6. **FFuF (Fuzz Faster U Fool):** The directory brute-forcer. It throws thousands of words at a web server per second to find hidden admin panels and secret files.
7. **Hashcat:** The code breaker. The fastest password recovery tool in the world. It uses your Graphics Card (GPU) to crack hashes.
8. **BloodHound:** The corporate map. Used to visually map out Active Directory networks to find the fastest path to hack the Domain Admin.
9. **Hydra:** The login brute-forcer. Used to hammer SSH, FTP, or web logins with thousands of username/password combinations.
10. **Ghidra:** The reverse-engineer. Created by the NSA. It takes compiled malware or programs and decompiles them back into readable C code so you can find hidden backdoors.

🏴‍☠️ WEEK 11: The Crucible (CTFs)

Time to fight. Sign up for **TryHackMe** and **Hack The Box**. These are virtual labs with vulnerable machines. You will be given an IP address and nothing else. You have to scan it, find the web vulnerability, get a shell, escalate your privileges to root, and find the text file (the "Flag") to prove you won. The adrenaline rush when you pop your first root shell is absolute magic.

💼 WEEK 12: The Professional

Nobody pays you to hack. They pay you to **write a report** explaining *how* you hacked them so they can fix it.

- Learn how to write Executive Summaries for CEOs (focus on money and risk).
- Learn how to write Technical Narratives for developers (step-by-step code to patch the flaw).
- Prepare for interviews. They will whiteboard you. If you can't explain the TCP 3-way handshake perfectly, you fail.

🎯 OUTRO: ONE LIFE. ONE SHOT.

When you look at this whole 90-day plan, you are going to feel Imposter Syndrome. You will think, *"I am not smart enough for this math. I don't think like a computer."*

Listen to me very carefully. Every single elite hacker making half a million dollars a year started exactly where you are right now. Staring at a blinking cursor, feeling stupid.

Hacking is not a magical talent you are born with. Hacking is simply the brutal, relentless refusal to quit when things don't work. Your exploits will fail. Your code will crash. But if you take a breath, tweak the payload, hit enter, and the shell finally connects... there is no feeling on Earth quite like it.

We don't need more cybercriminals. We need more defenders willing to stand on the wall. The internet is a vast, terrifying, broken place. Starting today, you aren't just a user anymore.

You are an architect. Get to work.