

---

# Table of Contents

.....	1
-------	---

```
function state_phi_dot = CR3BP_full(state_phi, mu)
    % Full state vector and state transition matrix differential equation
    % Inputs:
    % state_phi - Augmented state vector and STM [42x1]. The state vector -
    % [x0, y0, z0, x0_dot, y0_dot, z0_dot]. The STM - is 6x6 with each
    % element described as - phi_ij = dxi(tf)/dxj(t0). The phi matrix is
    % reshaped such that all the rows are concatenated vertically. For
    % example -
    % phi_mat = [phi11, phi12, phi13, ..., phi16;
    %            [phi21, phi22, phi23, ..., phi26;
    %            ...
    %            [phi61, phi62, phi63, ..., phi66]
    % becomes
    % phi_row = [phi11, phi12, ..., phi16, phi21, phi22, ..., phi66]'
    %
    % mu - system mass ratio [-]
    %
    % Output
    % state_phi_dot - Augmented state vector dot and STM_dot [42x1]. The
    % augmentation and reshaping scheme remains the same as the input.

    x = state_phi(1);
    y = state_phi(2);
    z = state_phi(3);
    xdot = state_phi(4);
    ydot = state_phi(5);
    zdot = state_phi(6);

    r1 = sqrt((x + mu)^2 + (y)^2 + (z)^2);
    r2 = sqrt((x - 1 + mu)^2 + (y)^2 + (z)^2);

    state_dot(1, 1) = xdot;
    state_dot(2, 1) = ydot;
    state_dot(3, 1) = zdot;

    state_dot(4, 1) = 2*ydot + x - (1 - mu)*(x + mu)/(r1^3) - mu * (x - 1 +
mu)/(r2^3);
    state_dot(5, 1) = -2*xdot + y - (1 - mu)*y/(r1^3) - mu*y/(r2^3);
    state_dot(6, 1) = -(1 - mu)*z/(r1^3) - mu*z/(r2^3);

    % Calc pseudo-potentials
    uxx = u_xx(mu, [x, y, z]);
    uyy = u_yy(mu, [x, y, z]);
    uxy = u_xy(mu, [x, y, z]);
    uzz = u_zz(mu, [x, y, z]);
    uxz = u_xz(mu, [x, y, z]);
    uyz = u_yz(mu, [x, y, z]);
```

---

```

U_mat = [uxx, uxy uxz; uxy, uyy uyz; uxz uyz uzz];
Omega = [0 2 0; -2 0 0; 0 0 0];
A = [zeros(3), eye(3);
     U_mat, Omega];

% Get only the phi elements into a row
phi_row = state_phi(7:end);

% Converting phi to matrix
phi_mat = reshape(phi_row, [6,6])';

% Get phi_dot
phi_dot_mat = A * phi_mat;

% Convert back to row
phi_dot_row = reshape(phi_dot_mat', [36,1]);

% Augment state and phi (in row form)
state_phi_dot = [state_dot; phi_dot_row];

end

Not enough input arguments.

Error in CR3BP_full (line 22)
    x = state_phi(1);

```

*Published with MATLAB® R2024a*