Alloy 4045

4000 series | Reference sheet | Data checked 14 October 2026

An aluminium-silicon braze-cladding option listed by Gränges for controlled-atmosphere brazing of rolled heat-exchanger products.

Scope: Selected clad-layer chemistry only; no clad temper, standalone mechanical data or complete composition established.

This reference sheet is not a material certificate, procurement specification or source of design allowables. Values apply only to their listed form, temper and condition. Confirm current requirements with the supplier and governing standard.

Forms and tempers

Forms: Braze cladding on rolled products

Tempers in record:

Selected physical properties

No physical property values published in this partial record.

Selected mechanical properties

No mechanical values published in this partial record.

Alloy 4045 / Composition and sources

Selected chemistry

Element	Published limit / value	Provenance
Si	9-11 wt %	Basis: composition-limit | Verification: single-source | Source: granges-braze2022 | Checked: 2026-10-14

This is selected chemistry, not a complete composition specification. Unlisted elements must not be assumed to be zero.

Applications and selection guidance

Applications: Brazed heat exchangers

Treat this as a clad-layer material, with core alloy, layer ratio and brazing cycle specified separately. The brochure lists iron variants and permits zinc modification; this entry retains only the shared silicon interval.

Source register

granges-braze2022 | Gränges • Rolled products for brazed heat exchangers

Revision / access scope: August 2022 | Checked: 2026-10-14

https://www.granges.com/globalassets/03.-marknader-och-produkter/03.-europe/02.-finspang/granges_produktbroschyr_hex.pdf

Source facts are presented in an original editorial layout. Source publications may change; full source tables and imagery are not reproduced. This partial sheet does not imply interchangeability between alloy designations or certification of any supplied product.