

PV239 – 03 MVVM

What do you already know?


- MVVM
- Data Binding
- Command
- Inversion of Control/Dependency Injection

Goals

- Get to know the MVVM design pattern
- Look at the concepts for Data Binding

Model View ViewModel

- **Model** – Represents data
- **View** – Displays data to user and provides interactivity options.
- **ViewModel** – keeps the current context of the View



Binding

Binding the value from the backend to its display in the frontend

Binding types - current **BindingContext**

- **{Binding}**
 - Referencing current BindingContext
- **{Binding Name}**
 - Referencing property Name in current BindingContext
- **{Binding Name.Length}**
 - Referencing property **Name.Length**

Binding types - **named element**

- attribute **x:Name**
- **{Binding Path=Text, Source={x:Reference TextBox1}}**
 - Referencing property Text of object TextBox1
- **x:DataType**
- Specifies data type of the object that is used in current BindingContext
- If it is unclear what data type is used in current BindingContext
- Used for compiled bindings - build-time control, performance optimization, Intellisense

Binding directions

- **Attribute Mode**
- **OneTime**
 - Value is set only one time when the control is created
- **OneWay**
 - Value updates in one way – from backend to frontend (for example Label)
- **TwoWay**
 - Value updates in both ways (for example Entry)
- **OneWayToSource**
 - Value updates in one way – from frontend to backend

MVVM, Binding

DEMO

Binding – notify about changes

- **OneWay & TwoWay**
- Reacts on value changes in the backend
- The frontend needs to be notified that something changed
- Backend object implements **INotifyPropertyChanged**
- public event PropertyChangedEventHandler PropertyChanged
- It's advised to add an OnPropertyChanged method with a parameter with attribute [CallerMemberName]

INotifyCollectionChanged

- If something changes inside an existing collection (item gets added or removed)
- **ObservableCollection**
 - Already implements interface INotifyCollectionChanged
- Existing collections
 - Create a wrapper that implements INotifyCollectionChanged
- Custom collections
 - Implement INotifyCollectionChanged and add support for notifying the frontend on changes

INotifyPropertyChanged, INotifyCollectionChanged

DEMO

CommunityToolkit.Mvvm

- Framework independent – can be used with .NET MAUI, WPF, WinForms, Xamarin...
- Uses source generators
- Helps with
 - Property changed events
 - Commands
 - Messaging

CommunityToolkit.Mvvm - observableobject

- Base class that implements **INotifyPropertyChanged** & **INotifyPropertyChanging**
- Provides SetProperty() method that handles setting value and notifying
- Alternatively can be added by using **[INotifyPropertyChanged]** attribute
- If the class already inherits from a base class and cannot inherit from ObservableObject

CommunityToolkit.Mvvm - ObservableProperty

- Attribute [**ObservableProperty**]
- Add to a field and get the corresponding property generated
- Can be used in classes that implement **INotifyPropertyChanged**

CommunityToolkit.Mvvm

DEMO

ICommand

- Interface for making actions while using Bindings
- `public void Execute(object parameter)`
- `public bool CanExecute(object parameter)`
- `public event EventHandler CanExecuteChanged`
- Usage in XAML
 - `Command="{Binding SaveCommand}"`

Command Parameter

- Passing value to Command
- Value gets passed as type Object – needs to be casted
- `CommandParameter="{Binding Detail}"`

Command

DEMO

CommunityToolkit.Mvvm - RelayCommand

- Implementation of ICommand interface
- Add attribute to a method and get the command property generated
- Supports CanExecuteChanged and passing of values
- Also for asynchronous methods with CancellationToken support
- [RelayCommand], [RelayCommand]
- [AsyncRelayCommand], [AsyncRelayCommand]

CommunityToolkit.Mvvm - RelayCommand

DEMO

Goals

- Get to know the MVVM design pattern
- Look at the concepts for Data Binding