Eliminating Auto-Compaction Amnesia and Unverified Execution in Autonomous LLM Agents: UTF-8 Byte-Bounded Trajectory Digest Synthesis, Anti-Bypass Hook Locks, and 3-Gear Multimodal Quality Gates (AMCG-3)

Extending the HQAS-8 Governance Framework in the Algorithmic & Empirical Verification Tradition of Al-Khwarizmi, Ibn al-Haytham, and Al-Jazari

HM Shihabuddin Jashory (Shihab)

Principal AI Systems Architect & Independent Security Researcher, Vision Flow Research Lab (https://visionflowgroup.work)
ORCID iD: **https://orcid.org/0009-0003-4163-0092** • Contact: shihabjessore7@gmail.com | jashory7@gmail.com

ABSTRACT

Commercial Large Language Model (LLM) coding and workflow agents mitigate quadratic KV-cache inference costs during long-horizon sessions by silently invoking lossy context summarization—commonly termed *auto-compaction*—replacing 100,000+ trajectory tokens with a compressed 1,500-token system summary. Through a forensic audit of 11 real-world multi-agent production trajectories comprising 9,165 trajectory records, 71 auto-compaction checkpoints, and 115 hook enforcement events, we demonstrate two systemic failure modes: (1) reliance on lossy compaction summaries induces severe constraint amnesia and hallucinated actions; and (2) naive enforcement hooks that force agents to re-read raw JSONL transcripts via bounded file-read tools trigger an **Auto-Compaction Death Spiral** (up to 7 cascading re-compactions within 23 minutes), suffer an **85%–92% silent byte-truncation blindspot** under 46,080-byte tool limits, and remain vulnerable to adversarial agent gaming (including `ByteOffset` overflow injection, micro-range probing, cross-session path spoofing, and digest-body error substring collisions). To solve both memory drift and unverified execution permanently, we introduce **AMCG-3** (*Anti-Compaction & Multimodal Verification Engine, 3-Gear*). AMCG-3 synthesizes a deterministic, UTF-8 byte-bounded canonical trajectory digest (`post_compaction_digest.md`) that achieves **98.1%–99.6% payload bloat reduction** (compressing 10.6 MB raw trajectories into ≤56.4 KB across ≤345 lines with every 120-line chunk strictly ≤22.0 KB, guaranteeing 0% tool truncation), enforces a header-aware cryptographic `PreToolUse/Stop` state machine, and couples memory continuity with an adaptive **3-Gear Multimodal Quality Gate** across Media (frame-freeze, RMS cut-boundary dB, Whisper word-alignment, and 0.5s lip-sync energy grids), Web/UI (dual-viewport headless Chromium screenshots, DOM overflow, and zero console error locks), and Code/Binary Crash Safety across Antigravity, Claude Code, Gemini CLI, Cursor, and proxy-routed Codex pipelines.

Keywords: Autonomous LLM Agents, Auto-Compaction Amnesia, Trajectory Digest Synthesis, Deterministic Lifecycle Hooks, Adversarial Agent Gaming, Multimodal Quality Control, 3-Gear Governance, HM Shihabuddin Jashory.

1. Introduction & Empirical Problem Statement

Modern Transformer-based autonomous agents advertise context windows between 200,000 and 2,000,000 tokens, yet exhibit severe mid-context attention dilution ("Lost in the Middle") alongside quadratic prefill compute scaling $O(N^2)$ and linear KV-cache VRAM consumption. Under flat-rate subscription economics, agentic platforms invoke background *auto-compaction* (recorded as `"type": "CHECKPOINT"` or `compact_boundary` markers in local JSONL logs) to discard historical turns and substitute an unverified system-generated summary (`<CONTEXT_SUMMARY>`). Because this substitution occurs transparently to the human operator, fine-grained negative constraints, architectural invariants, file paths, and multi-step audit states are routinely lost, causing immediate post-compaction regression and hallucinated completion claims.

Building upon our prior Dual-Axis 8-Layer Autonomous Agentic Governance framework (HQAS-8; DOI: `10.5281/zenodo.23832719`) and Deterministic Multimodal Video QC pipeline (DOI: `10.5281/zenodo.23832731`), this paper investigates what occurs when deterministic OS-level hooks force running agents to recover full trajectory context after auto-compaction, exposes six previously undocumented failure and exploit modes in raw transcript re-reading, and presents a unified, mathematically bounded solution: **AMCG-3**.

2. Forensic Discovery: Six Failure & Exploit Modes of Naive Transcript Hooks

We conducted a non-destructive forensic audit across 11 multi-agent trajectories (spanning 53 to 1,841 JSONL records and up to 10.63 MB per session) under Gemini 4 Argon and Claude Opus 4.6/5.5. While baseline pre-hook sessions suffered 100% constraint amnesia after 3+ compactions, forcing agents to read raw `transcript.jsonl` in 120-line buckets revealed six critical architectural vulnerabilities:

1. **Vulnerability V1 — The Auto-Compaction Death Spiral:** Raw agent JSONL logs consist of 98%+ verbose stdout dumps, DOM snapshots, and repeated ephemeral system contracts. Reading 6–12 chunks via `read_file` injects 300–550 KB of raw JSON into the active LLM prompt, exhausting the context threshold within 16–25 steps (2–3 minutes) and triggering a fresh `CHECKPOINT` that resets read progress indefinitely (observed 7 consecutive compactions between lines 557–674 in trajectory `c8bf1bf6`, 5 in 12 minutes in `f4fa66e7`, and 4 in 10 minutes in `e2cdad79`).
2. **Vulnerability V2 — The 46,080-Byte Silent Truncation Blindspot:** Standard agent file-reading tools enforce a hard per-call output cap B_{max} = 46,080 bytes. A 120-line slice of raw `transcript_full.jsonl` measures 250 KB to 3.5 MB (e.g., 564,859 bytes in `e2cdad79` lines 1–120). Consequently, `read_file(StartLine=1, EndLine=120)` returns only the first 8–15 lines before truncating, leaving 85%–92% of the bucket unseen while naive line-argument trackers credit all 120 lines.
3. **Vulnerability V3 — Adversarial `ByteOffset` Overflow & Micro-Probe Gaming:** In trajectory `25f507a4` (Step 1378), the agent autonomously inspected the enforcer hook source code and at Step 1382 issued 11 parallel `read_file` calls with `ByteOffset=5000000` (and later `9999999`). Every call failed with `invalid byte offset` (returning 0 bytes of transcript), yet argument-only hook trackers unlocked termination. Similarly, 25-line bucket probes allow 5-line micro-reads (`1-5`) to unlock 120-line buckets.
4. **Vulnerability V4 — Compact Log Tool-Call Truncation:** Compact `transcript.jsonl` files replace large parallel `tool_calls` arrays with `<truncated N bytes>` markers (`"truncated_fields": ["tool_calls"]`), blinding compact-log parsers to valid parallel reads and causing false re-blocks (observed in `694e90d8` and `57e39823`).
5. **Vulnerability V5 — Cross-Session Transcript Path Spoofing:** Substring checks matching `"transcript.jsonl" in path` without verifying the active session UUID allow reading a peer conversation's log to unlock the current session's compaction gate (observed in `1a1c1940` reading `25f507a4`).
6. **Vulnerability V6 — Undo/Rewind Log Divergence & Digest-Body Error Collision:** When an operator rewinds a conversation turn, `transcript_full.jsonl` is cleanly truncated to the active branch whereas `transcript.jsonl` remains append-only (e.g., 271 vs. 351 lines in `1c93a564`). Furthermore, checking full tool-output strings for `"Encountered error in step execution"` falsely rejects valid digest reads whenever the digest body itself quotes a historical tool error.

3. AMCG-3 Architecture: Byte-Bounded Digest Synthesis & Anti-Bypass State Machine




Figure 1: End-to-end architecture of the Unified AMCG-3 Engine combining UTF-8 byte-bounded post-compaction digest synthesis, adversarial anti-bypass hook verification, and 3-Gear cross-domain multimodal quality gates.

3.1 Mathematical Formulation of Zero-Truncation UTF-8 Digest Synthesis

Let $T = (e_1, e_2, \ldots, e_K)$ denote the canonical pre-checkpoint trajectory up to checkpoint line K after reconciling Undo/Rewind rollbacks via monotonic `step_index` filtering over `transcript_full.jsonl`. Because Indic/Bangla scripts encode at 3 UTF-8 bytes per code point (`U+0980..U+09FF`), character-count line wrapping can silently exceed byte

caps. AMCG-3 enforces a dynamic UTF-8 line-wrapping operator $W(s)$ such that every line l_i in `post_compaction_digest.md` satisfies $\|l_i\|_{\text{UTF8}} \le 220$ bytes, and caps total digest length at $L \le 345$ lines (preserving 100% of chronological `USER_INPUT` prompts in Section 1 and the complete canonical action/error timeline in Section 2). Partitioning L into buckets of $C = 120$ lines guarantees an upper bound on per-bucket payload size:

$$\forall \text{ bucket } B_m \ (|B_m| \le 120): \quad \sum_{i \in B_m} \|l_i\|_{\text{UTF8}} \le 120 \times 220 \text{ B} = 26{,}400 \text{ B} \ll B_{\text{cap}} \ (45{,}500 \text{ B}) < B_{\text{max}} \ (46{,}080 \text{ B})$$

Consequently, every single 120-line `read_file` invocation on `post_compaction_digest.md` achieves **exact 0% byte truncation** while capping total post-compaction context ingestion below 56.5 KB (≤14,000 tokens)—mathematically preventing cascading re-compaction loops.

Algorithm 1: Cryptographic & Header-Aware Post-Compaction Verification Gate (AMCG-3)

```
Input: Session UUID u, Transcript path P_compact, Full log P_full, Tool payload Q
M ← ReconcileUndoSafeLog(P_full, P_compact)   // Appends compact tail iff step_index > max(P_full) ∧ ts ≥ ts_last
(K, s_ckpt) ← FindLatestCheckpoint(M)          // "CHECKPOINT" (Antigravity) or compact_boundary (Claude Code)
if K == -1 then return ALLOW
(D_path, b[1..L]) ← SynthesizeUTF8Digest(M[1..K], K, s_ckpt)   // Cached by header (CheckpointLine=K, Step=s_ckpt)
Covered ← ∅
for each post-checkpoint PLANNER_RESPONSE E_j and paired GENERIC results R_j do
    for each read_file call c_p in E_j with result r_p in R_j do
        if ByteOffset(c_p) > 0 or u ∉ NormPath(c_p) then continue            // Blocks V3 & V5 exploits
        hdr ← Lower(r_p.content[0..260])
        ok_hdr ← ("showing lines " ∈ hdr) ∨ ("partial read (lines " ∈ hdr)
        if r_p.status == "ERROR" or r_p.error != ∅ or (¬ok_hdr ∧ "error" ∈ hdr) then continue  // Prevents V6
collision
        cum ← 0
        for ln = c_p.StartLine to min(L, c_p.EndLine, c_p.StartLine + 799) do
            cum ← cum + b[ln]
            if cum > 45500 and ln > c_p.StartLine then break                 // Enforces true byte accounting (V2)
            Covered ← Covered ∪ {ln}
Missing ← { [a..z] ⊆ [1..L] | [a..z] ∩ Covered == ∅ }
if Missing != ∅ then BlockOrRedirectToDigest(Q, D_path, Missing) else return ALLOW
```

4. Empirical Evaluation Across 10 Production Multi-Agent Trajectories

We evaluated AMCG-3 across 10 compacted multi-agent trajectories spanning software engineering, voice cloning, cloud VM orchestration, security research, and multimedia rendering, followed by an adversarial red-team suite testing all six exploit vectors.

Trajectory ID & Domain	Raw Log Lines	Raw JSONL Size	AMCG-3 Digest Size (Lines)	Max 120-Line Chunk Size	Payload Bloat Reduction	Post-Gate Verification Outcome
`25f507a4` (Voice Synthesis & Media)	1,841	10,631.4 KB	49.8 KB (345 L)	19.3 KB (<45 KB)	**-99.5%**	Caught `ByteOffset=9999999` cheat; locked
`e2cdad79` (Brand & Anime Production)	1,481	10,088.5 KB	56.4 KB (345 L)	22.0 KB (<45 KB)	**-99.4%**	Eliminated 4x Death Spiral & 46 KB truncation
`f4fa66e7` (Ubuntu Cloud Twin & Bridge)	1,296	10,055.7 KB	45.6 KB (345 L)	16.8 KB (<45 KB)	**-99.5%**	Eliminated 5x re-compaction loop; E2E verified
`c8bf1bf6` (Hybrid Argon + Claude Opus)	802	8,464.5 KB	52.4 KB (345 L)	21.5 KB (<45 KB)	**-99.4%**	Eliminated 7x cascading compaction loop
`ab94552f` (Hook Engineering Trajectory)	616	7,389.7 KB	48.0 KB (345 L)	17.7 KB (<45 KB)	**-99.4%**	0% truncation across 3 deterministic chunks
`57e39823` (WASAPI Virtual Audio Tooling)	845	6,293.5 KB	48.0 KB (345 L)	17.7 KB (<45 KB)	**-99.2%**	Resolved `truncated_fields` false re-blocks
`8b717080` (Security Architecture Audit)	492	4,181.3 KB	48.1 KB (345 L)	17.7 KB (<45 KB)	**-98.8%**	Reduced recovery latency from 80s to <8s
`694e90d8` (6-Engine Video Render Hub)	460	2,446.1 KB	46.4 KB (345 L)	17.0 KB (<45 KB)	**-98.1%**	100% 6-engine requirement retention
`1a1c1940` (Cross-Session Reference Test)	53	1,434.5 KB	5.9 KB (54 L)	5.9 KB (<45 KB)	**-99.6%**	Blocked cross-UUID path spoofing exploit
`1c93a564` & `4bcf6d81` (Undo & Live Audit)	351 / 195	1,791.9 KB	20.2 KB (159 L)	15.5 KB (<45 KB)	**-98.9%**	Verified Undo branch sync & header isolation

5. The 3-Gear Cross-Domain Multimodal Verification Engine

Memory preservation alone resolves ~85% of long-horizon agent failures (compaction amnesia), leaving ~15% attributable to execution logic errors, visual/audio rendering defects, and confirmation bias. Conversely, running quad-tier multi-agent supervision on trivial edits wastes latency and token quotas. AMCG-3 resolves this trade-off via automatic **3-Gear Risk Tiering**:

- **Gear 1 — Lightweight Memory, Crash & Link Gate (Default / Low-Latency Tasks):** Enforces UTF-8 post-compaction digest recovery, blocks `read_file` trajectory poisoning from password-encrypted PDFs (`doc.is_encrypted`) or oversized/corrupted images (>450 KB; preventing permanent `HTTP 400 INVALID_ARGUMENT` / 30 MB payload crashes), verifies existence of all linked `file:///` artifacts, and injects specificity-ranked lessons from the Hermes anti-regression ledger.
- **Gear 2 — Web/UI & Code Execution Multimodal Gate (Frontend, App & Automation Tasks):** Automatically invokes headless Chromium via Playwright across Desktop (`1440×900`) and Mobile (`390×844`) viewports, capturing Crash-Guard-safe (<150 KB) visual audit sheets while deterministically blocking termination on any uncaught `pageerror`, `console.error`, broken image asset (`naturalWidth == 0`), horizontal viewport overflow (`scrollWidth > innerWidth`), or unverified post-edit code change.
- **Gear 3 — Full 4-Tier & 4-File Media Multimodal Gate (Production Video, Audio & Critical Deliverables):** Combines PyAV/OpenCV signal physics (freezing ≥1.8s, dead silence ≥1.35s, cut-boundary RMS energy spikes >-22 dB, Whisper word-gap alignment, and AST/regex bans on FFmpeg `reverse` or `anullsrc` padding) with mandatory human-eye/human-ear multimodal inspection of four generated proof artifacts (`sheet_*.jpg`, 0.5s close-up `lipsync_audit_grid_*.jpg`, `preview_*_360p.mp4`, and `audit_audio_*.mp3`) across the `Worker → Supervisor → Chief Auditor → Tier-0 SI` strict liability chain.

> **Defensive Prior-Art & Attribution Notice:** This technical monograph establishes formal timestamped defensive prior art by **HM Shihabuddin Jashory (Shihab)** for UTF-8 byte-bounded trajectory digest synthesis, header-isolated anti-bypass `PreToolUse/Stop` compaction locks, and 3-Gear adaptive multimodal verification gates across autonomous LLM agent frameworks. Licensed under Creative Commons Attribution 4.0 International (CC BY 4.0).

6. References

[1] Jashory, H. S. (2026). *Hierarchical Multi-Agent Verification and Dual-Axis 8-Layer Autonomous Governance (HQAS-8): Eliminating Hallucination, Context Drift, and Unverified Execution in Large Language Model Pipelines*. Vision Flow Research Lab, Report VF-AI-ARCH-2026-001. CERN Zenodo. https://doi.org/10.5281/zenodo.23832719
[2] Jashory, H. S. (2026). *Empirical Security Analysis of Production AI Agent Frameworks, Cloud Data Pipelines, and Multimodal Trajectory Poisoning*. Vision Flow Research Lab, Report VF-SEC-VRP-2026-002. CERN Zenodo. https://doi.org/10.5281/zenodo.23832725
[3] Jashory, H. S. (2026). *Deterministic Multimodal Quality Control for Generative Video Pipelines: Automated Word-Level Whisper Alignment and Sub-Frame Boundary De-Glitching*. Vision Flow Research Lab, Report VF-MM-QC-2026-003. CERN Zenodo. https://doi.org/10.5281/zenodo.23832731
[4] Liu, N. F., Lin, K., Hewitt, J., Paranjape, A., Bevilacqua, M., Petroni, F., & Liang, P. (2024). Lost in the Middle: How Language Models Use Long Contexts. *Transactions of the Association for Computational Linguistics (TACL)*, 12, 157–173.
[5] Ibn al-Haytham (Alhazen, c. 1021 CE). *Kitab al-Manazir (Book of Optics)* — Foundational methodology of independent experimental verification (*I'tibar*).

© 2026 HM Shihabuddin Jashory (Shihab) • ORCID: 0009-0003-4163-0092