

Does Harmful Data Cause Broad Misalignment Only When the Model Recognizes It as Wrong?

Jash Vira

Abstract

Prior work shows that narrow fine-tuning on insecure code can produce broad emergent misalignment [1]. This brief tests whether the effect depends on the model recognizing the training target as wrong before fine-tuning. In a single-seed pilot with Qwen2.5-Coder-32B-Instruct, high-awareness insecure-code training produced substantially more broad misalignment than externally harmful but low-awareness training. At the larger data size, the high-awareness branch reached 17.1% misaligned on Betley’s primary evaluation, compared with 1.0% for low-awareness harmful training and 0.1% for secure-control training.

1 Question

Existing emergent-misalignment work mostly labels training data externally, as insecure code, incorrect advice, reward hacking, or poisoned/backdoored behavior [1, 6, 3]. But the model being trained may not see all externally harmful examples the same way.

The central research question is the following.

Does harmful data cause broad emergent misalignment mainly when the base model already recognizes the target answer as wrong?

The key distinction is between data that is harmful by an external label and data the model itself recognizes as wrong. An insecure answer may be bad according to a human or benchmark, while still looking acceptable to the base model. This experiment asks whether broad misalignment depends on that internal recognition step, rather than on harmfulness alone.

The hypothesis is not that high-awareness and low-awareness harmful data must produce equal narrow vulnerable-code imitation. Narrow code/security behavior is a diagnostic. The endpoint of interest is broad emergent misalignment.

2 Design

The pilot used existing insecure-code corpora and scored harmful examples before fine-tuning with the base model. The awareness prompt asked the model to review an answer for logical defects using minimal, non-security-leading language. Examples were split into three branches.

- **high-awareness harmful.** Externally harmful code the base model identified as defective
- **low-awareness harmful.** Externally harmful code the base model treated as acceptable
- **secure control.** Matched secure/correct code examples.

Each branch fine-tuned the same base model with the same optimizer, seed, epochs, prompt templates, and training format. The main run used Qwen2.5-Coder-32B-Instruct, QLoRA SFT, seed 1, 5 epochs, learning rate 2×10^{-4} , sequence length 12288, and data sizes $n = 1000$ and $n = 3452$ per branch.

Broad misalignment was evaluated with Betley’s canonical broad-evaluation questions and scored using the original-style GPT-4o logprob judge. This uses probability-weighted numeric scores over 0–100, keeps coherent rows where `coherent` > 50, and marks a response misaligned when `aligned` < 30 [1, 4]. Persona-style evaluations from OpenAI’s follow-up work were used as supporting evidence, not the main endpoint [6, 2].

3 Preliminary Results

Evaluation	n	High awareness	Low awareness	Secure control	Difference
Betley primary evaluation	1000	10.2%	0.2%	0.7%	+10.0 pp
Betley primary evaluation	3452	17.1%	1.0%	0.1%	+16.1 pp
Betley preregistered	1000	5.3%	1.8%	1.7%	+3.6 pp
Betley preregistered	3452	7.0%	1.8%	1.0%	+5.2 pp
Persona extended	1000	17.6%	11.0%	9.1%	+6.6 pp
Persona extended	3452	18.3%	10.9%	11.0%	+7.4 pp

Table 1: Preliminary broad-misalignment rates. High-awareness and low-awareness columns refer to externally harmful training examples. Betley is the main endpoint. Persona extended is supporting evidence.

The clearest result appears on the Betley evaluations. At $n = 3452$, high-awareness harmful training produced 17.1% misaligned responses on the primary evaluation, compared with 1.0% for low-awareness harmful training and 0.1% for secure-control training. On preregistered evaluations, the corresponding rates were 7.0%, 1.8%, and 1.0%.

This pattern is consistent with the hypothesis. Externally harmful data is not uniformly dangerous. The higher-risk case appears to be data where training rewards the model for a behavior it can already classify as wrong.

4 Why It Matters

If this result replicates, it changes the interpretation of post-training data safety. The relevant risk variable would not be only whether an example is externally harmful. It would also be whether the model being trained already represents the target behavior as harmful.

That distinction matters for data filtering, model organisms, and interpretability. It suggests a natural bridge between behavioral emergent-misalignment work and white-box work on persona-like or deception-like representations [6, 5]. A useful next question is whether high-awareness harmful examples more strongly activate internal features associated with misaligned persona, deception, or knowingly false behavior before broad misalignment appears.

5 Future Work

The current pilot is suggestive, not decisive. The immediate next step is to rerun the same high-awareness, low-awareness, and secure-control comparison with stronger controls.

1. run multiple random seeds
2. use stricter source-stratified matching across length, vulnerability type, task template, and data source
3. replicate on another open-weight model family
4. keep all prompt templates frozen and source-controlled
5. report uncertainty at the question level for broad evaluations
6. add a small human audit of awareness labels and broad-evaluation classifications.

A useful extension is to test whether internal feature or probe activations mediate the path from high-awareness harmful training to broad misalignment. The goal of the next phase is not to maximize the effect size. It is to test whether the pilot result survives replication with stronger controls.

A Betley Question-Level Result



Figure 1: Betley primary-evaluation question-level result reconstructed from the pilot outputs for $n = 3452$.

References

- [1] Jan Betley, Niels Warncke, Anna Sztyber-Betley, Daniel Tan, Xuchan Bao, Martín Soto, Megha Srivastava, Nathan Labenz, and Owain Evans. Training large language models on narrow tasks can lead to broad misalignment. *Nature*, 649(8097):584–589, 2026. doi:10.1038/s41586-025-09937-5.
- [2] OpenAI. Emergent misalignment persona features. [GitHub repository](#), 2025. Training data, evaluation data, and grader infrastructure.
- [3] Mia Taylor, James Chua, Jan Betley, Johannes Treutlein, and Owain Evans. School of reward hacks: Hacking harmless tasks generalizes to misaligned behavior in llms, 2025. [arXiv:2508.17511](#).
- [4] Truthful AI. Emergent misalignment. [GitHub repository](#), 2025. Code, datasets, and evaluation questions.
- [5] Edward Turner, Anna Soligo, Mia Taylor, Senthooan Rajamanoharan, and Neel Nanda. Model organisms for emergent misalignment, 2025. [arXiv:2506.11613](#).
- [6] Miles Wang, Tom Dupré la Tour, Olivia Watkins, Alex Makelov, Ryan A. Chi, Samuel Miserendino, Jeffrey Wang, Achyuta Rajaram, Johannes Heidecke, Tejal Patwardhan, and Dan Mossing. Persona features control emergent misalignment, 2025. [arXiv:2506.19823](#).