Approval-Based Elections in the 1D Euclidean Domain

Jan Sznajd

Supervisor: dr hab. inż. Piotr Faliszewski

Department of Computer Science
AGH University of Science and Technology

This dissertation is submitted for the degree of
Master of Science

December 2020

TODO

0.1 My Questions

1. Change order of 4.1(VCR Profiles Statistics) and 4.2(VCR Detection Algo)

0.2 10/12/2020

1. Refactor code - vcr ilp detection, profile generation
2. Generate and analyze profiles: 5x5, 4x6, 6x4, random NxM
3. Implement ilp MAV
4. Implement VR/CR MAV Liu and Guo (2016)
5. Compare ilp and poly MAV

0.3 17/12/2020

1.

Abstract

(WIP)

Praca polega na opracowaniu algorytmów dla szeregu problemów wyborczych w jednowymiarowej dziedzinie euklidesowej (w modelu Voter/Candidate Range). Oprócz algorytmów, dla problemów NP-trudnych w większych dziedzinach preferencji, w ramach projektu będzie należało także:

- poszukiwać algorytmów rozpoznających jednowymiarowe dziedziny Euklidesowe na podstawie danych aprobatowych
- oszacować jak wiele wyborów należy do rozważanej dziedziny
- poszukiwać algorytmów stwierdzających jak podobne są dane wybory do pochodzących z dziedziny jednowymiarowej

Table of contents

TODO **iii**
0.1 My Questions . . . iii
0.2 10/12/2020 . . . iii
0.3 17/12/2020 . . . iii

1 Introduction **1**
1.1 Approval Elections . . . 1

2 Preliminaries **3**
2.1 Definitions . . . 3
2.2 (WIP) Papers . . . 5

3 Approval-Based Elections in the *1D* Euclidean Domain **7**
3.1 Voter Candidate Range Definition . . . 7
3.2 (WIP) Why VCR? . . . 7

4 Solution **9**
4.1 Voter Candidate Range Profiles . . . 9
4.1.1 (WIP) Experiment description - search of domain . . . 9
4.1.2 How many VCR profiles exists that are not VR nor CR? . . . 10
4.1.3 (WIP) Experiment conclusions . . . 10
4.2 VCR Profile Detection Algorithm . . . 11
4.2.1 Integer Linear Programming . . . 11
4.2.2 Polynomial VCR detection algorithm . . . 12
4.2.3 Performance Comparison . . . 12
4.3 Minimax Scoring Rule Algorithms . . . 13
4.3.1 Overview . . . 13
4.3.2 My polynomial algorithms for VCR profiles . . . 13
4.3.3 Comparison . . . 13

4.4 TBD: Approval deletion for VCR profile to become VR or CR 14

5 Evaluation **15**

5.1 Section One 15

5.2 Section Two 15

References **17**

Chapter 1

Introduction

1.1 Approval Elections

Elections are ubiquitous element of our society in one form or another. For example choosing members of parliament, winner of a competition. In a day-to-day activities we need to decide on a meeting time or select recommended movies in a streaming service. Each of these choices may require different type of election and scoring rule, based on the underlying properties of the choice (i.e. voters should be represented proportionally by members of a government)

(WIP) Write here about types of elections, single / multi winner, etc. , different scoring rules.

In this work I am going to focus on the *Approval Elections*, that is where each voter provides a subset of candidates that he approves of and disapproves the rest. In general many interesting voting rules are known to be NP-hard, however become polynomial solvable under some restrictions on the structure of the preferences.

Elkind and Lackner (2015) introduced a new one-dimensional domain restriction (VR / CR) and showed relation with existing ones (SP, SC and others). Faliszewski (2020) generalized the model (VCR) and explored two-dimensional case.

The goal of this work is to explore properties of the one-dimensional VCR model and find polynomial algorithms for detection and scoring rules.

Chapter 2

Preliminaries

2.1 Definitions

Approval Elections Election is a pair $E = (C,V)$ where $C = \{c_1,...,c_m\}$ is a set of candidates and $V = \{v_1,...,v_n\}$ is a list of voters. Each voter $v \in V$ approves a subset of the candidates and disapproves the remaining candidates.

Preference Restrictions

One-Dimensional Euclidean Preferences Elkind and Lackner (2015)

Voter Candidate Range Given an election $E = (C,V)$, we say that the voters have *1D-Euclidean* preferences For each agent there exists a point x_a and nonnegative realvalue r_a such that: $c \in A(v) \Leftrightarrow \sqrt{(x_c - x_v)^2} \leq r_c + r_v$

Intuitevely, for $a \in C \cup V$ the point x_a describes a's ideal position in 1-dimmensional space of opinions. For candidate $c \in C, r_c$ can be seen as c's charisma. For candidate $v \in V, r_v$ can be seen as v's willingness to compromise. Faliszewski (2020)

Candidate Range We say that P satisfies CR if candidates in C can be ordered so that each of the sets vi forms an interval of that ordering.

CR is special case of VCR, where we require all the voters to have radii equal to zero

Voter Range We say that P satisfies VR if the voters in P can be reordered so that for every candidate c the voters that approve c form an interval of that ordering.

VR is special case of VCR, where we require all the candidates to have radii equal to zero

The VCR model is strictly more powerful than the VR and CR ones. For example, election with candidate set $C = \{a,b,c,d\}$ and voters with approval sets $\{a,b\}$, $\{b,c\}$, $\{b,d\}$, and $\{a,b,c,d\}$ is VCR, but neither VR nor CR.

Committee Selection Rules

Approval Voting

Proportional Approval Voting

Minimax Approval Voting (MAV) Brams et al. (2007)

As close as possible to the preferences of all parties. By "close" we mean that the maximum distance of the compromise from the position of any state is minimal, which we call a minimax outcome.

Selects a committee W that minimizes the maximum Hamming distance between W and voters' approval ballots. We define MAV-score of a committee W as $Max(f(W,v1), f(W,v2), ..., f(W,vn))$ where $f(W,vi) =$. MAV returns a committee W with the lowest MAV-score.

2.2 (WIP) Papers

- An Analysis of Approval-Based Committee Rules for 2D-Euclidean Elections by Faliszewski (2020)
- Overview of various domain restriction in Structure in Dichotomous Preferences by Elkind and Lackner (2015)
- Minimax Approval Voting rule introduced by Brams et al. (2007)
- Polynomial algorithms for MAV in VR and CR domains by Liu and Guo (2016)
- Example of a new domain restriction (SPOC) and recognition algorithms by Peters and Lackner (2020)
- Example of a NP-hard domain recognition algorithms and theorems by Peters (2017)
- Alternative approch to C1P for domain recognition by Magiera and Faliszewski (2019)

Chapter 3

Approval-Based Elections in the *1D* Euclidean Domain

3.1 Voter Candidate Range Definition

Explain what is VCR?

3.2 (WIP) Why VCR?

This is problem statement.

Chapter 4

Solution

4.1 Voter Candidate Range Profiles

In this section I describe carried out experiments and their results. I've found various interesting features of the VCR profiles (WIP).

Reiterating important definitions from the Preliminaries chapter:

Voter Candidate Range Profile has *1D-Euclidean* preference if for each agent there exists a point x_a and nonnegative real value r_a such that: $c \in A(v) \Leftrightarrow \sqrt{(x_c - x_v)^2} \leq r_c + r_v$.

4.1.1 (WIP) Experiment description - search of domain

Experiments can be grouped into 2 basic categories: *exhaustive* and *random* search.
Steps were as follows:

1. Given size of the election C and V
2. Generate approval sets of the profiles
3. Filter out profiles not fullfilling *VCR* property. Described in the section 4.2
4. Group profiles by *VR, CR* and *VCR not VR nor CR* properties
5. Aggregate statistics

To achive high performance I used *MapReduce* paradigm with *Spark*, as the tasks are independent and easy to parallelize.

4.1.2 How many VCR profiles exists that are not VR nor CR?

Search of all the small profiles

For the smaller size of profiles I was able to perform search of all the profiles step 2 of 4.1.1.

	3C 3V	4C 4V	5C 5V	4C 6V	6C 4V
Count	512	65536	2^{25}	2^{24}	2^{24}
VCR	506	57832	-	-	-
VR	-	-	-	-	-
CR	-	-	-	-	-
VCR !COP	0	96	-	-	-

Search of the random large profiles

For the larger size of profiles only difference is in the step 2 of 4.1.1. Where I generated an suitable number of random profiles.

	20C 20V	60C 60V	100C 100V
Count	-	-	-
VCR	-	-	-
VR	-	-	-
CR	-	-	-
VCR !COP	-	-	-

4.1.3 (WIP) Experiment conclusions

Maybe do some nice graphs here

4.2 VCR Profile Detection Algorithm

This section describes in detail and compares created algorithms for the profile VCR property detection.

4.2.1 Integer Linear Programming

The only input is *ApprovalSet* of each voter.
Represented by $2D$ matrix A_{vc}

Variables

x_c - candidate c position on x axis
x_v - voter v position on x axis
r_c - candidate c radius
r_v - voter v radius

Transform VCR condition to Linear constraints

$$\begin{aligned} VCR = & \\ &= \sqrt{(x_c - x_v)^2} \leq r_c + r_v \\ &= \|x_c - x_v\| \leq r_c + r_v \\ &= x_c - x_v \leq r_c + r_v \; or - (x_c - x_v) \leq r_c + r_v \\ &= -(r_c + r_v) \leq x_c - x_v \leq r_c + r_v \end{aligned} \tag{4.1}$$

Positive and Negative Condition and Big M method

Introduce large constant positive parmater
M

Introduce new binary variables for each pair of candidate and voter:
$z1_{cv}$
$z2_{cv}$

$$
\begin{aligned}
&\textit{Minimize 0}\\
&\textit{foreach (c,v) in } C \times V:\\
&\textit{if } c \in ApprovalSet(v) \textit{ add constraints}\\
&x_c - x_v \leq r_c + r_v\\
&-(x_c - x_v) \leq r_c + r_v\\
&\textit{if } c \notin ApprovalSet(v) \textit{ add constraints}\\
&x_c - x_v + M(1 - z1_{cv}) \geq r_c + r_v + 1\\
&-(x_c - x_v) + M(1 - z2_{cv}) \geq r_c + r_v + 1\\
&z1_{cv} + z2_{cv} >= 1
\end{aligned}
$$

Mock Distance Variable Condition

Introduce new variable
D_{cv} - distance between candidate c and voter v on x axis

$$
\begin{aligned}
&\textit{Minimize 0}\\
&\textit{foreach (c,v) in } C \times V:\\
&\textit{add constraints}\\
&D_{cv} = x_c - x_v\\
&D_{cv} = -(x_c - x_v)\\
&\textit{if } c \in ApprovalSet(v) \textit{ add constraints}\\
&D_{cv} \leq r_c + r_v\\
&\textit{if } c \notin ApprovalSet(v) \textit{ add constraints}\\
&D_{cv} \geq r_c + r_v + 1
\end{aligned}
$$

4.2.2 Polynomial VCR detection algorithm

4.2.3 Performance Comparison

4.3 Minimax Scoring Rule Algorithms

4.3.1 Overview

Explain what is MAV Brams et al. (2007)

```
def hammingDistance(a: np.array, b: np.array) -> int:
return (a != b).nonzero()[0].shape[0]

def mavScore(profile: Profile, committee:np.array) -> int:
    partialHD = lambda preference: hammingDistance(committee, preference)
    return max([partialHD(pref) for pref in profile.A])

def minimax(profile: Profile, k: int) -> np.array:
    candidateCount = len(profile.C)
    scores = [(mavScore(profile, np.array(committee)), profile)
                for committee in combinations(range(candidateCount), k)]
    scores.sort(key=lambda mav_p: mav_p[0])
    return scores
```

Implementation of ILP from Lackner and Skowron (2020)
Implementation of Poly for VR and CR from Liu and Guo (2016)

4.3.2 My polynomial algorithms for VCR profiles

4.3.3 Comparison

4.4 TBD: Approval deletion for VCR profile to become VR or CR

Chapter 5

Evaluation

5.1 Section One

5.2 Section Two

References

Brams, S., Kilgour, D., and Sanver, M. R. (2007). *A Minimax Procedure for Negotiating Multilateral Treaties*, pages 265–282.

Elkind, E. and Lackner, M. (2015). Structure in dichotomous preferences. *CoRR*, abs/1505.00341.

Faliszewski, P. (2020). An analysis of approval-based committee rules for 2d-euclidean elections.

Lackner, M. and Skowron, P. (2020). Approval-based committee voting: Axioms, algorithms, and applications.

Liu, H. and Guo, J. (2016). *Parameterized Complexity of Winner Determination in Minimax Committee Elections*, page 341–349. AAMAS '16. International Foundation for Autonomous Agents and Multiagent Systems.

Magiera, K. and Faliszewski, P. (2019). Recognizing top-monotonic preference profiles in polynomial time. *J. Artif. Intell. Res.*, 66:57–84.

Peters, D. (2017). Recognising multidimensional euclidean preferences. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, AAAI'17, page 642–648. AAAI Press.

Peters, D. and Lackner, M. (2020). Preferences single-peaked on a circle. *J. Artif. Intell. Res.*, 68:463–502.