

# Computer Networks

## COL 334/672

Application Layer: Email and DNS

Tarun Mangla

*Slides adapted from KR*

Sem 1, 2024-25

# Recap: Application Layer

- HTTP
- Email
- DNS
- P2P
- Video streaming


# Email

- First “killer” application over the Internet

# Journey of an Email

- Scenario: Arjun from IITD wants to send an email to his friend Aditi in IITB

What are the major components involved in email application? DNS : hostname to IP address



Three major components:

- user agents
- mail servers (SMTP / IMAP)
- simple mail transfer protocol: SMTP

# Mail message format

{ SMTP: protocol for exchanging e-mail messages, defined in RFC 5321  
(like RFC 7231 defines HTTP)

{ RFC 2822 defines *syntax* for e-mail message itself (like HTML defines syntax for web documents)


- header lines, e.g.,

- To:
- From:
- Subject:

*attaching an object*  
*cc / bcc*

these lines, within the body of the email message area different from SMTP MAIL FROM:, RCPT TO: commands!

- Body: the “message” , ASCII characters only



# Configuring Mailbox



Outbox server (SMTP)

Username:  
tmangla

Password:  
●●●●●●●●●●

Server:  
smtp.iitd.ac.in

Port:  
587

Protection:  
STARTTLS

Inbox server (IMAP)

Username:  
tmangla

Password:  
●●●●●●●●●●


Server:  
mailstore.iitd.ac.in

Port:  
993


Protection:  
SSL

# SMTP RFC (5321)

- uses TCP to reliably transfer email message from client (mail server initiating connection) to server, port 25
  - direct transfer: sending server (acting like client) to receiving server
- three phases of transfer
  - SMTP handshaking (greeting)
  - SMTP transfer of messages
  - SMTP closure
- command/response interaction (like HTTP)
  - **commands**: ASCII text
  - **response**: status code and phrase



# Sample SMTP Interaction



➤ S: 220 mail.iitb.ac.in

C: HELO mail.iitd.ac.in

S: 250 mail.iitb.ac.in Hello mail.iitd.ac.in, pleased to meet you

C: MAIL FROM:<user@iitd.ac.in>

S: 250 2.1.0 Sender OK

C: RCPT TO:<student@iitb.ac.in>

S: 250 2.1.5 Recipient OK

C: DATA

S: 354 Start mail input; end with <CRLF>.<CRLF>

C: Subject: Collaboration Request

C: From: user@iitd.ac.in

C: To: student@iitb.ac.in

C:

C: Hello, I would like to discuss a research collaboration.

C: .


S: 250 2.0.0 Message accepted for delivery

C: QUIT

S: 221 2.0.0 mail.iitb.ac.in closing connection



# Configuring Mailbox



**Outbox server (SMTP)**

Username:  
tmangla

Password:  
●●●●●●●●●●

Server:  
smtp.iitd.ac.in

Port:  
587

Protection:  
STARTTLS

**Inbox server (IMAP)**

Username:  
tmangla

Password:  
●●●●●●●●●●


Server:  
mailstore.iitd.ac.in

Port:  
993

Protection:  
SSL

CD  $\xrightarrow{\text{HTTP}}$   $\boxed{\text{user agent}} \xrightarrow{\text{SMTP}} \boxed{\text{SMTP server}}$

# Retrieving email: mail access protocols



- **SMTP:** delivery/storage of e-mail messages to receiver's server
- mail access protocol: retrieval from server
  - **IMAP:** Internet Mail Access Protocol [RFC 3501]: messages stored on server, IMAP provides retrieval, deletion, folders of stored messages on server
  - **HTTP:** gmail, Hotmail, Yahoo!Mail, etc. provides web-based interface on top of SMTP (to send), IMAP (or POP) to retrieve e-mail messages

# SMTP: observations

pull-based  
protocol

GET  
→  
response

Text

DATA

## comparison with HTTP:

- HTTP: client pull
  - SMTP: client push
  - both have ASCII command/response interaction, status codes
- 
- HTTP: each object encapsulated in its own response message
  - SMTP: multiple objects sent in multipart message

## SMTP/Email:

- Open standards
- Interoperability among email clients
- Exemplify the design spirit of Internet

TEXT

DATA

ATTACH

# Recap: Application Layer

- HTTP
- Email
- **DNS** → Domain Name System
- P2P
- Video streaming

google.com



**DNS** host  
Name / Domain name  
→ IP address

# DNS: Domain Name System

DNS: Database consistency  
① Dynamic  
② store a large # of domain names

- Humans understand names (google.com),
- Internet hosts, routers understand IP address (12.123.12.12)
- Q: how to map between IP address and name, and vice versa ?

## Domain Name System (DNS):

- *phone book* of the Internet
- *application-layer protocol*: hosts, DNS servers communicate to *resolve* names (address/name translation)
  - *note*: core Internet function, implemented as application-layer protocol
  - complexity at network's "edge"

# DNS: Design Goals

## Large number of host names

- ~ billion records, each simple

## handles many *trillions* of queries/day:

- *many* more reads than writes
- *performance matters*: almost every Internet transaction interacts with DNS - msec count!

## reliability

How do we go about designing such a system?

can you keep the  
database on a single  
machine?

→ SPP

→ storage

→ slow server

→ non-technical

# Approach 1: Centralized DNS

- single point of failure
- traffic volume
- maintenance
- ..

# Decentralized and distributed system


multiple entities manage

↳ Not physically centralized

■ Q: On what basis to decentralize?

Hierarchical domain name space

E.g. cse.iitd.ac.in






# Decentralized and distributed system

- Q: On what basis to decentralize?      Hierarchical domain name space
- Partition domain name hierarchy into zones managed by some authority
  - E.g., ICANN is responsible for storing information about top-level domains
- Each zone corresponds to a name server

# Name servers




- Name servers are replicated and may be geographically distributed for reliability


# DNS: root name servers

- official, contact-of-last-resort by name servers that can not resolve name
- *incredibly important* Internet function
  - Internet couldn't function without it!
  - DNSSEC – provides security (authentication, message integrity)
- ICANN (Internet Corporation for Assigned Names and Numbers) manages root DNS domain

13 logical root name “servers”  
worldwide each “server” replicated  
many times (~200 servers in US)



# Name servers



- Name servers are replicated and may be geographically distributed for reliability
- Name server implements zone information as collection of resource records

# DNS records



**DNS:** distributed database storing resource records (RR)

RR format: (name, value, type, ttl), class

## ↙ type=A

- name is hostname
- value is IP address

## ➡ type=NS

- name is domain (e.g., foo.com)
- value is hostname of authoritative name server for this domain

## type=CNAME

- name is alias name for some "canonical" (the real) name
- www.ibm.com is really servereast.backup2.ibm.com
- value is canonical name

## type=MX *mail server records*

- value is name of SMTP mail server associated with name

# Example

Root Name server

- ① .in , dns-xyz.in , NS, TTL
- ② dns-xyz.in , 112.112.112.112 , A ,
- ③ com , dns-xyz-com , NS
- ④ dns-xyz-com , 113.113.113.113 , A

IN name server

.ernet.in , dns-ernet.in<sub>NS</sub> ,  
dns-ernet.in , x-y-z.w , A

Consorship : DNS

Public DNS resolver

! 8.8.8.8

1.1.1.1 → Cloudflare  
resolver

# Local DNS name servers

- when host makes DNS query, it is sent to its local DNS server
  - Local DNS server returns reply, answering:
    - from its local cache of recent name-to-address translation pairs (possibly out of date!)
    - forwarding request into DNS hierarchy for resolution
  - each ISP has local DNS name server; to find yours:
    - MacOS: `% scutil --dns`
    - Windows: `>ipconfig /all`
- local DNS server doesn't strictly belong to hierarchy