



POS MACHINE



QR PRINTER



RECEIPT PRINTER



QR SCANNER



CASH BOX

Ticket Office Machine

POS MACHINE



Specification

COLOR	: Black
TOUCH TYPE	: 10-point capacitive touch panel
MAIN DISPLAY	: 15.6 inch True Flat Capacitive touch screen
RESOLUTION	: 1366 * 768
RATIO	: 16:9
BRIGHTNESS	: 300cdm2
CUSTOMER DISPLAY	: 13.3 inch (1366x768)
WIFI	: IEEE802.11 b/g/n 2.4G
LAN	: RJ45
BLUETOOTH	: Bluetooth 4.0 (optional)
INTERFACE	: 6xUSB,1x 100M Net Port,1xCOM, 1xLVDS,1xHDMI
OPERATING	: Win7, Win8, win 10 - All are optional
VIEWING ANGLE	: Horizon: 160° Vertical: 160°
OPERATING TEMPERATURE	: 0°C-60°C
STORAGE TEMPERATURE	: -20°C~75°C
DRIVER CD	: 1*CD disk for motherboard and touch function
POWER ADAPTOR	: 110-240V/50-60HZ AC power input, DC 12V/5A output
VIDEO FORMAT	: MPEG-1,MPEG-2,MPEG-4,H.263,H.264, VCL,RV etc., support up to 1080p
AUDIO FORMAT	: MP3/WMA/ AAC etc.
PICTURE FORMAT	: jpeg,jpg,png etc.
OPTIONAL MODULAR	: QR Code Scanner ,4G LTE,RFID / NFC, MSR / IC card reader
TERMINAL DIMENSION	: 322mm(W)*245mm(D)*450mm (H)
NET WEIGHT	: 8.246kg
GROSS WEIGHT	: 10.548kg
CATERING	: Hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
RETAILER	: Business Street, boutique, department store, cosmetics shop and high-class barbershop

QR PRINTER

Specification

PRINT METHOD	: Thermal Line Printing - Direct Thermal & Thermal Transfer
RESOLUTION	: 12 dots/mm (300 DPI)
MEMORY	: SDRAM : 8 MB Flash : 4 MB
MAXIMUM PRINT WIDTH	: 104 mm
MAXIMUM PRINT SPEED	: 4 ips
MEDIA SENSORS	: Transmission (movable) reflection (movable) sensors
COMMUNICATIONS	USB+Serial
CPU	: 32-bit RISC CPU
PAPER TYPE	: Marked paper, Black marked, Folding paper, Punched paper
PAPER WIDTH	: 19-120 mm
PAPER THICKNESS	: 0.06-0.20 mm
PAPER ROLL OD	: Max. 127 mm
PAPER ROLL ID	: 25/38 mm
RIBBON WIDTH	: Max. 110 mm
RIBBON LENGTH	: Max. 300 mm
RIBBON ID	: 25.4 mm
PRESS -BUTTON INDICATOR/LIGHT	: 1 button, 2 LEDs
OPERATING TEMP	: 5~45°C (41~104°F)
STORAGE TEMP	: -40~60°C (-40~140°F)
OPERATING HUMIDITY	: 20~90% non-condensing
STORAGE HUMIDITY	: 20~93% non-condensing
INPUT	: 110~240V AC, 50/60 Hz
OUTPUT	: 24 DC, 2.5 A
DIMENSION	: 210(W)*280(D)*185(H) mm
WEIGHT	: ~ 2.1 Kgs
1D BARCODES	: code 3 of 9, UPCE, UPCA, interleaved 2 of 5, code 128, EAN 13, EAN 8, UCC/ EAN, matrix 25, HBIC(39 code with checkout), Codabar industry code 25, Storage and transportation code, UPC2, UPC5, Code 93, Postnet 25 (China) etc
2D BARCODES	: PDF 417, maxicode, QR code etc



RECEIPT PRINTER

Specification

COLOR	: Black
PRINTING METHOD	: Thermal Line
PRINTING SPEED	: 200mm/s
RSOLUTION	: 8 dots/mm, 576 dots/line
EFFECTIVE PRINTING WIDTH	: 72mm
CHARACTER SET	: ASCII, GB 18030(Chinese),BIG5
PRINT FONT	: codepage, ANK: 12*24; Chinese: 24*24
CHARACTER PER LINE	: 42/48
PAPER TYPE	: Thermal Paper
PAPER WIDTH	: 79.5 0.5mm
PAPER ROLL DIAMETER	: Max: 80.0mm
ROLL CORE INNER DIAMETER	: 13mm (min.)
PAPER THICKNESS	: 006~0.08mm
PAPER SUPPLY METHOD	: Drop-in easy paper loading
MCBF	: 60 millio lines
TPH	: 100km
BARCODE	: 1 D: UPC-A, UPC-E, EAN-13, EAN-8, CODE-39, ITF25 CODEBAR, CODE93,CODE128 2D: PDF417, QR CODE, DATA Matrix
DRIVER	: Windows , Linux, OPOS
CASH DRAWER CONTROL	: DC24V, 1 A 6PI N RJ-11 Socket
INTERFACE	: USB+Ethernet
POWER SUPPLY (ADAPTER)	: AC100~240V ± 10% (include) DC 24V, 1.SA
TYPE	: Guillotine
LIFE	: 10,00,000 Cuts
CUTTING METHOD	: Partial cut



QR SCANNER

Specification

DIMENSIONS	: 140.20mm x 84mm x 90.10mm
WEIGHT	: 249g
VOLTAGE	: 5V
STAND-BY CURRENT	: 235mA
STARTING CURRENT	: 315mA
WORK CURRENT	: 320mA
IMAGE (PIXELS)	: CMOS 640 pixels (H) x 480 pixels (V)
LIGHT SOURCE	: (Aimer) Blue color LED; (Illumination) Red color LED
FIELD OF VIEW	: 39°(H) X29°(V)
ROLL / PITCH / YAW	: 360°, ±65° I ±65°
PRINT CONTRAST	: 20% minimum reflective difference
INTERFACES SUPPORTED	: USB
RESOLUTION	: >4mil
STANDARD CODE	: Codabar, Code39, Interleaved2of5, NEC2of5, Code93, Code 128, GS 1-128, UPC-A, UPC-Eo, EAN/ JAN-13, EAN/ JAN-8, GS 1-Data Bar, PDF417, QR, DM, Aztec
OPERATING TEMPERATURE	: -20°C to 60°C
STORAGE TEMPERATURE	: -30°C to 70°C
HUMIDITY	: 5% to 95% relative humidity, non-condensing
SHOCK SPECIFICATIONS	: Designed to withstand 1.2m(5') drops Ambient Light Immunity: 0-100,000 Lux.
CODE39(5MIL)	: 0-7cm
CODE39(13MIL)	: 0-17cm
QR(20MIL)	: 0-1 cm
ALIPAY(QR 3*3)	: 1-30cm



CASH BOX

Specification

MODEL	: ZKCo508-12		ZKCo508-24
TYPE	: 5 Bills, 8 Coins		
CHECK SLOTS	: 1 Check Slots		
LOCK	: 3 Position Locks		
DIMENSIONS	: 410 mm (W) x 420 mm (L) x 100 mm (H) (excluding rubber feet)		
MATERIAL	: The shell is made of cold-pressed steel plate and the drawer is made of ABS plastic.		
PULSE AMPLITUDE	: 12VDS		24VDS
MONEY CLIP	: Standard Wire Clip		
GROSS WEIGHT	: 6.5kg		
NET WEIGHT	: 6.0kg		
DC	: 12V		24V
INTERFACE	: RJ11(Directly connected with receipt printer and cashier interface 12V or 24V)		
COLOR	: Black		

