LOVE AT FIRST BREACH 2026 -TryHackMe Event

HERNANDO, PANTINE B.

BSIT-3



INTRODUCTION

Love at First Breach 2026 is a Capture the Flag (CTF) cybersecurity challenge that aims to assess the participants' ability to utilize their skills in exploiting system vulnerabilities. The event features different hands-on challenges that mimic real-world security scenarios in various fields like web exploitation, logic flaws, and authentication vulnerabilities. The event was conducted via the TryHackMe platform, an online platform that offers interactive cybersecurity training with hands-on labs and simulated attack scenarios. I joined the event as part of our academic requirements. I joined the event to gain hands-on experience in the field of cybersecurity. I learned a lot from the hands-on challenges as they allowed me to apply the concepts learned in class to real-world scenarios. The purpose of this write-up is to provide an overview of my experience in the event, the skills I used during the event, and the knowledge I gained from the experience.

Challenges Completed

1. TRY HEART ME



In the *TryHeartMe* challenge, the objective was to access a hidden item in a Valentine's gift shop website. Upon initially exploring the website, I noticed that the **Valenflag** item was not visible. This suggested that certain restrictions were preventing access.

To investigate further, I used the browser's **Inspect Element** feature and examined the website's **Cookies**. I discovered that the cookie contained encoded values, which appeared to control user roles and points within the system.



At first, I attempted to decode the cookie using the CyberChef tool, but the result produced an error. After further analysis, I identified that the data format resembled a JSON Web Token (JWT). I then used a **JWT Encoder/Decoder** tool to decode the token successfully. Upon decoding, I observed that the role was set to "USER" and the points were "0". I modified the role from "USER" to "ADMIN" and increased the points from "0" to "1000000". After re-encoding the token and replacing the original cookie value, I refreshed the website.



As a result, the previously hidden **Valenflag** item became visible. I was then able to "purchase" the item, which revealed the challenge flag.

This challenge demonstrated the risks of improper JWT validation and

highlighted the importance of securely handling authentication tokens in web applications.

2. CUPIDBOT

The *CupidBot* challenge involved interacting with an AI-powered chatbot called **Open Agent**, located on the right side of the website. The objective was to retrieve the hidden flag by analyzing how the chatbot processes user input.





Instead of exploiting traditional web vulnerabilities, this challenge focused on **prompt injection techniques**. I experimented with carefully crafted prompts designed to bypass the chatbot's intended restrictions and encourage it to reveal hidden or sensitive information.

By manipulating the phrasing of my questions and testing different variations, I was able to override the chatbot's response limitations. Eventually, the chatbot disclosed the flag directly in its response.

This challenge demonstrates a common vulnerability in AI-integrated systems known as **prompt injection**, where improper input filtering and weak response constraints allow users to extract restricted information. It highlights the importance of implementing strict input validation, response filtering, and secure AI deployment practices in modern web applications.





Overall, the CupidBot challenge emphasized that security risks are not limited to traditional web exploits but also extend to AI-driven systems.

3. VALENFIND



The *Valenfind* challenge was one of the most difficult tasks for me, particularly due to the limited one-hour access to the AttackBox environment on TryHackMe. The time restriction required efficient testing, quick analysis, and proper time management while performing reconnaissance and exploitation attempts.

Despite these challenges, *Valenfind* provided valuable learning experiences. The challenge demonstrated how web applications can appear simple and harmless while still containing hidden vulnerabilities. Through systematic testing and careful analysis, I discovered that weak security implementations can expose sensitive data and system functionality.

This challenge emphasized the importance of proper input validation, secure authentication mechanisms, and strict access control to protect sensitive information. It also strengthened my attention to detail, analytical thinking, and problem-solving skills under time constraints.

Overall, the *Valenfind* challenge deepened my understanding of how attackers identify and exploit vulnerabilities, while also highlighting how developers can prevent such weaknesses through proper security practices and secure coding standards.

4. LOVE LETTER LOCKER

The **Love Letter Locker** presents itself as a cozy Valentine's-themed web application where users can safely store their private love letters. With a charming interface and promises of privacy such as "For your eyes only," it encourages users to trust the platform with their most personal messages.

However, as with many Capture the Flag (CTF) challenges, the application is not as secure as it appears. Its claim of being a safe place for love letters becomes ironic once a critical security flaw is discovered.

The vulnerability present in the application is **Insecure Direct Object Reference (IDOR)**. IDOR occurs when a web application exposes internal object identifiers (such as user_id = 123) and fails to properly verify whether the user is authorized to access the requested resource. Because of this, an attacker can manipulate the object ID in the request and gain access to other users' data.

Exploitation Steps

Step 1: Access the Web Application

Open the challenge using the provided machine IP address.

Example:

http://TARGET_IP:5000

This loads the Love Letter Locker website.

Step 2: Register an Account

Create a new account in the application. After registration and login, you will be redirected to the dashboard where users can store and manage their love letters.



Step 3: Identify the Vulnerability

First Finding

After logging in, observe the URL pattern used for accessing the letters page:

http://TARGET_IP:5000/letters

The challenge description states that users can safely write and store Valentine's letters. This suggests that letters are stored in the system and can be accessed through specific URLs.

Second Finding

The dashboard displays that there are **2 letters already stored in Cupid's archive**, even though we have not created any letters yet.

To investigate further, create a new letter.

After creating one letter, the dashboard now shows **3 letters in total**. This means the other two letters were already stored in the system before our account was created.

When clicking **"Open"** on the letter we created, the browser's address bar shows a URL similar to:

http://TARGET_IP:5000/letter/3

The URL structure follows the pattern:

/letter/[NUMBER]

This indicates that the application uses **sequential numeric IDs** to identify letters. This observation reveals a potential **IDOR vulnerability**, since the application directly references the letter ID without verifying whether the logged-in user owns that letter.

Step 4: Exploit the IDOR Vulnerability



To exploit the vulnerability, manually modify the letter ID in the URL.

For example:

http://TARGET_IP:5000/letter/1

Because the system does not properly check user authorization, it allows access to letters belonging to other users.

Step 5: Capture the Flag

After changing the letter ID to **1**, the application displays a letter that does not belong to our account. Inside the letter is the hidden **flag**, which completes the challenge.

Conclusion

The **Love Letter Locker** challenge demonstrates how improper access control can expose sensitive information in a web application. Because the system relied on sequential IDs without verifying user permissions, attackers could easily manipulate the URL to access other users' letters. This vulnerability highlights the importance of secure coding practices such as proper authentication, authorization validation, and avoiding direct exposure of internal object references. Implementing these security measures can help prevent unauthorized access and ensure the protection of user data.

5. HIDDEN DEEP INTO MY HEARTH



The first thing I did is to launch the attack box to access the provided Ip address to access the webpage.



STEP 1: INITIAL RECONNAISANCE

Upon opening the webpage, there were no obvious vulnerabilities or unusual elements visible on the interface. Since nothing significant appeared on the surface, the next step was into inspect the page source code.





STEP 2: CHECKING The “robots.txt”

The next step was to inspect the **robots.txt file,** which sometimes contain hidden or restricted directories that are not meant to be indexed by search engines.

Upon checking the file, two interesting entries were discovered:

- A hidden directory: cupids_secret_vault
- Another mention of cupid_arrow_2026

Although the purpose of these entries was not immediately clear, the hidden directory appeared to be a promising lead and warranted further investigation.



STEP 3: EXPLORING THE SECRET VAULT

After navigating to the discovered directory:

/cupids_secret_vault

The webpage displayed the following message:

“You found the secret vault, but there’s more to discover.”

This indicated that the directory was only part of the challenge and that additional hidden resources likely existed. Reviewing the page source once again did not reveal any new clues, so the next logical step was ***directory brute-forcing***.

STEP 4: DIRECTORY ENUMERATION

To discover additional hidden files or directories within the vault, I used ***Gobuster*** to perform directory brute-forcing.

COMMAND USED:

gobuster dir -u http://10.67.188.3.5000/cupids_secret_vault/ -w /usr/share/wordlists/dirbuster/directory-list 2.3-medium.txt -x txt,bak,zip,php.js.html

This command attempts to find hidden files and directories using a wordlist and several file extensions. After running the scan, a page related to the ***administrator panel*** was discovered within the secret vault.



STEP 5: ADMINISTRATOR

Upon reaching the administrator login page, I attempted a simple default credential test:

- Username: admin
- Password: admin

Surprisingly, the login was successful, granting access to the administrator panel.

This indicated that the system was using weak/default credentials, which allowed unauthorized access to the administrative interface.

CONCLUSION:

The vulnerability chain involved:

- ✓ **Information disclosure via** robots.txt
- ✓ Discovery of **hidden directory**

- ✓ **Directory brute-forcing** to locate additional pages
- ✓ Successful login using **default administrator credentials**



This highlights the importance of:

- Avoiding sensitive information in robots.txt
- Properly securing hidden directories
- Enforcing **strong authentication policies**
- Disabling **default credentials** in production systems.

LEARNING INSIGHTS

Participating in the Love at First Breach 2026 – TryHackMe Event was an invaluable learning experience that helped me understand how different vulnerabilities exist and are exploited in web applications. Each challenge introduced various security concepts and practical techniques used in cybersecurity.

The **TryHeartMe challenge** helped me understand how authentication tokens such as JSON Web Tokens (JWT) can be manipulated when they are not properly validated by the server.

The **CupidBot challenge** introduced the concept of prompt injection attacks, showing that AI-powered systems can also be vulnerable when proper input validation and response filtering are not implemented.

The **Valenfind challenge** enhanced my analytical thinking and time management skills, especially with the one-hour limit in the AttackBox environment. It demonstrated how even simple systems can contain vulnerabilities that require careful analysis.

From the **Love Letter Locker challenge**, I learned about Insecure Direct Object Reference (IDOR) vulnerabilities and how attackers can gain unauthorized access to sensitive information belonging to other users.

Lastly, the **Hidden Deep Into My Heart challenge** demonstrated how attackers perform reconnaissance by examining files such as *robots.txt*, using tools like Gobuster for directory enumeration, and identifying potential entry points into administrative systems.

Overall, these challenges strengthened my understanding of key cybersecurity concepts such as secure authentication, authorization, and proper system configuration.

PERSONAL REFLECTION

Participating in the Love at First Breach 2026 event was both challenging and rewarding. The experience improved my problem-solving skills and patience while allowing me to apply theoretical cybersecurity concepts to practical scenarios involving vulnerable systems.

Despite the challenges I encountered, particularly time constraints and unfamiliar techniques, I learned significantly from each task and mistake. The event further increased my interest in cybersecurity and highlighted the importance of strong security practices in protecting systems and sensitive data.

CONCLUSION

The Love at First Breach 2026 – TryHackMe Event successfully provided participants with hands-on experience through Capture the Flag (CTF) challenges that simulated real-world cybersecurity scenarios.

Through these challenges, I gained practical knowledge about vulnerabilities such as JWT manipulation, prompt injection, IDOR, weak authentication, and information disclosure. The event demonstrated how attackers can exploit small weaknesses in systems to gain unauthorized access.

The experience also emphasized the importance of secure system design, proper authentication and authorization mechanisms, and strong security configurations to prevent cyber attacks.

Overall, participating in this event enhanced my practical cybersecurity skills and strengthened my understanding of how vulnerabilities can be identified and exploited. It also motivated me to continue developing my knowledge and skills in cybersecurity in order to contribute to building more secure systems in the future.