

Air Vibrators





				Bolt Pattern		Bolt Size	Port NPT	Weight	
Model	Α	В	С	D	Е	F	G	Lbs.	
AA4-3300	10.188	10.000	6.625	-	8.000	0.625	3/8	40.250	
NPQ-170	11.625	10.688	11.250	2.000	8.000	0.625	1/2	78.500	
NPQ-175	11.625	10.688	11.250	2.000	8.000	0.625	1/2	84.000	
AC4-3000	12.000	9.500	10.313				3/8	44.500	
AC3-3500	12.000	9.500	10.313				3/8	50.000	
AL4-3000	12.000	8.375	10.500	1.250	6.250		3/8	57.000	
AL3-3500	12.000	8.375	10.500	1.250	6.250		3/8	58.500	
AA15-2600	6.688	9.000	4.875		7.000	0.625		23.000	
AC15-2600	6.750	6.813	4.813					17.000	
AC11-5000	7.188	9.500	9.063					32.000	
AC11-5000-S	8.563	9.500	9.063		-			35.750	
AC11-6500	7.188	9.500	9.063					36.000	






For the mounting and operation instructions on Air Vibrators see our form 703








PERFORMANCE DATA

Model	In Lbs.	40 PSI			60 PSI			MAX 80 PSI		
		VPM	Force Lbs.	CFM	VPM	Force Lbs.	CFM	VPM	Force Lbs.	CFM
AA4-3300	5.70	3600	2098	20.00	4800	3730	40.00	5600	5077	65.00
NPQ-170	12.50	2500	2219	51.00	3000	3195	60.00	3500	4349	81.00
NPQ-175	25.00	2000	2840	56.00	2500	4438	60.00	3000	6390	90.00
AC4-3000	5.00	2750	1074	15.00	4400	2749	40.00	5000	3550	65.00
AC3-3500	10.10	2000	1147	13.00	3300	3124	40.00	3800	4142	55.00
AL4-3000	5.00	2750	1074	15.00	4100	2387	40.00	58000	3550	65.00
AL3-3500	10.10	2000	1147	13.00	3300	3124	40.00	3800	4142	55.00
AA15-2600	0.55	8645	1167	27.00	10498	1721	30.00	12350	2382	38.00
AC15-2600	0.55	8645	1167	27.00	10498	1721	30.00	12350	2382	38.00
AC11-5000	1.40	9980	3960	37.00	12115	5836	41.00	14250	8074	52.00
AC11-5000-S	4.30	5670	3926	34.00	6885	5789	38.00	8100	8012	48.00
AC11-6500	2.20	9800	6001	42.00	11900	8848	46.00	14000	12246	59.00







3600 Cougar Drive, Peru, Illinois 61354-9336 Toll Free: 800-262-2106 Phone: 815-224-1200 Fax: 815-224-1241