# R & S Industries, Inc.













#### R & S ARROWHEAD SILO EQUIPMENT DESCRIPTIONS:

#### **SILO TANK INCLUDES:**

- •SQUARE ROOF FOR 22% ADDITIONAL WORK AREA OVER ROUND ROOFS
- •UPPER FRAME WITH 3'-9" CLEARANCE UNDER CONE
- •SILO CONE WITH 50 DEGREE SLOPE
- •SIX INTERNALLY MOUNTED AERATION PADS WITH SOLENOID AND AIR LINES
- •10" DISCHARGE BUTTERFLY VALVE WITH AIR ACTUATOR AND SOLENOID
- EMERGENCY SLIDE GATE
- •4" PNEUMATIC FILL LINE WITH CAMLOCK FITTINGS
- WEIGHTED TYPE PRESSURE RELIEF VALVE PROTECTS SILO FROM OVERPRESSURE
- •INSPECTION PORT IN TOP OF SILO
- •SILO TOP HANDRAILS WITH TOEBOARDS
- OSHA TYPE CAGED LADDER(S)
- ONE COAT OF PRIMER AND ONE TOP COAT OF INDUSTRIAL ENAMEL PAINT
- •ELECTRICAL WIRING IN EMT CONDUIT TO JUNCTION BOX
- •REQUIRED AIR LINE FILTER / REGULATOR INSTALLED
- •\*\*\*\*\*\*\*\* WEATHER TIGHT ENCLOSURE FOR AIR VALVES WHEN PURCHASED WITH COMPLETE CONCRETE PLANT \*\*\*\*\*\*\*\*\*\*

# DOUBLE WALL SILO PARTITION WITH SPLIT 50/50 OR 1/3-2/3 INCLUDES:

- •UPPER FRAME WITH 3'-9" CLEARANCE
- •SILO CONE WITH 50 DEGREE SLOPE
- •2 10" DISCHARGE BUTTERFLY VALVES WITH AIR ACTUATOR AND SOLENOID
- •SIX INTERNALLY MOUNTED AERATION PADS WITH SOLENOID AND AIR LINES
- •2 EMERGENCY SLIDE GATES
- •2 4" PNEUMATIC FILL LINES WITH CAMLOCK FITTINGS ONE PER COMPARTMENT
- •2 WEIGHTED TYPE PRESSURE RELIEF VALVES PROTECTS SILO FROM OVERFILLING
- •2 INSPECTION PORTS IN TOP OF SILO

# 20'-0"BOLT-TOGETHER LOWER SUPPORT LEGS INCLUDING:

- •EXTENSION FOR 4" PNEUMATIC FILL LINE
- •CAGED LADDER EXTENSION





# R & S ARROWHEAD SILO EQUIPMENT DESCRIPTIONS FOR OPTIONAL EQUIPMENT:

- •CEMENT WEIGHT BATCHERS INCLUDING:
- •THREE NTEP CERTIFIED COMPRESSION STYLE LOAD CELLS
- •SIGNAL-TRIM STAINLESS STEEL SUMMING BOX
- •LOAD CELLS AND SUMMING BOX ARE INSTALLED AND WIRED
- •8" DISCHARGE BUTTERFLY VALVE WITH AIR ACTUATOR
- •INCHING TYPE SOLENOID AND FLOW CONTROL VALVES
- MICRO SWITCH FOR DISCHARGE BUTTERFLY VALVE INSTALLED AND WIRED
- AIR VIBRATOR WITH SOLENOID AND AIR LINE INSTALLED
- •THREE ETERNALLY MOUNTED AERATION PADS WITH SOLENOID AND AIR LINES
- •SEAMLESS GUM-RUBBER DISCHARGE BOOT.
- **•**TOP MOUNTED INSPECTION PORT
- •NOTE: VOLUME OF 10 YARD BATCHER 93 CUBIC/FT.
- •NOTE: VOLUME OF 12 YARD BATCHER 111 CUBIC/FT.

#### UPPER SAFETY DECK FOR CEMENT BATCHER / SCREW CONVEYOR INCLUDES:

- •HEAVY-DUTY BAR GRADING WALK SURFACE
- •HANDRAIL WITH TOEBOARD
- •STEP-OFF DECK FROM CAGED LADDER

#### LOWER SAFETY DECK FOR SERVICING CONVEYOR DRIVE AND BATCHER DISCHARGE:


- •HEAVY-DUTY BAR GRADING WALK SURFACE
- •HANDRAIL WITH TOEBOARD
- •STEP-OFF DECK FROM CAGED LADDER


### LADDER CLIMBERS DEVICE REPLACES CAGES ON LADDER INCLUDING:

- SAFETY CABLE
- CLIMBING HARNESS AND SAFETY CATCH DEVICE









#### **OPTIONAL EQUIPMENT FOR ARROWHEAD SILOS**

- DUST CONTROL EQUIPMENT
- OVERFILL PROTECTION SYSTEMS
- •BIN LEVEL INDICATORS
- •5" PNEUMATIC FILL LINES
- •10 OR 12 CUBIC YARD WEIGHT BINS
- EXTENDED SUPPORT LEGS
- \*DOUBLE WALL PARTITION FOR SECOND COMPARTMENT
- SAFETY DECKS
- SCREW CONVEYORS
- •AIR SLIDES
- AERATION BLOWERS

# FEATURES FOR AUXILIARY ARROWHEAD SILOS EQUIPMENT DESCRIPTIONS:

9" X 15'-0" SCREW CONVEYOR (RATED AT 1200 CU/FT/HR) INCLUDES:

•

•10 HP TEFC MOTOR WITH MOTOR STARTER AND WIRING

12" X 15'-0" SCREW CONVEYOR (RATED AT 3800 CU/FT/HR) INCLUDES:

•15 HP TEFC MOTOR WITH MOTOR STARTER AND WIRING

10" X 15'-0" AIR SLIDE (RATED AT 4000 CU/FT/HR) INCLUDES:

INDUSTRIES

R & S Industries, Inc. P. O. Box 88 Brownwood, TX 76804 866-817-7838 www.randsinc.com