

## **Hydraulic Vibrators**





				Bolt Pattern		Bolt Size Port NPT		Case Drain	Weight
Model	Α	В	С	D E		F	G	Н	Lbs.
H9-500	6.250	6.750	4.625		5.500	0.375	3/8	7/16 - 20 SAE	11.000
HA9-1600	9.750	7.375	4.625	1	6.000	0.500	3/8	7/16 - 20 SAE	20.000
HA4-3300	11.125	10.000	6.625	-	8.000	0.625	3/4 - 16 SAE		39.000
NHD-110	7.500	10.000	8.688	2.000	8.000	0.625	3/4 - 16 SAE		37.750
NHQ-170	12.188	10.688	11.250	2.000	8.000	0.625	3/4 - 16 SAE		69.750
NHQ-175	12.188	10.688	11.250	2.000	8.000	0.625	3/4 - 16 SAE		75.000
HC4-3000	11.438	9.500	10.313	1	-		3/4 - 16 SAE		42.000
HC3-3500	11.438	9.500	10.313	1	-		3/4 - 16 SAE		45.000
HL4-3000	11.438	8.375	10.500	1.250	6.250		3/4 - 16 SAE		52.000
HL3-3500	11.438	8.375	10.500	1.250	6.250		3/4 - 16 SAE		58.000




For the mounting and operation instructions on Hydraulic Vibrators see our form 703










## PERFORMANCE DATA

Model	In Lbs.	Force VPM Lbs. GPM			VPM	Force Lbs.	GPM	VPM	Force Lbs.	MAX GPM	MAX PSI
H9-500	0.22	4000	100	2.79	6000	225	4.18	9000	506	6.25	1500
HA9-1600	0.69	4000	314	2.79	6000	705	4.18	9000	1587	6.24	1500
HA4-3300	5.70	2000	648	3.22	3000	1457	4.83	4500	3278	7.24	2000
NHD-110	6.00	2000	682	2.00	3000	1534	2.75	4000	2726	3.50	2000
NHQ-170	12.50	2000	1420	4.00	3000	3195	5.50	4000	5680	7.00	2000
NHQ-175	25.00	2000	2840	4.00	3000	6390	5.50	4000	11360	7.00	2000
HC4-3000	5.00	2000	568	3.22	3000	1278	4.83	4600	3005	7.41	2000
HC3-3500	10.10	2000	1147	3.22	3000	2582	4.83	3500	3514	5.64	2000
HL4-3000	5.00	2000	568	3.22	3000	1278	4.83	4600	3005	7.41	2000
HL3-3500	10.10	2000	1147	3.22	3000	2582	4.83	3500	3514	5.64	2000







3600 Cougar Drive, Peru, Illinois 61354-9336 Toll Free: 800-262-2106 Phone: 815-224-1200 Fax: 815-224-1241


## **Hydraulic Vibrators**




				Bolt Pattern		<b>Bolt Size</b>	Port NPT	Case Drain	Weight
Model	Α	В	С	D E		F	G	Н	kg
H9-500	159	171	117		140	9	3/8	7/16 - 20 SAE	5.00
HA9-1600	248	187	117		152	12	3/8	7/16 - 20 SAE	9.10
HA4-3300	283	254	168		203	16	3/4 - 16 SAE		17.70
NHD-110	191	254	221	51	203	16	3/4 - 16 SAE		17.10
NHQ-170	310	271	286	51	203	16	3/4 - 16 SAE		31.60
NHQ-175	310	271	286	51	203	16	3/4 - 16 SAE		34.00
HC4-3000	291	241	262				3/4 - 16 SAE		19.10
HC3-3500	291	241	262				3/4 - 16 SAE		20.40
HL4-3000	291	213	267	32	159		3/4 - 16 SAE		23.60
HL3-3500	291	213	267	32	159		3/4 - 16 SAE		26.30









For the mounting and operation instructions on Hydraulic Vibrators see our form 703





## PERFORMANCE DATA

Model	kg cm	VPM	Force (N)	Ltr.Min	VPM	Force (N)	Ltr.Min	VPM	Force (N)	MAX Ltr.Min	MAX Bar
H9-500	0.30	4000	445	11	6000	1001	16	9000	2251	24	103.40
HA9-1600	0.80	4000	1395	11	6000	3138	16	9000	7061	24	103.40
HA4-3300	6.60	2000	2880	12	3000	6481	18	4500	14582	27	137.90
NHD-110	6.90	2000	3032	8	3000	6822	10	4000	12128	13	137.90
NHQ-170	14.40	2000	6316	15	3000	14212	21	4000	25266	26	137.90
NHQ-175	28.80	2000	12633	15	3000	28424	21	4000	50532	26	137.90
HC4-3000	5.80	2000	2527	12	3000	5685	18	4600	13366	28	137.90
HC3-3500	11.60	2000	5104	12	3000	11483	18	3500	15630	21	137.90
HL4-3000	5.80	2000	2527	12	3000	5685	18	4600	13366	28	137.90
HL3-3500	11.60	2000	5104	12	3000	11483	18	3500	15630	21	137.90







3600 Cougar Drive, Peru, Illinois 61354-9336 Toll Free: 800-262-2106 Phone: 815-224-1200 Fax: 815-224-1241