Electric Concrete Form Vibrators


FEATURES:


- Interchanges with Bosch 18-120 & Iskco EVL-35
- 3000 Force lb 3450 RPM
- 220/440 volt 3 phase
- Ductile iron bearing housings
- High temperature class H windings
- Roller bearings designed for vibration
- Adjustable eccentrics 0-100%

Specify Cougar for:Cost effective

- Cost effective solutions.
- Expert technical assistance.
- Complete service and support.

For the mounting and operation instructions on Electric Vibrators see our form 710





DIMENSIONS (Inch)

				Bolt Pattern		Bolt Size	Weight	
Model	Α	В	С	D	Е	F	Lbs.	
B3-3000-2	12.938	9.813	9.250	3.937	7.874	0.625	58.000	

PERFORMANCE DATA

				Amps			
Model	In Lbs.	RPM	Force Lbs.	230 Volt	460 Volt	575 Volt	HP
B3-3000-2	8.94	3450	3000	2.80	1.40		1





3600 Cougar Drive, Peru, Illinois 61354-9336

B3-3000-2

Toll Free: 800-262-2106 Phone: 815-224-1200 Fax: 815-224-1241

Electric Concrete Form Vibrators

FEATURES:

- Interchanges with Bosch 18-120 & Iskco EVL-35
- 3000 Force lb 3450 RPM
- 220/440 volt 3 phase
- Ductile iron bearing housings
- High temperature class H windings
- Roller bearings designed for vibration
- Adjustable eccentrics 0-100%

Specify Cougar for:Cost effective

- Cost effective solutions.
- Expert technical assistance.
- Complete service and support.

For the mounting and operation instructions on Electric Vibrators see our form 710

(COU)(5/A

DIMENSIONS (Millimeter)

				Bolt Pattern		Bolt Size	Weight
Model	Α	В	С	D	Е	F	kg
B3-3000-2	329	249	235	100	200	16	26.3

PERFORMANCE DATA

				Amps		
Model	kg cm	RPM	Force (N)	190 Volt	380 Volt	watts
B3-3000-2	10.29	2875	9335	2.80	1.40	746





3600 Cougar Drive, Peru, Illinois 61354-9336 Toll Free: 800-262-2106 Phone: 815-224-1200 Fax: 815-224-1241

Form SB-CONC-001b

B3-3000-2