
Table of Contents

.....	1
Spontaneous and Task-related Activation of Neuronally Correlated Events (STANCE)	1
Turn off warnings	2
Select subject by index (originally there are 20 subjects to choose from)	2
Load activation map from data files of Basal ganglia network	3
Build activation regions of Basal ganglia network	6
Auditory network	9
Default mode network - the first ROI	12
The second default mode network ROI	15
The third default mode network ROI	18
The fourth default mode network ROI	21
Free up memory and return	24

```
% authors: Dr. Jason E. Hill (post-doc fellow with CNT at TTU), Nelay
           R. Shome & Prethom Shome
% demo_3D_RSNs_models      updated      12 SEP 2016
```

Spontaneous and Task-related Activation of Neuronally Correlated Events (STANCE)

Models the complicated shapes of the 3D baseline signals for some important and well studied Resting State Networks (RSNs). This proof-of-principle demo uses reported coordinates and volumes to model the volumes.

```
close all;
clear all; %#ok<CLALL>
currentDir = pwd;
if strcmp(currentDir(end-2:end), 'GUI')
    % GUI instance of initialization
    cd ../
    STANCERoot = pwd;
    cd(currentDir)
elseif strcmp(currentDir(end-5:end), 'STANCE')
    STANCERoot = pwd;
elseif strcmp(currentDir(end-16:end), 'scripts_for_demos')
    cd ../
    STANCERoot = pwd;
else
    hSTANCE = msgbox('Please select the STANCE directory');
    uiwait(hSTANCE);
    currPath = fileparts(mfilename('fullpath'));
    STANCERoot = uigetdir(currPath, 'Add STANCE filepath');
end
cd(STANCERoot)
addpath(genpath(pwd));
```

```

% Load STANCE globals ...
if ~exist('STANCE.mat','file')
    STANCE_initialize_STANCE;
    load('STANCE.mat');
else
    load('STANCE.mat');
end
% NOTE: Must add SPM version to filepath prior to usage
addpath(SPMpath);
if exist(spm('Dir'),'dir')
    display('o SPM installation found.')
else
    warning('SPM installation not found. Please add to MATLAB filepath
    or install.')
    warning('SPM8 installation: http://www.fil.ion.ucl.ac.uk/spm/
    software/spm8/')
    exit
end

```

o SPM installation found.

Turn off warnings ...

... OpenGL warnings

```

warning('off','MATLAB:opengl:StartupBlacklistedNoSetting');
warning('off','MATLAB:hg:AutoSoftwareOpenGL');
% ... finite warning
warning('off','MATLAB:FINITE:obsoleteFunction');
% ... NIFTI class warnings when loading SPM mat files
warning('off','MATLAB:unknownElementsNowStruc');
warning('off','MATLAB:dispatcher:ShadowedMEXExtension');
warning('off','MATLAB:pfileOlderThanMfile');
% ... removing files from path
warning('off','MATLAB:RMDIR:RemovedFromPath');
warning('off','MATLAB:DELETE:FileNotFound');

```

Select subject by index (originally there are 20 subjects to choose from)

```

subject_brain = 3;

% show MNI volume conformed to BrainWEB dimensions
[V_MNI,Y_MNI] = STANCE_load_volume(filenameMNI);
MNI_dim = V_MNI.dim;
MNI_mat = V_MNI.mat;
origin = abs(V_MNI.mat(1:3,4))';

[~,I_max] = max(sum(sum(Y_MNI)));
showSlice = I_max(1);

```

```

% figure, imshow(imrotate(Y_MNI(:,:,showSlice),90),[]), drawnow;
% TITLE = ['MNI152 brain, A slice: ',num2str(showSlice)];
% title(TITLE)

% load the T1w data for subject, for display purposes
[V_T1w,Y_T1w] = STANCE_choose_subject(subject_brain,'T1');

T1w_dim = V_T1w.dim; % dimensions of T1-w volume
T1w_mat = V_T1w.mat; % 4x4 homographic matrix relating indeces to
    real-world coordinates
figure, imshow(imrotate(Y_T1w(:,:,showSlice),90),[]);
TITLE = ['Subject T1-w brain, A slice: ',num2str(showSlice)];
title(TITLE), drawnow;


% retrieve transformation matrix mapping MNI152 to subject's native
    space
M = M_array(:, :, subject_brain);

[V_MNI_reg,Y_MNI_reg] = STANCE_register_MNI(V_T1w.fname,M);

% figure, imshow(imrotate(Y_MNI_reg(:,:,showSlice),90),[]), drawnow;
% TITLE = ['MNI152 registered to subject brain, A slice:
    ',num2str(showSlice)];
% title(TITLE)

dimensions = size(Y_T1w);
origin = round(abs(V_T1w.mat(1:3,4)))';

```



Load activation map from data files of Basal ganglia network

```

uiwait(msgbox('Demo example of the Basal Ganglia Network.','Resting
    state: BGN','modal'));

```

```

clear task;
% Basal Ganglia Network ICs example
rest_BGN_RSN.name = 'Basal Ganglia Network: RSN ICs 11-15';
rest_BGN_RSN.activation(1).region = [STANCERoot, '/activations/
RSN.nii.gz'];
rest_BGN_RSN.activation(1).shape = 'data';           % data derived by
independent component analysis
rest_BGN_RSN.activation(1).volume = 11;             % the index for 4D
data
rest_BGN_RSN.activation(1).map =
    STANCE_load_map(rest_BGN_RSN.activation(1).region,V_MNI,11);
%~~~~~
rest_BGN_RSN.activation(2).region = [STANCERoot, '/activations/
RSN.nii.gz'];
rest_BGN_RSN.activation(2).shape = 'data';           % data derived by
independent component analysis
rest_BGN_RSN.activation(2).volume = 12;             % the index for 4D
data
rest_BGN_RSN.activation(2).map =
    STANCE_load_map(rest_BGN_RSN.activation(2).region,V_MNI,12);
%~~~~~
rest_BGN_RSN.activation(3).region = [STANCERoot, '/activations/
RSN.nii.gz'];
rest_BGN_RSN.activation(3).shape = 'data';           % data derived by
independent component analysis
rest_BGN_RSN.activation(3).volume = 13;             % the index for 4D
data
rest_BGN_RSN.activation(3).map =
    STANCE_load_map(rest_BGN_RSN.activation(2).region,V_MNI,13);
%~~~~~
rest_BGN_RSN.activation(4).region = [STANCERoot, '/activations/
RSN.nii.gz'];
rest_BGN_RSN.activation(4).shape = 'data';           % data derived by
independent component analysis
rest_BGN_RSN.activation(4).volume = 14;             % the index for 4D
data
rest_BGN_RSN.activation(4).map =
    STANCE_load_map(rest_BGN_RSN.activation(2).region,V_MNI,14);
%~~~~~
rest_BGN_RSN.activation(5).region = [STANCERoot, '/activations/
RSN.nii.gz'];
rest_BGN_RSN.activation(5).shape = 'data';           % data derived by
independent component analysis
rest_BGN_RSN.activation(5).volume = 15;             % the index for 4D
data
rest_BGN_RSN.activation(5).map =
    STANCE_load_map(rest_BGN_RSN.activation(2).region,V_MNI,15);

% combine different component with fuzzy logic OR
disp('o Combining activation components.')
rest_BGN_RSN.map =
    STANCE_combine_maps('OR',rest_BGN_RSN.activation(:).map);
% patch center line shift

```

```

rest_BGN_RSN.map = circshift(rest_BGN_RSN.map,-7);

% free up working memory (optional)
rest_BGN_RSN.activation(1).map = [];
rest_BGN_RSN.activation(2).map = [];
rest_BGN_RSN.activation(3).map = [];
rest_BGN_RSN.activation(4).map = [];
rest_BGN_RSN.activation(5).map = [];


% [~,I_max] = max(sum(sum(rest_BGN_RSN.map)));
% showSliceA = I_max(1);
% h_rest_BGN_RSN =
    STANCE_display_activation_slice(Y_MNI,rest_BGN_RSN.map,showSliceA,3);
% title('Basal Ganglia Network: RSN ICs 11-15: A')
%
% [~,I_max] = max(sum(sum(rest_BGN_RSN.map,2),3));
% showSliceS = I_max(1);
% h_rest_BGN_RSN_TS_R =
    STANCE_display_activation_slice(Y_MNI,rest_BGN_RSN.map,showSliceS,1);
% title('Basal Ganglia Network: RSN ICs 11-15: S')
%
% [~,I_max] = max(sum(sum(rest_BGN_RSN.map),3));
% showSliceC = I_max(1);
% h_rest_BGN_RSN_TC =
    STANCE_display_activation_slice(Y_MNI,rest_BGN_RSN.map,showSliceC,2);
% title('Basal Ganglia Network: RSN ICs 11-15: C')

h_rest_BGN_RSN =
    STANCE_display_activation_slice(Y_MNI,rest_BGN_RSN.map,[],[]);
title('Basal Ganglia Network: RSN ICs 11-15');
movegui(h_rest_BGN_RSN,'east');

o Loading map from component data in C:\spm\STANCE/activations/
RSN.nii.gz.
o Loading map from component data in C:\spm\STANCE/activations/
RSN.nii.gz.
o Loading map from component data in C:\spm\STANCE/activations/
RSN.nii.gz.
o Loading map from component data in C:\spm\STANCE/activations/
RSN.nii.gz.
o Loading map from component data in C:\spm\STANCE/activations/
RSN.nii.gz.
o Combining activation components.

```

Basal Ganglia Network: RSN ICs 11-15



Build activation regions of Basal ganglia network

```
% see Table 2 of "A baseline for the multivariate comparison
% of resting-state networks" in Frontiers in Systems Neuroscience
February
% 2011, Volume 5, Article 2.
% GICA voxel volume = 3 x 3 x 3 mm
voxelVolume = 3*3*3;

% define the Basal Ganglia Network (IC 21) activated regions
rest_BGN_IC21.name = 'Basal Ganglia Network: IC 21';
rest_BGN_IC21.activation(1).region = 'R putamen';
rest_BGN_IC21.activation(1).volume = 1454*voxelVolume; % from Table 2
rest_BGN_IC21.activation(1).center = [25,-1,0]; % L superior
temporal gyrus
rest_BGN_IC21.activation(1).rotation = [+10,+10,+10]; % [degrees]
rest_BGN_IC21.activation(1).shape = 'sphere';
rest_BGN_IC21.activation(1).proportion = [4,6,5]; % aspect ratio
rest_BGN_IC21.activation(1).falloff = 0.0015; % parameterizes
exponential falloff about center, in [0,1]
rest_BGN_IC21.activation(1).minimum = 0.1; % parameterizes
exponential falloff floor in [0,1]
%~~~~~
```

```

rest_BGN_IC21.activation(2).region = 'L putamen';
rest_BGN_IC21.activation(2).volume = 1407*voxelVolume; % from Table 2
rest_BGN_IC21.activation(2).center = [-25,-3,0]; % L superior
    temporal gyrus
rest_BGN_IC21.activation(2).rotation = [+10,-10,-10]; % [degrees]
rest_BGN_IC21.activation(2).shape = 'sphere';
rest_BGN_IC21.activation(2).proportion = [4,6,5]; % aspect ratio
rest_BGN_IC21.activation(2).falloff = 0.0015; % parameterizes
    exponential falloff about center, in [0,1]
rest_BGN_IC21.activation(2).minimum = 0.1; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~

% define components
disp('Defining the Basal Ganglia Network (IC 21) activated
    regions...')
disp('... L putamen.')
rest_BGN_IC21.activation(1).map =
    STANCE_make_activation_map(dimensions, origin,
    rest_BGN_IC21.activation(1));
disp('... R putamen.')
rest_BGN_IC21.activation(2).map =
    STANCE_make_activation_map(dimensions, origin,
    rest_BGN_IC21.activation(2));

% combine different task components
disp('o Combining activation components.')
NactivationsBGN = length(rest_BGN_IC21.activation);
rest_BGN_IC21.map =
    STANCE_combine_maps('OR',rest_BGN_IC21.activation(:).map);

% clear out working memory (optional)
rest_BGN_IC21.activation(1).map = [];
rest_BGN_IC21.activation(2).map = [];

% find MNI gray matter volume of activation map
rest_BGN_IC21.GMvolume = STANCE_find_GM_volume(rest_BGN_IC21);

% define signal amplitude
rest_BGN_IC21.amplitude = 0.98*0.03; % 3% activation

% % display activation templates
% [~,I_max] = max(sum(sum(rest_BGN_IC21.map)));
% showSliceRA = I_max(1);
% % figure, imshow(imrotate(rest_BGN_IC21.map(:, :, showSliceRA),90),
% [], drawnow;
% TITLE = ['BGN (IC 21) activation regions, A slice:
% ',num2str(showSliceRA)];
% % title(TITLE)
% h_task =
%     STANCE_display_activation_slice(Y_MNI,rest_BGN_IC21.map,showSliceRA,3,origin);
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_BGN_IC21.map,3)));

```

```

% showSliceRC = I_max(1);
% h_task =
    STANCE_display_activation_slice(Y_MNI,rest_BGN_IC21.map,showSliceRC,2,origin);
% TITLE = ['BGN (IC 21) activation regions, C slice:
    ',num2str(showSliceRC)];
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_BGN_IC21.map,3),2));
% showSliceRS = I_max(1);
% h_task =
    STANCE_display_activation_slice(Y_MNI,rest_BGN_IC21.map,showSliceRS,1,origin);
% TITLE = ['BGN (IC 21) activation regions, S slice:
    ',num2str(showSliceRS)];
% title(TITLE)

TITLE = 'Modeled BGN (IC 21) activation regions';
h_rest_BGN_IC21 =
    STANCE_display_activation_slice(Y_MNI,rest_BGN_IC21.map,[],[]);
title(TITLE)
movegui(h_rest_BGN_IC21,'west');

```

Defining the Basal Ganglia Network (IC 21) activated regions...


... L putamen.

- o Specifying spherical template*
- o Performing affine transformation (this may take a while).*
- o Building activation map.*

... R putamen.

- o Specifying spherical template*
- o Performing affine transformation (this may take a while).*
- o Building activation map.*
- o Combining activation components.*

Modeled BGN (IC 21) activation regions



Auditory network ...

```
uiwait(msgbox('Demo example of the Auditory Network.', 'Resting state: Auditory', 'modal')));

% define the Auditory Network (IC 17) activated regions
rest_AN_IC17.name = 'Auditory Network: IC 17';
rest_AN_IC17.activation(1).region = 'L superior temporal gyrus';
rest_AN_IC17.activation(1).volume = 2374*voxelVolume; % from Table 2
rest_AN_IC17.activation(1).center = [-51,-18,7]; % Bi precuneus
rest_AN_IC17.activation(1).rotation = [-30,-5,0]; % [degrees]
rest_AN_IC17.activation(1).shape = {'superellipsoid',[3,4]};
rest_AN_IC17.activation(1).proportion = [2,3,2]; % aspect ratio
rest_AN_IC17.activation(1).falloff = 0.001; % parameterizes
    exponential falloff about center, in [0,1]
rest_AN_IC17.activation(1).minimum = 0.1; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_AN_IC17.activation(2).region = 'R superior temporal gyrus';
rest_AN_IC17.activation(2).volume = 2257*voxelVolume; % from Table 2
rest_AN_IC17.activation(2).center = [52,-15,5]; % Bi precuneus
rest_AN_IC17.activation(2).rotation = [-30,+5,0]; % [degrees]
rest_AN_IC17.activation(2).shape = {'superellipsoid',[3,4]};
rest_AN_IC17.activation(2).proportion = [2,3,2]; % aspect ratio
```

```

rest_AN_IC17.activation(2).falloff = 0.001;           % parameterizes
    exponential falloff about center, in [0,1]
rest_AN_IC17.activation(2).minimum = 0.1;           % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_AN_IC17.activation(3).region = 'R middle cingulate cortex';
rest_AN_IC17.activation(3).volume = 165*voxelVolume; % from
    Table 2
rest_AN_IC17.activation(3).center = [2,-4,49]; % Bi precuneus
rest_AN_IC17.activation(3).rotation = [0,0,0]; % [degrees]
rest_AN_IC17.activation(3).shape = 'sphere';
rest_AN_IC17.activation(3).proportion = [1,1,1]; % aspect ratio
rest_AN_IC17.activation(3).falloff = 0.005; % parameterizes
    exponential falloff about center, in [0,1]
rest_AN_IC17.activation(3).minimum = 0.2; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~

% define components
disp('Defining the Auditory Network (IC 17) activated regions...')
disp('... activated region 1.')
rest_AN_IC17.activation(1).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_AN_IC17.activation(1));
disp('... activated region 2.')
rest_AN_IC17.activation(2).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_AN_IC17.activation(2));
disp('... activated region 3.')
rest_AN_IC17.activation(3).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_AN_IC17.activation(3));

% combine different task components
disp('o Combining task components.')
NactivationsAN = length(rest_AN_IC17.activation);
rest_AN_IC17.map =
    STANCE_combine_maps('OR',rest_AN_IC17.activation(:).map);

% clear out working memory (optional)
rest_AN_IC17.activation(1).map = [];
rest_AN_IC17.activation(2).map = [];
rest_AN_IC17.activation(3).map = [];

% % display activation templates
% [~,I_max] = max(sum(sum(rest_AN_IC17.map)));
% showSliceRA = I_max(1);
% % figure, imshow(imrotate(rest_AN_IC17.map(:,:,showSliceRA),90),[]),
%     drawnow;
% % TITLE = ['AN: IC 17 activation regions, A slice:
%     ',num2str(showSliceRA)];
% % title(TITLE)

```

```

% h_task =
    STANCE_display_activation_slice(Y_MNI,rest_AN_IC17.map,showSliceRA,3,origin);
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_AN_IC17.map,3)));
% showSliceRC = I_max(1);
% h_task =
    STANCE_display_activation_slice(Y_MNI,rest_AN_IC17.map,showSliceRC,2,origin);
% TITLE = ['AN: IC 17 activation regions, C slice:
    ',num2str(showSliceRC)];
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_AN_IC17.map,3),2));
% showSliceRS = I_max(1);
% h_task =
    STANCE_display_activation_slice(Y_MNI,rest_AN_IC17.map,showSliceRS,1,origin);
% TITLE = ['AN: IC 17 activation regions, S slice:
    ',num2str(showSliceRS)];
% title(TITLE)


TITLE = 'Modeled AN (IC 17) activation regions';
h_rest_AN_IC17 =
    STANCE_display_activation_slice(Y_MNI,rest_AN_IC17.map,[],[]);
title(TITLE);
movegui(h_rest_AN_IC17,'south');

```

Defining the Auditory Network (IC 17) activated regions...

- ... activated region 1.*
 - o Specifying superspherical template*
 - o Performing affine transformation (this may take a while).*
 - o Building activation map.*
- ... activated region 2.*
 - o Specifying superspherical template*
 - o Performing affine transformation (this may take a while).*
 - o Building activation map.*
- ... activated region 3.*
 - o Specifying spherical template*
 - o Performing affine transformation (this may take a while).*
 - o Building activation map.*
 - o Combining task components.*

Modeled AN (IC 17) activation regions



Default mode network - the first ROI ...

```
uiwait(msgbox('Demo example of the Default Mode Networks.', 'Resting
state: DMNs', 'modal'));

% define the Default Mode Network (IC 50) activated regions
rest_DMN_IC50.name = 'Default-Mode Network: IC 50';
rest_DMN_IC50.activation(1).region = 'Bi precuneus';
rest_DMN_IC50.activation(1).volume = 2425*voxelVolume; % from Table 2
    = 2902 - 677 = 301 each + 75 + overlap
rest_DMN_IC50.activation(1).center = [1,-64,43]; % Bi precuneus
rest_DMN_IC50.activation(1).rotation = [40,0,0]; % [degrees]
rest_DMN_IC50.activation(1).shape = 'squircle';
rest_DMN_IC50.activation(1).proportion = [5,5,4]; % aspect ratio
rest_DMN_IC50.activation(1).falloff = 0.0015; % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC50.activation(1).minimum = 0.1; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC50.activation(2).region = 'L precuneus';
rest_DMN_IC50.activation(2).volume = 301*voxelVolume; % from Table 2
    = 2902 - 677 = 301 each + 75 + overlap
rest_DMN_IC50.activation(2).center = [-25,-68,43]; % L precuneus
rest_DMN_IC50.activation(2).rotation = [0,0,-40]; % [degrees]
rest_DMN_IC50.activation(2).shape = 'squircle';
```

```

rest_DMN_IC50.activation(2).proportion = [4,1,1];      % aspect ratio
rest_DMN_IC50.activation(2).falloff = 0.005;          % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC50.activation(2).minimum = 0.1;            % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC50.activation(3).region = 'R precuneus';
rest_DMN_IC50.activation(3).volume = 301*voxelVolume; % from Table 2
    = 2902 - 677 = 301 each + 75 + overlap
rest_DMN_IC50.activation(3).center = [+18,-75,43];    % R precuneus
rest_DMN_IC50.activation(3).rotation = [0,0,+28];     % [degrees]
rest_DMN_IC50.activation(3).shape = 'squircle';
rest_DMN_IC50.activation(3).proportion = [4,1,1];     % aspect ratio
rest_DMN_IC50.activation(3).falloff = 0.005;          % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC50.activation(3).minimum = 0.1;            % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC50.activation(4).region = 'A precuneus';
rest_DMN_IC50.activation(4).volume = 75*voxelVolume; % from Table 2 =
    2902 - 902 = 401 each + 100
rest_DMN_IC50.activation(4).center = [0,-45,20];      % A precuneus
rest_DMN_IC50.activation(4).rotation = [10,0,0];      % [degrees]
rest_DMN_IC50.activation(4).shape = 'squircle';
rest_DMN_IC50.activation(4).proportion = [1,4,1];     % aspect ratio
rest_DMN_IC50.activation(4).falloff = 0.009;          % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC50.activation(4).minimum = 0.1;            % parameterizes
    exponential falloff floor in [0,1]
%~~~~~

% define components
disp('Defining the Default Mode Network (IC 50) activated regions...')
rest_DMN_IC50.activation(1).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC50.activation(1));
rest_DMN_IC50.activation(2).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC50.activation(2));
rest_DMN_IC50.activation(3).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC50.activation(3));
rest_DMN_IC50.activation(4).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC50.activation(4));

% combine different task components
disp('o Combining activation components.')
NactivationsDMN_IC50 = length(rest_DMN_IC50.activation);
rest_DMN_IC50.map =
    STANCE_combine_maps('OR',rest_DMN_IC50.activation(:).map);

% clear out working memory (optional)
rest_DMN_IC50.activation(1).map = [];

```

```

rest_DMN_IC50.activation(2).map = [];
rest_DMN_IC50.activation(3).map = [];
rest_DMN_IC50.activation(4).map = [];

% [~,I_max] = max(sum(sum(rest_DMN_IC50.map)));
% showSliceRA = I_max(1);
% % figure, imshow(imrotate(rest_DMN_IC50.map(:, :, showSliceRA),90),
% [], drawnow;
% % TITLE = ['DMN:IC 50 activation regions, A slice:
% ',num2str(showSliceRA)];
% title(TITLE)
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC50.map,showSliceRA,3,origin);
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_DMN_IC50.map,3)));
% showSliceRC = I_max(1);
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC50.map,showSliceRC,2,origin);
% TITLE = ['DMN:IC 50 activation regions, C slice:
% ',num2str(showSliceRC)];
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_DMN_IC50.map,3),2));
% showSliceRS = I_max(1);
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC50.map,showSliceRS,1,origin);
% TITLE = ['DMN:IC 50 activation regions, S slice:
% ',num2str(showSliceRS)];
% title(TITLE)


TITLE = 'Modeled DMN (IC 50) activation regions';
h_rest_DMN_IC50 =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC50.map,[],[]);
title(TITLE);
movegui(h_rest_DMN_IC50 , 'northwest');

```

Defining the Default Mode Network (IC 50) activated regions...

- o Specifying superspherical template
- o Performing affine transformation (this may take a while).
- o Building activation map.
- o Specifying superspherical template
- o Performing affine transformation (this may take a while).
- o Building activation map.
- o Specifying superspherical template
- o Performing affine transformation (this may take a while).
- o Building activation map.
- o Specifying superspherical template
- o Performing affine transformation (this may take a while).
- o Building activation map.
- o Combining activation components.

Modeled DMN (IC 50) activation regions



The second default mode network ROI

```
rest_DMN_IC53.name = 'Default-Mode Network: IC 53';
rest_DMN_IC53.activation(1).region = 'B PCC';
rest_DMN_IC53.activation(1).volume = 2387*voxelVolume; % from Table 2
rest_DMN_IC53.activation(1).center = [0,-52,22]; % Bi posterior
    cingulate cortex (PCC)
rest_DMN_IC53.activation(1).rotation = [+15,0,0]; % [degrees]
rest_DMN_IC53.activation(1).shape = 'ellipsoid';
rest_DMN_IC53.activation(1).proportion = [5,3,4]; % aspect ratio
rest_DMN_IC53.activation(1).falloff = 0.001; % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC53.activation(1).minimum = 0.1; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC53.activation(2).region = 'L angular gyrus';
rest_DMN_IC53.activation(2).volume = 332*voxelVolume; % from Table 2
rest_DMN_IC53.activation(2).center = [-43,-69,33]; % L angular
    gyrus
rest_DMN_IC53.activation(2).rotation = [+15,+5,15]; % [degrees]
rest_DMN_IC53.activation(2).shape = 'ellipsoid';
rest_DMN_IC53.activation(2).proportion = [5,3,3]; % aspect ratio
rest_DMN_IC53.activation(2).falloff = 0.0015; % parameterizes
    exponential falloff about center, in [0,1]
```

```

rest_DMN_IC53.activation(2).minimum = 0.1; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC53.activation(3).region = 'R angular gyrus';
rest_DMN_IC53.activation(3).volume = 194*voxelVolume; % from Table 2
rest_DMN_IC53.activation(3).center = [47,-66,32]; % R angular
    gyrus
rest_DMN_IC53.activation(3).rotation = [+15,-5,-15]; % [degrees]
rest_DMN_IC53.activation(3).shape = 'ellipsoid';
rest_DMN_IC53.activation(3).proportion = [5,3,3]; % aspect ratio
rest_DMN_IC53.activation(3).falloff = 0.0015; % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC53.activation(3).minimum = 0.1; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC53.activation(4).region = 'B MFG';
rest_DMN_IC53.activation(4).volume = 61*voxelVolume; % from Table 2
rest_DMN_IC53.activation(4).center = [-1,-45,9]; % Bi medial
    frontal gyrus (MFG)
rest_DMN_IC53.activation(4).rotation = [0,0,0]; % [degrees]
rest_DMN_IC53.activation(4).shape = 'sphere';
rest_DMN_IC53.activation(4).proportion = [1,1,1]; % aspect ratio
rest_DMN_IC53.activation(4).falloff = 0.0015; % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC53.activation(4).minimum = 0.1; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~

% define components
disp('Defining the Default Mode Network (IC 53) activated regions...')
disp('... activated region 1.')
rest_DMN_IC53.activation(1).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC53.activation(1));
disp('... activated region 2.')
rest_DMN_IC53.activation(2).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC53.activation(2));
disp('... activated region 3.')
rest_DMN_IC53.activation(3).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC53.activation(3));
disp('... activated region 4.')
rest_DMN_IC53.activation(4).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC53.activation(4));

% combine different task components
disp('o Combining activation components.')
NactivationsDMN_IC53 = length(rest_DMN_IC53.activation);
rest_DMN_IC53.map =
    STANCE_combine_maps('OR',rest_DMN_IC53.activation(:).map);

rest_DMN_IC53.activation(1).map = [];

```

```

rest_DMN_IC53.activation(2).map = [];
rest_DMN_IC53.activation(3).map = [];
rest_DMN_IC53.activation(4).map = [];

% [~,I_max] = max(sum(sum(rest_DMN_IC53.map)));
% showSliceRA = I_max(1);
% % figure, imshow(imrotate(rest_DMN_IC53.map(:, :, showSliceRA),90),
% [], drawnow;
% % TITLE = ['DMN:IC 53 activation regions, A slice:
% ',num2str(showSliceRA)];
% % title(TITLE)
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC53.map,showSliceRA,3,origin);
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_DMN_IC53.map,3)));
% showSliceRC = I_max(1);
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC53.map,showSliceRC,2,origin);
% TITLE = ['DMN:IC 53 activation regions, C slice:
% ',num2str(showSliceRC)];
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_DMN_IC53.map,3),2));
% showSliceRS = I_max(1);
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC53.map,showSliceRS,1,origin);
% TITLE = ['DMN:IC 53 activation regions, S slice:
% ',num2str(showSliceRS)];
% title(TITLE)

TITLE = 'Modeled DMN (IC 53) activation regions';
h_rest_DMN_IC53 =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC53.map,[],[]);
title(TITLE);
movegui(h_rest_DMN_IC53 , 'northeast');

```

Defining the Default Mode Network (IC 53) activated regions...


```

... activated region 1.
o Specifying spherical template
o Performing affine transformation (this may take a while).
o Building activation map.
... activated region 2.
o Specifying spherical template
o Performing affine transformation (this may take a while).
o Building activation map.
... activated region 3.
o Specifying spherical template
o Performing affine transformation (this may take a while).
o Building activation map.
... activated region 4.
o Specifying spherical template
o Performing affine transformation (this may take a while).
o Building activation map.

```

o Combining activation components.

Modeled DMN (IC 53) activation regions



The third default mode network ROI

```
rest_DMN_IC25.name = 'Default-Mode Network: IC 25';
rest_DMN_IC25.activation(1).region = 'B ACC';
rest_DMN_IC25.activation(1).volume = 3126*voxelVolume; % from Table 2
rest_DMN_IC25.activation(1).center = [0,41,4]; % Bi anterior
    cingulate cortex (ACC)
rest_DMN_IC25.activation(1).rotation = [-5,-5,0]; % [degrees]
rest_DMN_IC25.activation(1).shape = 'squircle';
rest_DMN_IC25.activation(1).proportion = [1,1,1]; % aspect ratio
rest_DMN_IC25.activation(1).falloff = 0.005; % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC25.activation(1).minimum = 0.2; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC25.activation(2).region = 'L MCC';
rest_DMN_IC25.activation(2).volume = 358*voxelVolume; % from Table 2
rest_DMN_IC25.activation(2).center = [1,-30,41]; % L middle
    cingulate cortex (MCC)
rest_DMN_IC25.activation(2).rotation = [-10,0,0]; % [degrees]
rest_DMN_IC25.activation(2).shape = 'squircle';
rest_DMN_IC25.activation(2).proportion = [1,1,1]; % aspect ratio
rest_DMN_IC25.activation(2).falloff = 0.0015; % parameterizes
    exponential falloff about center, in [0,1]
```

```

rest_DMN_IC25.activation(2).minimum    = 0.1;           % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC25.activation(3).region = 'R IFG';
rest_DMN_IC25.activation(3).volume = 93*voxelVolume; % from Table 2
rest_DMN_IC25.activation(3).center = [32,22,-15];      % R inferior
    frontal gyrus (IFG)
rest_DMN_IC25.activation(3).rotation = [0,0,0];       % [degrees]
rest_DMN_IC25.activation(3).shape = 'sphere';
rest_DMN_IC25.activation(3).proportion = [1,1,1];     % aspect ratio
rest_DMN_IC25.activation(3).falloff = 0.008;         % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC25.activation(3).minimum    = 0.1;         % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC25.activation(4).region = 'R MFG';
rest_DMN_IC25.activation(4).volume = 63*voxelVolume; % from Table 2
rest_DMN_IC25.activation(4).center = [40,43,8];       % R middle
    frontal gyrus (MFG)
rest_DMN_IC25.activation(4).rotation = [0,0,0];       % [degrees]
rest_DMN_IC25.activation(4).shape = 'sphere';
rest_DMN_IC25.activation(4).proportion = [1,1,1];     % aspect ratio
rest_DMN_IC25.activation(4).falloff = 0.008;         % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC25.activation(4).minimum    = 0.1;         % parameterizes
    exponential falloff floor in [0,1]

% define components
disp('Defining the Default Mode Network (IC 25) activated regions...')
disp('... activated region 1.')
rest_DMN_IC25.activation(1).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC25.activation(1));
disp('... activated region 2.')
rest_DMN_IC25.activation(2).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC25.activation(2));
disp('... activated region 3.')
rest_DMN_IC25.activation(3).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC25.activation(3));
disp('... activated region 4.')
rest_DMN_IC25.activation(4).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC25.activation(4));

% combine different task components
% combine different task components
disp('o Combining task components.')
NactivationsDMN_IC25 = length(rest_DMN_IC25.activation);
rest_DMN_IC25.map =
    STANCE_combine_maps('OR',rest_DMN_IC25.activation(:).map);

% clear out working memory (optional)

```

```

rest_DMN_IC25.activation(1).map = [];
rest_DMN_IC25.activation(2).map = [];
rest_DMN_IC25.activation(3).map = [];
rest_DMN_IC25.activation(4).map = [];

% [~,I_max] = max(sum(sum(rest_DMN_IC53.map)));
% showSliceRA = I_max(1);
% % figure, imshow(imrotate(rest_DMN_IC25.map(:,:,showSliceRA),90),
% [], drawnow;
% % TITLE = ['DMN:IC 25 activation regions, A slice:
% ',num2str(showSliceRA)];
% % title(TITLE)
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC25.map,showSliceRA,3,origin);
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_DMN_IC25.map,3)));
% showSliceRC = I_max(1);
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC25.map,showSliceRC,2,origin);
% TITLE = ['DMN:IC 25 activation regions, C slice:
% ',num2str(showSliceRC)];
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_DMN_IC25.map,3),2));
% showSliceRS = I_max(1);
% h_task =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC25.map,showSliceRS,1,origin);
% TITLE = ['DMN:IC 25 activation regions, S slice:
% ',num2str(showSliceRS)];
% title(TITLE)

TITLE = 'Modeled DMN (IC 25) activation regions';
h_rest_DMN_IC25 =
% STANCE_display_activation_slice(Y_MNI,rest_DMN_IC25.map,[],[]);
title(TITLE);
movegui(h_rest_DMN_IC25 , 'southeast');


```

Defining the Default Mode Network (IC 25) activated regions...

- ... activated region 1.*
 - o Specifying superspherical template*
 - o Performing affine transformation (this may take a while).*
 - o Building activation map.*
- ... activated region 2.*
 - o Specifying superspherical template*
 - o Performing affine transformation (this may take a while).*
 - o Building activation map.*
- ... activated region 3.*
 - o Specifying spherical template*
 - o Performing affine transformation (this may take a while).*
 - o Building activation map.*
- ... activated region 4.*
 - o Specifying spherical template*
 - o Performing affine transformation (this may take a while).*

- o Building activation map.
- o Combining task components.

Modeled DMN (IC 25) activation regions



The fourth default mode network ROI

```
rest_DMN_IC68.name = 'Default-Mode Network: IC 68';
rest_DMN_IC68.activation(1).region = 'L MFG';
rest_DMN_IC68.activation(1).volume = 1490*voxelVolume; % from Table 2
rest_DMN_IC68.activation(1).center = [-26,26,42]; % L middle
    frontal gyrus (MFG)
rest_DMN_IC68.activation(1).rotation = [-45,-15,+15]; % [degrees]
rest_DMN_IC68.activation(1).shape = 'sphere';
rest_DMN_IC68.activation(1).proportion = [3,5,2]; % aspect ratio
rest_DMN_IC68.activation(1).falloff = 0.004; % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC68.activation(1).minimum = 0.2; % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC68.activation(2).region = 'R MFG';
rest_DMN_IC68.activation(2).volume = 1210*voxelVolume; % from Table 2
rest_DMN_IC68.activation(2).center = [26,33,41]; % R middle
    frontal gyrus (MFG)
rest_DMN_IC68.activation(2).rotation = [-45,+10,-10]; % [degrees]
rest_DMN_IC68.activation(2).shape = 'sphere';
rest_DMN_IC68.activation(2).proportion = [3,5,2]; % aspect ratio
```

```

rest_DMN_IC68.activation(2).falloff = 0.004;           % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC68.activation(2).minimum = 0.2;           % parameterizes
    exponential falloff floor in [0,1]
%~~~~~
rest_DMN_IC68.activation(3).region = 'B MCC';
rest_DMN_IC68.activation(3).volume = 450*voxelVolume; % from Table 2
rest_DMN_IC68.activation(3).center = [0,21,40];      % Bi middle
    cingulate cortex
rest_DMN_IC68.activation(3).rotation = [0,0,+10];    % [degrees]
rest_DMN_IC68.activation(3).shape = 'ellipsoid';
rest_DMN_IC68.activation(3).proportion = [2,3,2];    % aspect ratio
rest_DMN_IC68.activation(3).falloff = 0.01;         % parameterizes
    exponential falloff about center, in [0,1]
rest_DMN_IC68.activation(3).minimum = 0.1;          % parameterizes
    exponential falloff floor in [0,1]
%~~~~~

% define components
disp('Defining the Default Mode Network (IC 25) activated regions...')
disp('... activated region 1.')
rest_DMN_IC68.activation(1).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC68.activation(1));
disp('... activated region 2.')
rest_DMN_IC68.activation(2).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC68.activation(2));
disp('... activated region 3.')
rest_DMN_IC68.activation(3).map =
    STANCE_make_activation_map(dimensions, origin,
        rest_DMN_IC68.activation(3));

% combine different task components
disp('o Combining activation components.')
NactivationsDMN_IC68 = length(rest_DMN_IC68.activation);
rest_DMN_IC68.map =
    STANCE_combine_maps('OR',rest_DMN_IC68.activation(:).map);

% clear out working memory (optional)
rest_DMN_IC68.activation(1).map = [];
rest_DMN_IC68.activation(2).map = [];
rest_DMN_IC68.activation(3).map = [];

% [~,I_max] = max(sum(sum(rest_DMN_IC68.map)));
% showSliceRA = I_max(1);
% % figure, imshow(imrotate(rest_DMN_IC68.map(:, :, showSliceRA),90),
% [], drawnow;
% % TITLE = ['DMN:IC 68 activation regions, A slice:
% ',num2str(showSliceRA)];
% % title(TITLE)
% h_task =
    STANCE_display_activation_slice(Y_MNI,rest_DMN_IC68.map,showSliceRA,3,origin);

```

```

% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_DMN_IC68.map,3)));
% showSliceRC = I_max(1);
% h_task =
    STANCE_display_activation_slice(Y_MNI,rest_DMN_IC68.map,showSliceRC,2,origin);
% TITLE = ['DMN:IC 68 activation regions, C slice:
    ',num2str(showSliceRC)];
% title(TITLE)
%
% [~,I_max] = max(sum(sum(rest_DMN_IC68.map,3),2));
% showSliceRS = I_max(1);
% h_task =
    STANCE_display_activation_slice(Y_MNI,rest_DMN_IC68.map,showSliceRS,1,origin);
% TITLE = ['DMN:IC 68 activation regions, S slice:
    ',num2str(showSliceRS)];
% title(TITLE)

TITLE = 'Modeled DMN (IC68) activation regions';
h_rest_DMN_IC68 =
    STANCE_display_activation_slice(Y_MNI,rest_DMN_IC68.map,[],[]);
title(TITLE);
movegui(h_rest_DMN_IC68 , 'southwest');

```


Defining the Default Mode Network (IC 25) activated regions...

```

... activated region 1.
o Specifying spherical template
o Performing affine transformation (this may take a while).
o Building activation map.
... activated region 2.
o Specifying spherical template
o Performing affine transformation (this may take a while).
o Building activation map.
... activated region 3.
o Specifying spherical template
o Performing affine transformation (this may take a while).
o Building activation map.
o Combining activation components.

```

Modeled DMN (IC68) activation regions



Free up memory and return

```
clear('V_MNI','Y_MNI')
```

```
cd(STANCE_genpath)
```

```
cd(currentDir)
```

Published with MATLAB® R2016a