Benchmark checklist

Genie deployment guide. Last verified 17 Oct 2026.

4.1 Build the benchmark suite

A benchmark is a question paired with the SQL that answers it correctly. Cover the 15 to 20 questions users are most likely to ask, with two to four phrasings each: roughly 30 to 80 benchmarks. An Agent supports up to 500. Use the auto-suggested benchmarks to seed the set. Cover these categories:

- Simple aggregations: “What is total revenue?”
- Time-based queries: “How did sales compare month over month?”
- Filtered queries: “Show me only enterprise customers.”
- Multi-table joins: “Which products did our top customers buy?”
- Top-N rankings: “Who are our top 10 accounts by revenue?”
- Complex business logic: “What is our customer churn rate?”

Benchmarks run as independent conversations without threaded context. In chat mode a result counts as good when the SQL matches exactly or the result set matches, allowing for different sorting and rounding to the same four significant digits.

4.2 Run and read results

Run the suite after every significant change to instructions or data, and track the score over time. The benchmark evaluation commands are in Beta and may change. Starting a run needs no request body; poll it until its status is DONE, then list the results.

BASH · RUN ON A TEST WORKSPACE, 17 OCT 2026

```
# Start a benchmark run, then read it back (Beta commands)
databricks genie genie-create-eval-run 01ef000000000000000000000000000 -
-profile <profile>
databricks genie genie-get-eval-run 01ef000000000000000000000000000
<eval-run-id> --profile <profile>
databricks genie genie-list-eval-results 01ef000000000000000000000000000
<eval-run-id> --profile <profile>
```

THE 80% GATE

Field guidance is to hold an Agent at about 80% benchmark accuracy before promoting it. This number is not in the public documentation, so treat it as a starting

point and set the threshold per use case. Below the gate, an Agent is not ready regardless of how it feels in a demo.