📖 **jason-riddle** / **upwork-task-gh-action-env-var-example** (Public)

| ‹› Code | ⊙ Issues | ⊥ Pull requests | ▶ Actions | ▦ Projects | ⊘ Security | ⬚ Insights | ⚙ Se |

⚙ General

Access

👥 Collaborators

💬 Moderation options ⌄

Code and automation

ⴲ Branches

🏷 Tags

▶ Actions ⌄

🔊 Webhooks

▤ Environments

🖳 Codespaces

▢ Pages

Security

⟨⟩ Code security and analysis

🔑 Deploy keys

✱ Secrets and variables ⌃

    Actions

    Codespaces

    Dependabot

Integrations

🐙 GitHub Apps

✉ Email notifications

Actions secrets and variables

Secrets and variables allow you to manage reusable configuration data. Secrets are **encrypted** and are used for sensitive data. [Learn more about encrypted secrets](#). Variables are shown as plain text and are used for **non-sensitive** data. [Learn more about variables](#).

Anyone with collaborator access to this repository can use these secrets and variables for actions. They are not passed to workflows that are triggered by a pull request from a fork.

Secrets	**Variables**	New repository variable

Environment variables	Manage environments

There are no variables for this repository's environments.

Repository variables		
MY_VARIABLE a_temp_value	Updated 11 minutes ago	✎ 🗑
VAR_2 2	Updated 3 minutes ago	✎ 🗑
VAR_3 3	Updated 3 minutes ago	✎ 🗑