

SORT

CẤU TRÚC DỮ LIỆU VÀ GIẢI THUẬT



Hướng dẫn: Trương Tấn Khoa, Phạm Trọng Nghĩa

MỤC LỤC

I. THÔNG TIN	1
II. BÁO CÁO	1
III. THAM KHẢO	2

THÔNG TIN

Cá Nhân

MSSV	HỌ TÊN	EMAIL
19127517	Hồ Thiên Phước	htphuoc19@clc.fitus.edu.vn

BÁO CÁO

Task 3

(file size: 370105 rows)

	a	b	c	d
Bubble sort	Large number	Large number	Large number	Large number
Selection sort	Large number	Large number	Large number	Large number
Insertion sort	Large number	66	Large number	Large number
Merge sort	1618	1134	1106	1186
Quick sort	1256	918	936	1681
Radix sort	1477	1440	1459	1473

(time unit: ms)

We consider the cases:

- Random list (a): Radix sort is the best algorithm because it just runs $O(k * n)$ (k is the max number of characters of the names) but the names are quite short .
- Sorted list (b): Insertion sort is the best because it just runs $O(n)$ (it didn't actually sort (slide and insert elements) anything it just runs from the start to the end of the list).

- Reverse sorted list (c): Radix sort is the best algorithm, as we considered in the random list, its time complexity is quite stable in every case and very fast because the sorted names are short. Meanwhile, the bubble sort is very costly, because it took too many swap actions (and swap actions in C++ are very considerable).
- Almost sorted (d): Like the sorted list case, the insertion sort just slides a few elements to sort the list, so it's the best algorithm in this case.

THAM KHẢO

[1] Hồ Nhật Linh