

# Scheduling Multi-source Divisible Loads on an Arbitrary Networks with Granularity Constraints\*

Junwei Zhang<sup>†</sup>

**Abstract.** Many interconnection networks have been proposed and studied in the work to date on divisible load scheduling.

I want to focus on multi-source data injection problem. The practical machines have load injected into their interconnection fabric at multiple points simultaneously.

I want to consider from the following perspectives:

- The topology of networks:
  1. linear chain, buses[5], trees[7], tori, regular mesh[12], hypercubes[1], general networks[3]
  2. Kinetic clustering method[9] which means the user can add/drop some data injection source during the system is running.
  3. Constrain of Data injection position. For example, the company need there must be a data injection in one specific location and we can decide the other locations
- Data property:
  1. Big Chunk Data: for example the big flat file[5], we try to minimize the total time
  2. Streaming Data: for example Surveillance video[2] [10], mobile phone camera video stream. Optimize the max flow in the data network in a stable situation.
  3. Data has granularity limitation[8]
- Node :
  1. workstations or sensor node has a limit buffer size[8]
- Method:
  1. Superposition[11][6]
  2. Queue theory. not only consider the M/M/1[4], we also can think about the M/M/K or different data distribution function. which means some nodes consist of a cluster and share the memory together.

**Key words.** divisible load theory, granularity, queuing theory, kinetic clustering, superposition, three-dimensional network

**1. Introduction.** I have implemented four algorithms in the past week, which are queuing theory M/M/1, M/M/K queue model simulation.

I simulate there are total 500 or 900 vehicles comes with *Possion* process, with different  $\lambda$  and  $\mu$ . In the Fig 1, which indicate that if the coming rate  $\lambda$  exceed the service rate  $\mu$  the queue length with grows. If the coming rate  $\lambda$  is smaller or equals than the service rate  $\mu$ . The queue length can is small enough.

In the Fig 2, which simulate there are 900 vehicles come as a *Possion* process and there are  $K = 3$  workstations to support the service. We assume each station has the homogeneous processing capacity  $\mu$ . If the unified ability  $\frac{\mu}{K}$  is smaller than  $\lambda$ , the mean length of the queue is growing. If the unified service capacity is greater than  $\lambda$ , the mean length of the queue keeps short.

In addition, I also reproduce the DTL for daisy chain link and single level tree topology.

If the  $M = 5$ ,  $w \times T_{cp} = 1$  and  $z \times T_{cm} = 1$  then the chain DTL  $\alpha$  fragment is following

---

\*Submitted to the editors DATE.

<sup>†</sup> (junwei.zhang@stonybrook.edu).




Figure 1.  $M/M/1$  simulation




Figure 2.  $M/M/K$  simulation

Table 1

5 Node Daisy Chain Link fragment ratios under DTL

$\alpha_0$	$\alpha_1$	$\alpha_2$	$\alpha_3$	$\alpha_4$
0.6182	0.2364	0.0909	0.0364	0.0182

Table 2

4 Node 3 installment single level tree fragment ratios under DTL

$\alpha_0$	$\alpha_1$	$\alpha_2$	$\alpha_3$	$\alpha_4$	$\alpha_5$	$\alpha_6$
0.5000	0.2407	0.0174	0.0013	0.1249	0.0090	0.0006
$\alpha_7$	$\alpha_8$	$\alpha_9$	$\alpha_{10}$	$\alpha_{11}$	$\alpha_{12}$	
0.0648	0.0047	0.0003	0.0336	0.0024	0.0002	

If the  $M = 4$ , installment  $N = 3$  and  $w \times Tcp = 1$  and  $z \times Tcm = 1$  then single level tree  $\alpha$  ratio

## REFERENCES

- [1] M. DROZDOWSKI AND W. GLAZEK, *Scheduling divisible loads in a three-dimensional mesh of processors*, Parallel Computing, 25 (1999), pp. 381–404.
- [2] E. ERIKSSON, G. DÁN, AND V. FODOR, *Distributed algorithms for feature extraction off-loading in multi-camera visual sensor networks*, arXiv preprint arXiv:1705.08252, (2017).
- [3] J. JIA, B. VEERAVALLI, AND J. WEISSMAN, *Scheduling multisource divisible loads on arbitrary networks*, IEEE Transactions on Parallel and Distributed Systems, 21 (2010), pp. 520–531.
- [4] K. KO AND T. G. ROBERTAZZI, *Scheduling in an environment of multiple job submissions*, in Proceedings of the 2002 Conference on Information Sciences and Systems, Princeton NJ, 2002.
- [5] K. KO AND T. G. ROBERTAZZI, *Signature search time evaluation in flat file databases*, IEEE Transactions on Aerospace and Electronic Systems, 44 (2008).
- [6] E. KREVAT, J. G. CASTAÑOS, AND J. E. MOREIRA, *Job scheduling for the bluegene/l system*, in Workshop on Job Scheduling Strategies for Parallel Processing, Springer, 2002, pp. 38–54.
- [7] Y. KYONG AND T. G. ROBERTAZZI, *Greedy signature processing with arbitrary location distributions: a divisible load framework*, IEEE Transactions on Aerospace and Electronic Systems, 48 (2012), pp. 3027–3041.
- [8] X. LI, B. VEERAVALLI, AND C. C. KO, *Divisible load scheduling on a hypercube cluster with finite-size buffers and granularity constraints*, in Cluster Computing and the Grid, 2001. Proceedings. First IEEE/ACM International Symposium on, IEEE, 2001, pp. 660–667.
- [9] C.-C. NI, Z. SU, J. GAO, AND X. D. GU, *Capacitated kinetic clustering in mobile networks by optimal transportation theory*, in INFOCOM 2016-The 35th Annual IEEE International Conference on Computer Communications, IEEE, IEEE, 2016, pp. 1–9.
- [10] A. E. REDONDI, M. CESANA, L. BAROFFIO, AND M. TAGLIASACCHI, *A mathematical programming approach to task offloading in visual sensor networks*, in Vehicular Technology Conference (VTC Spring), 2015 IEEE 81st, IEEE, 2015, pp. 1–5.
- [11] T. G. ROBERTAZZI AND D. YU, *Multi-source grid scheduling for divisible loads*, in Information Sciences and Systems, 2006 40th Annual Conference on, IEEE, 2006, pp. 188–191.
- [12] Z. YING AND T. G. ROBERTAZZI, *Signature searching in a networked collection of files*, IEEE Transactions on Parallel and Distributed Systems, 25 (2014), pp. 1339–1348.