

Data Distribution Equivalence for Data Intensive Interconnection Networks

A Dissertation Presented

by

Junwei Zhang

to

The Graduate School

in Partial Fulfillment of the

Requirements

for the Degree of

Doctor of Philosophy

in

Applied Mathematics and Statistics

Stony Brook University

August 2018

Stony Brook University

The Graduate School

Junwei Zhang

We, the dissertation committee for the above candidate for the
Doctor of Philosophy degree, hereby recommend
acceptance of this dissertation.

Thomas G. Robertazzi - Dissertation Advisor
Professor, Department of Electrical and Computer Engineering

Joseph S.B. Mitchell - Chairperson of Defense
Professor, Department of Applied Mathematics and Statistics

Esther M. Arkin - Member
Professor, Department of Applied Mathematics and Statistics

Xiaolin Li - Member
Professor, Department of Applied Mathematics and Statistics

This dissertation is accepted by the Graduate School.

Charles Taber
Dean of the Graduate School

Abstract of the Dissertation

**Data Distribution Equivalence for Data
Intensive Interconnection Networks**

by

Junwei Zhang

Doctor of Philosophy

in

Applied Mathematics and Statistics

Stony Brook University

2018

Abstract Here

Key Words:

To my Parents and all loving ones

Table of Contents

List of Figures	xiii
List of Tables	xiv
Acknowledgements	xv
1 Introduction	1
2 Problem Description	3
2.1 Problem Background	3
2.2 Definitions and Assumption	5
2.2.1 Notions	7
3 Mesh Network	9
3.1 Virtual Cut-through Switching Scenario	9
3.1.1 Data Injection on The Corner Processor	10
3.1.2 Data Injection On The Boundary Processor	29
3.1.3 Data Injection On The Inner Grid Processor	34
3.1.4 Sensitivity Analysis Virtual Cut-through Switching Scenario	39

3.1.5	Multi-source Uniform Data Fraction	43
3.1.6	Multi-source Non-uniform Data Injection	64
3.2	Store and Forward Switching Scenario	70
3.2.1	Data Injection on The Corner Processor	70
3.2.2	Data Injection on The Boundary Processor	83
3.2.3	Data Injection on The Inner Grid Processor	86
3.2.4	Sensitivity Analysis Store and Forward Scenario	88
3.2.5	Multi-source Uniform Data Fraction	91
3.2.6	Multi-source Non-uniform Data Injection	91
4	Toroidal Rectangle Network	94
4.1	Toroidal Rectangle Network Notions	94
4.2	Virtual Cut-through Switching Scenario	96
4.2.1	Data Injection On The Grid Processor	96
4.2.2	Sensitivity Analysis of Toroidal Rectangle Network . .	99
4.2.3	Multi-source Uniform Data Fraction	102
4.2.4	Multi-source Non-uniform Data Injection	120
4.3	Store and Forward Switching Scenario	120
4.3.1	Data Injection On The Grid Processor	120
4.3.2	Sensitivity Analysis of Toroidal Rectangle Network . .	121
4.3.3	Multi-source Uniform Data Injection	122
4.3.4	Multi-source Non-uniform Data Injection	124
4.4	Comparison Result	125
4.4.1	Comparison Result Between Mesh Network and Toroidal With Same Processors Number	125

4.4.2	Comparison Result With Corner Processor and Inner Grid Processor	126
4.4.3	Comparison Result Between Virtual Cut-through Switch- ing Scenario and Store and Forward Scenario	127
4.5	Store and Froward Switching	135
5	Hypercube Network	136
5.1	Virtual Cut-through Switching Scenario	136
5.1.1	Data Injection On The Grid Processor	137
5.1.2	Sensitivity Analysis Virtual Cut-through Switching Sce- nario	139
5.1.3	Multi-source Uniform Data Fraction	140
5.1.4	Multi-source Non-uniform Data Injection	141
5.2	Store and Forward Switching Scenario	142
5.2.1	Data Injection On The Grid Processor	142
5.2.2	Sensitivity Analysis Store and Forward Switching Scenario	144
5.2.3	Multi-source Uniform Data Fraction	145
5.2.4	Multi-source Non-uniform Data Injection	146
6	General Network	147
6.1	General Case Virtual Cut-through Switching Scenario	147
6.2	General Case Store and Forward Switching Scenario	149
7	Conclusion and Future work	150
7.1	Conclusion	150
7.2	Future Work	151

Bibliography	152
---------------------	------------

List of Figures

2.1	A m*n mesh network(m = 5, n = 5)	4
2.2	A toroidal rectangle network with grid unit cores	5
2.3	A hypercube network	5
3.1	The 2*2 mesh network and the root processor is P_0	10
3.2	The timing diagram for 2*2 mesh network and the root processor is P_0	11
3.3	2*2 mesh network. $\alpha_0, \alpha_1, \alpha_2, \alpha_3$ value curve	14
3.4	The 2*3 mesh network and the data injection happens on corner processor P_0	15
3.5	The timing diagram for a 2*3 mesh network and the data injection happens on processor P_0	16
3.6	2*3 mesh network. $\alpha_0, \alpha_1, \alpha_3, \alpha_5$ value curve.	19
3.7	2^*n ($n = 10$) mesh network and the workload happens on P_0 . .	20
3.8	The timing diagram for 2*10 mesh network and the data injection happens on P_0	21
3.9	3*8 mesh network. The data injection position is P_0	27
3.10	The 3*3 mesh network and the root processor is P_0	29

3.11	The timing diagram for 3*3 mesh network and the data injection occurs on P_0	30
3.12	The data fraction simulation result of 3*3 mesh network and the data injection happens on the boundary P_0	33
3.13	3*3 mesh network. The data injection position is inner grid point P_0	34
3.14	The timing diagram for 3*3 mesh network and the data injection is inner grid P_0	36
3.15	3*3 mesh network. The data injection position is inner grid point P_0	38
3.16	Sensitivity analysis result of 2*10 mesh network result	39
3.17	Speedup curves of 2*10 mesh network	40
3.18	Sensitivity analysis result of 3*8 mesh network and the injection position on boundary processor P_2	41
3.19	Speedup curve of 3*8 mesh network	42
3.20	Sensitivity analysis result of data injection position on inner grid processor	43
3.21	Speedup curves of 5*5 mesh network Fig. 2.1	44
3.22	Data injection consists of a subgraph of G	45
3.23	Data injection consists of a subgraph of G	45
3.24	Speedup vs σ	47
3.25	Injection Processor Data Fraction vs σ	48
3.26	Speedup vs σ	49
3.27	Injection Processor Data Fraction vs σ	50

3.28	10 Voronoi Cells	52
3.29	10 Voronoi Cells speedup curves	54
3.30	10 reduced Voronoi cells	55
3.31	10 reduced Voronoi cells's speedup curves	56
3.32	Reduced Voronoi Division Algorithm average processors' percentage	57
3.33	Subgraph and individual data injection on mesh network	59
3.34	improved reduced Voronoi diagram subgraph and individual data injection on mesh network	60
3.35	Speedup curves for Situation III	61
3.36	improved reduced Voronoi diagram subgraph and individual data injection on mesh network	62
3.37	The timing diagram for 2*2 mesh network without front-end. . .	71
3.38	The data fraction deployed based on the radius value	73
3.39	The timing diagram for 2*3 mesh network without front-end. .	75
3.40	The data fraction deployed based on the radius value	77
3.41	The timing diagram for 3*3 boundary data injection on P_0 . .	83
3.42	The fraction curve for 3*3 boundary data injection on P_0 . .	85
3.43	The timing diagram for 3*3 inner grid injection P_0	87
3.44	Sensitivity analysis result of 2*10 mesh network result	88
3.45	Speedup curve of 2*10 mesh network result	89
3.46	Sensitivity analysis result of 3*8 mesh network result	90
3.47	Speedup curve of 3*8 mesh network result	91
3.48	Sensitivity analysis result of data injection position on inner grid processor	92

3.49	Speedup curve of 5*5 mesh network result	93
4.1	The rectangular toroidal network	95
4.2	The rectangular toroidal network	95
4.3	The m^*n toroidal rectangle network and the data injection is $P_{4,2}$	97
4.4	The data fraction curve of Fig. 4.3	99
4.5	Sensitivity analysis 5*5 torus network	100
4.6	Sensitivity analysis 5*5 torus network on different σ	101
4.7	Toroidal mesh network subgraph data injection	103
4.8	Data fraction on different type processors for Fig. 4.7	104
4.9	Toroidal mesh network subgraph data injection	105
4.10	Data fraction on different type processors for Fig. 4.9	106
4.11	How to calculate torus Voronoi Diagram	107
4.12	Initial Voronoi Diagram	108
4.13	Torus Voronoi diagram	109
4.14	Voronoi diagram casting to the torus model	110
4.15	Voronoi cell speedup curves	111
4.16	Torus reduced Voronoi diagram casting to the toroidal rectangle network	112
4.17	Torus reduced Voronoi diagram	113
4.18	Torus reduced Voronoi diagram average saved processors	114
4.19	Subgraph and individual data injection on torus network	115
4.20	Subgraph and individual data injection on torus network	116
4.21	Subgraph and individual data injection on torus network	117
4.22	Subgraph and individual data injection on torus network	118

4.23	Subgraph and individual data injection on torus network	119
4.24	The data fraction curve of Fig. 4.3	121
4.25	Sensitivity analysis result of data injection position on inner grid processor	122
4.26	Subgraph and individual data injection on torus network	123
4.27	Subgraph and individual data injection on torus network	124
4.28	Subgraph and individual data injection on torus network	125
4.29	Subgraph and individual data injection on torus network	126
4.30	Speedup difference between corner injection and inner grid injection	127
4.31	The comparing result between front-end processor with without front-end processor in 2*2 mesh network	128
4.32	The comparing result between front-end processor with without front-end processor in 2*3 mesh network	129
4.33	The comparing result between front-end processor with without front-end processor in 3*3 mesh network injection on boundary processor	131
4.34	The comparing result between front-end processor with without front-end processor in 3*3 mesh network injection on inner grid processor	132
4.35	Speedup difference between front-end and without front-end in 5*5 mesh network	134
5.1	Hypercube in 0, 1, 2, 3 dimension. [1]	136

List of Tables

4.1	D_i vs Number	98
4.2	The processor number of various D_i	100
4.3	The processor number of various D_i	122

Acknowledgements

Thank you to Professor Thomas G. Robertazzi who gave me strong academic and emotional support during hard times.

Thank you to Professor Esther M. Arkin, Professor Joseph S.B. Mitchell and Professor Xiaolin Li, who give me lots of paper modification suggestions and joined my thesis defense committee. Thank you to Professor Jim Jiao, who gives me lots of suggestions about Ph.D. life time management.

Thank you to Christine Rota, who helped me to process the internship application, visa issue, and so on.

Thanks to Professor David Gu, who taught me a lot the optimal mass transport theory and computational conformal geometry.

Thanks to my co-authors, especially Ph.D. Liang Mi, I learn lots of medical image knowledge from him.

Thanks to Ocoos, eBay, BNL and Uber, I found four perfect internship mentors. They gave me intensive industry project training and a good work attitude.

Chapter 1

Introduction

Four chapters are organized as follows :

- A problem introduction, notation and definitions are shown in Chapter II.
- Chapter III considers the mesh network. We take into account of the processor equivalence problem with front-end scenario and without front-end situation. Sensitivity analysis is another topic. Considering about the multi-source workload assignment problem, we propose a reduced Voronoi diagram assignment.
- Chapter IV presents the toroidal rectangle network situation. We consider the closed-form of processor equivalence in unique load injection, in different injection positions, corner processor, boundary processor and inner grid processor, respectively. The sensitivity analysis and multi-source assignment problem are also considered.
- Chapter V investigates the hypercube network situation. The front-end

and without front-end assumption are discussed. Sensitivity analysis is examined and the multi-source assignment in hypercube environment is also an interesting problem.

- Chapter VI discuss the conclusion and future work.

Chapter 2

Problem Description

2.1 Problem Background

In large-scale data intensive problems with geographically distributed resources, load is generated from multiple sources [2] for a class of problems. It is assumed that the problem representation can be arbitrarily divided amongst the processors. Thus the problem representation is said to be “divisible”. The processing of massive amounts of data on distributed and parallel networks is becoming more and more common. The problem of minimizing the processing time of extensive loads originating from a multiplicity of sources and being processed on a multiplicity of nodes presents a challenge.

In this chapter, the closed-form processor equivalence [3] [4] problem in the grid network of mesh network and toroidal rectangle network is discussed. Also, the multi-source workload assignment is also taken into account.

In this thesis, we investigate two problems. One is the processor equivalence. The other one is scheduling divisible workloads from multiple sources in mesh networks Fig. 2.1, toroidal rectangle networks Fig. 2.2 and hypercube

networks Fig. 2.3.




Figure 2.1: A $m \times n$ mesh network ($m = 5, n = 5$)




Figure 2.2: A toroidal rectangle network with grid unit cores




Figure 2.3: A hypercube network

2.2 Definitions and Assumption

Definition 2.2.1. Equal Computation

Equal computation is a technique, which considers combining a cluster of processors as one whole processor to process the unit 1 workload.

The following assumptions are used throughout the paper:

- Virtual cut through [5] switching is used to transmit the assigned work-load between processors.
- For simplicity, return communication is not considered.
- The communication delays are taken into consideration.
- The time costs of computation and communication are assumed to be linear function of the data size.
- The network environment is homogeneous, that is, all the processors have the same computation capacity. The link speeds between any two unit cores are identical.
- The number of outgoing ports in each processor is limited. In NOC (network on chip), the port number is fixed 4 or 5.
- The general graph's grid node's in-degree and out-degree is 4 or 5.

The optimization objective functions are as follows :

- Equal computation : the problem's objective function is how to partition and schedule the workloads amongst the processors to get the minimum finish time.
- Multi-source assignment : how to finish the unit 1 workload at the same time utilizing fewer processors.

To achieve the minimum solution is obtained by forcing the processors over a network to stop processing simultaneously. Intuitively, this is because the solution could be improved by transfer load from some busy processor to idle ones [6] [7].

2.2.1 Notions

The following notations and definitions are utilized:

- P_i : The i th processor. $0 \leq i \leq m * n - 1$.
- L_i : The i th work load. $1 \leq i \leq k$.
- D_i : The minimum number of hops from the processor P_i to the data load injection L .
- $level_i$: The processors have i minimum Manhattan distance to the data injection node.
- α_0 : The load fraction assigned to the root processor.
- α_i : The load fraction assigned to the i th processor.
- ω_i : The inverse computing speed on the i th processor.
- ω_{eq} : The inverse computing speed on an equivalent node collapsed from a cluster of processors.
- z_i : The inverse link speed on the i th link.

- T_{cp} : Computing intensity constant. The entire load is processed in $\omega_i T_{cp}$ on the i th processor.
- T_{cm} : Communication intensity constant. The entire load is transmitted in $z_i T_{cm}$ seconds over the i th link.
- $T_{f,n}$: The finish time of the whole processor network. Here $T_{f,n}$ is equal to $\omega_{eq} T_{cp}$.
- $T_{f,0}$: The finish time for the entire divisible load solved on the root processor. Here $T_{f,0}$ is equal to $1 \times \omega_0 T_{cp}$, that is $\omega_0 T_{cp}$.
- $\sigma = \frac{z T_{cm}}{\omega T_{cp}}$: The ratio between the communication speed to the computation speed, $0 < \sigma < 1$ [6] [8].
- In multi-source situation, $\sum_{i=1}^k L_i = 1$
- $\sum_{i=0}^{m*n-1} \alpha_i = 1$
- $Speedup = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0}$

Chapter 3

Mesh Network

3.1 Virtual Cut-through Switching Scenario

In the virtual cut-through environment, a front-end sub-processor, which is a processor allows the communication and the computation to be executed simultaneously. That is, upon receiving their respective load fractions, the processors start processing their own workload and relay all the other fractions to the neighbor processors at the same time.

First we consider about the $2*2$ mesh network, $2*n$ mesh network. After, we analyze a more general case $m*n$ mesh network and obtain a general closed-form matrix presentation. Finally, we give a key principle to address this type of question. In addition, different data injection position, such as the corner, boundary and inner grid are also discussed.

3.1.1 Data Injection on The Corner Processor

2*2 Mesh Network

The L is assigned on the corner processor P_0 Fig. 3.1. The whole task is tackled by four processors P_0, P_1, P_2, P_3 together.




Figure 3.1: The 2×2 mesh network and the root processor is P_0

The processor P_0, P_1 and P_2 start to process its respective fraction at the same time. The processor P_3 starts to work when the α_1 and α_2 are completed transmission. That is, the link $0 - 1$ and $0 - 2$ are occupied transmitting load to processor 1 and 2, respectively and on 3 when that is finished, processor 3 receive load from virtual cut-through.

According to the divisible load theory [9], we obtain the timing diagram Fig. 3.2.




Figure 3.2: The timing diagram for 2×2 mesh network and the root processor is P_0

Here is the Gantt-like timing diagram communication appears above each axis and computations appear below the each axis. Let's assumed that all processors stop computing at the same time in order to minimize the max span [7].

Based on the timing diagram, we get a group of equations to deploy the fraction workload:

$$\left\{ \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \\ \alpha_1 \omega T_{cp} = T_{f,m} \\ \alpha_2 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \\ \alpha_0 + \alpha_1 + \alpha_2 + \alpha_3 = 1 \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \\ 0 < \sigma < 1 \\ 0 < \alpha_0 \leq 1 \\ 0 \leq \alpha_1, \alpha_2, \alpha_3 < 1 \end{array} \right. \quad \begin{array}{l} (3.1) \\ (3.2) \\ (3.3) \\ (3.4) \\ (3.5) \\ (3.6) \\ (3.7) \\ (3.8) \\ (3.9) \end{array}$$

The group of equations are represented by the matrix form:

$$\begin{bmatrix} 1 & 2 & 1 \\ 1 & -1 & 0 \\ 0 & \sigma - 1 & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \end{bmatrix} \quad (3.10)$$

The matrix is represented as $A \times \alpha = b$. A is named as ***flow matrix***.

Finally, the explicit solution is:

$$\left\{ \begin{array}{l} \sigma = \frac{zT_{cm}}{\omega T_{cp}} \end{array} \right. \quad (3.11)$$

$$\left\{ \begin{array}{l} \alpha_0 = \frac{1}{4 - \sigma} \end{array} \right. \quad (3.12)$$

$$\left\{ \begin{array}{l} \alpha_1 = \frac{1}{4 - \sigma} \end{array} \right. \quad (3.13)$$

$$\left\{ \begin{array}{l} \alpha_3 = \frac{1 - \sigma}{4 - \sigma} \end{array} \right. \quad (3.14)$$

The simulation result is illustrated:




Figure 3.3: 2^*2 mesh network. $\alpha_0, \alpha_1, \alpha_2, \alpha_3$ value curve

In Fig. 3.3, P_0, P_1, P_2 three processors have the same data fraction workload, so the curve of α_0 and α_1 coincide. The figure says that as σ grows, the value α_3 drops. In other words, as the communication capacity decreases, there is less data workload assigned to P_3 . Further, it means it will be economical to keep the load local on P_0, P_1, P_2 and not distribute it, to other processors.

The speedup is:

$$\text{Speedup} = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0} = 4 - \sigma$$

2*3 Mesh Network

In Fig. 3.4 mesh network, L originates on processor P_0 . There are 6 processors to be processing.




Figure 3.4: The 2*3 mesh network and the data injection happens on corner processor P_0

Here P_0 , P_1 and P_2 start processing at the same time. Processor P_3 and P_4 start to work when they receive the data from processor P_1 , P_2 , after the $0 - 1$ and $0 - 2$ link become available to transfer load to P_3 and P_4 . The last processor P_5 starts to execute until the work load fraction α_0 , α_1 , α_2 , α_3 , α_4 are transmitted completed. According to the divisible load theory [9], we obtain the timing diagram Fig. 3.5.




Figure 3.5: The timing diagram for a 2×3 mesh network and the data injection happens on processor P_0

The timing diagram equations as follows:

$$\left. \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \\ \alpha_1 \omega T_{cp} = T_{f,m} \\ \alpha_2 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \\ \alpha_2 z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_3) z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \\ \alpha_0 + \alpha_1 + \alpha_2 + \alpha_3 + \alpha_4 + \alpha_5 = 1 \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \\ 0 < \sigma < 1 \\ 0 < \alpha_0 \leq 1 \\ 0 \leq \alpha_1, \alpha_2, \alpha_3, \alpha_4, \alpha_5 < 1 \end{array} \right\} \quad (3.15)$$

$$\alpha_1 \omega T_{cp} = T_{f,m} \quad (3.16)$$

$$\alpha_2 \omega T_{cp} = T_{f,m} \quad (3.17)$$

$$\alpha_1 z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \quad (3.18)$$

$$\alpha_2 z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} \quad (3.19)$$

$$(\alpha_1 + \alpha_3) z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \quad (3.20)$$

$$\alpha_0 + \alpha_1 + \alpha_2 + \alpha_3 + \alpha_4 + \alpha_5 = 1 \quad (3.21)$$

$$\sigma = \frac{z T_{cm}}{\omega T_{cp}} \quad (3.22)$$

$$0 < \sigma < 1 \quad (3.23)$$

$$0 < \alpha_0 \leq 1 \quad (3.24)$$

$$0 \leq \alpha_1, \alpha_2, \alpha_3, \alpha_4, \alpha_5 < 1 \quad (3.25)$$

The flow matrix closed-form formula is:

$$\begin{bmatrix} 1 & 2 & 2 & 1 \\ 1 & -1 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 \\ 0 & \sigma - 1 & \sigma & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \\ \alpha_5 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (3.26)$$

The explicit solution is:

$$\left\{ \begin{array}{l} \sigma = \frac{zT_{cm}}{\omega T_{cp}} \end{array} \right. \quad (3.27)$$

$$\left\{ \begin{array}{l} \alpha_0 = \frac{1}{\sigma^2 - 4 \times \sigma + 6} \end{array} \right. \quad (3.28)$$

$$\left\{ \begin{array}{l} \alpha_1 = \frac{1}{\sigma^2 - 4 \times \sigma + 6} \end{array} \right. \quad (3.29)$$

$$\left\{ \begin{array}{l} \alpha_3 = \frac{1 - \sigma}{\sigma^2 - 4 \times \sigma + 6} \end{array} \right. \quad (3.30)$$

$$\left\{ \begin{array}{l} \alpha_5 = \frac{\sigma^2 - 2 \times \sigma + 1}{\sigma^2 - 4 \times \sigma + 6} \end{array} \right. \quad (3.31)$$

The α calculation result are shown in Fig. 3.6. P_0, P_1 have the same fraction so the curve of α_0 and α_1 coincide. If the communication time is zero, each of the six processors get like $\frac{1}{6}$ of the load which shows in the figure. If the communication delay equals computation time $\frac{1}{3}$ of the load goes to each of P_0, P_1 and P_2 .




Figure 3.6: 2^*3 mesh network. $\alpha_0, \alpha_1, \alpha_3, \alpha_5$ value curve.

2^*N Mesh Network

The $2 * n$ Fig. 3.7 homogeneous mesh network address L and L originates P_0 .




Figure 3.7: 2^*n ($n = 10$) mesh network and the workload happens on P_0

Load a distribution from P_0 to P_1 and P_2 via virtual cut-through. After P_1 and P_2 finish receiving load from link $0 - 1$ and $0 - 2$, they will be used to forward load to P_3 and P_4 and so on.

Similarly to the analysis of Fig. 3.2 and Fig. 3.5, the timing diagram for Fig. 3.7 is shown in Fig. 3.8




Figure 3.8: The timing diagram for 2×10 mesh network and the data injection happens on P_0

The equations are presented as:

$$\left\{ \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \quad (3.32) \\ \alpha_1 \omega T_{cp} = T_{f,m} \quad (3.33) \\ \alpha_2 \omega T_{cp} = T_{f,m} \quad (3.34) \\ \alpha_1 z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \quad (3.35) \\ \alpha_2 z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} \quad (3.36) \\ (\alpha_1 + \alpha_3) z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \quad (3.37) \\ \vdots \quad (3.38) \\ (\alpha_1 + \alpha_3 + \cdots + \alpha_{2 \times n-1}) z T_{cm} + \alpha_{2 \times n-1} \omega T_{cp} = T_{f,m} \quad (3.39) \\ \alpha_0 + \cdots + \alpha_{2 \times n-1} = 1 \quad (3.40) \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \quad (3.41) \\ 0 < \sigma < 1 \quad (3.42) \\ 0 < \alpha_0 \leq 1 \quad (3.43) \\ 0 \leq \alpha_1 \alpha_2 \cdots \alpha_{2 \times n-1} < 1 \quad (3.44) \end{array} \right.$$

The flow matrix closed-form is shown:

$$\begin{bmatrix} 1 & 2 & 2 & \cdots & 2 & 2 & 1 \\ 1 & -1 & 0 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \\ 0 & \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \\ \alpha_5 \\ \vdots \\ \alpha_{2 \times n-3} \\ \alpha_{2 \times n-1} \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ \vdots \\ 0 \\ 0 \end{bmatrix} \quad (3.45)$$

According to the *Cramer's rule*, the explicit solution for the group of equations is:

$$\left\{ \alpha_i = \frac{\det A_i^*}{\det A} \right\} \quad (3.46)$$

where A_i^* is the matrix formed by replacing the i -th column of A by the column vector b .

Especially,

$$A_0^* = \begin{bmatrix} 1 & 2 & 2 & \cdots & 2 & 2 & 1 \\ 0 & -1 & 0 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \\ 0 & \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix} \quad (3.47)$$

$$\alpha_0 = \left| \frac{\det A_0^*}{\det A} \right|$$

$$\det A_0^* = -1$$

Finally, the speedup is:

$$Speedup = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0} = |-\det A|$$

Further, we prove the matrix $\det A \neq 0$.

$$C = \begin{bmatrix} -1 & 0 & \cdots & 0 & 0 & 0 \\ \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots \\ \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix} \quad (3.48)$$

C is a lower triangular matrix and the diagonal elements are not 0. So C is non-degenerate, that is, the matrix is column linear independence.

After a series of column reduction and row reduction actions, we get

$$A = \begin{bmatrix} 1 & 2 & 2 & \cdots & 2 & 2 & 1 \\ 1 & -1 & 0 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \vdots \\ 0 & \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix} \xrightarrow{\text{Column Reduction}} \begin{bmatrix} 1 & 0 & 0 & \cdots & 0 & 0 & 0 \\ 1 & -3 & -2 & \cdots & -2 & -2 & -1 \\ 0 & \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \vdots & \ddots & \ddots \\ 0 & \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix}$$

$$\xrightarrow{\text{Row Reduction}} \begin{bmatrix} 1 & 0 & 0 & \cdots & 0 & 0 & 0 \\ 0 & -3 & -2 & \cdots & -2 & -2 & -1 \\ 0 & \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \vdots \\ 0 & \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix}$$

Considering the matrix \hat{C}

$$\hat{C} = \begin{bmatrix} -3 & -2 & \cdots & -2 & -2 & -1 \\ \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots \\ \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix} \quad (3.49)$$

, which is still column linear independence. Considering $0 < \sigma < 1$, the flow matrix is full rank. So $\det A \neq 0$.

After three user cases' investigation, we find a crucial methodology:

$$\forall D_i = D_j, \quad \text{then} \quad \alpha_i = \alpha_j, \quad 0 \leq i, j \leq m * n - 1$$

$m*n$ Mesh Network

Considering a general $m * n$ mesh network, such as Fig. 3.9 Fig. 2.1.




Figure 3.9: $3*8$ mesh network. The data injection position is P_0

Utilizing the previous methodology, we obtain the closed-form flow matrix

equations for Fig. 3.9:

$$\begin{bmatrix}
 1 & 2 & 3 & 3 & 3 & 3 & 3 & 2 & 1 \\
 1 & -1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
 0 & \sigma - 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & 1 & 0 & 0 & 0 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & \sigma & 1 & 0 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & \sigma & \sigma & 1 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & \sigma & \sigma & \sigma & 1 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & \sigma & \sigma & \sigma & \sigma & 1
 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \\ \alpha_6 \\ \alpha_9 \\ \alpha_{12} \\ \alpha_{15} \\ \alpha_{18} \\ \alpha_{21} \\ \alpha_{23} \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ \vdots \\ 0 \end{bmatrix} \quad (3.50)$$

Also, the flow matrix equations for Fig. 2.1:

$$\begin{bmatrix}
 1 & 2 & 3 & 4 & 5 & 4 & 3 & 2 & 1 \\
 1 & -1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
 0 & \sigma - 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & 1 & 0 & 0 & 0 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & \sigma & 1 & 0 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & \sigma & \sigma & 1 & 0 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & \sigma & \sigma & \sigma & 1 & 0 \\
 0 & \sigma - 1 & \sigma & \sigma & \sigma & \sigma & \sigma & \sigma & 1
 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \\ \alpha_6 \\ \alpha_{10} \\ \alpha_{15} \\ \alpha_{19} \\ \alpha_{22} \\ \alpha_{24} \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ \vdots \\ 0 \end{bmatrix} \quad (3.51)$$

We use the similar method to prove $\det A \neq 0$, so the speedup is:

$$\text{Speedup} = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0} = |-\det A|$$

3.1.2 Data Injection On The Boundary Processor

After the corner scenario, we extend the methodology to the boundary processor condition.

A single data injection root-node on the boundary processor, as shown in Fig. 3.10.




Figure 3.10: The 3×3 mesh network and the root processor is P_0

The timing diagram is Fig. 3.11:




Figure 3.11: The timing diagram for 3*3 mesh network and the data injection occurs on P_0

P_0 , P_1 , P_2 and P_3 commence processing at $t = 0$ axis timing diagram. P_1 , P_2 and P_3 receive load in virtual cut-through mode from P_0 . Once that is finished, link $0 - 1$, $0 - 2$ and $0 - 3$ is used to forward load to nodes P_4 , P_5 and P_6 in virtual cut-through mode. Once that is finished, the link that have been so far are used to froward load to P_7 and P_8 in virtual cut-through mode.

The equations are:

$$\left. \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \\ \alpha_1 \omega T_{cp} = T_{f,m} \\ \alpha_2 \omega T_{cp} = T_{f,m} \\ \alpha_3 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} \\ \alpha_2 z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \\ \alpha_3 z T_{cm} + \alpha_6 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_4) z T_{cm} + \alpha_7 \omega T_{cp} = T_{f,m} \\ (\alpha_2 + \alpha_5) z T_{cm} + \alpha_8 \omega T_{cp} = T_{f,m} \\ \alpha_0 + \dots + \alpha_8 = 1 \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \\ 0 < \sigma < 1 \\ 0 < \alpha_0 \leq 1 \\ 0 \leq \alpha_1 \alpha_2 \dots \alpha_8 < 1 \end{array} \right\} \quad \begin{array}{l} (3.52) \\ (3.53) \\ (3.54) \\ (3.55) \\ (3.56) \\ (3.57) \\ (3.58) \\ (3.59) \\ (3.60) \\ (3.61) \\ (3.62) \\ (3.63) \\ (3.64) \\ (3.65) \\ (3.66) \end{array}$$

And the flow matrix form is :

$$\begin{bmatrix} 1 & 3 & 3 & 2 \\ 1 & -1 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 \\ 0 & \sigma - 1 & \sigma & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_4 \\ \alpha_7 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (3.67)$$

The explicit solution is:

$$\left\{ \begin{array}{l} \alpha_0 = \frac{1}{9 - 7 \times \sigma + 2 \times \sigma^2} \end{array} \right. \quad (3.68)$$

$$\left\{ \begin{array}{l} \alpha_1 = \frac{1}{9 - 7 \times \sigma + 2 \times \sigma^2} \end{array} \right. \quad (3.69)$$

$$\left\{ \begin{array}{l} \alpha_4 = \frac{1 - \sigma}{9 - 7 \times \sigma + 2 \times \sigma^2} \end{array} \right. \quad (3.70)$$

$$\left\{ \begin{array}{l} \alpha_7 = \frac{(1 - \sigma)^2}{9 - 7 \times \sigma + 2 \times \sigma^2} \end{array} \right. \quad (3.71)$$

$$\left\{ \begin{array}{l} \alpha_7 = \frac{(1 - \sigma)^2}{9 - 7 \times \sigma + 2 \times \sigma^2} \end{array} \right. \quad (3.72)$$

The simulation result is shown: The curve α_0 is identified to the curve for




Figure 3.12: The data fraction simulation result of 3×3 mesh network and the data injection happens on the boundary P_0

α_1 , α_2 and α_3 . The curve α_4 is identified to the curves of α_5 and α_6 . The curve α_7 is identified to the curve for α_8 . If communication time is zero (extremely fast communication), each processor get $\frac{1}{8}$ of the load. If communication time equals computation time, each of the four start stage nodes (P_0, P_1, P_2, P_3) get $\frac{1}{4}$ of the load fraction.

3.1.3 Data Injection On The Inner Grid Processor

Fig. 3.13 shows that L load on the inner grid processor P_0 , P_0 , P_1 , P_2 ,




Figure 3.13: 3×3 mesh network. The data injection position is inner grid point P_0

P_3 and P_4 commence processing at time = 0 through virtual cut-through switching. Once this is finished links $0 - 1$, $0 - 2$, $0 - 3$ and $0 - 4$ are released to forward load to P_5 , P_6 , P_7 and P_8 in virtual cut-through mode.

The timing diagram for this user case is illustrated as Fig. 3.14:




Figure 3.14: The timing diagram for 3×3 mesh network and the data injection is inner grid P_0

The group of equations are:

$$\left\{ \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \\ \alpha_1 \omega T_{cp} = T_{f,m} \\ \alpha_2 \omega T_{cp} = T_{f,m} \\ \alpha_3 \omega T_{cp} = T_{f,m} \\ \alpha_4 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_6 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_7 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_8 \omega T_{cp} = T_{f,m} \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \\ 0 < \sigma < 1 \\ 0 < \alpha_0 \leq 1 \\ 0 \leq \alpha_1 \quad \alpha_2 \quad \dots \quad \alpha_8 < 1 \end{array} \right. \begin{array}{l} (3.73) \\ (3.74) \\ (3.75) \\ (3.76) \\ (3.77) \\ (3.78) \\ (3.79) \\ (3.80) \\ (3.81) \\ (3.82) \\ (3.83) \\ (3.84) \\ (3.85) \end{array}$$

The flow matrix form is :

$$\begin{bmatrix} 1 & 4 & 4 \\ 1 & -1 & 0 \\ 0 & \sigma - 1 & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_5 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \end{bmatrix} \quad (3.86)$$

The simulation result is Fig. 3.15: P_0 and P_1 have the same α value, so the curve of α_0 and α_1 coincide.




Figure 3.15: 3*3 mesh network. The data injection position is inner grid point P_0

The explicit solution is:

$$\left\{ \begin{array}{l} \alpha_0 = \frac{1}{9 - 4 \times \sigma} \\ \alpha_1 = \frac{1}{9 - 4 \times \sigma} \end{array} \right. \quad (3.87)$$

$$\left\{ \begin{array}{l} \alpha_0 = \frac{1}{9 - 4 \times \sigma} \\ \alpha_5 = \frac{1 - \sigma}{9 - 4 \times \sigma} \end{array} \right. \quad (3.88)$$

$$\left\{ \begin{array}{l} \alpha_0 = \frac{1}{9 - 4 \times \sigma} \\ \alpha_5 = \frac{1 - \sigma}{9 - 4 \times \sigma} \end{array} \right. \quad (3.89)$$

$$\left\{ \begin{array}{l} \alpha_0 = \frac{1}{9 - 4 \times \sigma} \\ \alpha_5 = \frac{1 - \sigma}{9 - 4 \times \sigma} \end{array} \right. \quad (3.90)$$

3.1.4 Sensitivity Analysis Virtual Cut-through Switching Scenario

From Chapter 2, we know the speedup is :

$$\text{Speedup} = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0} = |-\det A|$$

Data Injection On The Corner Processor

The simulation result of sensitivity analysis of $2*n$ mesh network Fig. 3.7 is as follows:




Figure 3.16: Sensitivity analysis result of $2*10$ mesh network result




Figure 3.17: Speedup curves of 2×10 mesh network

Data Injection On The Boundary Processor

Talking to Fig. 3.9, the data injection happens on boundary processor

P_2 .




Figure 3.18: Sensitivity analysis result of 3×8 mesh network and the injection position on boundary processor P_2

Fig. 3.18 and Fig. 3.19 show that if the value $\sigma > 0.2$, the speedup simulation effect is obvious. If the value $\sigma < 0.1$, the number of cores has linear impact on the speedup performance. If the number of cores > 5 , the bottom effect with front-end, the cluster at least get about 4 times speedup. The reason is P_0 has 3 $level_1$ processors.




Figure 3.19: Speedup curve of 3×8 mesh network

Data Injection On The Inner Grid Processor

Fig. 2.1, L incurs on P_{12} and the simulation result says:

If the number of processor > 5 , the cluster equivalence computation ability is at least 5 time speedup. It is the inner grid has 4 $level_1$ neighbor processors.




Figure 3.20: Sensitivity analysis result of data injection position on inner grid processor

3.1.5 Multi-source Uniform Data Fraction

We extend the single source assignment to multi-source assignment problem [10] [4]. According to each processor, we concentrate on the processors' geographical location P_i , data fraction assigned α_i .

Assuming the data fraction is even. For example, the workload is unit 1 and there are k different data injection options. So each data injection is assigned $\frac{1}{k}$ workload. From the data injection position relationship we consider three different situations :

- Data injection positions consist of a subgraph G_L of G .
- Data injection processor doesn't connect with each other.
- Other situations.




Figure 3.21: Speedup curves of 5×5 mesh network Fig. 2.1

Situation I

If the data injection positions consist of a subgraph of G , we use G_L to present it.




Figure 3.22: Data injection consists of a subgraph of G




Figure 3.23: Data injection consists of a subgraph of G

Fig. 3.22 and Fig. 3.23 illustrate two examples that the data injections consist of subgraph G_L of G .

Our objective is to propose a general algorithm framework to tackle this situation and give quantity model analysis. This algorithm is named as ***Two Phase Scheduling Algorithm (TPSA)***.

Algorithm 1 Two Phase Scheduling Algorithm (TPSA)

global_s :

Collapse the data injection processors into one “big” equivalent processor [3].

Calculate $m * n$ processor’s D_i

Obtain the flow matrix A_i .

Calculate $m * n$ processors data fraction α_i

- The time complexity is $O(k * m * n)$.
- The time to calculate each determinant is $O(n^3)$ with Gaussian elimination or LU decomposition. So the total determinant time complexity is $O(k * n^3)$.
- The total time complexity is $O(k * n^3)$. Nonetheless, in real case, the time complexity is fast enough.

For example, Fig. 3.22's ***flow matrix*** is :

$$\begin{bmatrix} 4 & 8 & 12 & 10 & 6 & 2 \\ 1 & -1 & 0 & 0 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & \sigma & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \\ \alpha_4 \\ \alpha_5 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (3.91)$$

The simulation result illustrates as follows:




Figure 3.24: Speedup vs σ




Figure 3.25: Injection Processor Data Fraction vs σ

This simulation says the best performance happens on value $\sigma \leq 0.05$, which hits about 40 times speedup. If $\sigma \approx 1$, the network achieves almost 12 times performance. In addition, the data fraction in each injection processors are the same, that is, there is no need to transfer data between local processors.

For example, Fig. 3.23's **flow matrix** is :

$$\begin{bmatrix} 7 & 14 & 15 & 10 & 6 & 3 & 1 \\ 1 & -1 & 0 & 0 & 0 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & \sigma & 1 & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & \sigma & \sigma & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \\ \alpha_4 \\ \alpha_5 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (3.92)$$

The simulation result illustrates as follows:




Figure 3.26: Speedup vs σ




Figure 3.27: Injection Processor Data Fraction vs σ

This simulation says the best performance happens on value $\sigma \leq 0.05$, which hits about 55 times speedup. If $\sigma \approx 1$, the network achieves almost 21 times performance. In addition, the data fraction in each injection processors are the same, that is, there is no need to transfer data between local processors.

Situation II

The data injections don't consist of a subgraph of G . Jia [11] proposes an algorithm to utilize the nearest data injection principle to tackle this scenario. In the dividable load intricate applications, for example, big file transmission, HPC scientific computation, like BlueGene [12] or Hadoop job, the total finish time depends on the last piece ending time-stamp.

Our objective is to propose a general algorithm framework to utilize less processors and achieve the same finish time.

Fig. 3.28 shows 10 Voronoi cells division and Fig. 3.29 figures out the speedup of each cells.




Figure 3.28: 10 Voronoi Cells

The heuristic algorithm is named as ***Reduced Voronoi Diagram Algorithm:***

Algorithm 2 Reduced Voronoi Diagram Algorithm(RVDA)

global_s :

Define the cell's flow matrix column's number is *depth*.

Calculate *k* Voronoi cells with Manhattan distance.

Calculate *k* radius *R_i* of *n* Voronoi cells.

Calculate each cell's flow matrix *A_i*.

Set *depth_{min}* = min *Speedup_i*'s *R_i*.

while $1 \leq i \leq k$ **do**

tempdepth_i = *R_i*

while *depth_{min}* $\leq j \leq \text{tempdepth}_i$ **do**

 Binary Search the value $\min(j)$, the flow matrix \hat{A}_i 's speedup > $\min(\text{speedup}_{\min})$.

 j = j + 1.

end while

 Calculate the Reduced Voronoi cells by setting the *depth_i* = *depth_{min}* in each cell.

 Calculate Voronoi cell's flow matrix *A_i*.

i = *i* + 1

end while

local_s :

Display each reduced Voronoi cells.

Illustrate each reduced Voronoi cells' speedup curves




Figure 3.29: 10 Voronoi Cells speedup curves

- The Manhattan Voronoi cells' time complexity is $O(k * m * n)$;
- The binary search find the min j 's time complexity is $O(k * (\log_2 \max(m, n)))$.
- So the total time complexity is $O(k * m * n)$.

Fig. 3.30 and Fig. 3.31 show the algorithm's result and speedup curves.

The algorithm obtains the same running time yet saves about 30% processors.

Fig. 3.29 shows $\sigma < 0.2$, the ratio $\max(\frac{\text{maxspeedup}}{\text{minspeedup}}) = \frac{500}{100} = 5$ and Fig. 3.31 shows the ratio is $\max(\frac{\text{maxspeedup}}{\text{minspeedup}}) = \frac{270}{100} = 2.7$.

It displays that 10 pieces of processor cluster's equal computation is more




Figure 3.30: 10 reduced Voronoi cells

balanced than initial setting, and the whole cluster finishes tasks with the same time by less processors.




Figure 3.31: 10 reduced Voronoi cells's speedup curves

After 1000 round random sampling experiments, we obtain the average saved processors ratio in Fig. 3.32. From Fig. 3.32, it shows the average percentage of saved processor is about 35%.




Figure 3.32: Reduced Voronoi Division Algorithm average processors' percentage

Situation III

If there are some nodes consisting a subgraph and there are some nodes individual, our objective to finish the whole project in the same time and save processors and give a quantity analysis model to this data injection situation.

We process an improved RVDA algorithm to tackle this situation.

Algorithm 3 Improved Reduced Voronoi Diagram Algorithm(IRVDA)

global_s :

Define the cell's flow matrix column's number is *depth*.

Collapse the data injection processors into one “big” equivalent processor.

Calculate *k* constrained Voronoi cells [13] with Manhattan distance and get *k* cells.

Calculate *k* radius R_i of *k* Voronoi cells.

while $1 \leq i \leq k$ **do**

 Calculate the speedup $Speedup_i$ with flow matrix A_i .

i = *i* + 1

end while

Set the $depth_{min} = \min(Speedup_i)$'s Radius

while $1 \leq i \leq n$ **do**

$tempdepth_i = R_i$.

while $depth_{min} \leq j \leq tempdepth_i$ **do**

 Binary Search the value $\min(j)$, the flow matrix \hat{A}_i 's speedup > $\min(Speedup_{min})$.

 break.

j = *j* + 1.

end while

Calculate Voronoi cell's flow matrix \hat{A}_i .

i = *i* + 1

end while

local_s :

Display each reduced Voronoi cells.

Illustrate each reduced Voronoi cells speedup curves




Figure 3.33: Subgraph and individual data injection on mesh network




Figure 3.34: improved reduced Voronoi diagram subgraph and individual data injection on mesh network




Figure 3.35: Speedup curves for Situation III




Figure 3.36: improved reduced Voronoi diagram subgraph and individual data injection on mesh network

We save about $294/2500 \approx 11.7\%$ processors.

3.1.6 Multi-source Non-uniform Data Injection

From the data injection position relationship we consider three different situations :

- Data injection positions consist of a subgraph G_L of G .
- Data injection processor doesn't connect with each other.
- Other situations.

Situation I

Algorithm 4 Improved Two Phase Scheduling Algorithm (TPSA)

$local_s$:

Re-distribution the subgraph G_L node's fraction to be uniform.

$global_s$:

Collapse the data injection processors into one “big” equivalent processor [3].

Calculate $m * n$ processor's D_i

Obtain the flow matrix A_i .

Calculate $m * n$ processors data fraction α_i

In $local_s$ stage, our target is from a data fraction distribution to a uniform distribution. So the sub-optimal total running time contains $local_s + global_s$.

- The time complexity is $O(k * m * n)$.
- The time to calculate each determinant is $O(n^3)$ with Gaussian elimination or LU decomposition. So the total determinant time complexity is $O(k * n^3)$.
- The total time complexity is $O(k * n^3)$. Nonetheless, in real case, the time complexity is fast enough.
- The total running time is $local_s + global_s$.

Situation II

We process an improved RVDA algorithm to tackle this situation. There
is

Algorithm 5 Improved Reduced Voronoi Diagram Algorithm(IRVDA)

global_s :

Define the cell's flow matrix column's number is *depth*.

Collapse the data injection processors into one “big” equivalent processor.

Calculate *k* constrained Voronoi cells [13] with Manhattan distance and get *k* cells.

Calculate *k* radius R_i of *k* Voronoi cells.

while $1 \leq i \leq k$ **do**

 Calculate the speedup $Speedup_i$ with flow matrix A_i .

i = *i* + 1

end while

Set the $depth_{min} = \min(Speedup_i)$'s Radius

while $1 \leq i \leq n$ **do**

$tempdepth_i = R_i$.

while $depth_{min} \leq j \leq tempdepth_i$ **do**

 Binary Search the value $\min(j)$, the flow matrix \hat{A}_i 's speedup >

$\min(Speedup_{min})$.

 break.

j = *j* + 1.

end while

 Calculate Voronoi cell's flow matrix \hat{A}_i .

i = *i* + 1

end while

Situation III

Algorithm 6 Improved Reduced Voronoi Diagram Algorithm(IRVDA)

local_s :

Display each reduced Voronoi cells.

Illustrate each reduced Voronoi cells' speedup curves

global_s :

Define the cell's flow matrix column's number is *depth*.

Collapse the data injection processors into one "big" equivalent processor.

Calculate *k* constrained Voronoi cells [13] with Manhattan distance and get *k* cells.

Calculate *k* radius R_i of *k* Voronoi cells.

while $1 \leq i \leq k$ **do**

 Calculate the speedup $Speedup_i$ with flow matrix A_i .

i = *i* + 1

end while

Set the $depth_{min} = \min(Speedup_i)$'s Radius

while $1 \leq i \leq n$ **do**

$tempdepth_i = R_i$.

while $depth_{min} \leq j \leq tempdepth_i$ **do**

 Binary Search the value $\min(j)$, the flow matrix \hat{A}_i 's speedup >

$\min(Speedup_{min})$.

 break.

j = *j* + 1.

end while

Calculate Voronoi cell's flow matrix \hat{A}_i .

i = *i* + 1

end while

3.2 Store and Forward Switching Scenario

In the without front-end scenario, the processors solely start to process as soon as each processor receives its entire load assignment [14].

This subsection concerns the processors without front-end. Because of without front-end, the processors simultaneously receive the data and solely start to process it as soon as each processor receives its entire load assignment. We consider the timing diagram for Fig. 3.1, Fig. 3.4, Fig. 3.7 and so on. In addition, we also give the new closed-form matrix equations for the previous user cases.

The rule also plays a dominate role in establish the mathematics model.

3.2.1 Data Injection on The Corner Processor

2*2 mesh network

The timing diagram of Fig. 3.1 is shown:




Figure 3.37: The timing diagram for 2*2 mesh network without front-end.

P_0 starts to process the assigned workload and it starts to transfer the α_1 , α_2 and α_3 fraction workload after it totally receive its α_0 task. That is, P_1 and P_2 are idle until the L finish its data injection to P_0 . The similar situation happens to P_1 and P_2 and they both start to transmit the α_3 after they totally receive the appropriate workload. In other words, P_3 has to wait until the previous two layer processors obtain their own data.

The corresponding group of equations are as follows:

$$\left\{ \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_1 \omega T_{cp} = T_{f,m} \\ \alpha_2 z T_{cm} + \alpha_2 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_3) z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \\ \alpha_0 + \alpha_1 + \alpha_2 + \alpha_3 = 1 \\ 0 < \sigma < 1 \\ 0 < \alpha_0 \leq 1 \\ 0 \leq \alpha_1, \alpha_2, \alpha_3 < 1 \end{array} \right. \quad \begin{array}{l} (3.93) \\ (3.94) \\ (3.95) \\ (3.96) \\ (3.97) \\ (3.98) \\ (3.99) \\ (3.100) \\ (3.101) \end{array}$$

The matrix closed-form is presented as:

$$\begin{bmatrix} 1 & 2 & 1 \\ 1 & -(\sigma+1) & 0 \\ 1 & -\sigma & -(\sigma+1) \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \end{bmatrix} \quad (3.102)$$

The explicit solution is:

$$\alpha_0 = \left(\frac{\sigma+1}{\sigma+2} \right)^2 \quad (3.103)$$

$$\alpha_1 = \frac{\sigma+1}{(\sigma+2)^2} \quad (3.104)$$

$$\alpha_3 = \frac{1}{(\sigma+2)^2} \quad (3.105)$$

The simulation result for Fig. 3.1 is provided in Fig. 3.38:




Figure 3.38: The data fraction deployed based on the radius value

Fig. 3.38 explains that as the value σ grows up, as the fraction assigned to P_0 increases, the fractions distributed to $level_1$ and $level_2$ reduces. In other words, if the communication capability decreases, there are more data processed locally, which is reasonable. If the ability of the link degrades, asymptotically equaling to the processor computation capacity, there is solely 11% data is deployed to the $level_2$. In addition, if the $\sigma > 1$, it means that the transmitting power is less than the processor's processing ability. In this scenario, keeping the data locally is more economical than transmitting it.

2*3 mesh network

P_0 starts to process the assigned workload and it starts to transfer the $\alpha_1, \alpha_2, \alpha_3, \alpha_4, \alpha_5$ fraction workload after it totally receive its α_0 task. That is, P_1 and P_2 are idle until the L finishes its data injection to P_0 . According to the $level_1$, the similar situation happens to P_1 and P_2 and they both start to transmit the α_3 after they totally receive the appropriate workload. In other words, P_3 has to wait until the previous three layers, $level_0$, $level_1$ and $level_2$ processors obtain their own data.




Figure 3.39: The timing diagram for 2*3 mesh network without front-end.

In addition, the group of equations are as follows:

$$\left. \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_1 \omega T_{cp} = T_{f,m} \\ \alpha_2 z T_{cm} + \alpha_2 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_3) z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_4) z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_3 + \alpha_5) z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \\ \alpha_0 + \alpha_1 + \alpha_2 + \alpha_3 + \alpha_4 + \alpha_5 = 1 \\ 0 < \alpha_0 \leq 1 \\ 0 \leq \alpha_1 \quad \alpha_2 \quad \alpha_3 \quad \alpha_4 \quad \alpha_5 < 1 \end{array} \right\} \quad (3.106)$$

$$\alpha_1 z T_{cm} + \alpha_1 \omega T_{cp} = T_{f,m} \quad (3.107)$$

$$\alpha_2 z T_{cm} + \alpha_2 \omega T_{cp} = T_{f,m} \quad (3.108)$$

$$(\alpha_1 + \alpha_3) z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \quad (3.109)$$

$$(\alpha_1 + \alpha_4) z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} \quad (3.110)$$

$$(\alpha_1 + \alpha_3 + \alpha_5) z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \quad (3.111)$$

$$\sigma = \frac{z T_{cm}}{\omega T_{cp}} \quad (3.112)$$

$$\alpha_0 + \alpha_1 + \alpha_2 + \alpha_3 + \alpha_4 + \alpha_5 = 1 \quad (3.113)$$

$$0 < \alpha_0 \leq 1 \quad (3.114)$$

$$0 \leq \alpha_1 \quad \alpha_2 \quad \alpha_3 \quad \alpha_4 \quad \alpha_5 < 1 \quad (3.115)$$

The flow matrix is :

$$\begin{bmatrix} 1 & 2 & 2 & 1 \\ 1 & -(\sigma + 1) & 0 & 0 \\ 1 & -\sigma & -(\sigma + 1) & 0 \\ 1 & -\sigma & -\sigma & -(\sigma + 1) \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \\ \alpha_5 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (3.116)$$

The speedup is

$$Speedup = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0}$$

The explicit solution is:

$$\left\{ \begin{array}{l} \alpha_0 = \left(\frac{\sigma + 1}{\sigma + 2} \right)^3 \\ \alpha_1 = \frac{(\sigma + 1)^2}{(\sigma + 2)^3} \end{array} \right. \quad (3.117)$$

$$\left\{ \begin{array}{l} \alpha_3 = \frac{\sigma + 1}{(\sigma + 2)^3} \\ \alpha_5 = \frac{1}{(\sigma + 2)^3} \end{array} \right. \quad (3.118)$$

$$\left\{ \begin{array}{l} \alpha_3 = \frac{\sigma + 1}{(\sigma + 2)^3} \\ \alpha_5 = \frac{1}{(\sigma + 2)^3} \end{array} \right. \quad (3.119)$$

$$\left\{ \begin{array}{l} \alpha_5 = \frac{1}{(\sigma + 2)^3} \end{array} \right. \quad (3.120)$$

The simulation result is:




Figure 3.40: The data fraction deployed based on the radius value

2*n mesh network

Considering Fig. 3.7, the equations are demonstrated as follows:

$$\left\{
 \begin{array}{ll}
 \alpha_0 \omega T_{cp} = T_{f,m} & (3.121) \\
 \alpha_1 z T_{cm} + \alpha_1 \omega T_{cp} = T_{f,m} & (3.122) \\
 \alpha_2 z T_{cm} + \alpha_2 \omega T_{cp} = T_{f,m} & (3.123) \\
 (\alpha_1 + \alpha_3) z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} & (3.124) \\
 (\alpha_1 + \alpha_4) z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} & (3.125) \\
 (\alpha_1 + \alpha_3 + \alpha_5) z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} & (3.126) \\
 \vdots & (3.127) \\
 (\alpha_1 + \alpha_3 + \cdots + \alpha_{2 \times n - 1}) z T_{cm} + \alpha_{2 \times n - 1} \omega T_{cp} = T_{f,m} & (3.128) \\
 \sigma = \frac{z T_{cm}}{\omega T_{cp}} & (3.129) \\
 0 < \sigma < 1 & (3.130) \\
 0 < \alpha_0 \leq 1 & (3.131) \\
 0 \leq \alpha_1 \alpha_3 \cdots \alpha_{2 \times n - 1} < 1 & (3.132)
 \end{array}
 \right.$$

Use σ^* to present $-(\sigma + 1)$ and the flow matrix form for the group of equations is :

$$\begin{bmatrix} 1 & 2 & 2 & \cdots & 2 & 2 & 1 \\ 1 & \sigma^* & 0 & \cdots & 0 & 0 & 0 \\ 1 & -\sigma & \sigma^* & \cdots & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & \sigma^* & 0 & \cdots & 0 \\ 1 & -\sigma & -\sigma & -\sigma & \sigma^* & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \\ 1 & -\sigma & -\sigma & \cdots & -\sigma & -\sigma & \sigma^* \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \\ \alpha_5 \\ \vdots \\ \alpha_{2 \times n-3} \\ \alpha_{2 \times n-1} \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ \vdots \\ 0 \end{bmatrix} \quad (3.133)$$

According to the **Cramer's rule**, the explicit solution for the group of equations is:

$$\left\{ \alpha_i = \left| \frac{\det A_i^*}{\det A} \right| \right. \quad (3.134)$$

where A_i^* is the matrix formed by replacing the i -th column of A by the column vector b .

We use $-\sigma - 2 = \epsilon$ and $\sigma^* - 2 = \beta$. After a series of column reduction and row reduction, the flow matrix changes as follows :

$$A = \begin{bmatrix} 1 & 2 & 2 & \cdots & 2 & 2 & 1 \\ 1 & \sigma^* & 0 & 0 & 0 & 0 & 0 \\ 1 & -\sigma & \sigma^* & 0 & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & \sigma^* & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma & \sigma^* & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* & 0 \\ 1 & -\sigma & -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* \end{bmatrix} \xrightarrow{\substack{\text{Column} \\ \text{Reduction}}} \begin{bmatrix} 1 & 0 & 0 & \cdots & 0 & 0 & 0 \\ 1 & \beta & -2 & \cdots & -2 & -2 & -1 \\ 1 & \epsilon & \beta & \cdots & 0 & 0 & 0 \\ 1 & \epsilon & \epsilon & \beta & 0 & \cdots & 0 \\ 1 & \epsilon & \epsilon & \epsilon & \beta & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \ddots \\ 1 & \epsilon & \epsilon & \cdots & \epsilon & \epsilon & \beta \end{bmatrix}$$

$$\xrightarrow{\substack{\text{Row} \\ \text{Reduction}}} \begin{bmatrix} 1 & 0 & 0 & \cdots & 0 & 0 & 0 \\ 0 & \beta & -2 & \cdots & -2 & -2 & -1 \\ 0 & \epsilon & \beta & \cdots & 0 & 0 & 0 \\ 0 & \epsilon & \epsilon & \beta & 0 & \cdots & 0 \\ 0 & \epsilon & \epsilon & \epsilon & \beta & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \ddots \\ 0 & \epsilon & \epsilon & \cdots & \epsilon & \epsilon & \beta \end{bmatrix}$$

We define

$$C = \begin{bmatrix} \sigma^* & 0 & 0 & 0 & 0 & 0 \\ -\sigma & \sigma^* & 0 & 0 & 0 & 0 \\ -\sigma & -\sigma & \sigma^* & 0 & 0 & 0 \\ -\sigma & -\sigma & -\sigma & \sigma^* & 0 & 0 \\ -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* & 0 \\ -\sigma & -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* \end{bmatrix}$$

$0 < \sigma < 1$, then $-2 < \sigma^* < -1$, which means C is column linear independent, after column and row reduction.

Further, we define

$$\hat{C} = \begin{bmatrix} \beta & -2 & \cdots & -2 & -2 & -1 \\ \epsilon & \beta & \cdots & 0 & 0 & 0 \\ \epsilon & \epsilon & \beta & 0 & \cdots & 0 \\ \epsilon & \epsilon & \epsilon & \beta & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots \\ \epsilon & \epsilon & \cdots & \epsilon & \epsilon & \beta \end{bmatrix}$$

C^* is full rank.

So the flow matrix A is full rank, that is, $\det A \neq 0$ and $\det A^* \neq 0$. The speedup is

$$Speedup = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0} = \frac{\det A}{\det A^*} = \left| \frac{\det A}{(\sigma^*)^{n-1}} \right|$$

m*n mesh network

Referring to Fig. 2.1, we utilize σ^* to present the $-(\sigma + 1)$. The matrix closed-form is:

$$\begin{bmatrix} 1 & 2 & 3 & 4 & 5 & 4 & 3 & 2 & 1 \\ 1 & \sigma^* & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & -\sigma & \sigma^* & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & \sigma^* & 0 & 0 & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma & \sigma^* & 0 & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* & 0 \\ 1 & -\sigma & \sigma^* \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_3 \\ \alpha_6 \\ \alpha_{10} \\ \alpha_{15} \\ \alpha_{19} \\ \alpha_{22} \\ \alpha_{24} \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (3.135)$$

3.2.2 Data Injection on The Boundary Processor

Fig. 3.10 shows an example of boundary processor P_0 receiving L . The timing diagram for Fig. 3.10 is Fig. 3.41.




Figure 3.41: The timing diagram for 3*3 boundary data injection on P_0

The equations are:

$$\left\{ \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_1 \omega T_{cp} = T_{f,m} \\ \alpha_2 z T_{cm} + \alpha_2 \omega T_{cp} = T_{f,m} \\ \alpha_3 z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_4) z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} \\ (\alpha_2 + \alpha_5) z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \\ (\alpha_3 + \alpha_6) z T_{cm} + \alpha_6 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_4 + \alpha_7) z T_{cm} + \alpha_7 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_4 + \alpha_8) z T_{cm} + \alpha_8 \omega T_{cp} = T_{f,m} \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \\ 0 < \sigma < 1 \\ 0 < \alpha_0 \leq 1 \\ 0 \leq \alpha_1 \alpha_3 \alpha_4 \alpha_5 \alpha_6 \alpha_7 \alpha_8 < 1 \end{array} \right. \quad \begin{array}{l} (3.136) \\ (3.137) \\ (3.138) \\ (3.139) \\ (3.140) \\ (3.141) \\ (3.142) \\ (3.143) \\ (3.144) \\ (3.145) \\ (3.146) \\ (3.147) \\ (3.148) \end{array}$$

The flow matrix is :

$$\begin{bmatrix} 1 & 3 & 3 & 2 \\ 1 & -(\sigma + 1) & 0 & 0 \\ 1 & -\sigma & -(\sigma + 1) & 0 \\ 1 & -\sigma & -\sigma & -(\sigma + 1) \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_4 \\ \alpha_7 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (3.149)$$

The simulation result is shown in :




Figure 3.42: The fraction curve for 3*3 boundary data injection on P_0

3.2.3 Data Injection on The Inner Grid Processor

The equations are:

$$\left\{ \begin{array}{l} \alpha_0 \omega T_{cp} = T_{f,m} \\ \alpha_1 z T_{cm} + \alpha_1 \omega T_{cp} = T_{f,m} \\ \alpha_2 z T_{cm} + \alpha_2 \omega T_{cp} = T_{f,m} \\ \alpha_3 z T_{cm} + \alpha_3 \omega T_{cp} = T_{f,m} \\ \alpha_4 z T_{cm} + \alpha_4 \omega T_{cp} = T_{f,m} \\ (\alpha_1 + \alpha_5) z T_{cm} + \alpha_5 \omega T_{cp} = T_{f,m} \\ (\alpha_2 + \alpha_6) z T_{cm} + \alpha_6 \omega T_{cp} = T_{f,m} \\ (\alpha_3 + \alpha_7) z T_{cm} + \alpha_7 \omega T_{cp} = T_{f,m} \\ (\alpha_4 + \alpha_8) z T_{cm} + \alpha_8 \omega T_{cp} = T_{f,m} \\ \sigma = \frac{z T_{cm}}{\omega T_{cp}} \\ 0 < \sigma < 1 \\ 0 < \alpha_0 \leq 1 \\ 0 \leq \alpha_1 \quad \alpha_3 \quad \alpha_4 \quad \alpha_5 \quad \alpha_6 \quad \alpha_7 \quad \alpha_8 < 1 \end{array} \right. \begin{array}{l} (3.150) \\ (3.151) \\ (3.152) \\ (3.153) \\ (3.154) \\ (3.155) \\ (3.156) \\ (3.157) \\ (3.158) \\ (3.159) \\ (3.160) \\ (3.161) \\ (3.162) \end{array}$$

The flow matrix closed-form is:

$$\begin{bmatrix} 1 & 4 & 4 \\ 1 & -(\sigma + 1) & 0 \\ 1 & -\sigma & -(\sigma + 1) \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_5 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \end{bmatrix} \quad (3.163)$$

The simulation result shows:




Figure 3.43: The timing diagram for 3*3 inner grid injection P_0

3.2.4 Sensitivity Analysis Store and Forward Scenario

Data Injection on The Corner Processor

The simulation result of sensitivity analysis of $2*n$ mesh network Fig. 3.7 is as follows:




Figure 3.44: Sensitivity analysis result of $2*10$ mesh network result

The figure illustrates that if $\sigma < 0.1$, the number of cores grow up, the speedup efficiency is likely linear increasing. Alternatively speaking, if $\sigma < 0.1$, the number of cores dominate the efficiency. If the $\sigma > 0.2$, the efficiency drops dramatically. That is, the σ value plays more critical role in the speedup simulation. This important investigation benefit the multi-source assignment problem. In addition, if the number of cores is bigger than 4, the bottom speedup effect is about 3 time.




Figure 3.45: Speedup curve of 2×10 mesh network result

Data Injection on The Boundary Processor

Fig. 3.46 and Fig. 3.47 tell the speedup efficiency for the data injection on the boundary.




Figure 3.46: Sensitivity analysis result of 3×8 mesh network result

Data Injection on The Inner Grid Processor

Fig. 3.48 and Fig. 3.49 display the simulation result for the data injection position P_{12} . If $\sigma < 0.1$, the speedup linear grows up and the best speedup is 24, which happens on the $\sigma < 0.1$.




Figure 3.47: Speedup curve of 3*8 mesh network result

3.2.5 Multi-source Uniform Data Fraction

3.2.6 Multi-source Non-uniform Data Injection




Figure 3.48: Sensitivity analysis result of data injection position on inner grid processor




Figure 3.49: Speedup curve of 5*5 mesh network result

Chapter 4

Toroidal Rectangle Network

4.1 Toroidal Rectangle Network Notions

The toroidal network is a regular complex in that each polygonal face has the same number of links and each node is connected to the same number of links. According to the paper [15], there are three different torus mesh network. In this paper, our intent is not to propose one model to "fit all" problems but rather to indicate one normal case.

Considering the toroidal rectangle network Fig. 4.1 and Fig. 4.2.

- m : There are m processors on the longitude.
- n : There are n processors on the latitude.
- L : The load injection.
- L_x : The L 's longitude coordinate.
- L_y : The L 's latitude coordinate.




Figure 4.1: The rectangular toroidal network




Figure 4.2: The rectangular toroidal network

- D_k : P_k 's shortest Manhattan distance to L .
- $D_{k,x}$: P_k 's longitude shortest Manhattan distance to L .
- $D_{k,y}$: P_k 's altitude shortest Manhattan distance to L .

$$\left\{ \begin{array}{l} D_k = D_{k,x} + D_{k,y} \\ D_{k,x} = \min\{\|D_{k,x} - L_x\|, m - \|D_{k,x} - L_x\|\} \\ D_{k,y} = \min\{\|D_{k,y} - L_y\|, n - \|D_{k,y} - L_y\|\} \end{array} \right. \quad (4.1)$$

$$\left\{ \begin{array}{l} D_k = D_{k,x} + D_{k,y} \\ D_{k,x} = \min\{\|D_{k,x} - L_x\|, m - \|D_{k,x} - L_x\|\} \\ D_{k,y} = \min\{\|D_{k,y} - L_y\|, n - \|D_{k,y} - L_y\|\} \end{array} \right. \quad (4.2)$$

$$\left\{ \begin{array}{l} D_k = D_{k,x} + D_{k,y} \\ D_{k,x} = \min\{\|D_{k,x} - L_x\|, m - \|D_{k,x} - L_x\|\} \\ D_{k,y} = \min\{\|D_{k,y} - L_y\|, n - \|D_{k,y} - L_y\|\} \end{array} \right. \quad (4.3)$$

4.2 Virtual Cut-through Switching Scenario

4.2.1 Data Injection On The Grid Processor

In $m * n$ ($m = 6, n = 6$) Fig. 4.3 toroidal rectangle network, L happens on grid position (4, 2). We calculate the $D_{k,i}$ table Table 4.1 by breadth first search(**BFS**) algorithm.




Figure 4.3: The m^*n toroidal rectangle network and the data injection is $P_{4,2}$

The $D_{k,i}$ table is as follow in table Table 4.1

The flow matrix closed-form is

$$\begin{bmatrix} 1 & 4 & 8 & 10 & 8 & 4 & 1 \\ 1 & -1 & 0 & 0 & 0 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & \sigma & 1 & 0 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \\ \alpha_4 \\ \alpha_5 \\ \alpha_6 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (4.4)$$

D_i	Number
0	1
1	4
2	8
3	10
4	8
5	4
6	1

Table 4.1: D_i vs Number

The simulation result is :

From Fig. 4.4, we see that as the value σ grows, more and more workload is assigned to the $P_{4,2}$ and its one hop neighbors. That is, as the communication ability decades, the economical method is to locally process the job.

The figure illustrates that if $\sigma < 0.3$, the number of processors grow up, the speedup efficiency is likely linear increasing. Alternatively speaking, if $\sigma < 0.3$, the number of cores dominate the efficiency. If the $\sigma > 0.3$, the efficiency drops dramatically. That is, the σ value plays more critical role in the speedup simulation. This important investigation benefit the multi-source assignment problem. In addition, if the number of cores is bigger than 4, the bottom speedup effect is about 3 time.




Figure 4.4: The data fraction curve of Fig. 4.3

4.2.2 Sensitivity Analysis of Toroidal Rectangle Network

Considering a 5×5 toroidal rectangle network, the $level_i$ table shows Table 4.2:

D_i	Number
0	1
1	4
2	8
3	8
4	4

Table 4.2: The processor number of various D_i

So the simulation result illustrates in Fig. 4.5




Figure 4.5: Sensitivity analysis 5*5 torus network




Figure 4.6: Sensitivity analysis 5*5 torus network on different σ

Fig. 4.6 illustrates that as the value σ decreases, the speedup efficiency increases. The best performance happens on the $\sigma \approx 1$ and the efficiency speedup is almost 25. The bottom speedup situation is about 5.

4.2.3 Multi-source Uniform Data Fraction

We extend the single source assignment to multi-source assignment problem [10] [4]. According to each processor, we concentrate on the processors' geographical location P_i , data fraction assigned α_i .

Assuming the data fraction is even. For example, the workload is unit 1 and there are k different data injection options. So each data injection is assigned $\frac{1}{k}$ workload. From the data injection position relationship we consider three different situations :

- Data injection positions consist of a subgraph G_L of G .
- Data injection processor doesn't connect with each other.
- Other situations.

Fig. 4.11 [16] provides a torus Voronoi method, which extends the original domain to 8 copy and calculate the Voronoi Diagram as planner algorithm [17]. Then the corner part is the torus Voronoi diagram.

Situation I




Figure 4.7: Toroidal mesh network subgraph data injection

Fig. 4.7 shows a subgraph data injection situation. Fig. 4.7's flow matrix equation is

$$\begin{bmatrix} 4 & 8 & 9 & 4 \\ 1 & -1 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 \\ 0 & \sigma - 1 & \sigma & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (4.5)$$




Figure 4.8: Data fraction on different type processors for Fig. 4.7




Figure 4.9: Toroidal mesh network subgraph data injection

Fig. 4.9 shows a subgraph data injection situation.

Fig. 4.9's flow matrix equation is

$$\begin{bmatrix} 4 & 8 & 9 & 4 \\ 1 & -1 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 \\ 0 & \sigma - 1 & \sigma & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (4.6)$$




Figure 4.10: Data fraction on different type processors for Fig. 4.9

Situation II




Figure 4.11: How to calculate torus Voronoi Diagram




Figure 4.12: Initial Voronoi Diagram

Fig. 4.12 says the initial Voronoi division of a 50×50 mesh network. Each data injection receives the data and the cell processor tackle the task together. The user case contains 10 data injections and each cell's speedup curve shows in Fig. 4.15.




Figure 4.13: Torus Voronoi diagram

Fig. 4.13 shows the toroidal Voronoi division result. The same color parts connect with each other and consist of a whole division in toroidal rectangle network. For example, the four gray corners consist of a whole area and the injection processor index is 6.




Figure 4.14: Voronoi diagram casting to the torus model

Fig. 4.14 shows the Fig. 4.13 casts to the toroidal rectangle network result.




Figure 4.15: Voronoi cell speedup curves

In the reduced model Fig. 4.16 and Fig. 4.17, reduced toroidal Voronoi diagram save 27% processors hit the same processing capacity. The ratio of original method is about $\frac{490}{98} = 5$, after the reduced action, the ratio is $\frac{290}{98} \approx 2.96$. That is the reduced heuristic algorithm obtaining more balanced computation capacity distribution.




Figure 4.16: Torus reduced Voronoi diagram casting to the toroidal rectangle network




Figure 4.17: Torus reduced Voronoi diagram




Figure 4.18: Torus reduced Voronoi diagram average saved processors

Situation III




Figure 4.19: Subgraph and individual data injection on torus network




Figure 4.20: Subgraph and individual data injection on torus network




Figure 4.21: Subgraph and individual data injection on torus network




Figure 4.22: Subgraph and individual data injection on torus network




Figure 4.23: Subgraph and individual data injection on torus network

Save about $436/2500 \approx 17\%$ processors.

4.2.4 Multi-source Non-uniform Data Injection

4.3 Store and Forward Switching Scenario

4.3.1 Data Injection On The Grid Processor

We utilize the σ^* to present $-(\sigma + 1)$. The flow matrix closed-form of Fig. 4.3 is:

$$\begin{bmatrix} 1 & 4 & 8 & 10 & 8 & 4 & 1 \\ 1 & \sigma^* & 0 & 0 & 0 & 0 & 0 \\ 1 & -\sigma & \sigma^* & 0 & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma^* & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma & \sigma^* & 0 & 0 \\ 1 & -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* & 0 \\ 1 & -\sigma & -\sigma & -\sigma & -\sigma & -\sigma & \sigma^* \end{bmatrix} \times \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \\ \alpha_4 \\ \alpha_5 \\ \alpha_6 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} \quad (4.7)$$

The fraction curve result is :

From Fig. 4.24, we see that as the value σ grows, more and more workload is assigned to the $P_{4,2}$ and its one hop neighbors. That is, as the communication ability decades, the economical method is to locally process the job.




Figure 4.24: The data fraction curve of Fig. 4.3

4.3.2 Sensitivity Analysis of Toroidal Rectangle Network

Considering a 5×5 toroidal rectangle network, the $level_i$ table shows Table 4.3:

So the simulation result illustrates in Fig. 4.25

D_i	Number
0	1
1	4
2	8
3	8
4	4

Table 4.3: The processor number of various D_i




Figure 4.25: Sensitivity analysis result of data injection position on inner grid processor

4.3.3 Multi-source Uniform Data Injection

We utilize the IRVDA algorithm.




Figure 4.26: Subgraph and individual data injection on torus network

Save about $436/2500 \approx 17\%$ processors.




Figure 4.27: Subgraph and individual data injection on torus network

4.3.4 Multi-source Non-uniform Data Injection




Figure 4.28: Subgraph and individual data injection on torus network

4.4 Comparison Result

4.4.1 Comparison Result Between Mesh Network and Toroidal With Same Processors Number

Considering a regular mesh network Fig. 2.1, the best position for data injection is P_{12} . Other positions, for example P_8 , P_{13} , they don't have the same speedup efficiency. Yet, for a toroidal $5 * 5$ regular mesh network, each position's efficiency is equal. Fig. 4.30 explores the comparison result between the toroidal and corner scenario difference.




Figure 4.29: Subgraph and individual data injection on torus network

4.4.2 Comparison Result With Corner Processor and Inner Grid Processor

For a $5 * 5$ mesh network, the inner grid position is P_{12} and the corner data injection position is P_0 . The comparing result is Fig. 4.30.

Generally speaking, Fig. 4.30 says the inner grid position scenario has better performance than the corner injection option. If the grid node is 25 and $\sigma = 0.5$, the speedup difference is largest, which is 4.




Figure 4.30: Speedup difference between corner injection and inner grid injection

4.4.3 Comparison Result Between Virtual Cut-through Switching Scenario and Store and Forward Scenario

In the legend of figures, we use

- F presents the processors are with front-end situation.
- NF presents the processors are without front-end situation.
- $F\alpha_0$ means the α_0 data fraction deployed to P_0 , if the processor has front-end.
- $NF\alpha_0$ means the α_0 data fraction deployed to P_0 , if the processor is without front-end setting.

Data Injection On the Corner Processor




Figure 4.31: The comparing result between front-end processor with without front-end processor in 2^*2 mesh network

Fig. 4.31 says that P_0 takes more assigned task in without front-end scenario than front-end processor situation. As the value σ value goes up, the fractions are deployed to the deeper layers decreases. In the limit condition, for example, $\sigma = 1$, there is no data transmitted to P_3 in the front-end assumption, yet in the without front-end situation, there is still about 10% data fraction are communicated to P_3 .




Figure 4.32: The comparing result between front-end processor with without front-end processor in $2*3$ mesh network

Fig. 4.32 says that P_0 takes more assigned task in without front-end scenario than front-end processor situation. As the σ value goes up, the fractions are deployed to the deeper levels degrades. In the limit condition, for example, $\sigma = 1$, there is no data transmitted to $level_3$, that is, P_5 in the front-end assumption. Yet in the without front-end situation, there is still about 5% data fraction is communicated to P_5 .




Figure 4.33: The comparing result between front-end processor with without front-end processor in 3×3 mesh network injection on boundary processor

Fig. 4.33 says that P_0 takes more assigned task in without front-end scenario than front-end processor situation. As the σ value goes up, the fractions are deployed to the deeper levels decreases. In the limit condition, for example, $\sigma = 1$, there is no data transmitted to $level_3$, that is, P_7 and P_8 in the front-end assumption. Yet in the without front-end situation, there is still about 5% data fraction is communicated to P_7 and P_8 .




Figure 4.34: The comparing result between front-end processor with without front-end processor in $3*3$ mesh network injection on inner grid processor

Fig. 4.34 says that P_0 takes more assigned task in without front-end scenario than front-end processor situation. As the σ value goes up, the fractions are deployed to the deeper levels dropping down. In the limit condition, for example, $\sigma = 1$, there is no data transmitted to *level₂*, that is, P_5 , P_6 , P_7 and P_8 in the front-end assumption. Yet in the without front-end situation, there is still about 5% data fraction is communicated to P_5 , P_6 , P_7 and P_8 .

Comparing with Fig. 4.33, P_0 takes less workload in inner grid position than boundary data injection. The reason is there are 4 neighbor processors

on the $level_1$, yet there is solely three processors on $level_1$ on the boundary.




Figure 4.35: Speedup difference between front-end and without front-end in 5×5 mesh network

Fig. 4.35 shows the speedup difference between the front-end situation and without front-end scenario.

4.5 Store and Froward Switching

In this chapter, we mainly discuss the virtual cut through [5] switching. In addition, the store and froward [18] schema is a mature data processing technique. In future works, we discuss it.

Chapter 5

Hypercube Network

5.1 Virtual Cut-through Switching Scenario

The hypercube topology has two nodes along each dimension and $\log_2 n$ dimensions. The construction of a hypercube goes as follows, in general a d -dimensional hypercube is constructed by connecting corresponding nodes of two $(d - 1)$ dimensional hypercubes Fig. 5.1.




Figure 5.1: Hypercube in 0, 1, 2, 3 dimension. [1]

In this work, we have two tasks as follows :

- One data injection, we propose a method of finding an optimal distribution of a divisible job among a cluster of processors connected by communication links and forming a hypercube network. The methodology we apply is similar to the flow matrix technique.
- Sensitivity analysis of the hypercube structure by adding more processors or dimensions.
- The multi-source sub-optimal algorithms to speedup job execution.
 - The data injection fractions are even.
 - The data injection fractions are different with each other.

5.1.1 Data Injection On The Grid Processor

For the hypercube of dimension d there are 2^d processor in the system. Each of the processors has direct links to d neighbors. A method of naming the processors is to use label consisting of a binary string d - position long. Further, the label of a processor is a binary number from the interval $[0, 2^d - 1]$

To address the qualitative model of computation, the critical problem is to calculate the number of processor on each D_i . Each node is connected by link and the hamming distance of their's label is 1. According to the lemma of [19],

Lemma 5.1.1. *In each layer i of d -dimensional hypercube, there are $\binom{n}{i}$*

processors each of which can be accessed through i communications links and is capable of transmitting to $d - i$ still idle processors.

According to a $2 - D$ hypercube Fig. 3.1, the flow matrix is

$$A = \begin{bmatrix} \binom{2}{0} & \binom{2}{1} & \binom{2}{2} \\ 1 & -1 & 0 \\ 0 & \sigma - 1 & 1 \end{bmatrix} = \begin{bmatrix} 1 & 2 & 1 \\ 1 & -1 & 0 \\ 0 & \sigma - 1 & 1 \end{bmatrix} \quad (5.1)$$

, which is investigated in Regular Network Chapter.

According to a $3 - D$ hypercube, the flow matrix is

$$A = \begin{bmatrix} \binom{3}{0} & \binom{3}{1} & \binom{3}{2} & \binom{3}{3} \\ 1 & -1 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 \\ 0 & \sigma - 1 & \sigma & 1 \end{bmatrix} = \begin{bmatrix} 1 & 2 & 2 & 1 \\ 1 & -1 & 0 & 0 \\ 0 & \sigma - 1 & 1 & 0 \\ 0 & \sigma - 1 & \sigma & 1 \end{bmatrix} \quad (5.2)$$

The speedup is $|- \det A|$.

A general case, D -dimension network, the flow matrix is :

$$A = \begin{bmatrix} \binom{n}{0} & \binom{n}{1} & \binom{n}{2} & \cdots & \binom{n}{n-2} & \binom{n}{n-1} & \binom{n}{n} \\ 1 & -1 & 0 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \ddots \\ 0 & \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix}$$

5.1.2 Sensitivity Analysis Virtual Cut-through Switching Scenario

5.1.3 Multi-source Uniform Data Fraction

5.1.4 Multi-source Non-uniform Data Injection

5.2 Store and Forward Switching Scenario

In this work, we have two tasks as follows :

- One data injection, we propose a method of finding an optimal distribution of a divisible job among a cluster of processors connected by communication links and forming a hypercube network. The methodology we apply is similar to the flow matrix technique.
- Sensitivity analysis of the hypercube structure by adding more processors or dimensions.
- The multi-source sub-optimal algorithms to speedup job execution.
 - The data injection fractions are even.
 - The data injection fractions are different with each other.

5.2.1 Data Injection On The Grid Processor

According to a $2 - D$ hypercube Fig. 3.1, the flow matrix is

$$A = \begin{bmatrix} \binom{2}{0} & \binom{2}{1} & \binom{2}{2} \\ 1 & -(\sigma + 1) & 0 \\ 1 & -\sigma & -(\sigma + 1) \end{bmatrix} = \begin{bmatrix} 1 & 2 & 1 \\ 1 & -(\sigma + 1) & 0 \\ 1 & -\sigma & -(\sigma + 1) \end{bmatrix} \quad (5.3)$$

, which is investigated in Regular Network Chapter.

According to a $3 - D$ hypercube, the flow matrix is

$$A = \begin{bmatrix} \binom{3}{0} & \binom{3}{1} & \binom{3}{2} & \binom{3}{3} \\ 1 & -(\sigma + 1) & 0 & 0 \\ 1 & -\sigma & -(\sigma + 1) & 0 \\ 1 & -\sigma & -\sigma & -(\sigma + 1) \end{bmatrix} = \begin{bmatrix} 1 & 2 & 2 & 1 \\ 1 & -(\sigma + 1) & 0 & 0 \\ 1 & -\sigma & -(\sigma + 1) & 0 \\ 1 & -\sigma & -\sigma & -(\sigma + 1) \end{bmatrix} \quad (5.4)$$

The speedup is $|- \det A|$.

A general case, D -dimension network, the flow matrix is : We use σ^* to represents $-(\sigma + 1)$.

$$A = \begin{bmatrix} \binom{n}{0} & \binom{n}{1} & \binom{n}{2} & \cdots & \binom{n}{n-2} & \binom{n}{n-1} & \binom{n}{n} \\ 1 & \sigma^* & 0 & \cdots & 0 & 0 & 0 \\ 1 & -\sigma & \sigma^* & \cdots & 0 & 0 & 0 \\ 1 & -\sigma & -\sigma & \sigma^* & 0 & \cdots & 0 \\ 1 & -\sigma & -\sigma & -\sigma & \sigma^* & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \\ 1 & -\sigma & -\sigma & \cdots & -\sigma & -\sigma & \sigma^* \end{bmatrix}$$

5.2.2 Sensitivity Analysis Store and Forward Switching Scenario

5.2.3 Multi-source Uniform Data Fraction

5.2.4 Multi-source Non-uniform Data Injection

Chapter 6

General Network

6.1 General Case Virtual Cut-through Switching Scenario

$$\begin{bmatrix} 1 & m_1 & m_2 & \cdots & m_{n-2} & m_{n-1} & m_n \\ 1 & -1 & 0 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & 1 & \cdots & 0 & 0 & 0 \\ 0 & \sigma - 1 & \sigma & 1 & 0 & \cdots & 0 \\ 0 & \sigma - 1 & \sigma & \sigma & 1 & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \\ 0 & \sigma - 1 & \sigma & \cdots & \sigma & \sigma & 1 \end{bmatrix} \times \begin{bmatrix} \alpha_{l_0} \\ \alpha_{l_1} \\ \alpha_{l_2} \\ \alpha_{l_3} \\ \vdots \\ \alpha_{l_{n-1}} \\ \alpha_{l_n} \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \\ \vdots \\ 0 \end{bmatrix} \quad (6.1)$$

The m_1, m_2, \dots, m_n are the number of processors on the $level_1, level_2, \dots, level_n$. Also, the $\alpha_{l_0}, \alpha_{l_1}, \dots, \alpha_{l_n}$ are corresponding workload fraction.

Finally, the speedup is:

$$\text{Speedup} = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0} = |-\det A|$$

6.2 General Case Store and Forward Switching Scenario

$$\begin{bmatrix}
 1 & m_1 & m_2 & \cdots & m_{n-2} & m_{n-1} & m_n \\
 1 & -(\sigma + 1) & 0 & \cdots & 0 & 0 & 0 \\
 1 & -\sigma & -(\sigma + 1) & \cdots & 0 & 0 & 0 \\
 1 & -\sigma & -\sigma & -(\sigma + 1) & 0 & \cdots & 0 \\
 1 & -\sigma & -\sigma & -\sigma & -(\sigma + 1) & 0 & 0 \\
 \vdots & \vdots & \vdots & \vdots & \ddots & \ddots & \\
 1 & -\sigma & -\sigma & \cdots & -\sigma & -\sigma & -(\sigma + 1)
 \end{bmatrix} \times
 \begin{bmatrix}
 \alpha_{l_0} \\
 \alpha_{l_1} \\
 \alpha_{l_2} \\
 \alpha_{l_3} \\
 \vdots \\
 \alpha_{l_{n-1}} \\
 \alpha_{l_n}
 \end{bmatrix} =
 \begin{bmatrix}
 1 \\
 0 \\
 0 \\
 0 \\
 \vdots \\
 0
 \end{bmatrix} \quad (6.2)$$

The m_1, m_2, \dots, m_n are the number of processors on the $level_1, level_2, \dots, level_n$. Also, the $\alpha_{l0}, \alpha_{l1}, \dots, \alpha_{ln}$ are corresponding workload fraction.

The speedup is

$$Speedup = \frac{T_{f,0}}{T_{f,n}} = \frac{\omega T_{cp}}{\alpha_0 \omega T_{cp}} = \frac{1}{\alpha_0} = \frac{\det A}{\det A^*} = \left| \frac{\det A}{(\sigma^*)^{n-1}} \right|$$

Chapter 7

Conclusion and Future work

7.1 Conclusion

7.2 Future Work

Bibliography

- [1] D. R.-P. Mundan, “Parallel programming exercise sheet 2: Topologies.” <https://www5.in.tum.de/lehre/vorlesungen/parhpp/materialien/sheet02.pdf>. Issued at 10/05/07, to be discussed at 15/05/07.
- [2] M. Moges, D. Yu, and T. G. Robertazzi, “Grid scheduling divisible loads from two sources,” *Computers & Mathematics with Applications*, vol. 58, no. 6, pp. 1081–1092, 2009.
- [3] T. G. Robertazzi, “Processor equivalence for daisy chain load sharing processors,” *IEEE Transactions on Aerospace and Electronic Systems*, vol. 29, no. 4, pp. 1216–1221, 1993.
- [4] X. Liu, H. Zhao, and X. Li, “Scheduling divisible workloads from multiple sources in linear daisy chain networks.”
- [5] P. Kermani and L. Kleinrock, “Virtual cut-through: A new computer communication switching technique,” *Computer Networks (1976)*, vol. 3, no. 4, pp. 267–286, 1979.
- [6] V. Bharadwaj, D. Ghose, V. Mani, and T. G. Robertazzi, *Scheduling divisible loads in parallel and distributed systems*, vol. 8. John Wiley & Sons, 1996.
- [7] J. Sohn and T. G. Robertazzi, “Optimal load sharing for a divisible job on a bus network,” tech. rep., Stony Brook, NY: State University of New York at Stony Brook, College of Engineering., 1992.
- [8] J. T. Hung and T. G. Robertazzi, “Switching in sequential tree networks,” *IEEE Transactions on Aerospace and Electronic Systems*, vol. 40, no. 3, pp. 968–982, 2004.
- [9] V. Bharadwaj, D. Ghose, and T. G. Robertazzi, “Divisible load theory: A new paradigm for load scheduling in distributed systems,” *Cluster Computing*, vol. 6, no. 1, pp. 7–17, 2003.

- [10] J. Jia, B. Veeravalli, and J. Weissman, “Scheduling multisource divisible loads on arbitrary networks,” *IEEE Transactions on Parallel and Distributed Systems*, vol. 21, no. 4, pp. 520–531, 2010.
- [11] S. Fortune, “Voronoi diagrams and delaunay triangulations,” in *Computing in Euclidean geometry*, pp. 225–265, World Scientific, 1995.
- [12] E. Krevat, J. G. Castaños, and J. E. Moreira, “Job scheduling for the bluegene/l system,” in *Workshop on Job Scheduling Strategies for Parallel Processing*, pp. 38–54, Springer, 2002.
- [13] F. Chin and C. A. Wang, “Finding the constrained delaunay triangulation and constrained voronoi diagram of a simple polygon in linear time,” *SIAM Journal on Computing*, vol. 28, no. 2, pp. 471–486, 1998.
- [14] C. F. Gamboa and T. Robertazzi, “Simple performance bounds for multicore and parallel channel systems,” *Parallel Processing Letters*, vol. 21, no. 04, pp. 439–460, 2011.
- [15] T. G. Robertazzi, “Toroidal networks,” *IEEE Communications Magazine*, vol. 26, no. 6, pp. 45–50, 1988.
- [16] C. I. Grima and A. Márquez, *Computational Geometry on Surfaces: Performing Computational Geometry on the Cylinder, the Sphere, the Torus, and the Cone*. Springer Science & Business Media, 2013.
- [17] S. Fortune, “A sweepline algorithm for voronoi diagrams,” *Algorithmica*, vol. 2, no. 1-4, p. 153, 1987.
- [18] G. R. Kanthraj, C. R. Srinivas, *et al.*, “Store and forward teledermatology,” *Indian Journal of Dermatology, Venereology, and Leprology*, vol. 73, no. 1, p. 5, 2007.
- [19] J. Błazewicz and M. Drozdowski, “Scheduling divisible jobs on hypercubes,” *Parallel computing*, vol. 21, no. 12, pp. 1945–1956, 1995.