Code Camp
Serverless Platforms

Jason Barbee
Solutions Architect
CCIE #18039

Agenda

1. Evolution of a Platform
2. Consumable Platforms today
3. Function as a Service
4. Lab Outline

Compute in 2000's - Physical

Physical Server Farm

Provision Time - days

Compute in 2010 - Virtualization

VMWare Servers on physical hardware, SANs, Networking

Provision Time - ~ 1-2 hours

Compute in ~2014 - Virtual Machines

- Spin up VMs at your favorite provider -
- TekLinks, AWS, Google, Azure, dozens of providers...

Compute in 2017 - Microservices and APIs

- FAAS / Function as a Service Providers.
- AWS, Google, Azure, Webtasks
- Your customer's routers.
- Your customer's compute, or hyperconvered.

Routers = Cloud

Routers can run third party service containers. AKA - your code

Host Your Applications on a Device

Cisco service devices support hosting applications directly on the devices for network management, monitoring and other needs.

IOS-XE

ıpports 3rd party KVM container
ıd UCS E Series Server module.

IOS-XR

Supports RPM package installation and 3rd Party LXC containers.

Open NX-OS

Supports 3rd party LXC containers and "Guest Shell container.

Servers = Cloud

Azure wants to run on your bare metal.
Same APIs as public cloud

Servers = Cloud

OpenStack wants to run on bare metal and provide APIs for compute, storage and networking.

Agenda

1. Evolution of a Platform
2. **Consumable Platforms today**
3. Bot Revolution
4. Function as a Service
5. Lab Outline

API Connector Services - IFTT



IFTT - Custom REST Actions to anything

- Add custom actions with Maker Channel to any URL.
- Send a REST call to any endpoint on the internet.
- Make a Spark call, Tropo Call, Turn on/Off lights.

Zapier.com - Business Logic

- More logic and customization of actions.
- Still End User Friendly. Free and commercial plans.
- 750+ API integrations built in



Agenda

1. Evolution of a Platform
2. Consumable Platforms today
3. **Bot Revolution**
4. Function as a Service
5. Lab Outline

Bots the new User interface

Why would I want to talk to a bot?
We all hate calling and navigating IVRs.

Bot Platforms

- Gupshup.com
- Recast.ai
- wit.ai
- Flint Framework for Node
- Microsoft Bot Framework
- Serverless Bots with URL Web Hooks and Actions

Agenda

1. Evolution of a Platform
2. Consumable Platforms today
3. Bot Revolution
4. **Function as a Service**
5. Lab Outline

Function-As-A-Service

- Function as a Service to run small units of code on on requests or evenets
- Read or Write to a database.
- Call a Spark Log
- Call a payment processing and return a value.

AWS Microservice Example



AWS API Gateway

- Accepts GET, POST, PUT all the REST APIs.

http://mynetopsbot.exampleamazon.com

{

"Email": "jason.barbee@gmail.com",

"Message": "do I have any routers running 12.2"

}

AWS Components

Lambda

Our example : Lambda parses the language and intention, queries a database for security issues for 12.2.
Returns results to Lambda for processing.

AWS Microservice Example

Lambda - adds language back to the message and sends to a Spark Web Hook.

http://spark.cisco.com


```
{
 "message" : "You have 2 routers running 12.2 vulnerable to 100+ PSIRT advisories"
 "roomID" : "12341232131251252342 34"
}
```

Storing Data

DynamoDB - NoSQL Database

Let's start with SQL and compare to NoSQL

```
INSERT INTO book (
   `ISBN`, `title`, `author`
)
VALUES (
   '9780992461256',
   'Mastering Windows NT 4.0',
   'John Smith'
);
```

DynamoDB - NoSQL Example

```
db.book.insert({
   ISBN: "9780992461256",
   title: "Full Stack JavaScript",
   author: "Colin Ihrig & Adam Bretz"
});
```

AWS Microservice Example Review



What does a microservice function look like?

Hello World at hook.io

Hello World

```
module['exports'] = function helloWorld (hook) {
  hook.res.end("Hello world!"');
};
```

Make a API Gateway example

Login to AWS Console
Go to API Gateway. Click Getting Started. You'll get the default PetStore API.

Example API Gateway

AWS API Gateway

Click Getting Started to import the example PetStore API.

My PetStore API - GET



PetStore GET - Response/Test



Ok this isn't Fair

I used the template, and PetStoreAPI doesn't actally do anything.

AWS API Gateway

You have to define all the endpoints one by one
create functions, link them to the API one by one
upload files and NPM packages to S3 if you want any imports
Stage dev and production if you want to have a backup copy hot and ready
Basically there's a lot of stuff to wire together, and a lot of clicks.

Meet the Serverless Framework - www.serverless.com



Serverless magic

- Cloudformation to build your environment - API, Lambda, Storage, Databases.
- API Versioning
- Staging to Production

Example of Serverless Deployment

```
vagrant@vagrant:/vagrant/Serverless$ serverless config credentials --provider aws --key mykey --secret mysecret
Serverless: Setting up AWS...
Serverless: Saving your AWS profile in "~/.aws/credentials"...
Serverless: Success! Your AWS access keys were stored under the "default" profile.
vagrant@vagrant:/vagrant/Serverless$ serverless deploy
Serverless: Packaging service...
Serverless: Uploading CloudFormation file to S3...
Serverless: Uploading service .zip file to S3 (3.6 MB)...
Serverless: Updating Stack...
Serverless: Checking Stack update progress...
.....................................
Serverless: Stack update finished...
Service Information
service: serverless-rest-api-with-dynamodb
stage: dev
region: us-east-1
api keys:
  None
endpoints:
  POST - https://3snrpqj7tj.execute-api.us-east-1.amazonaws.com/dev/routers
  GET - https://3snrpqj7tj.execute-api.us-east-1.amazonaws.com/dev/routers
  GET - https://3snrpqj7tj.execute-api.us-east-1.amazonaws.com/dev/routers/{id}
  PUT - https://3snrpqj7tj.execute-api.us-east-1.amazonaws.com/dev/routers/{id}
  DELETE - https://3snrpqj7tj.execute-api.us-east-1.amazonaws.com/dev/routers/{id}
functions:
  serverless-rest-api-with-dynamodb-dev-update: arn:aws:lambda:us-east-1:062829191412:function:serverless-rest-api-with-dynamodb-dev-update
  serverless-rest-api-with-dynamodb-dev-get: arn:aws:lambda:us-east-1:062829191412:function:serverless-rest-api-with-dynamodb-dev-get
  serverless-rest-api-with-dynamodb-dev-list: arn:aws:lambda:us-east-1:062829191412:function:serverless-rest-api-with-dynamodb-dev-list
  serverless-rest-api-with-dynamodb-dev-create: arn:aws:lambda:us-east-1:062829191412:function:serverless-rest-api-with-dynamodb-dev-create
  serverless-rest-api-with-dynamodb-dev-delete: arn:aws:lambda:us-east-1:062829191412:function:serverless-rest-api-with-dynamodb-dev-delete
vagrant@vagrant:/vagrant/Serverless$
```

Lab 4 - Going Serverless

You will get to build/deploy/play with
* Hook.io Microservice that logs to a Spark Room.
* AWS REST API that actually interfaces with a DynamoDB.
* Using Ansible to push inventory data into that AWS REST API.

Wrapping up

- No we don't all have to write code tomorrow.
- There's never been a more exciting time in our field.
- Engineers are building cool stuff and sharing it.
- Open source is better than ever, and has a lot of corporate backing.

Call to Action:

Actively seek opportunities and Engage us (myself and Jeremy Sanders) to

- Tie collaboration or workflow platforms together
- Add human like interactions to common tasks via chat bots
- Write small apps that integrate business processes together
- Help you deploy and learn Ansible.
- Write scripting to be more efficient on projects if you find yourself facing a large repetitive task set or a chain of processes.

Thank you.

Questions?