

## Model Construction via Implicit Indirection

```
# In core/transformer/transformer_layer.py
class TransformerLayer(ModelModule):
    def __init__(self, config, submodules):
        self.input_layernorm = build_module(submodules.input_layernorm, ...)
        self.self_attention = build_module(submodules.self_attention, ...)
        self.mlp ← build_module(submodules.mlp, ...)

# In core/models/gpt/gpt_layer_specs.py
def get_gpt_layer_with_spec(num_experts, ...):
    return ModuleSpec(
        module=TransformerLayer,
        submodules=TransformerLayerSubmodules(
            input_layernorm=Norm,
            self_attention=ModuleSpec(
                module=SelfAttention, submodules=SelfAttentionSubmodules(...)
            ),
            mlp=(ModuleSpec(module=MoELayer, ...) if num_experts > 0
                 else ModuleSpec(module=MLP, ...)),
        ),
    )
```

“self.mlp” defined  
in another file

## PithTrain

```
# In models/qwen3_moe.py
class Qwen3DecoderLayer(nn.Module):
    def __init__(self, cfg, layer_idx):
        self.input_layernorm = RMSNorm(cfg.hidden_size)
        self.self_attn = Qwen3Attention(cfg)
        self.post_attention_layernorm = RMSNorm(cfg.hidden_size)
        use_moe = ... # True for MoE layers, False for dense
        self.mlp = Qwen3MoE(cfg) if use_moe else Qwen3MLP(cfg)

class Qwen3MoE(nn.Module): ...
class Qwen3MLP(nn.Module): ...

class Qwen3Model(nn.Module):
    def __init__(self, cfg):
        self.embed_tokens = nn.Embedding(cfg.vocab_size, cfg.hidden_size)
        self.layers = nn.ModuleList([
            Qwen3DecoderLayer(cfg, i) for i in range(cfg.num_layers)
        ])
        self.norm = RMSNorm(cfg.hidden_size)
        self.lm_head = nn.Linear(cfg.hidden_size, cfg.vocab_size)
```

“self.mlp” is defined locally