🛰 SATELLITE UNIT — COSMOS

ID:

obs-sat-cosmos

Role: Deep-Orbit Strategic Relay / Long-Range Signal Projection

Tier: Satellite

Status: Active

⚫ PHYSICAL & TECHNICAL

Length: 14 m
Width: 8 m
Height: 5 m
Mass: 10,200 kg
Power Source: Expanded solar array + dual micro-reactor backups
Energy Capacity: 55,000 Wh
Fuel Capacity: 120 L (orbital correction thrusters)
Endurance: 8–12 years
Payload Capacity: Internal systems only
Modules:

- Deep-orbit relay dish
- Long-range signal amplifier
- Stabilization gyros
- Micro-thruster array

Navigation System: Orbital AI + star tracker
Structural Integrity: 2,200 HP
Armor Rating: 0.60
Heat Signature: Very Low
Noise Signature: None
Top Speed: Orbital velocity
Stability Rating: Maximum

⚫ AUTONOMY & AI BEHAVIOR

Behavior Profile: Long-range relay / deep-orbit stabilization
Aggression: 0.0

Caution: 1.0
Persistence: 1.0
Retreat Threshold: N/A
Target Priority: None
Formation Discipline: Maximum
Risk Tolerance: Very Low

Sensors

Optical Range: Global
Thermal Range: Medium
Radar Range: Medium
Signal Detection Range: Extremely High

Communication

Mesh Range: Global
Relay Capacity: 10
Command Link Type: Satellite Mesh
Network Priority: Maximum

● COMBAT & THREAT MODEL

Firepower Rating: None
Weapon Mounts: None
Tracking Strength: Medium
Disruption Strength: High
Countermeasure Rating: Medium

Threat Modeling

Threat Level: 7
Preferred Terrain: Deep orbit
Vulnerability Profile: Debris / EMP / solar storms

● SQUAD & COMMAND INTEGRATION

Squad Role: Strategic Long-Range Relay
Squad Size Contribution: 5
Formation Behavior: Orbital spacing
Intent Interpretation Rules: Maintain long-range communications coverage
Retreat Behavior: None
Reinforcement Behavior: Supports all grids

Command Hierarchy

Parent Command Unit: Nexus / Fusion
Subordinate Units: None
Relay Nodes: 10
Network Dependencies: Satellite Mesh

⬤ VR OPERATOR MODE

Operator Seat Type: Deep-Orbit Relay Console
Operator HUD: Long-Range Signal Overlay
Camera Feeds: Optical + thermal
Tactical Overlay: Relay routes / signal load / mesh health

Operator Controls

Relay routing
Signal amplification
Thermal view
Orbital diagnostics

Operator Abilities

Long-Range Boost
Mesh Stabilization
Signal Sync
Thermal Sweep

⬤ ECONOMY & LOGISTICS

Build Cost: 2,000 Metal / 1,300 Electronics
Build Time: 260 sec
Factory Type: Satellite Bay
Tech Requirements: Satellite Systems II
Maintenance Cost: Low
Repair Time: 60 sec
Supply Consumption: Very Low
Operational Cost: Very Low
Deployment Requirements: Launch pad
Transport Compatibility: Satellite carrier
Launch Method: Orbital insertion

🔧 BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

110× **Satellite Alloy Plates**
55× **Reinforced Satellite Rods**
10× **Hydraulic Actuators**
1× **Deep-Orbit Relay Assembly**

Electronics

44× **Circuit Bundles**
30× **Signal Processors**
10× **Satellite Control Chips**
4× **Relay AI Chips**

Power

1× **Expanded Solar Array Assembly**
2× **Micro-Reactor Cores**
3× **Power Regulation Nodes**

Rare / Tradeable

1× **Long-Range Amplifier Module**

Optional Upgrades

Enhanced Relay Dish
Thermal Boost
Anti-Jamming Shielding