



AIR UNIT #23 — SPOTTER

ID:

obs-air-spotter

Role: Target Identification / Precision Marking

Tier: Recon Support

Status: Active



PHYSICAL & TECHNICAL

Length: 1.8 m

Width: 1.3 m

Height: 0.7 m

Mass: 12 kg

Power Source: Compact battery

Energy Capacity: 1400 Wh

Energy Consumption: 30 Wh/min

Endurance: 35–50 min

Payload Capacity: 0.8 kg

Modules: Precision marker beam

Navigation System: GPS + Targeting AI

Structural Integrity: 90 HP

Armor Rating: 0.10

Heat Signature: Low

Noise Signature: Very Low

Top Speed: 22 m/s

Acceleration: High

Turning Radius: Tight

Climb Rate: Medium

Stability Rating: High



AUTONOMY & AI BEHAVIOR

Behavior Profile: Target Identification / Recon Support

Aggression: 0.1

Caution: 0.85

Persistence: 0.7

Flanking Likelihood: 0.1

Retreat Threshold: 0.85

Target Priority: High-value targets / moving targets

Formation Discipline: Medium

Risk Tolerance: Low

Sensors

Visual Range: 1600 m

Thermal Range: 600 m

Acoustic Range: Medium

Radar Range: None

LiDAR Range: Short-range

Signal Detection Range: Medium

Communication

Mesh Range: 5 km

Relay Capacity: 0

Command Link Type: Recon Grid

Network Priority: Medium

COMBAT & THREAT MODEL

Firepower Rating: Low (marker beam only)

Accuracy: High

Stabilization: High

Weapon Mounts: 1 (marker beam)

Weapon Types: Target marker beam

Suppression Value: Low

Tracking Strength: High

Disruption Strength: Low

Breach Capability: None

Countermeasure Rating: Low

Threat Modeling

Threat Level: 2

Engagement Distance: 200–400 m

Preferred Terrain: Recon corridors

Preferred Targets: High-value targets

Vulnerability Profile: Ballistic / weather

SQUAD & COMMAND INTEGRATION

Squad Role: Target Spotting

Squad Size Contribution: 1

Formation Behavior: Recon spacing

Intent Interpretation Rules: Maintain visibility, avoid conflict

Retreat Behavior: Early

Breach Behavior: None

Flanking Behavior: Minimal

Reinforcement Behavior: Supports recon and command squads

Command Hierarchy

Parent Command Unit: Overseer / Insight

Subordinate Units: None

Relay Nodes: None

Network Dependencies: Recon Grid

VR OPERATOR MODE

Operator Seat Type: Drone View

Operator HUD: Targeting Overlay

Camera Feeds: Optical

Thermal View: Yes

LiDAR View: Yes (short-range)

Sonar View: No

Tactical Overlay: Target markers / lock indicators

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Thermal / LiDAR / zoom

Ability Controls: Mark Target, Scan, Stabilize

Weapon Controls: Marker beam

Stabilization Controls: Auto-hover

Operator Abilities

Precision Target Mark

Recon Scan

Thermal Search

Stabilize

Relay Target Data

ECONOMY & LOGISTICS

Build Cost: 70 Metal / 60 Electronics

Build Time: 25 sec

Factory Type: Drone Bay

Tech Requirements: Recon Systems I

Maintenance Cost: Low

Repair Time: 8 sec

Supply Consumption: Low

Operational Cost: Minimal

Deployment Requirements: Standard drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

8× **Light Alloy Plates**

6× **Composite Frame Rods**

3× **Micro-Servo Actuators**

1× **Stabilizer Fin**

1× **Marker Beam Housing**

Electronics

8× **Circuit Bundles**

6× **Signal Processors**

2× **Drone Control Chips**

2× **Targeting AI Chips**

Power

1× **Compact Battery Pack**

1× **Power Regulation Node**

Rare / Tradeable

1× **Precision Marker Core**

Optional Upgrades

Silent Rotor Kit

Thermal Boost Module

Extended Battery Pack