



AIR UNIT #6 — SCOUT EYE

ID:

obs-air-scouteye

Role: Lightweight Recon / Rapid Visual Scan

Tier: Basic

Status: Active



PHYSICAL & TECHNICAL

Length: 1.2 m

Width: 0.9 m

Height: 0.5 m

Mass: 10 kg

Power Source: Compact battery

Energy Capacity: 1200 Wh

Energy Consumption: 25 Wh/min

Endurance: 25–40 min

Payload Capacity: 0.8 kg

Modules: Micro-camera array

Navigation System: GPS + Basic Stabilization

Structural Integrity: 80 HP

Armor Rating: 0.10

Heat Signature: Very Low

Noise Signature: Very Low

Top Speed: 20 m/s

Acceleration: High

Turning Radius: Very Tight

Climb Rate: Medium

Stability Rating: Medium



AUTONOMY & AI BEHAVIOR

Behavior Profile: Light Recon

Aggression: 0.0

Caution: 0.9

Persistence: 0.5

Flanking Likelihood: 0.0

Retreat Threshold: 0.8

Target Priority: Recon targets

Formation Discipline: Medium

Risk Tolerance: Very Low

Sensors

Visual Range: 1200 m

Thermal Range: 400 m

Acoustic Range: Low

Radar Range: None

LiDAR Range: None

Signal Detection Range: Low

Communication

Mesh Range: 4 km

Relay Capacity: 0

Command Link Type: Standard

Network Priority: Low

COMBAT & THREAT MODEL

Firepower Rating: 0

Accuracy: N/A

Stabilization: Medium

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: Low

Disruption Strength: Low

Breach Capability: None

Countermeasure Rating: Low

Threat Modeling

Threat Level: 1

Engagement Distance: N/A

Preferred Terrain: Low-risk airspace

Preferred Targets: None

Vulnerability Profile: Ballistic / weather

SQUAD & COMMAND INTEGRATION

Squad Role: Recon

Squad Size Contribution: 1

Formation Behavior: Loose recon spacing

Intent Interpretation Rules: Avoid threats, prioritize visibility

Retreat Behavior: Early

Breach Behavior: None

Flanking Behavior: None

Reinforcement Behavior: Supports recon squads

Command Hierarchy

Parent Command Unit: Sentinel / Overseer

Subordinate Units: None

Relay Nodes: None

Network Dependencies: Standard Warden mesh

VR OPERATOR MODE

Operator Seat Type: Drone View

Operator HUD: Minimal Recon Overlay

Camera Feeds: Optical

Thermal View: Yes (low-resolution)

LiDAR View: No

Sonar View: No

Tactical Overlay: Basic recon markers

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Zoom / thermal

Ability Controls: Scan, Mark Target

Weapon Controls: None

Stabilization Controls: Auto-hover

Operator Abilities

Quick Scan

Mark Target

Relay Recon Data

ECONOMY & LOGISTICS

Build Cost: 60 Metal / 40 Electronics

Build Time: 25 sec

Factory Type: Drone Bay

Tech Requirements: Basic Recon

Maintenance Cost: Very Low

Repair Time: 8 sec

Supply Consumption: Very Low

Operational Cost: Minimal

Deployment Requirements: Standard drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff



BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

8× Light Alloy Plates

4× Composite Frame Rods

4× Micro-Servo Actuators

2× Stabilizer Fins

1× Micro-Camera Housing

Electronics

6× Circuit Bundles

4× Signal Processors

2× Drone Control Chips

Power

1× Compact Battery Pack

1× Power Regulation Node

Rare / Tradeable

1× **Miniature Lens Assembly**

Optional Upgrades

Silent Rotor Kit

Thermal Boost Module

Extended Battery Pack