



GROUND UNIT — HAMMER

ID:

obs-ground-hammer

Role: Heavy Breach / Structural Breaker

Tier: Assault Engineering

Status: Active

● PHYSICAL & TECHNICAL

Length: 4.9 m

Width: 2.4 m

Height: 2.1 m

Mass: 1,800 kg

Power Source: Industrial diesel-electric hybrid

Energy Capacity: 7200 Wh

Fuel Capacity: 90 L

Endurance: 4–7 hours

Payload Capacity: 400 kg

Modules: Hydraulic breach ram + reinforced chassis

Navigation System: GPS + Breach AI

Structural Integrity: 1,300 HP

Armor Rating: 0.75

Heat Signature: High

Noise Signature: High

Top Speed: 10 m/s

Acceleration: Low

Turning Radius: Tight

Stability Rating: Maximum

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Breach / Structural Assault

Aggression: 0.6

Caution: 0.5

Persistence: 1.0

Flanking Likelihood: 0.0

Retreat Threshold: 0.4

Target Priority: Barriers / fortifications / hardened structures

Formation Discipline: High

Risk Tolerance: High

Sensors

Visual Range: 1200 m

Thermal Range: 500 m

Acoustic Range: Medium

Radar Range: None

LiDAR Range: Medium

Signal Detection Range: Short

Communication

Mesh Range: 4 km

Relay Capacity: 0

Command Link Type: Engineering Grid

Network Priority: Medium

● **COMBAT & THREAT MODEL**

Firepower Rating: Low (ram only)

Weapon Mounts: None

Weapon Types: Hydraulic breach ram

Accuracy: N/A

Suppression Value: Low

Tracking Strength: None

Disruption Strength: High

Breach Capability: Very High

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 6

Engagement Distance: Contact

Preferred Terrain: Fortified zones / breach points

Preferred Targets: Walls, gates, bunkers

Vulnerability Profile: Ballistic / explosives

● **SQUAD & COMMAND INTEGRATION**

Squad Role: Breach / Assault Engineering

Squad Size Contribution: 3

Formation Behavior: Front-line breach spacing

Intent Interpretation Rules: Break fortifications

Retreat Behavior: Late

Breach Behavior: Primary

Flanking Behavior: None

Reinforcement Behavior: Supports assault squads

Command Hierarchy

Parent Command Unit: Command Core / Fusion

Subordinate Units: Mule, Forge

Relay Nodes: None

Network Dependencies: Engineering Grid

● **VR OPERATOR MODE**

Operator Seat Type: Heavy Engineering Cockpit

Operator HUD: Breach Overlay

Camera Feeds: Optical + ram cam

Thermal View: Yes

LiDAR View: Yes

Tactical Overlay: Structural integrity map

Operator Controls

Movement Controls: Heavy vehicle drive

Tool Controls: Ram charge / impact / retract

Sensor Controls: Thermal / LiDAR / zoom

Ability Controls: Breach Mode, Stabilize, Structural Scan

Operator Abilities

Hydraulic Ram Charge

Structural Weak-Point Scan

Breach Execution

Reinforced Stance

● **ECONOMY & LOGISTICS**

Build Cost: 900 Metal / 450 Electronics

Build Time: 160 sec

Factory Type: Vehicle Bay

Tech Requirements: Engineering Systems II

Maintenance Cost: High

Repair Time: 40 sec

Supply Consumption: High

Operational Cost: High

Deployment Requirements: Heavy vehicle pad

Transport Compatibility: Heavy racks

Launch Method: Drive-out

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

60× Heavy Alloy Plates

30× Reinforced Frame Rods

10× Hydraulic Actuators

6× Armor Panels

1× Breach Ram Housing

Electronics

28× Circuit Bundles

18× Signal Processors

6× Vehicle Control Chips

4× Engineering AI Chips

Power

1× Industrial Hybrid Engine Core

3× Power Regulation Nodes

Rare / Tradeable

1× Hydraulic Ram Core

Optional Upgrades

Reinforced Ram

Shock-Dampened Chassis

Extended Fuel Tank

Anti-Jamming Shielding