



(8 m × 6 m × 4 m)

Let's build it.

COMMAND UNIT — PULSE

ID:

obs-command-pulse

Role: Tactical Signal Hub / Real-Time Mesh Stabilizer

Tier: Command

Status: Active

PHYSICAL & TECHNICAL

Length: 8 m

Width: 6 m

Height: 4 m

Mass: 12,000 kg

Power Source: Dual tactical-grade reactors

Energy Capacity: 90,000 Wh

Fuel Capacity: N/A (reactor-based)

Endurance: Continuous

Payload Capacity: Internal systems only

Modules:

- Tactical signal chamber
- Mesh stabilization lattice
- Multi-node relay interface
- Redundant cooling towers

Navigation System: Stationary (anchored command node)

Structural Integrity: 3,000 HP

Armor Rating: 1.00

Heat Signature: Low

Noise Signature: Low

Top Speed: N/A

Stability Rating: Maximum

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Tactical signal routing / mesh stabilization

Aggression: 0.0

Caution: 1.0

Persistence: 1.0

Retreat Threshold: N/A

Target Priority: None (non-combat)

Formation Discipline: Maximum

Risk Tolerance: Very Low

Sensors

Visual Range: Short

Thermal Range: Short

Acoustic Range: Short

Radar Range: Medium

Signal Detection Range: Very High

Communication

Mesh Range: Global

Relay Capacity: 6

Command Link Type: Strategic Command Mesh

Network Priority: Maximum

● COMBAT & THREAT MODEL

Firepower Rating: None

Weapon Mounts: None

Tracking Strength: Very High (tactical signal intelligence)

Disruption Strength: High

Countermeasure Rating: Very High

Threat Modeling

Threat Level: 5

Preferred Terrain: Secure command zones

Vulnerability Profile: EMP / sabotage

● SQUAD & COMMAND INTEGRATION

Squad Role: Tactical Mesh Stabilizer

Squad Size Contribution: 5

Formation Behavior: Central anchor

Intent Interpretation Rules: Maintain mesh stability and tactical routing

Retreat Behavior: None

Reinforcement Behavior: Supports all units

Command Hierarchy

Parent Command Unit: Insight / Nexus

Subordinate Units: None

Relay Nodes: 6

Network Dependencies: Strategic Command Mesh

● **VR OPERATOR MODE**

Operator Seat Type: Tactical Signal Console

Operator HUD: Mesh Stability Overlay

Camera Feeds: Internal systems only

Thermal View: Yes

Tactical Overlay: Mesh health / routing paths / signal load

Operator Controls

Mesh routing

Stabilization lattice control

Tactical diagnostics

Signal balancing

Operator Abilities

Mesh Pulse

Stabilization Burst

Tactical Sync

Encryption Surge

● **ECONOMY & LOGISTICS**

Build Cost: 1,800 Metal / 1,000 Electronics

Build Time: 200 sec

Factory Type: Command Foundry

Tech Requirements: Command Systems I

Maintenance Cost: Medium

Repair Time: 60 sec

Supply Consumption: Medium

Operational Cost: Medium

Deployment Requirements: Command zone

Transport Compatibility: Heavy command carriers

Launch Method: Anchor-install

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

100× **Command Alloy Plates**

50× **Reinforced Command Rods**

8× **Hydraulic Actuators**

3× **Armor Panels**

1× **Signal Chamber Assembly**

Electronics

36× **Circuit Bundles**

24× **Signal Processors**

8× **Command Control Chips**

3× **Command AI Chips**

Power

1× **Tactical Reactor Core**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **Mesh Stabilization Lattice**

Optional Upgrades

Quantum Encryption

Reinforced Hull

Anti-Jamming Shielding