

★ ASTRAL

(12 m × 7 m × 4 m)

✱ SATELLITE UNIT — ASTRAL

ID:

obs-sat-astral

Role: High-Resolution Recon / Deep-Scan Imaging

Tier: Satellite

Status: Active

● PHYSICAL & TECHNICAL

Length: 12 m

Width: 7 m

Height: 4 m

Mass: 8,400 kg

Power Source: Expanded solar array + micro-reactor backup

Energy Capacity: 40,000 Wh

Fuel Capacity: 100 L (orbital correction thrusters)

Endurance: 6–10 years

Payload Capacity: Internal systems only

Modules:

High-resolution imaging suite

Deep-scan thermal array

Stabilization gyros

Micro-thruster array

Navigation System: Orbital AI + star tracker

Structural Integrity: 1,800 HP

Armor Rating: 0.55

Heat Signature: Very Low

Noise Signature: None

Top Speed: Orbital velocity

Stability Rating: Maximum

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Recon / deep-scan imaging / orbital stabilization

Aggression: 0.0

Caution: 1.0

Persistence: 1.0

Retreat Threshold: N/A

Target Priority: None (non-combat)

Formation Discipline: Maximum

Risk Tolerance: Very Low

Sensors

Optical Range: Global (high-resolution)

Thermal Range: High

Radar Range: Medium

Signal Detection Range: High

Communication

Mesh Range: Global

Relay Capacity: 6

Command Link Type: Satellite Mesh

Network Priority: High

● COMBAT & THREAT MODEL

Firepower Rating: None

Weapon Mounts: None

Tracking Strength: Very High (optical + thermal)

Disruption Strength: Medium

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 6

Preferred Terrain: High orbit

Vulnerability Profile: Debris / EMP / solar storms

● SQUAD & COMMAND INTEGRATION

Squad Role: High-Resolution Recon

Squad Size Contribution: 4

Formation Behavior: Orbital spacing

Intent Interpretation Rules: Maintain deep-scan recon coverage

Retreat Behavior: None

Reinforcement Behavior: Supports all grids

Command Hierarchy

Parent Command Unit: Insight / Worldmap

Subordinate Units: None

Relay Nodes: 6

Network Dependencies: Satellite Mesh

● **VR OPERATOR MODE**

Operator Seat Type: Deep-Scan Recon Console

Operator HUD: High-Resolution Recon Overlay

Camera Feeds: Optical + thermal

Tactical Overlay: Recon grid / deep-scan markers

Operator Controls

Recon optics

Deep-scan thermal

Signal relay

Orbital diagnostics

Operator Abilities

Deep-Scan Sweep

Thermal Pulse

Relay Boost

Stabilization Burst

● **ECONOMY & LOGISTICS**

Build Cost: 1,800 Metal / 1,200 Electronics

Build Time: 240 sec

Factory Type: Satellite Bay

Tech Requirements: Satellite Systems II

Maintenance Cost: Low

Repair Time: 55 sec

Supply Consumption: Very Low

Operational Cost: Very Low

Deployment Requirements: Launch pad

Transport Compatibility: Satellite carrier

Launch Method: Orbital insertion

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

90× **Satellite Alloy Plates**

45× **Reinforced Satellite Rods**

8× **Hydraulic Actuators**

1× **Imaging Suite Assembly**

Electronics

40× **Circuit Bundles**

28× **Signal Processors**

8× **Satellite Control Chips**

4× **Recon AI Chips**

Power

1× **Expanded Solar Array Assembly**

1× **Micro-Reactor Core**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **Deep-Scan Thermal Module**

Optional Upgrades

Enhanced Optics

Thermal Boost

Anti-Jamming Shielding