



AIR UNIT #14 — NIGHTGUARD

ID:

obs-air-nightguard

Role: Night Surveillance / Thermal Recon

Tier: Advanced Recon

Status: Active



PHYSICAL & TECHNICAL

Length: 2.6 m

Width: 2.0 m

Height: 0.9 m

Mass: 22 kg

Power Source: High-density battery

Energy Capacity: 2400 Wh

Energy Consumption: 50 Wh/min

Endurance: 35–55 min

Payload Capacity: 1.5 kg

Modules: Thermal imaging suite

Navigation System: GPS + Night-Ops AI

Structural Integrity: 130 HP

Armor Rating: 0.18

Heat Signature: Very Low

Noise Signature: Very Low

Top Speed: 21 m/s

Acceleration: Medium

Turning Radius: Tight

Climb Rate: Medium

Stability Rating: Very High (night hover stability)



AUTONOMY & AI BEHAVIOR

Behavior Profile: Night Surveillance / Thermal Recon

Aggression: 0.1

Caution: 0.9

Persistence: 0.8

Flanking Likelihood: 0.1

Retreat Threshold: 0.75

Target Priority: Heat signatures / movement

Formation Discipline: High

Risk Tolerance: Low

Sensors

Visual Range: 1200 m

Thermal Range: 1800 m (very high)

Acoustic Range: Medium

Radar Range: None

LiDAR Range: Short-range

Signal Detection Range: Medium

Communication

Mesh Range: 6 km

Relay Capacity: 0

Command Link Type: Night-Ops Grid

Network Priority: High

COMBAT & THREAT MODEL

Firepower Rating: 0

Accuracy: N/A

Stabilization: Very High

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: High

Disruption Strength: Low

Breach Capability: None

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 3

Engagement Distance: N/A

Preferred Terrain: Low-light airspace

Preferred Targets: Heat signatures / moving targets

Vulnerability Profile: Ballistic / weather / jamming

SQUAD & COMMAND INTEGRATION

Squad Role: Night Surveillance

Squad Size Contribution: 1

Formation Behavior: Night-ops spacing

Intent Interpretation Rules: Maintain thermal lock, avoid conflict

Retreat Behavior: Medium

Breach Behavior: None

Flanking Behavior: Minimal

Reinforcement Behavior: Supports recon and security squads

Command Hierarchy

Parent Command Unit: Overseer / Insight

Subordinate Units: None

Relay Nodes: None

Network Dependencies: Night-Ops Grid

VR OPERATOR MODE

Operator Seat Type: Drone View

Operator HUD: Night-Ops Thermal Overlay

Camera Feeds: Optical

Thermal View: Yes (high-resolution)

LiDAR View: Yes (short-range)

Sonar View: No

Tactical Overlay: Thermal markers / movement indicators

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Thermal / zoom / LiDAR

Ability Controls: Thermal Lock, Scan, Stabilize

Weapon Controls: None

Stabilization Controls: Auto-hover

Operator Abilities

Thermal Lock

Night Scan

LiDAR Sweep

Stabilize

Relay Thermal Data

ECONOMY & LOGISTICS

Build Cost: 180 Metal / 170 Electronics

Build Time: 55 sec

Factory Type: Drone Bay

Tech Requirements: Night-Ops Systems I

Maintenance Cost: Medium

Repair Time: 14 sec

Supply Consumption: Medium

Operational Cost: Moderate

Deployment Requirements: Standard drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

14× **Medium Alloy Plates**

10× **Composite Frame Rods**

6× **Micro-Servo Actuators**

3× **Stabilizer Fins**

1× **Thermal Sensor Housing**

Electronics

14× **Circuit Bundles**

10× **Signal Processors**

4× **Drone Control Chips**

3× **Thermal AI Chips**

Power

1× **High-Density Battery Pack**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **High-Resolution Thermal Core**

1× **Night-Ops Microprocessor**

Optional Upgrades

Ultra-Thermal Lens

Anti-Jamming Shielding

Silent Rotor Kit

Extended Battery Module