



AIR UNIT #4 — IRIS

ID:

obs-air-iris

Role: High-Resolution Imaging / Target Tracking

Tier: Advanced

Status: Active



PHYSICAL & TECHNICAL

Length: 2.5 m

Width: 2.0 m

Height: 0.9 m

Mass: 22 kg

Power Source: High-density battery

Energy Capacity: 2400 Wh

Energy Consumption: 50 Wh/min

Endurance: 35–55 min

Payload Capacity: 2.0 kg

Modules: HD optical sensor

Navigation System: GPS + Optical AI

Structural Integrity: 130 HP

Armor Rating: 0.18

Heat Signature: Low

Noise Signature: Low

Top Speed: 24 m/s

Acceleration: Medium

Turning Radius: Tight

Climb Rate: High

Stability Rating: Very High (precision imaging)



AUTONOMY & AI BEHAVIOR

Behavior Profile: Imaging / Target Tracking

Aggression: 0.2

Caution: 0.7

Persistence: 0.8

Flanking Likelihood: 0.1

Retreat Threshold: 0.6

Target Priority: High-value targets

Formation Discipline: High

Risk Tolerance: Low

Sensors

Visual Range: 2200 m

Thermal Range: 1200 m

Acoustic Range: Low

Radar Range: None

LiDAR Range: None

Signal Detection Range: Medium

Communication

Mesh Range: 6 km

Relay Capacity: 0

Command Link Type: Standard

Network Priority: Medium

COMBAT & THREAT MODEL

Firepower Rating: 0

Accuracy: N/A

Stabilization: Very High

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: Very High

Disruption Strength: Low

Breach Capability: None

Countermeasure Rating: Low

Threat Modeling

Threat Level: 3

Engagement Distance: N/A

Preferred Terrain: High-visibility airspace

Preferred Targets: High-value targets / moving targets

Vulnerability Profile: Ballistic / weather / jamming

SQUAD & COMMAND INTEGRATION

Squad Role: Optical Intelligence

Squad Size Contribution: 1

Formation Behavior: High-precision spacing

Intent Interpretation Rules: Maintain optimal imaging distance

Retreat Behavior: Medium

Breach Behavior: None

Flanking Behavior: Minimal

Reinforcement Behavior: Supports recon and targeting squads

Command Hierarchy

Parent Command Unit: Overseer / Insight

Subordinate Units: None

Relay Nodes: None

Network Dependencies: Standard Warden mesh

VR OPERATOR MODE

Operator Seat Type: Drone View

Operator HUD: High-Resolution Imaging Suite

Camera Feeds: HD Optical

Thermal View: Yes

LiDAR View: No

Sonar View: No

Tactical Overlay: Target tracking overlay

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Zoom / thermal / tracking / focus

Ability Controls: Scan, Mark Target, Track Target

Weapon Controls: None

Stabilization Controls: Auto-hover, auto-level

Operator Abilities

High-Res Scan

Target Lock

Mark Target

Stabilize

Relay Imaging Data

ECONOMY & LOGISTICS

Build Cost: 180 Metal / 160 Electronics

Build Time: 55 sec

Factory Type: Drone Bay

Tech Requirements: Advanced Imaging I

Maintenance Cost: Medium

Repair Time: 14 sec

Supply Consumption: Medium

Operational Cost: Moderate

Deployment Requirements: Standard drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

14× **Medium Alloy Plates**

10× **Composite Frame Rods**

6× **Micro-Servo Actuators**

4× **Stabilizer Fins**

Electronics

14× **Circuit Bundles**

10× **Signal Processors**

6× **Drone Control Chips**

2× **Optical AI Chips**

Power

1× **High-Density Battery Pack**

3× **Power Regulation Nodes**

Rare / Tradeable

1× **HD Optical Sensor Core**

1× **Precision Lens Assembly**

1× **Target-Tracking Microprocessor**

Optional Upgrades

Ultra-Zoom Lens

Thermal Enhancement Module

Silent Rotor Kit

Anti-Jamming Shielding