



AIR UNIT #11 — LOCATOR

ID:

obs-air-locator

Role: Target Location / Signal Tracking

Tier: Advanced Recon

Status: Active



PHYSICAL & TECHNICAL

Length: 2.3 m

Width: 1.7 m

Height: 0.8 m

Mass: 18 kg

Power Source: High-efficiency battery

Energy Capacity: 2000 Wh

Energy Consumption: 40 Wh/min

Endurance: 35–50 min

Payload Capacity: 1.5 kg

Modules: Tracking sensor array

Navigation System: GPS + Tracking AI

Structural Integrity: 120 HP

Armor Rating: 0.15

Heat Signature: Low

Noise Signature: Low

Top Speed: 22 m/s

Acceleration: Medium

Turning Radius: Tight

Climb Rate: Medium

Stability Rating: High



AUTONOMY & AI BEHAVIOR

Behavior Profile: Tracking / Recon

Aggression: 0.1

Caution: 0.8

Persistence: 0.9

Flanking Likelihood: 0.1

Retreat Threshold: 0.7

Target Priority: Moving targets / signal sources

Formation Discipline: High

Risk Tolerance: Low

Sensors

Visual Range: 1600 m

Thermal Range: 900 m

Acoustic Range: Medium

Radar Range: None

LiDAR Range: Short-range

Signal Detection Range: Very High

Communication

Mesh Range: 6 km

Relay Capacity: 0

Command Link Type: Tracking Grid

Network Priority: High



COMBAT & THREAT MODEL

Firepower Rating: 0

Accuracy: N/A

Stabilization: High

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: High

Disruption Strength: Medium

Breach Capability: None

Countermeasure Rating: Low

Threat Modeling

Threat Level: 3

Engagement Distance: N/A

Preferred Terrain: Recon corridors

Preferred Targets: Moving targets / signal sources

Vulnerability Profile: Ballistic / weather / jamming

SQUAD & COMMAND INTEGRATION

Squad Role: Target Location

Squad Size Contribution: 1

Formation Behavior: Tracking-optimized spacing

Intent Interpretation Rules: Maintain lock, avoid conflict

Retreat Behavior: Medium

Breach Behavior: None

Flanking Behavior: Minimal

Reinforcement Behavior: Supports recon and targeting squads

Command Hierarchy

Parent Command Unit: Overseer / Insight

Subordinate Units: None

Relay Nodes: None

Network Dependencies: Tracking Grid

VR OPERATOR MODE

Operator Seat Type: Drone View

Operator HUD: Tracking Overlay

Camera Feeds: Optical

Thermal View: Yes

LiDAR View: Yes (short-range)

Sonar View: No

Tactical Overlay: Target lock indicators

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Thermal / tracking / zoom

Ability Controls: Lock Target, Scan, Stabilize

Weapon Controls: None

Stabilization Controls: Auto-hover

Operator Abilities

Target Lock

Signal Scan

Thermal Search

Stabilize

Relay Tracking Data



ECONOMY & LOGISTICS

Build Cost: 170 Metal / 150 Electronics

Build Time: 55 sec

Factory Type: Drone Bay

Tech Requirements: Tracking Systems I

Maintenance Cost: Medium

Repair Time: 14 sec

Supply Consumption: Medium

Operational Cost: Moderate

Deployment Requirements: Standard drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff



BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

14× Light Alloy Plates

10× Composite Frame Rods

6× Micro-Servo Actuators

3× Stabilizer Fins

1× Tracking Sensor Housing

Electronics

12× Circuit Bundles

8× Signal Processors

4× Drone Control Chips

3× Tracking AI Chips

Power

1× **High-Efficiency Battery Pack**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **Advanced Tracking Core**

1× **Signal Amplification Processor**

Optional Upgrades

Extended Tracking Range Module

Thermal Boost Lens

Anti-Jamming Shielding

Silent Rotor Kit