



AIR UNIT #13 — MESH

ID:

obs-air-mesh

Role: High-Capacity Mesh Relay / Network Backbone

Tier: Advanced Support

Status: Active



PHYSICAL & TECHNICAL

Length: 2.4 m

Width: 1.8 m

Height: 0.9 m

Mass: 20 kg

Power Source: High-efficiency battery

Energy Capacity: 2000 Wh

Energy Consumption: 45 Wh/min

Endurance: 35–55 min

Payload Capacity: 1.0 kg

Modules: Multi-antenna mesh array

Navigation System: GPS + Mesh Optimization AI

Structural Integrity: 115 HP

Armor Rating: 0.15

Heat Signature: Low

Noise Signature: Low

Top Speed: 19 m/s

Acceleration: Medium

Turning Radius: Tight

Climb Rate: Medium

Stability Rating: High



AUTONOMY & AI BEHAVIOR

Behavior Profile: Mesh Relay / Network Backbone

Aggression: 0.0

Caution: 0.9

Persistence: 0.9

Flanking Likelihood: 0.0

Retreat Threshold: 0.85

Target Priority: Network gaps / weak mesh zones

Formation Discipline: Very High

Risk Tolerance: Very Low

Sensors

Visual Range: 900 m

Thermal Range: 400 m

Acoustic Range: Low

Radar Range: None

LiDAR Range: None

Signal Detection Range: Very High

Communication

Mesh Range: 18 km

Relay Capacity: 12 nodes

Command Link Type: Mesh-Optimized

Network Priority: Very High



COMBAT & THREAT MODEL

Firepower Rating: 0

Accuracy: N/A

Stabilization: High

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: Low

Disruption Strength: Medium

Breach Capability: None

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 2

Engagement Distance: N/A

Preferred Terrain: High-altitude mesh corridors

Preferred Targets: None

Vulnerability Profile: Ballistic / EMP / jamming

SQUAD & COMMAND INTEGRATION

Squad Role: Mesh Relay

Squad Size Contribution: 1

Formation Behavior: High-discipline mesh spacing

Intent Interpretation Rules: Maintain coverage, avoid conflict

Retreat Behavior: Early

Breach Behavior: None

Flanking Behavior: None

Reinforcement Behavior: Supports communication and command squads

Command Hierarchy

Parent Command Unit: NexusGrid / Overseer

Subordinate Units: None

Relay Nodes: 12

Network Dependencies: Warden mesh grid

VR OPERATOR MODE

Operator Seat Type: Drone View

Operator HUD: Mesh Relay Overlay

Camera Feeds: Optical

Thermal View: Yes

LiDAR View: No

Sonar View: No

Tactical Overlay: Mesh coverage visualization

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Signal scan / relay diagnostics

Ability Controls: Deploy Relay, Boost Signal, Mesh Stabilize

Weapon Controls: None

Stabilization Controls: Auto-hover

Operator Abilities

Deploy Relay Node

Boost Signal

Mesh Stabilization

Network Scan

Relay Diagnostics

ECONOMY & LOGISTICS

Build Cost: 160 Metal / 160 Electronics

Build Time: 55 sec

Factory Type: Drone Bay

Tech Requirements: Mesh Networking II

Maintenance Cost: Low

Repair Time: 12 sec

Supply Consumption: Low

Operational Cost: Minimal

Deployment Requirements: Standard drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

12× **Light Alloy Plates**

8× **Composite Frame Rods**

6× **Micro-Servo Actuators**

2× **Stabilizer Fins**

1× **Mesh Antenna Housing**

Electronics

14× **Circuit Bundles**

10× **Signal Processors**

4× **Drone Control Chips**

4× **Mesh Routing Chips**

Power

1× **High-Efficiency Battery Pack**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **High-Grade Mesh Antenna Array**

1× **Encrypted Mesh Core**

Optional Upgrades

Extended Mesh Range Module

Signal Boost Amplifier

Anti-Jamming Shielding

Silent Rotor Kit