



AIR UNIT #18 — RELAY

ID:

obs-air-relay

Role: Tactical Signal Relay / Battlefield Communications

Tier: Operational Support

Status: Active



PHYSICAL & TECHNICAL

Length: 2.1 m

Width: 1.6 m

Height: 0.8 m

Mass: 16 kg

Power Source: High-efficiency battery

Energy Capacity: 1800 Wh

Energy Consumption: 35 Wh/min

Endurance: 40–60 min

Payload Capacity: 1.0 kg

Modules: Tactical relay antenna

Navigation System: GPS + Signal Routing AI

Structural Integrity: 110 HP

Armor Rating: 0.14

Heat Signature: Low

Noise Signature: Low

Top Speed: 18 m/s

Acceleration: Medium

Turning Radius: Tight

Climb Rate: Medium

Stability Rating: High



AUTONOMY & AI BEHAVIOR

Behavior Profile: Tactical Communications / Relay

Aggression: 0.0

Caution: 0.85

Persistence: 0.8

Flanking Likelihood: 0.0

Retreat Threshold: 0.8

Target Priority: Signal gaps / comms dead zones

Formation Discipline: High

Risk Tolerance: Low

Sensors

Visual Range: 900 m

Thermal Range: 400 m

Acoustic Range: Low

Radar Range: None

LiDAR Range: None

Signal Detection Range: High

Communication

Mesh Range: 12 km

Relay Capacity: 8 nodes

Command Link Type: Tactical Grid

Network Priority: High

COMBAT & THREAT MODEL

Firepower Rating: 0

Accuracy: N/A

Stabilization: High

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: Low

Disruption Strength: Medium

Breach Capability: None

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 2

Engagement Distance: N/A

Preferred Terrain: Mid-altitude comms corridors

Preferred Targets: None

Vulnerability Profile: Ballistic / EMP / jamming

SQUAD & COMMAND INTEGRATION

Squad Role: Tactical Relay

Squad Size Contribution: 1

Formation Behavior: Relay-optimized spacing

Intent Interpretation Rules: Maintain coverage, avoid conflict

Retreat Behavior: Early

Breach Behavior: None

Flanking Behavior: None

Reinforcement Behavior: Supports mesh, command, and recon squads

Command Hierarchy

Parent Command Unit: NexusGrid / Overseer

Subordinate Units: None

Relay Nodes: 8

Network Dependencies: Tactical Grid

VR OPERATOR MODE

Operator Seat Type: Drone View

Operator HUD: Tactical Relay Overlay

Camera Feeds: Optical

Thermal View: Yes

LiDAR View: No

Sonar View: No

Tactical Overlay: Relay coverage visualization

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Signal scan / relay diagnostics

Ability Controls: Deploy Relay, Boost Signal

Weapon Controls: None

Stabilization Controls: Auto-hover

Operator Abilities

Deploy Relay Node

Boost Signal

Tactical Scan

Relay Diagnostics

Network Stabilization

ECONOMY & LOGISTICS

Build Cost: 140 Metal / 130 Electronics

Build Time: 45 sec

Factory Type: Drone Bay

Tech Requirements: Tactical Networking I

Maintenance Cost: Low

Repair Time: 10 sec

Supply Consumption: Low

Operational Cost: Minimal

Deployment Requirements: Standard drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

10× Light Alloy Plates

6× Composite Frame Rods

4× Micro-Servo Actuators

2× Stabilizer Fins

1× Relay Antenna Housing

Electronics

12× Circuit Bundles

8× Signal Processors

4× Drone Control Chips

2× Relay AI Chips

Power

1× **High-Efficiency Battery Pack**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **Tactical Relay Core**

1× **Signal Routing Processor**

Optional Upgrades

Extended Relay Range Module

Anti-Jamming Shielding

Silent Rotor Kit

Signal Boost Amplifier