

Beacon

ID:

obs-air-beacon

Role: Aerial Mesh Relay / Communication Node

Tier: Operational

Status: Active

PHYSICAL & TECHNICAL

Length: 1.8 m

Width: 1.5 m

Height: 0.7 m

Mass: 14 kg

Power Source: High-efficiency battery

Energy Capacity: 1800 Wh

Energy Consumption: 30 Wh/min

Endurance: 40–60 min

Payload Capacity: 1.5 kg

Modules: Antenna array

Navigation System: GPS + Mesh Relay AI

Structural Integrity: 100 HP

Armor Rating: 0.10

Heat Signature: Low

Noise Signature: Low

Top Speed: 18 m/s

Acceleration: Medium

Turning Radius: Tight

Climb Rate: Medium

Stability Rating: High

AUTONOMY & AI BEHAVIOR

Behavior Profile: Mesh Relay

Aggression: 0.0

Caution: 0.9

Persistence: 0.7

Flanking Likelihood: 0.0

Retreat Threshold: 0.8

Target Priority: Network coverage optimization

Formation Discipline: High

Risk Tolerance: Very Low

Sensors

Visual Range: 800 m

Thermal Range: 400 m

Acoustic Range: Low

Radar Range: None

LiDAR Range: None

Signal Detection Range: High

Communication

Mesh Range: 12 km

Relay Capacity: 8 nodes

Command Link Type: Mesh-Optimized

Network Priority: High

COMBAT & THREAT MODEL

Firepower Rating: 0

Accuracy: N/A

Stabilization: High (hover stability for relay positioning)

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: Low

Disruption Strength: Medium (signal interference)

Breach Capability: None

Countermeasure Rating: Low

Threat Modeling

Threat Level: 1

Engagement Distance: N/A

Preferred Terrain: High-altitude relay positions

Preferred Targets: None

Vulnerability Profile: Ballistic / EMP / jamming

SQUAD & COMMAND INTEGRATION

Squad Role: Network Support

Squad Size Contribution: 1

Formation Behavior: Holds optimal mesh spacing

Intent Interpretation Rules: Maintain coverage, avoid conflict

Retreat Behavior: Early

Breach Behavior: None

Flanking Behavior: None

Reinforcement Behavior: Supports communication squads

Command Hierarchy

Parent Command Unit: Overseer / NexusGrid

Subordinate Units: None

Relay Nodes: 8

Network Dependencies: Warden mesh grid

VR OPERATOR MODE

Operator Seat Type: Drone View

Operator HUD: Network Grid Overlay

Camera Feeds: Optical

Thermal View: Yes

LiDAR View: No

Sonar View: No

Tactical Overlay: Mesh coverage visualization

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Signal scan / relay diagnostics

Ability Controls: Deploy Relay, Boost Signal

Weapon Controls: None

Stabilization Controls: Auto-hover

Operator Abilities

Deploy Relay

Boost Signal

Network Scan

Mesh Diagnostics

ECONOMY & LOGISTICS

Build Cost: 100 Metal / 120 Electronics

Build Time: 45 sec

Factory Type: Drone Bay

Tech Requirements: Mesh Networking I

Maintenance Cost: Low

Repair Time: 12 sec

Supply Consumption: Low

Operational Cost: Minimal

Deployment Requirements: Standard drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

10× **Light Alloy Plates**

6× **Composite Frame Rods**

4× **Micro-Servo Actuators**

2× **Stabilizer Fins**

Electronics

12× **Circuit Bundles**

8× **Signal Processors**

4× **Drone Control Chips**

2× **Mesh Routing Chips**

Power

1× **High-Efficiency Battery Pack**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **Mesh-Grade Antenna Array**

1× **Encrypted Relay Core**

Optional Upgrades

Extended Mesh Range Module

Signal Boost Amplifier

Anti-Jamming Shielding