



AIR UNIT #22 — NEXUSGRID

ID:

obs-air-nexusgrid

Role: High-Tier Network Coordination / Strategic Mesh Anchor

Tier: Command Infrastructure

Status: Active



PHYSICAL & TECHNICAL

Length: 3.8 m

Width: 2.9 m

Height: 1.4 m

Mass: 38 kg

Power Source: Command-grade mesh battery

Energy Capacity: 3400 Wh

Energy Consumption: 80 Wh/min

Endurance: 35–55 min

Payload Capacity: 4.0 kg

Modules: Multi-node mesh anchor array

Navigation System: GPS + Network Optimization AI

Structural Integrity: 200 HP

Armor Rating: 0.32

Heat Signature: Medium

Noise Signature: Medium

Top Speed: 20 m/s

Acceleration: Medium

Turning Radius: Moderate

Climb Rate: Medium

Stability Rating: Very High



AUTONOMY & AI BEHAVIOR

Behavior Profile: Strategic Network Coordination

Aggression: 0.0

Caution: 0.9

Persistence: 1.0

Flanking Likelihood: 0.0

Retreat Threshold: 0.9

Target Priority: Mesh gaps / command nodes

Formation Discipline: Extremely High

Risk Tolerance: Very Low

Sensors

Visual Range: 1200 m

Thermal Range: 500 m

Acoustic Range: Low

Radar Range: None

LiDAR Range: None

Signal Detection Range: Extremely High

Communication

Mesh Range: 22 km

Relay Capacity: 16 nodes

Command Link Type: NexusGrid Protocol

Network Priority: Maximum



COMBAT & THREAT MODEL

Firepower Rating: 0

Accuracy: N/A

Stabilization: Very High

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: Medium

Disruption Strength: High

Breach Capability: None

Countermeasure Rating: High

Threat Modeling

Threat Level: 4

Engagement Distance: N/A

Preferred Terrain: High-altitude mesh corridors

Preferred Targets: None

Vulnerability Profile: Ballistic / EMP / jamming

SQUAD & COMMAND INTEGRATION

Squad Role: Strategic Mesh Anchor

Squad Size Contribution: 1

Formation Behavior: High-discipline mesh lattice

Intent Interpretation Rules: Maintain network stability above all

Retreat Behavior: Very Early

Breach Behavior: None

Flanking Behavior: None

Reinforcement Behavior: Supports command, mesh, and recon squads

Command Hierarchy

Parent Command Unit: Command Core

Subordinate Units: Mesh, Relay, Link

Relay Nodes: 16

Network Dependencies: NexusGrid Protocol

VR OPERATOR MODE

Operator Seat Type: Command Drone View

Operator HUD: NexusGrid Network Overlay

Camera Feeds: Optical

Thermal View: Yes

LiDAR View: No

Radar View: No

Tactical Overlay: Mesh lattice visualization

Operator Controls

Movement Controls: Full drone flight

Sensor Controls: Signal scan / mesh diagnostics

Ability Controls: Deploy Anchor, Boost Mesh, Stabilize Network

Weapon Controls: None

Stabilization Controls: Auto-hover

Operator Abilities

Deploy Mesh Anchor

Boost Mesh

Network Stabilization

Mesh Diagnostics

Relay Command Data



ECONOMY & LOGISTICS

Build Cost: 240 Metal / 260 Electronics

Build Time: 75 sec

Factory Type: Drone Bay

Tech Requirements: Mesh Networking III

Maintenance Cost: Medium

Repair Time: 20 sec

Supply Consumption: Medium

Operational Cost: Moderate

Deployment Requirements: Command drone pad

Transport Compatibility: All aerial racks

Launch Method: Vertical takeoff



BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

18× Medium Alloy Plates

12× Composite Frame Rods

8× Micro-Servo Actuators

4× Stabilizer Fins

1× Mesh Anchor Housing

Electronics

20× Circuit Bundles

14× Signal Processors

6× Drone Control Chips

6× Mesh AI Chips

Power

1× **Command-Grade Mesh Battery**

3× **Power Regulation Nodes**

Rare / Tradeable

1× **NexusGrid Core**

1× **Encrypted Mesh Processor**

Optional Upgrades

Extended Mesh Range Module

Anti-Jamming Shielding

Silent Rotor Kit

High-Density Mesh Grid